

**COSEL New Products POWER SUPPLIES/NOISE(EMI/EMC) FILTER catalog  
2013-2014 , 2014-2015 , 2015-2016 and 2016-2017**

## <Corrections for Catalog (GHA series)>

**AUX output signage is not correct in our new product catalogue,  
2013-2014 , 2014-2015 , 2015-2016 and 2016-2017**

### <Page GHA-1>

#### ■ Feature

Wattage 500Wmax  
Conduction cooling (GHA500F)  
3" X 5" standard footprint  
Less than 1U high  
For medical electric equipment  
Low leakage current  
With Remote (Option)  
**With AUX1(5V), AUX2(12V) (Option)**

### <Page GHA-3>

#### Features

- High Power density:14.3W/inch<sup>3</sup>
- High efficiency 92% typ (Input Voltage 230V, Output Voltage 24V)
- 3" X 5" standard footprint
- Fits 1U applications
- Industrial and Medical safety approvals
- Low leakage current
- With Remote On/Off (Optional)
- With AUX1 (5V), AUX2 (12V) (Optional)**
- No minimum load is required

### <Page GHA-5>

#### Features

- Wattage 500W max
- High Power density:24.1W/inch<sup>3</sup>
- High efficiency 92% typ (Input Voltage 230V, Output Voltage 24V)
- Conduction cooling
- 3" X 5" standard footprint
- Fits 1U applications
- Industrial and Medical safety approvals
- Low leakage current
- With Remote On/Off (Optional)
- With AUX1 (5V), AUX2 (12V) (Optional)**
- No minimum load is required

**Incorrect**

**· With AUX1 (5V), AUX2 (12V) (Optional)**



**Correct**

**· With AUX1 (12V), AUX2 (5V) (Optional)**