

LCC series Recommended Models for Replacements

(Please check detail specifications in the catalog.)

LCC30A

No.	Discontinued Models					Recommended Models for Replacement						
	Model	Input Voltage [V]	No.	Output Voltage [V]	Output Current [A] *1	Remarks	Model	Input Voltage [V]	No.	Output Voltage [V]	Output Current [A] *1	Remarks
1	LCC30A-1	AC85-132	V1	5	3(4.5)		LDC30F-1	AC85-264	V1	5	3(4.5)	For isolation of V3, LFA10F-12 is recommended for V3.
			V2	12	1.2(2)				V2	12	1.2(2)	
			V3	12	0.3(0.45)				V3	-12	0.3(0.45)	
2	LCC30A-2		V1	5	3(4.5)		LDC30F-2		V1	5	3(4.5)	For isolation of V3, LFA10F-15 is recommended for V3.
			V2	15	1(2)				V2	15	1(2)	
			V3	15	0.3(0.45)				V3	-15	0.3(0.45)	
3	LCC30A-3		V1	5	3(4.5)		LFA15F-5-J1		V1	5	3	Three units of power supplies should be used . *2
			V2	24	0.5(1.3)		LFA30F-24-J1		V2	24	1.3	
			V3	5	0.5(0.75)		LFA10F-5-J1		V3	5	2	
4	LCC30A-4	V1	3.3	4(6)		LFA30F-3R3-J1Y	V1	3.3	6	Two units of power supplies should be used .		
		V2	12	1.2(2)		LDC30F-1	V2	12	1.2(2)			
		V3	5	0.5(0.75)			V3	5	3(4.5)			

*1 () means output peak current.

*2 Please check actual output current value of your application.