



ADA750F EMI/EMS Test result

October 13, 2004
Design engineering dep.

Approved : Takahiro Yoneda
Takahiro Yoneda

Prepared : Katsumi Ishikawa
Katsumi Ishikawa

No.	Test item	Conditions	Conditions of Acceptability	Result
1	Line conduction	(1) Rated input(AC100V,120V,230V) (2) Rated load (3) Ambient temp. 25±10°C	(1)Meets the undermentioned standard. FCC Part15 classB , VCCI classB CISPR22 classB , EN55022-B	OK
2	Radiated emission	(1) Rated input(AC100V,120V,230V) (2) Rated load (3) Ambient temp. 25±10°C	(1)Meets the undermentioned standard. FCC Part15 classB , VCCI classB CISPR22 classB , EN55022-B	OK
3	Harmonic current (EN61000-3-2)	(1) Rated input (AC100V,230V) (2) Load 0 - Rated load (3) Ambient temp. 25±10°C	(1)Meets the undermentioned standard. EN61000-3-2 classA	OK
4	Static electricity immunity test (EN61000-4-2)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. 25±10°C (4) Contact discharge voltage 8[kV] (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
5	Radiated, radio-frequency, electromagnetic field immunity test (EN61000-4-3)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. 25±10°C (4)Testing field strength 10[V/m] (Level 3)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
6	Electrical fast transient/ burst immunity test (EN61000-4-4)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. 25±10°C (4) Test peak voltage 4[kV] (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
7	Surge immunity test (EN61000-4-5)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. 25±10°C (4) Test voltage Line to line 2[kV] (Level 3) Line to earth 4[kV] (Level 4)	(1)The power supply is not stop (2)Circuit does not malfunction. (3)No abnormality of the insulation destruction etc. (4)Parts are no damaged.	OK
8	Immunity to conducted disturbances, induced by radio-frequency fields (EN61000-4-6)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. 25±10°C (4) Voltage level (e.m.f.) 10[V] (Level 3)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
9	Power frequency magnetic field immunity test (EN61000-4-8)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. 25±10°C (4) Magnetic field 30A/m (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK
10	Voltage dips, short interruptions and voltage variations immunity test (EN61000-4-11)	(1) Rated input (AC230V) •30% reduction at 10mS min. •60% reduction at 100mS min •95% reduction at 5S min. • ±10% variation at 15 minutes (2) Rated load (3) Ambient temp. 25±10°C	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	OK



RADIATED EMISSION

Model Name : ADA750F-48

Model No. :

Serial No. :

Points : 2

Detector : PEAK/QP

Polarization : Horizontal

Limit: [EN 55022] Class B<3m>

Power Supply : 230V(1Phase) 50Hz


Temp. : 25deg C

Humi. : 45%

Date : 2002/10/31 17:13

Test Equip. : R3132,ESPC

Comment : Load100%(+48V15.5A)



Frequency [MHz]	Meter Reading (QP) [dBμV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level (QP) [dBμV/m]	Angle[°]	Height [cm]	Polar.	Limit [dBμV/m]	Margin [dB]
143.818	47.0	BL	10.7	-24.7	33.0	19	155	Hori.	40.0	7.0
148.055	46.7	BL	10.5	-24.6	32.6	359	148	Hori.	40.0	7.4


BL: Biconi-Log



LINE CONDUCTION

Model Name : ADA750F-48
 Model No. :
 Serial No. :
 Points : 20
 Detector : PEAK/QP/Ave.
 Line Mode : VA/VB
 Limit1: [EN 55022] Class B(QP)
 Limit2: [EN 55022] Class B(Ave.)

Power Supply : 230V(1Phase) 50Hz
 Temp. : 25deg C
 Humi. : 45%
 Date : 2002/10/31 16:41
 Test Equip. : R3132,ESPC
 Comment : Load100%(+48V15.5A)



Frequency [MHz]	Meter Reading (QP) [dBμV]	Meter Reading (Ave.) [dBμV]	Factor [dB]	Level (QP) [dBμV]	Level (Ave.) [dBμV]	Line	Limit (QP) [dBμV]	Limit (Ave.) [dBμV]	Margin (QP)[dB]	Margin (Ave.) [dB]
0.1758	39.4	32.9	10.0	49.4	42.9	VA	64.7	54.7	15.3	11.8
0.2718	34.9	33.7	10.0	44.9	43.7	VA	61.1	51.1	16.2	7.4
0.6794	30.1	29.1	10.1	40.2	39.2	VA	56.0	46.0	15.8	6.8
1.2191	30.5	29.6	10.1	40.6	39.7	VA	56.0	46.0	15.4	6.3
1.6263	30.2	29.2	10.1	40.3	39.3	VA	56.0	46.0	15.7	6.7
1.7649	29.7	27.7	10.1	39.8	37.8	VA	56.0	46.0	16.2	8.2
2.1677	30.4	28.2	10.2	40.6	38.4	VA	56.0	46.0	15.4	7.6
0.3552	32.7	25.5	10.0	42.7	35.5	VB	58.9	48.9	16.2	13.4
0.4447	35.0	25.8	10.1	45.1	35.9	VB	57.0	47.0	11.9	11.1
0.5346	35.3	27.1	10.1	45.4	37.2	VB	56.0	46.0	10.6	8.8
0.6185	32.9	24.6	10.1	43.0	34.7	VB	56.0	46.0	13.0	11.3
0.7119	30.9	25.0	10.1	41.0	35.1	VB	56.0	46.0	15.0	10.9
0.8910	31.7	24.2	10.1	41.8	34.3	VB	56.0	46.0	14.2	11.7
0.9790	32.3	24.6	10.1	42.4	34.7	VB	56.0	46.0	13.6	11.3
2.3067	29.0	25.9	10.2	39.2	36.1	VB	56.0	46.0	16.8	9.9
2.5775	30.2	27.7	10.2	40.4	37.9	VB	56.0	46.0	15.6	8.1
2.7099	30.5	27.7	10.2	40.7	37.9	VB	56.0	46.0	15.3	8.1
3.1158	29.7	25.5	10.2	39.9	35.7	VB	56.0	46.0	16.1	10.3
13.8693	39.8	33.0	10.6	50.4	43.6	VB	60.0	50.0	9.6	6.4
20.7944	32.1	26.4	10.8	42.9	37.2	VB	60.0	50.0	17.1	12.8