



TEST DATA OF ADA750F

ADA750F-48
(100V INPUT)Regulated DC power supply
Mar. 24, 2003Approved by : *Kuniaki Nagahara*
Kuniaki Nagahara Design ManagerPrepared by : *Katsumi Ishikawa*
Katsumi Ishikawa Design Engineer

INPUT : AC 85~132V

OUTPUT : V1: 48V 12.5A

コーセル株式会社
COSEL CO.,LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Power)	2
入力電流 (負荷電力特性)	
3. Input Power (by Load Power)	3
入力電力 (負荷電力特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Power)	5
効率 (負荷電力特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Power)	7
力率 (負荷電力特性)	
8. Hold-Up Time (by Load Power)	8
出力保持時間 (負荷電力特性)	
9. Instantaneous Interruption Compensation (by Load Power)	9
瞬時停電保障 (負荷電力特性)	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷電流特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Overvoltage Protection	14
過電圧保護	
15. Inrush Current	15
突入電流	
16. Rise and Fall Time	16
立上り、立下り時間	
17. Ambient Temperature Drift	17
周囲温度変動	
18. Minimum Input Voltage for Regulated Output Voltage	18
最低レギュレーション電圧	
19. Ripple Voltage (by Ambient Temperature)	19
リップル電圧 (周囲温度特性)	
20. Time Lapse Drift	20
経時ドリフト	
21. Output Voltage Accuracy	21
定電圧精度	
22. Leakage Current	22
漏洩電流	
23. Figure of Testing Circuitry	23
測定回路図	

(Final Page 23)



Model		ADA750F (ADA750F-48)		Temperature		25°C																																	
Item		Line Regulation 静の入力変動		Testing Circuitry		Figure A																																	
Object		V1:+48V12.5A																																					
1. Graph				2. Values																																			
<p>---□--- Load 50% —△— Load 100%</p> <p>Note: Slanted line shows the range of the rated input voltage. (注) 斜線は定格入力電圧範囲を示す。</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>47.967</td><td>47.952</td></tr> <tr><td>80</td><td>47.966</td><td>47.952</td></tr> <tr><td>85</td><td>47.966</td><td>47.952</td></tr> <tr><td>90</td><td>47.965</td><td>47.951</td></tr> <tr><td>100</td><td>47.965</td><td>47.952</td></tr> <tr><td>110</td><td>47.964</td><td>47.952</td></tr> <tr><td>120</td><td>47.964</td><td>47.951</td></tr> <tr><td>132</td><td>47.964</td><td>47.951</td></tr> <tr><td>140</td><td>47.963</td><td>47.950</td></tr> </tbody> </table>				Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	47.967	47.952	80	47.966	47.952	85	47.966	47.952	90	47.965	47.951	100	47.965	47.952	110	47.964	47.952	120	47.964	47.951	132	47.964	47.951	140	47.963	47.950
Input Voltage [V]	Output Voltage [V]																																						
	Load 50%	Load 100%																																					
75	47.967	47.952																																					
80	47.966	47.952																																					
85	47.966	47.952																																					
90	47.965	47.951																																					
100	47.965	47.952																																					
110	47.964	47.952																																					
120	47.964	47.951																																					
132	47.964	47.951																																					
140	47.963	47.950																																					



Model		ADA750F (ADA750F-48)		Temperature		25°C																																																				
Item		Input Current (by Load Current) 入力電流 (負荷電力特性)		Testing Circuitry		Figure A																																																				
Object																																																										
1. Graph		—△— Input Volt. 85 V - - -□- - - Input Volt. 100 V - · - ○ - · - Input Volt. 132 V		2. Values																																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.300</td><td>0.280</td><td>0.230</td></tr> <tr><td>120</td><td>1.960</td><td>1.680</td><td>1.300</td></tr> <tr><td>240</td><td>3.480</td><td>2.960</td><td>2.250</td></tr> <tr><td>360</td><td>5.040</td><td>4.250</td><td>3.230</td></tr> <tr><td>480</td><td>6.560</td><td>5.580</td><td>4.200</td></tr> <tr><td>600</td><td>8.170</td><td>6.890</td><td>5.190</td></tr> <tr><td>660</td><td>8.970</td><td>7.550</td><td>5.690</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>						Load Power [W]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.300	0.280	0.230	120	1.960	1.680	1.300	240	3.480	2.960	2.250	360	5.040	4.250	3.230	480	6.560	5.580	4.200	600	8.170	6.890	5.190	660	8.970	7.550	5.690	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Power [W]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	0.300	0.280	0.230																																																							
120	1.960	1.680	1.300																																																							
240	3.480	2.960	2.250																																																							
360	5.040	4.250	3.230																																																							
480	6.560	5.580	4.200																																																							
600	8.170	6.890	5.190																																																							
660	8.970	7.550	5.690																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
Note: Slanted line shows the range of the rated load power. (注) 斜線は定格電力範囲を示す。																																																										



Model		ADA750F (ADA750F-48)		Temperature		25°C																																																				
Item		Input Power (by Load Power) 入力電力 (負荷電力特性)		Testing Circuitry		Figure A																																																				
Object		_____																																																								
1. Graph				2. Values																																																						
<p> \triangle Input Volt. 85 V \square Input Volt. 100 V \circ Input Volt. 132 V </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>21.0</td><td>23.0</td><td>20.0</td></tr> <tr><td>120</td><td>158.0</td><td>158.0</td><td>158.0</td></tr> <tr><td>240</td><td>288.0</td><td>287.0</td><td>285.0</td></tr> <tr><td>360</td><td>420.0</td><td>416.0</td><td>413.0</td></tr> <tr><td>480</td><td>551.0</td><td>550.0</td><td>543.0</td></tr> <tr><td>600</td><td>690.0</td><td>681.0</td><td>674.0</td></tr> <tr><td>660</td><td>759.0</td><td>749.0</td><td>741.0</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Load Power [W]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	21.0	23.0	20.0	120	158.0	158.0	158.0	240	288.0	287.0	285.0	360	420.0	416.0	413.0	480	551.0	550.0	543.0	600	690.0	681.0	674.0	660	759.0	749.0	741.0	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Power [W]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	21.0	23.0	20.0																																																							
120	158.0	158.0	158.0																																																							
240	288.0	287.0	285.0																																																							
360	420.0	416.0	413.0																																																							
480	551.0	550.0	543.0																																																							
600	690.0	681.0	674.0																																																							
660	759.0	749.0	741.0																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
<p>Note: Slanted line shows the range of the rated load power.</p> <p>(注) 斜線は定格電力範囲を示す。</p>																																																										



Model		ADA750F (ADA750F-48)																																	
Item		Efficiency (by Input Voltage) 効率 (入力電圧特性)																																	
Object		Temperature 25°C Testing Circuitry Figure A																																	
1. Graph		2. Values																																	
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>83.2</td><td>85.3</td></tr> <tr><td>80</td><td>83.5</td><td>85.9</td></tr> <tr><td>85</td><td>84.0</td><td>86.3</td></tr> <tr><td>90</td><td>84.4</td><td>86.8</td></tr> <tr><td>100</td><td>84.0</td><td>87.4</td></tr> <tr><td>110</td><td>84.7</td><td>87.4</td></tr> <tr><td>120</td><td>84.6</td><td>88.0</td></tr> <tr><td>132</td><td>84.4</td><td>88.2</td></tr> <tr><td>140</td><td>84.7</td><td>88.3</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	83.2	85.3	80	83.5	85.9	85	84.0	86.3	90	84.4	86.8	100	84.0	87.4	110	84.7	87.4	120	84.6	88.0	132	84.4	88.2	140	84.7	88.3
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	83.2	85.3																																	
80	83.5	85.9																																	
85	84.0	86.3																																	
90	84.4	86.8																																	
100	84.0	87.4																																	
110	84.7	87.4																																	
120	84.6	88.0																																	
132	84.4	88.2																																	
140	84.7	88.3																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																			



Model		ADA750F (ADA750F-48)		Temperature		25°C																																																				
Item		Efficiency (by Load Power) 効率 (負荷電力特性)		Testing Circuitry		Figure A																																																				
Object		_____																																																								
1. Graph				2. Values																																																						
<p> —△— Input Volt. 85 V -□- Input Volt. 100 V -○- Input Volt. 132 V </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>120</td><td>74.1</td><td>74.1</td><td>74.1</td></tr> <tr><td>240</td><td>82.1</td><td>82.4</td><td>83.1</td></tr> <tr><td>360</td><td>84.8</td><td>85.6</td><td>86.2</td></tr> <tr><td>480</td><td>86.4</td><td>86.5</td><td>87.6</td></tr> <tr><td>600</td><td>86.3</td><td>87.4</td><td>88.3</td></tr> <tr><td>660</td><td>86.3</td><td>87.5</td><td>88.4</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Power [W]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	—	—	—	120	74.1	74.1	74.1	240	82.1	82.4	83.1	360	84.8	85.6	86.2	480	86.4	86.5	87.6	600	86.3	87.4	88.3	660	86.3	87.5	88.4	--	—	—	—	--	—	—	—	--	—	—	—	--	—	—	—
Load Power [W]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	—	—	—																																																							
120	74.1	74.1	74.1																																																							
240	82.1	82.4	83.1																																																							
360	84.8	85.6	86.2																																																							
480	86.4	86.5	87.6																																																							
600	86.3	87.4	88.3																																																							
660	86.3	87.5	88.4																																																							
--	—	—	—																																																							
--	—	—	—																																																							
--	—	—	—																																																							
--	—	—	—																																																							
<p>Note: Slanted line shows the range of the rated load power.</p> <p>(注) 斜線は定格電力範囲を示す。</p>																																																										



Model		ADA750F (ADA750F-48)		Temperature		25°C																																	
Item		Power Factor (by Input Voltage) 力率 (入力電圧特性)		Testing Circuitry		Figure A																																	
Object		_____																																					
1. Graph				2. Values																																			
<p>Legend: ---□--- Load 50% ---△--- Load 100%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.981</td><td>0.999</td></tr> <tr><td>80</td><td>0.981</td><td>0.996</td></tr> <tr><td>85</td><td>0.981</td><td>0.994</td></tr> <tr><td>90</td><td>0.978</td><td>0.993</td></tr> <tr><td>100</td><td>0.975</td><td>0.988</td></tr> <tr><td>110</td><td>0.972</td><td>0.990</td></tr> <tr><td>120</td><td>0.967</td><td>0.990</td></tr> <tr><td>132</td><td>0.967</td><td>0.983</td></tr> <tr><td>140</td><td>0.970</td><td>0.983</td></tr> </tbody> </table>				Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.981	0.999	80	0.981	0.996	85	0.981	0.994	90	0.978	0.993	100	0.975	0.988	110	0.972	0.990	120	0.967	0.990	132	0.967	0.983	140	0.970	0.983
Input Voltage [V]	Power Factor																																						
	Load 50%	Load 100%																																					
75	0.981	0.999																																					
80	0.981	0.996																																					
85	0.981	0.994																																					
90	0.978	0.993																																					
100	0.975	0.988																																					
110	0.972	0.990																																					
120	0.967	0.990																																					
132	0.967	0.983																																					
140	0.970	0.983																																					
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																							



Model		ADA750F (ADA750F-48)		Temperature		25°C																																																				
Item		Power Factor (by Load Power) 力率 (負荷電力特性)		Testing Circuitry		Figure A																																																				
Object		_____																																																								
1. Graph				2. Values																																																						
<p> —△— Input Volt. 85 V ---□--- Input Volt. 100 V -·-○-·- Input Volt. 132 V </p> <p>Power Factor</p> <p>Load Power [W]</p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.808</td><td>0.821</td><td>0.667</td></tr> <tr><td>120</td><td>0.946</td><td>0.940</td><td>0.924</td></tr> <tr><td>240</td><td>0.973</td><td>0.970</td><td>0.960</td></tr> <tr><td>360</td><td>0.981</td><td>0.979</td><td>0.969</td></tr> <tr><td>480</td><td>0.989</td><td>0.986</td><td>0.980</td></tr> <tr><td>600</td><td>0.994</td><td>0.988</td><td>0.984</td></tr> <tr><td>660</td><td>0.996</td><td>0.992</td><td>0.985</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Load Power [W]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.808	0.821	0.667	120	0.946	0.940	0.924	240	0.973	0.970	0.960	360	0.981	0.979	0.969	480	0.989	0.986	0.980	600	0.994	0.988	0.984	660	0.996	0.992	0.985	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Power [W]	Power Factor																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	0.808	0.821	0.667																																																							
120	0.946	0.940	0.924																																																							
240	0.973	0.970	0.960																																																							
360	0.981	0.979	0.969																																																							
480	0.989	0.986	0.980																																																							
600	0.994	0.988	0.984																																																							
660	0.996	0.992	0.985																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
<p>Note: Slanted line shows the range of the rated load power.</p> <p>(注) 斜線は定格電力範囲を示す。</p>																																																										



Model		ADA750F (ADA750F-48)		Temperature		25°C																																																				
Item		Hold-Up Time (by Load Power) 出力保持時間 (負荷電力特性)		Testing Circuitry		Figure A																																																				
Object																																																										
1. Graph				2. Values																																																						
<p> —△— Input Volt. 85V ---□--- Input Volt. 100V -·-○-·- Input Volt. 132V </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Hold-Up Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>120</td><td>148</td><td>152</td><td>158</td></tr> <tr><td>240</td><td>73</td><td>76</td><td>81</td></tr> <tr><td>360</td><td>46</td><td>50</td><td>54</td></tr> <tr><td>480</td><td>33</td><td>35</td><td>39</td></tr> <tr><td>600</td><td>24</td><td>27</td><td>30</td></tr> <tr><td>660</td><td>21</td><td>24</td><td>27</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>--</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Power [W]	Hold-Up Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	—	—	—	120	148	152	158	240	73	76	81	360	46	50	54	480	33	35	39	600	24	27	30	660	21	24	27	--	—	—	—	--	—	—	—	--	—	—	—	--	—	—	—
Load Power [W]	Hold-Up Time [mS]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	—	—	—																																																							
120	148	152	158																																																							
240	73	76	81																																																							
360	46	50	54																																																							
480	33	35	39																																																							
600	24	27	30																																																							
660	21	24	27																																																							
--	—	—	—																																																							
--	—	—	—																																																							
--	—	—	—																																																							
--	—	—	—																																																							
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated load power.</p>																																																										
<p>出力保持時間とは、入力電圧断から出力電圧が定電圧精度の範囲を保持しているところまでの時間。 (注) 斜線は定格電力範囲を示す。</p>																																																										



Model		ADA750F (ADA750F-48)		Temperature	25°C																																																			
Item		Instantaneous Interruption Compensation (by Load Power) 瞬時停電保障 (負荷電力特性)				Testing Circuitry	Figure A																																																	
Object																																																								
1. Graph			2. Values																																																					
<p> \triangle — Input Volt. 85V \square --- Input Volt. 100V \circ - - - Input Volt. 132V </p> <p style="text-align: center;">Load Power [W]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>120</td><td>115</td><td>124</td><td>139</td></tr> <tr><td>240</td><td>73</td><td>76</td><td>81</td></tr> <tr><td>360</td><td>45</td><td>48</td><td>54</td></tr> <tr><td>480</td><td>31</td><td>35</td><td>39</td></tr> <tr><td>600</td><td>22</td><td>26</td><td>30</td></tr> <tr><td>660</td><td>20</td><td>22</td><td>27</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Power [W]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	—	—	—	120	115	124	139	240	73	76	81	360	45	48	54	480	31	35	39	600	22	26	30	660	20	22	27	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Power [W]	Time [mS]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0	—	—	—																																																					
120	115	124	139																																																					
240	73	76	81																																																					
360	45	48	54																																																					
480	31	35	39																																																					
600	22	26	30																																																					
660	20	22	27																																																					
--	--	--	--																																																					
--	--	--	--																																																					
--	--	--	--																																																					
--	--	--	--																																																					
<p>Note: Slanted line shows the range of the rated load power.</p> <p>(注) 斜線は定格電力範囲を示す。</p>																																																								



Model		ADA750F (ADA750F-48)		Temperature		25°C																																																				
Item		Load Regulation 静的負荷変動		Testing Circuitry		Figure A																																																				
Object		V1:+48V12.5A																																																								
1. Graph				2. Values																																																						
<p> —△— Input Volt. 85 V ---□--- Input Volt. 100 V -·-○-·- Input Volt. 132 V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Load Current [A]</p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>47.982</td><td>47.982</td><td>47.982</td></tr> <tr><td>2.00</td><td>47.952</td><td>47.952</td><td>47.954</td></tr> <tr><td>4.00</td><td>47.950</td><td>47.951</td><td>47.950</td></tr> <tr><td>6.00</td><td>47.947</td><td>47.947</td><td>47.948</td></tr> <tr><td>8.00</td><td>47.944</td><td>47.944</td><td>47.944</td></tr> <tr><td>10.00</td><td>47.938</td><td>47.940</td><td>47.942</td></tr> <tr><td>12.50</td><td>47.937</td><td>47.938</td><td>47.941</td></tr> <tr><td>13.75</td><td>47.930</td><td>47.933</td><td>47.936</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	47.982	47.982	47.982	2.00	47.952	47.952	47.954	4.00	47.950	47.951	47.950	6.00	47.947	47.947	47.948	8.00	47.944	47.944	47.944	10.00	47.938	47.940	47.942	12.50	47.937	47.938	47.941	13.75	47.930	47.933	47.936	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	47.982	47.982	47.982																																																							
2.00	47.952	47.952	47.954																																																							
4.00	47.950	47.951	47.950																																																							
6.00	47.947	47.947	47.948																																																							
8.00	47.944	47.944	47.944																																																							
10.00	47.938	47.940	47.942																																																							
12.50	47.937	47.938	47.941																																																							
13.75	47.930	47.933	47.936																																																							
--	--	--	--																																																							
--	--	--	--																																																							
--	--	--	--																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																										



Model		ADA750F (ADA750F-48)	Temperature		25°C																																						
Item		Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Testing Circuitry		Figure A																																						
Object		V1:+48V12.5A																																									
1. Graph			2. Values																																								
<p>—△— Input Volt. 85 V - - ○ - - Input Volt. 132 V</p> <p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p-p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>25</td><td>25</td></tr> <tr><td>2.00</td><td>30</td><td>30</td></tr> <tr><td>4.00</td><td>30</td><td>30</td></tr> <tr><td>6.00</td><td>40</td><td>40</td></tr> <tr><td>8.00</td><td>50</td><td>50</td></tr> <tr><td>10.00</td><td>60</td><td>60</td></tr> <tr><td>12.00</td><td>65</td><td>65</td></tr> <tr><td>12.50</td><td>65</td><td>65</td></tr> <tr><td>13.75</td><td>65</td><td>65</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85[V]	Input Volt. 132[V]	0.00	25	25	2.00	30	30	4.00	30	30	6.00	40	40	8.00	50	50	10.00	60	60	12.00	65	65	12.50	65	65	13.75	65	65	--	--	--	--	--	--
Load Current [A]	Ripple Output Voltage [mV]																																										
	Input Volt. 85[V]	Input Volt. 132[V]																																									
0.00	25	25																																									
2.00	30	30																																									
4.00	30	30																																									
6.00	40	40																																									
8.00	50	50																																									
10.00	60	60																																									
12.00	65	65																																									
12.50	65	65																																									
13.75	65	65																																									
--	--	--																																									
--	--	--																																									



Model		ADA750F (ADA750F-48)	Temperature		25°C																																						
Item		Ripple-Noise リップルノイズ	Testing Circuitry		Figure A																																						
Object		V1:+48V12.5A																																									
1. Graph			2. Values																																								
<p>—△— Input Volt. 85 V -·-○-·- Input Volt. 132 V</p> <p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p-p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>30</td><td>30</td></tr> <tr><td>2.00</td><td>35</td><td>35</td></tr> <tr><td>4.00</td><td>35</td><td>35</td></tr> <tr><td>6.00</td><td>45</td><td>45</td></tr> <tr><td>8.00</td><td>55</td><td>55</td></tr> <tr><td>10.00</td><td>65</td><td>65</td></tr> <tr><td>12.00</td><td>70</td><td>70</td></tr> <tr><td>12.50</td><td>70</td><td>70</td></tr> <tr><td>13.75</td><td>70</td><td>70</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85[V]	Input Volt. 132[V]	0.00	30	30	2.00	35	35	4.00	35	35	6.00	45	45	8.00	55	55	10.00	65	65	12.00	70	70	12.50	70	70	13.75	70	70	--	--	--	--	--	--
Load Current [A]	Ripple-Noise [mV]																																										
	Input Volt. 85[V]	Input Volt. 132[V]																																									
0.00	30	30																																									
2.00	35	35																																									
4.00	35	35																																									
6.00	45	45																																									
8.00	55	55																																									
10.00	65	65																																									
12.00	70	70																																									
12.50	70	70																																									
13.75	70	70																																									
--	--	--																																									
--	--	--																																									




<p>Model ADA750F (ADA750F-48)</p> <p>Item Overcurrent Protection 過電流保護</p> <p>Object V1:+48V12.5A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																										
<p>1. Graph</p> <p>— Input Volt. 85 V</p> <p>— Input Volt. 100 V</p> <p>— Input Volt. 132 V</p> <p>Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。</p> <p>Intermittent operation occurs when the output voltage is from 28.8V to 0V. 28.8V~0V間は、間欠モードとなる。</p>	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>48.0</td><td>22.56</td><td>23.01</td><td>23.42</td></tr> <tr><td>45.6</td><td>23.89</td><td>24.01</td><td>24.41</td></tr> <tr><td>43.2</td><td>24.06</td><td>24.21</td><td>24.62</td></tr> <tr><td>38.4</td><td>24.54</td><td>24.69</td><td>25.09</td></tr> <tr><td>33.6</td><td>25.15</td><td>25.28</td><td>25.69</td></tr> <tr><td>28.8</td><td>25.77</td><td>25.85</td><td>26.26</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	48.0	22.56	23.01	23.42	45.6	23.89	24.01	24.41	43.2	24.06	24.21	24.62	38.4	24.54	24.69	25.09	33.6	25.15	25.28	25.69	28.8	25.77	25.85	26.26	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																									
48.0	22.56	23.01	23.42																																																									
45.6	23.89	24.01	24.41																																																									
43.2	24.06	24.21	24.62																																																									
38.4	24.54	24.69	25.09																																																									
33.6	25.15	25.28	25.69																																																									
28.8	25.77	25.85	26.26																																																									
--	--	--	--																																																									
--	--	--	--																																																									
--	--	--	--																																																									
--	--	--	--																																																									
--	--	--	--																																																									
--	--	--	--																																																									
--	--	--	--																																																									



Model	ADA750F (ADA750F-48)
Item	Overvoltage Protection 過電圧保護
Object	V1:+48V12.5A

Testing Circuitry Figure A

1. Graph
- △— Input Volt. 85 V
 - Input Volt. 100 V
 - Input Volt. 132 V



2. Values


Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	67.86	67.74	67.74
-10	68.55	68.44	68.44
0	69.26	69.14	69.14
10	69.84	69.72	69.72
20	70.54	70.42	70.42
25	70.95	70.77	70.66
30	71.12	71.06	71.06
40	71.82	71.65	71.65
50	72.47	72.35	72.23
60	73.05	72.93	72.82
--	--	--	--

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。




Model	ADA750F (ADA750F-48)	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	_____		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %

Inrush Current

- ① 12.0 [A]
- ② 27.6 [A] (0.2msec or less)*1
- ③ 9.6 [A]



*1 The specification of the inrush current (primary surge) means that the surge current to a built-in noise filter (0.2msec or less : waveform ②) is excluded.


本製品の突入電流(1次サージ)の仕様は、内蔵ノイズフィルタ部へのサージ電流(0.2msec以下:波形②)を除きます。



Model	ADA750F (ADA750F-48)	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	V1:+48V12.5A		


1. Graph

Input Volt. 100 V



2. Values

		[mS]				
Load	Time	T d	T r	T s	T h	T f
50 %		353.0	9.5	362.5	78.8	95.3
100 %		352.0	10.5	362.5	36.8	50.3






Model	ADA750F (ADA750F-48)
Item	Ambient Temperature Drift 周囲温度変動
Object	V1:+48V12.5A

Testing Circuitry Figure A

1. Graph
- △— Input Volt. 85 V
 - Input Volt. 100 V
 - Input Volt. 132 V



2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	48.036	48.035	48.035
-10	48.023	48.022	48.022
0	48.013	48.012	48.012
10	48.001	48.001	48.001
20	47.996	47.995	47.995
25	47.991	47.991	47.990
30	47.987	47.986	47.987
40	47.964	47.963	47.962
50	47.940	47.940	47.938
60	47.885	47.884	47.883
--	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。



Model		ADA750F (ADA750F-48)	Testing Circuitry Figure A																																						
Item		Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧																																							
Object		V1:+48V12.5A																																							
1. Graph		<div style="text-align: right;"> ---□--- Load 50% —△— Load 100% </div> <p style="text-align: center;">Ambient Temperature [°C]</p>	2. Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>67</td><td>67</td></tr> <tr><td>-10</td><td>67</td><td>67</td></tr> <tr><td>0</td><td>67</td><td>67</td></tr> <tr><td>10</td><td>67</td><td>67</td></tr> <tr><td>20</td><td>67</td><td>67</td></tr> <tr><td>25</td><td>67</td><td>67</td></tr> <tr><td>30</td><td>67</td><td>67</td></tr> <tr><td>40</td><td>67</td><td>67</td></tr> <tr><td>50</td><td>67</td><td>67</td></tr> <tr><td>60</td><td>67</td><td>67</td></tr> <tr><td>--</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	67	67	-10	67	67	0	67	67	10	67	67	20	67	67	25	67	67	30	67	67	40	67	67	50	67	67	60	67	67	--	—	—	
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	67	67																																							
-10	67	67																																							
0	67	67																																							
10	67	67																																							
20	67	67																																							
25	67	67																																							
30	67	67																																							
40	67	67																																							
50	67	67																																							
60	67	67																																							
--	—	—																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									
(注) 斜線は定格周囲温度範囲を示す。																																									



COSEL																												
Model	ADA750F (ADA750F-48)																											
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																										
Object	V1:+48V12.5A																											
<p>1. Graph</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p>Input Volt. 100 V Load 100 %</p> <p>Note: Slanted line shows the range of the rated ambient temperature. (注) 斜線は定格周囲温度範囲を示す。</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV]</th> </tr> </thead> <tbody> <tr> <td>-10</td> <td>115</td> </tr> <tr> <td>0</td> <td>95</td> </tr> <tr> <td>25</td> <td>65</td> </tr> <tr> <td>50</td> <td>50</td> </tr> <tr> <td>--</td> <td>--</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]	-10	115	0	95	25	65	50	50	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Ambient Temperature [°C]	Ripple Voltage [mV]																											
-10	115																											
0	95																											
25	65																											
50	50																											
--	--																											
--	--																											
--	--																											
--	--																											
--	--																											
--	--																											
--	--																											
--	--																											



COSEL																									
Model	ADA750F (ADA750F-48)	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	V1:+48V12.5A																								
1. Graph		2. Values																							
<p style="text-align: center;">Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>48.070</td></tr> <tr><td>0.5</td><td>48.044</td></tr> <tr><td>1.0</td><td>48.046</td></tr> <tr><td>2.0</td><td>48.044</td></tr> <tr><td>3.0</td><td>48.046</td></tr> <tr><td>4.0</td><td>48.045</td></tr> <tr><td>5.0</td><td>48.047</td></tr> <tr><td>6.0</td><td>48.046</td></tr> <tr><td>7.0</td><td>48.046</td></tr> <tr><td>8.0</td><td>48.046</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	48.070	0.5	48.044	1.0	48.046	2.0	48.044	3.0	48.046	4.0	48.045	5.0	48.047	6.0	48.046	7.0	48.046	8.0	48.046
Time since start [H]	Output Voltage [V]																								
0.0	48.070																								
0.5	48.044																								
1.0	48.046																								
2.0	48.044																								
3.0	48.046																								
4.0	48.045																								
5.0	48.047																								
6.0	48.046																								
7.0	48.046																								
8.0	48.046																								

COSEL

Model	ADA750F (ADA750F-48)	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	V1:+48V12.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 50°C

Input Voltage : 85 ~ 132V

Load Current : 0 ~ 12.5A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -10 ~ 50°C

入力電圧 : 85 ~ 132V

負荷電流 : 0 ~ 12.5A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output		Output Voltage Accuracy	
			Current [A]	Voltage [V]	Value [mV]	Ration [%]
Maximum Voltage	-10	85	0	48.044	±63	±0.1
Minimum Voltage	50	100	15.5	47.919		

COSEL

Model		ADA750F (ADA750F-48)	Temperature		25°C
Item		Leakage Current 漏洩電流	Testing Circuitry		Figure B
Object					

1. Results

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
	85 [V]	100 [V]	132 [V]
(A) DEN-AN	0.19	0.22	0.28
(B) IEC60950	0.19	0.22	0.28

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
	170 [V]	230 [V]	264 [V]
(B) IEC60950	—	—	—

2. Condition

Leakage current value is concluded after measuring each phases of AC input and by choosing the larger one.

交流入力各相について測定し、その大きい方を漏洩電流測定値とする。




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)