



# TEST DATA OF AEA800F-36

Regulated DC Power Supply  
August 9, 2022

Approved by : \_\_\_\_\_ Jun Uchida  
\_\_\_\_\_  
Design Manager

Prepared by : \_\_\_\_\_ Koro Yo  
\_\_\_\_\_  
Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Efficiency (by Load Current) . . . . .	2
3.Power Factor (by Load Current) . . . . .	3
4.Inrush Current . . . . .	4
5.Leakage Current . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Ripple-Noise . . . . .	7
9.Dynamic Load Response . . . . .	8
10.Rise and Fall Time . . . . .	9
11.Hold-Up Time . . . . .	10
12.Instantaneous Interruption Compensation . . . . .	11
13.Overcurrent Protection . . . . .	12
14.Ambient Temperature Drift . . . . .	13
15.Minimum Input Voltage for Regulated Output Voltage . . . . .	13
16.Overvoltage Protection . . . . .	13
17.Figure of Testing Circuitry . . . . .	14


(Final Page 15)

**COSEL**

Model	AEA800F-36
Item	Input Current (by Load Current)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	0.131	0.173	0.194
3.0	1.374	0.740	0.672
6.0	2.540	1.315	1.170
9.0	3.704	1.890	1.667
12.0	4.858	2.455	2.162
15.0	6.006	3.024	2.658
18.0	7.172	3.598	3.150
21.0	-	4.166	3.645
22.7	-	4.491	3.927
25.0	-	4.930	4.313
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**




Model	AEA800F-36																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>3.0</td><td>89.1</td><td>90.3</td><td>90.7</td></tr> <tr> <td>6.0</td><td>92.3</td><td>93.8</td><td>94.0</td></tr> <tr> <td>9.0</td><td>93.3</td><td>94.9</td><td>95.1</td></tr> <tr> <td>12.0</td><td>93.6</td><td>95.3</td><td>95.6</td></tr> <tr> <td>15.0</td><td>93.7</td><td>95.5</td><td>95.8</td></tr> <tr> <td>18.0</td><td>93.6</td><td>95.6</td><td>95.8</td></tr> <tr> <td>21.0</td><td>-</td><td>95.5</td><td>95.8</td></tr> <tr> <td>22.7</td><td>-</td><td>95.5</td><td>95.8</td></tr> <tr> <td>25.0</td><td>-</td><td>95.4</td><td>95.7</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	3.0	89.1	90.3	90.7	6.0	92.3	93.8	94.0	9.0	93.3	94.9	95.1	12.0	93.6	95.3	95.6	15.0	93.7	95.5	95.8	18.0	93.6	95.6	95.8	21.0	-	95.5	95.8	22.7	-	95.5	95.8	25.0	-	95.4	95.7	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
3.0	89.1	90.3	90.7																																																			
6.0	92.3	93.8	94.0																																																			
9.0	93.3	94.9	95.1																																																			
12.0	93.6	95.3	95.6																																																			
15.0	93.7	95.5	95.8																																																			
18.0	93.6	95.6	95.8																																																			
21.0	-	95.5	95.8																																																			
22.7	-	95.5	95.8																																																			
25.0	-	95.4	95.7																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

Model	AEA800F-36																																																						
Item	Power Factor (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul> <p>Approximate data points from graph:</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>100V Power Factor</th> <th>200V Power Factor</th> <th>230V Power Factor</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.492</td><td>0.165</td><td>0.130</td></tr> <tr><td>3</td><td>0.897</td><td>0.820</td><td>0.783</td></tr> <tr><td>6</td><td>0.937</td><td>0.888</td><td>0.867</td></tr> <tr><td>9</td><td>0.953</td><td>0.917</td><td>0.901</td></tr> <tr><td>12</td><td>0.964</td><td>0.936</td><td>0.922</td></tr> <tr><td>15</td><td>0.973</td><td>0.948</td><td>0.935</td></tr> <tr><td>18</td><td>0.979</td><td>0.955</td><td>0.946</td></tr> <tr><td>21</td><td>-</td><td>0.963</td><td>0.954</td></tr> <tr><td>22.7</td><td>-</td><td>0.966</td><td>0.957</td></tr> <tr><td>25</td><td>-</td><td>0.970</td><td>0.961</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	100V Power Factor	200V Power Factor	230V Power Factor	0	0.492	0.165	0.130	3	0.897	0.820	0.783	6	0.937	0.888	0.867	9	0.953	0.917	0.901	12	0.964	0.936	0.922	15	0.973	0.948	0.935	18	0.979	0.955	0.946	21	-	0.963	0.954	22.7	-	0.966	0.957	25	-	0.970	0.961	--	-	-	-						
Load Current [A]	100V Power Factor	200V Power Factor	230V Power Factor																																																				
0	0.492	0.165	0.130																																																				
3	0.897	0.820	0.783																																																				
6	0.937	0.888	0.867																																																				
9	0.953	0.917	0.901																																																				
12	0.964	0.936	0.922																																																				
15	0.973	0.948	0.935																																																				
18	0.979	0.955	0.946																																																				
21	-	0.963	0.954																																																				
22.7	-	0.966	0.957																																																				
25	-	0.970	0.961																																																				
--	-	-	-																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.492</td><td>0.165</td><td>0.130</td></tr> <tr><td>3.0</td><td>0.897</td><td>0.820</td><td>0.783</td></tr> <tr><td>6.0</td><td>0.937</td><td>0.888</td><td>0.867</td></tr> <tr><td>9.0</td><td>0.953</td><td>0.917</td><td>0.901</td></tr> <tr><td>12.0</td><td>0.964</td><td>0.936</td><td>0.922</td></tr> <tr><td>15.0</td><td>0.973</td><td>0.948</td><td>0.935</td></tr> <tr><td>18.0</td><td>0.979</td><td>0.955</td><td>0.946</td></tr> <tr><td>21.0</td><td>-</td><td>0.963</td><td>0.954</td></tr> <tr><td>22.7</td><td>-</td><td>0.966</td><td>0.957</td></tr> <tr><td>25.0</td><td>-</td><td>0.970</td><td>0.961</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.492	0.165	0.130	3.0	0.897	0.820	0.783	6.0	0.937	0.888	0.867	9.0	0.953	0.917	0.901	12.0	0.964	0.936	0.922	15.0	0.973	0.948	0.935	18.0	0.979	0.955	0.946	21.0	-	0.963	0.954	22.7	-	0.966	0.957	25.0	-	0.970	0.961	--	-	-	-			
Load Current [A]	Power Factor																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	0.492	0.165	0.130																																																				
3.0	0.897	0.820	0.783																																																				
6.0	0.937	0.888	0.867																																																				
9.0	0.953	0.917	0.901																																																				
12.0	0.964	0.936	0.922																																																				
15.0	0.973	0.948	0.935																																																				
18.0	0.979	0.955	0.946																																																				
21.0	-	0.963	0.954																																																				
22.7	-	0.966	0.957																																																				
25.0	-	0.970	0.961																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated load current.																																																							

**COSEL**

Model	AEA800F-36	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	_____		





Model	AEA800F-36	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	_____		

## 1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	240 [V]	264 [V]	
DEN-AN	Figure B-1	Both phases	0.08	0.21	0.23	Operation
		One of phases	0.15	0.39	0.44	Stand by
IEC62368-1	Figure B-2	Both phases	0.08	0.20	0.23	Operation
		One of phases	0.15	0.39	0.43	Stand by
	Figure B-3	Both phases	0.08	0.20	0.23	Operation
		One of phases	0.15	0.38	0.43	Stand by
IEC60601-1	Figure B-4	Both phases	0.08	0.20	0.23	Operation
		One of phases	0.15	0.38	0.43	Stand by

The value for "One of phases" is the reference value only.



## 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	AEA800F-36																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+36V22.7A																																	
1.Graph																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>36.440</td> <td>36.430 ※1</td> </tr> <tr> <td>90</td> <td>36.440</td> <td>36.430 ※2</td> </tr> <tr> <td>100</td> <td>36.440</td> <td>36.431 ※2</td> </tr> <tr> <td>200</td> <td>36.440</td> <td>36.431</td> </tr> <tr> <td>230</td> <td>36.440</td> <td>36.431</td> </tr> <tr> <td>264</td> <td>36.440</td> <td>36.431</td> </tr> <tr> <td>280</td> <td>36.440</td> <td>36.431</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	36.440	36.430 ※1	90	36.440	36.430 ※2	100	36.440	36.431 ※2	200	36.440	36.431	230	36.440	36.431	264	36.440	36.431	280	36.440	36.431	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	36.440	36.430 ※1																																
90	36.440	36.430 ※2																																
100	36.440	36.431 ※2																																
200	36.440	36.431																																
230	36.440	36.431																																
264	36.440	36.431																																
280	36.440	36.431																																
--	-	-																																
--	-	-																																
※1 : Load 60% ※2 : Load 75%																																		



**COSEL**

Model	AEA800F-36	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+36V22.7A																																																					
1.Graph		2.Values																																																				
<p>—△— Input Volt. 100V        - - -□- - Input Volt. 200V        - - -○- - Input Volt. 230V</p> 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>36.471</td><td>36.472</td><td>36.472</td></tr> <tr><td>3.0</td><td>36.456</td><td>36.456</td><td>36.456</td></tr> <tr><td>6.0</td><td>36.453</td><td>36.453</td><td>36.453</td></tr> <tr><td>9.0</td><td>36.450</td><td>36.449</td><td>36.449</td></tr> <tr><td>12.0</td><td>36.446</td><td>36.446</td><td>36.446</td></tr> <tr><td>15.0</td><td>36.444</td><td>36.444</td><td>36.443</td></tr> <tr><td>18.0</td><td>36.441</td><td>36.441</td><td>36.440</td></tr> <tr><td>21.0</td><td>--</td><td>36.438</td><td>36.438</td></tr> <tr><td>22.7</td><td>--</td><td>36.436</td><td>36.436</td></tr> <tr><td>25.0</td><td>--</td><td>36.434</td><td>36.433</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	36.471	36.472	36.472	3.0	36.456	36.456	36.456	6.0	36.453	36.453	36.453	9.0	36.450	36.449	36.449	12.0	36.446	36.446	36.446	15.0	36.444	36.444	36.443	18.0	36.441	36.441	36.440	21.0	--	36.438	36.438	22.7	--	36.436	36.436	25.0	--	36.434	36.433	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	36.471	36.472	36.472																																																			
3.0	36.456	36.456	36.456																																																			
6.0	36.453	36.453	36.453																																																			
9.0	36.450	36.449	36.449																																																			
12.0	36.446	36.446	36.446																																																			
15.0	36.444	36.444	36.443																																																			
18.0	36.441	36.441	36.440																																																			
21.0	--	36.438	36.438																																																			
22.7	--	36.436	36.436																																																			
25.0	--	36.434	36.433																																																			
--	--	--	--																																																			
Note: Slanted line shows the range of the rated load current.																																																						
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+36V22.7A	Testing Circuitry	Figure C																																																			
1.Graph																																																						
<p>Input Voltage 200V        Load 100%</p> 																																																						



# COSEL

Model	AEA800F-36	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+36V22.7A		



Input Volt. 200 V  
Cycle 1000 ms

Response.  $t_1=t_2=50\mu\text{s}$ . Typ

Load 0%(0A)  $\longleftrightarrow$   
Load 100%(22.7A)




Load 50%(11.35A)  $\longleftrightarrow$   
Load 100%(22.7A)



**COSEL**


Model	AEA800F-36	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+36V22.7A		

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
100 %		555.0	4.5	559.5	30.7	18.4	
100 %		554.0	4.5	558.5	23.2	12.7	



**COSEL**

Model	AEA800F-36	Temperature	25°C
Item	Hold-Up Time	Testing Circuitry	Figure A
Object	+36V22.7A		

## 1. Graph



## 2. Values


Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	44	37 ※1
90	45	30 ※2
100	45	29 ※2
200	44	24
230	44	25
264	44	25
280	44	25
--	-	-
--	-	-

※1 : Load 60%

※2 : Load 75%

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	AEA800F-36																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+36V22.7A																																																					
1.Graph																																																						
—△— Input Volt. 100V - - □--- Input Volt. 200V - - ○--- Input Volt. 230V			2.Values																																																			
																																																						
Note: Slanted line shows the range of the rated load current.																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>3.0</td><td>160</td><td>159</td><td>160</td></tr> <tr> <td>6.0</td><td>81</td><td>81</td><td>82</td></tr> <tr> <td>9.0</td><td>55</td><td>56</td><td>55</td></tr> <tr> <td>12.0</td><td>40</td><td>41</td><td>40</td></tr> <tr> <td>15.0</td><td>32</td><td>32</td><td>32</td></tr> <tr> <td>18.0</td><td>28</td><td>28</td><td>27</td></tr> <tr> <td>21.0</td><td>-</td><td>23</td><td>23</td></tr> <tr> <td>22.7</td><td>-</td><td>21</td><td>22</td></tr> <tr> <td>25.0</td><td>-</td><td>20</td><td>19</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	3.0	160	159	160	6.0	81	81	82	9.0	55	56	55	12.0	40	41	40	15.0	32	32	32	18.0	28	28	27	21.0	-	23	23	22.7	-	21	22	25.0	-	20	19	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
3.0	160	159	160																																																			
6.0	81	81	82																																																			
9.0	55	56	55																																																			
12.0	40	41	40																																																			
15.0	32	32	32																																																			
18.0	28	28	27																																																			
21.0	-	23	23																																																			
22.7	-	21	22																																																			
25.0	-	20	19																																																			
--	-	-	-																																																			

**COSEL**

Model	AEA800F-36		
Item	Overcurrent Protection	Temperature Testing Circuitry	25°C Figure A
Object	+36V22.7A		
1.Graph			
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> <li>100V</li> <li>200V</li> <li>230V</li> </ul>			
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Overcurrent protection is Hiccup mode</p>			
2.Values			
Output Voltage [V]	Load Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
36	52.23	57.20	57.20
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	AEA800F-36	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+36V22.7A	

## 1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-20	36.257	36.257	36.257
25	36.431	36.431	36.432
50	36.484	36.484	36.484

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A	
Object	+36V22.7A		

## 1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	72	72
25	72	72
50	72	72

Item	Overvoltage Protection	Testing Circuitry Figure A	
Object	+36V22.7A		

## 1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 200V
-20	47.12	46.60
25	48.52	48.52
50	49.51	49.51

**COSEL**




Figure A




Figure B-1 ( DEN-AN )




Figure B-2 ( IEC62368-1 refer to IEC60990 Fig.4 )

**COSEL**




Figure B-3 ( IEC62368-1 refer to IEC60990 Fig.5 )




Figure B-4 ( IEC60601-1)




Figure C