



TEST DATA OF CBS2004812

(48V INPUT)

Regulated DC Power Supply
Feb. 21, 2001

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Atsushi Yoshiyama
Atsushi Yoshiyama Design Engineer

コーワセル株式会社
COSEL CO., LTD.

C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSSEL

Model	CBS2004812	Temperature	25°C																																
Item	Line Regulation 静的の入力変動	Testing Circuitry	Figure A																																
Object	+12V16.7A																																		
1. Graph		2. Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>11.967</td><td>11.965</td></tr> <tr><td>36</td><td>11.966</td><td>11.964</td></tr> <tr><td>40</td><td>11.966</td><td>11.964</td></tr> <tr><td>48</td><td>11.966</td><td>11.964</td></tr> <tr><td>55</td><td>11.966</td><td>11.964</td></tr> <tr><td>60</td><td>11.966</td><td>11.963</td></tr> <tr><td>70</td><td>11.966</td><td>11.963</td></tr> <tr><td>76</td><td>11.966</td><td>11.963</td></tr> <tr><td>80</td><td>11.965</td><td>11.963</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	11.967	11.965	36	11.966	11.964	40	11.966	11.964	48	11.966	11.964	55	11.966	11.964	60	11.966	11.963	70	11.966	11.963	76	11.966	11.963	80	11.965	11.963
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
33	11.967	11.965																																	
36	11.966	11.964																																	
40	11.966	11.964																																	
48	11.966	11.964																																	
55	11.966	11.964																																	
60	11.966	11.963																																	
70	11.966	11.963																																	
76	11.966	11.963																																	
80	11.965	11.963																																	

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。


COSEL

Model	CBS2004812	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object																																																																										
1. Graph																																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>30.6</td><td>0.081</td><td>3.693</td><td>7.334</td></tr> <tr><td>31.4</td><td>0.079</td><td>3.578</td><td>7.310</td></tr> <tr><td>33.0</td><td>0.076</td><td>3.378</td><td>6.880</td></tr> <tr><td>36.0</td><td>0.070</td><td>3.068</td><td>6.230</td></tr> <tr><td>40.0</td><td>0.060</td><td>2.750</td><td>5.560</td></tr> <tr><td>48.0</td><td>0.049</td><td>2.288</td><td>4.590</td></tr> <tr><td>60.0</td><td>0.044</td><td>1.840</td><td>3.654</td></tr> <tr><td>70.0</td><td>0.040</td><td>1.582</td><td>3.132</td></tr> <tr><td>76.0</td><td>0.037</td><td>1.463</td><td>2.886</td></tr> <tr><td>80.0</td><td>0.037</td><td>1.394</td><td>2.744</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.009	0.009	0.009	30.6	0.081	3.693	7.334	31.4	0.079	3.578	7.310	33.0	0.076	3.378	6.880	36.0	0.070	3.068	6.230	40.0	0.060	2.750	5.560	48.0	0.049	2.288	4.590	60.0	0.044	1.840	3.654	70.0	0.040	1.582	3.132	76.0	0.037	1.463	2.886	80.0	0.037	1.394	2.744	--	--	--	--	--	--	--	--	--	--	--	--
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
8.0	0.000	0.000	0.000																																																																							
16.0	0.000	0.000	0.000																																																																							
24.0	0.009	0.009	0.009																																																																							
30.6	0.081	3.693	7.334																																																																							
31.4	0.079	3.578	7.310																																																																							
33.0	0.076	3.378	6.880																																																																							
36.0	0.070	3.068	6.230																																																																							
40.0	0.060	2.750	5.560																																																																							
48.0	0.049	2.288	4.590																																																																							
60.0	0.044	1.840	3.654																																																																							
70.0	0.040	1.582	3.132																																																																							
76.0	0.037	1.463	2.886																																																																							
80.0	0.037	1.394	2.744																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。


COSSEL

Model	CBS2004812																																																				
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																		
Object	_____																																																				
1. Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> 																																																				
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.070</td><td>0.050</td><td>0.037</td></tr> <tr><td>3.0</td><td>1.167</td><td>0.875</td><td>0.578</td></tr> <tr><td>6.0</td><td>2.249</td><td>1.679</td><td>1.083</td></tr> <tr><td>9.0</td><td>3.369</td><td>2.510</td><td>1.600</td></tr> <tr><td>12.0</td><td>4.535</td><td>3.362</td><td>2.132</td></tr> <tr><td>15.0</td><td>5.750</td><td>4.242</td><td>2.676</td></tr> <tr><td>16.7</td><td>6.460</td><td>4.750</td><td>2.986</td></tr> <tr><td>18.4</td><td>7.200</td><td>5.280</td><td>3.308</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.070	0.050	0.037	3.0	1.167	0.875	0.578	6.0	2.249	1.679	1.083	9.0	3.369	2.510	1.600	12.0	4.535	3.362	2.132	15.0	5.750	4.242	2.676	16.7	6.460	4.750	2.986	18.4	7.200	5.280	3.308	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.0	0.070	0.050	0.037																																																		
3.0	1.167	0.875	0.578																																																		
6.0	2.249	1.679	1.083																																																		
9.0	3.369	2.510	1.600																																																		
12.0	4.535	3.362	2.132																																																		
15.0	5.750	4.242	2.676																																																		
16.7	6.460	4.750	2.986																																																		
18.4	7.200	5.280	3.308																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS2004812	Temperature	25°C																																																					
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Testing Circuitry	Figure A																																																					
Object	<hr/>																																																							
1. Graph																																																								
—△— Input Volt. 36V - - -□--- Input Volt. 48V - - ○--- Input Volt. 76V			2. Values																																																					
 <p>The graph plots Input Power [W] on the Y-axis (0 to 500) against Load Current [A] on the X-axis (0 to 20). Three curves are shown for different input voltages: 36V (solid line with open triangle markers), 48V (dashed line with open square markers), and 76V (dash-dot line with open circle markers). All curves show a linear increase in power with load current. A diagonal hatched line represents the rated load current range, which is approximately between 12.0A and 16.7A.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.5</td><td>2.4</td><td>2.9</td></tr> <tr><td>3.0</td><td>41.9</td><td>41.9</td><td>43.9</td></tr> <tr><td>6.0</td><td>80.5</td><td>80.2</td><td>82.4</td></tr> <tr><td>9.0</td><td>119.9</td><td>119.8</td><td>121.6</td></tr> <tr><td>12.0</td><td>160.7</td><td>160.0</td><td>162.2</td></tr> <tr><td>15.0</td><td>203.1</td><td>201.4</td><td>203.1</td></tr> <tr><td>16.7</td><td>227.5</td><td>225.4</td><td>226.5</td></tr> <tr><td>18.4</td><td>252.9</td><td>250.0</td><td>250.7</td></tr> <tr><td>---</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>---</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>---</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	2.5	2.4	2.9	3.0	41.9	41.9	43.9	6.0	80.5	80.2	82.4	9.0	119.9	119.8	121.6	12.0	160.7	160.0	162.2	15.0	203.1	201.4	203.1	16.7	227.5	225.4	226.5	18.4	252.9	250.0	250.7	---	-	-	-	---	-	-	-	---	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.0	2.5	2.4	2.9																																																					
3.0	41.9	41.9	43.9																																																					
6.0	80.5	80.2	82.4																																																					
9.0	119.9	119.8	121.6																																																					
12.0	160.7	160.0	162.2																																																					
15.0	203.1	201.4	203.1																																																					
16.7	227.5	225.4	226.5																																																					
18.4	252.9	250.0	250.7																																																					
---	-	-	-																																																					
---	-	-	-																																																					
---	-	-	-																																																					
Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。																																																								

COSEL

Model	CBS2004812	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (72 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>33</td><td>88.9</td><td>87.0</td></tr> <tr><td>36</td><td>89.3</td><td>87.5</td></tr> <tr><td>40</td><td>89.5</td><td>87.9</td></tr> <tr><td>48</td><td>89.5</td><td>88.2</td></tr> <tr><td>55</td><td>89.2</td><td>88.3</td></tr> <tr><td>60</td><td>88.9</td><td>88.3</td></tr> <tr><td>70</td><td>88.4</td><td>87.8</td></tr> <tr><td>76</td><td>88.0</td><td>87.7</td></tr> <tr><td>80</td><td>87.8</td><td>87.7</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	33	88.9	87.0	36	89.3	87.5	40	89.5	87.9	48	89.5	88.2	55	89.2	88.3	60	88.9	88.3	70	88.4	87.8	76	88.0	87.7	80	87.8	87.7
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
33	88.9	87.0																													
36	89.3	87.5																													
40	89.5	87.9																													
48	89.5	88.2																													
55	89.2	88.3																													
60	88.9	88.3																													
70	88.4	87.8																													
76	88.0	87.7																													
80	87.8	87.7																													
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																															

COSEL

Model	CBS2004812	Temperature Testing Circuitry	25°C Figure A																																																																										
Item	Efficiency (by Load Current) 効率(負荷特性)																																																																												
Object	_____																																																																												
1. Graph		2. Values																																																																											
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] (%)</th> <th>Efficiency [48V] (%)</th> <th>Efficiency [76V] (%)</th> </tr> </thead> <tbody> <tr><td>4</td><td>85.0</td><td>85.0</td><td>80.9</td></tr> <tr><td>8</td><td>88.7</td><td>89.0</td><td>86.6</td></tr> <tr><td>12</td><td>89.4</td><td>89.5</td><td>88.2</td></tr> <tr><td>16</td><td>89.0</td><td>89.4</td><td>88.2</td></tr> <tr><td>20</td><td>88.1</td><td>88.8</td><td>88.0</td></tr> </tbody> </table>	Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)	4	85.0	85.0	80.9	8	88.7	89.0	86.6	12	89.4	89.5	88.2	16	89.0	89.4	88.2	20	88.1	88.8	88.0	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>85.0</td><td>85.0</td><td>80.9</td></tr> <tr><td>6.0</td><td>88.7</td><td>89.0</td><td>86.6</td></tr> <tr><td>9.0</td><td>89.4</td><td>89.5</td><td>88.2</td></tr> <tr><td>12.0</td><td>89.0</td><td>89.4</td><td>88.2</td></tr> <tr><td>15.0</td><td>88.1</td><td>88.8</td><td>88.0</td></tr> <tr><td>16.7</td><td>87.4</td><td>88.2</td><td>87.8</td></tr> <tr><td>18.4</td><td>86.7</td><td>87.7</td><td>87.5</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	3.0	85.0	85.0	80.9	6.0	88.7	89.0	86.6	9.0	89.4	89.5	88.2	12.0	89.0	89.4	88.2	15.0	88.1	88.8	88.0	16.7	87.4	88.2	87.8	18.4	86.7	87.7	87.5	—	-	-	-	—	-	-	-	—	-	-	-
Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)																																																																										
4	85.0	85.0	80.9																																																																										
8	88.7	89.0	86.6																																																																										
12	89.4	89.5	88.2																																																																										
16	89.0	89.4	88.2																																																																										
20	88.1	88.8	88.0																																																																										
Load Current [A]	Efficiency [%]																																																																												
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																										
0.0	-	-	-																																																																										
3.0	85.0	85.0	80.9																																																																										
6.0	88.7	89.0	86.6																																																																										
9.0	89.4	89.5	88.2																																																																										
12.0	89.0	89.4	88.2																																																																										
15.0	88.1	88.8	88.0																																																																										
16.7	87.4	88.2	87.8																																																																										
18.4	86.7	87.7	87.5																																																																										
—	-	-	-																																																																										
—	-	-	-																																																																										
—	-	-	-																																																																										

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。



COSSEL

Model	CBS2004812																																																	
Item	Load Regulation 静的負荷変動	Temperature Testing Circuitry	25°C Figure A																																															
Object	+12V16.7A																																																	
1. Graph																																																		
			2. Values																																															
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11.968</td><td>11.966</td><td>11.965</td></tr> <tr><td>3.0</td><td>11.967</td><td>11.966</td><td>11.965</td></tr> <tr><td>6.0</td><td>11.967</td><td>11.966</td><td>11.965</td></tr> <tr><td>9.0</td><td>11.967</td><td>11.966</td><td>11.965</td></tr> <tr><td>12.0</td><td>11.967</td><td>11.965</td><td>11.965</td></tr> <tr><td>15.0</td><td>11.967</td><td>11.966</td><td>11.965</td></tr> <tr><td>16.7</td><td>11.967</td><td>11.965</td><td>11.965</td></tr> <tr><td>18.4</td><td>11.967</td><td>11.965</td><td>11.965</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	11.968	11.966	11.965	3.0	11.967	11.966	11.965	6.0	11.967	11.966	11.965	9.0	11.967	11.966	11.965	12.0	11.967	11.965	11.965	15.0	11.967	11.966	11.965	16.7	11.967	11.965	11.965	18.4	11.967	11.965	11.965	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																															
0.0	11.968	11.966	11.965																																															
3.0	11.967	11.966	11.965																																															
6.0	11.967	11.966	11.965																																															
9.0	11.967	11.966	11.965																																															
12.0	11.967	11.965	11.965																																															
15.0	11.967	11.966	11.965																																															
16.7	11.967	11.965	11.965																																															
18.4	11.967	11.965	11.965																																															
--	-	-	-																																															
--	-	-	-																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																		

COSEL

Model	CBS2004812	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Testing Circuitry	Figure A																																						
Object	+12V16.7A																																								
1. Graph			2. Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>3.3</td><td>10</td><td>15</td></tr> <tr><td>6.7</td><td>10</td><td>15</td></tr> <tr><td>10.0</td><td>10</td><td>15</td></tr> <tr><td>13.4</td><td>10</td><td>15</td></tr> <tr><td>16.7</td><td>10</td><td>15</td></tr> <tr><td>20.0</td><td>10</td><td>15</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.0	5	5	3.3	10	15	6.7	10	15	10.0	10	15	13.4	10	15	16.7	10	15	20.0	10	15	---	—	—	---	—	—	---	—	—	---	—	—
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.0	5	5																																							
3.3	10	15																																							
6.7	10	15																																							
10.0	10	15																																							
13.4	10	15																																							
16.7	10	15																																							
20.0	10	15																																							
---	—	—																																							
---	—	—																																							
---	—	—																																							
---	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形図</p>																																									

COSSEL

Model	CBS2004812																																							
Item	Ripple-Noise リップルノイズ	Temperature Testing Circuitry 25°C Figure A																																						
Object	+12V16.7A																																							
1. Graph																																								
<p style="text-align: center;"> —△— Input Volt. 36V ---○--- Input Volt. 76V </p> 																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>20</td></tr> <tr><td>3.3</td><td>30</td><td>30</td></tr> <tr><td>6.7</td><td>30</td><td>40</td></tr> <tr><td>10.0</td><td>35</td><td>40</td></tr> <tr><td>13.4</td><td>40</td><td>40</td></tr> <tr><td>16.7</td><td>50</td><td>45</td></tr> <tr><td>20.0</td><td>55</td><td>50</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.0	15	20	3.3	30	30	6.7	30	40	10.0	35	40	13.4	40	40	16.7	50	45	20.0	55	50	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.0	15	20																																						
3.3	30	30																																						
6.7	30	40																																						
10.0	35	40																																						
13.4	40	40																																						
16.7	50	45																																						
20.0	55	50																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図p-p値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																								
																																								
<p>Fig. Complex Ripple Noise Wave Form 図 リップルノイズ波形</p>																																								

COSEL

Model	CBS2004812
Item	Overcurrent Protection 過電流保護
Object	+12V16.7A

1. Graph

Output Voltage [V]

Load Current [A]

Note: Slanted line shows the range of the rated load current.
(注) 斜線は定格負荷電流範囲を示す。

Intermittent operation occurs when the output voltage is from 8V to 0V.
8V～0V間は、間欠モードとなる。


Temperature 25°C
Testing Circuitry Figure A

2. Values








Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
12.0	18.79	20.59	20.46
11.4	21.98	21.85	22.43
10.8	21.91	21.90	22.54
9.6	22.07	21.99	22.75
8.4	22.04	22.07	23.00
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--

COSEL

Model	CBS2004812	Testing Circuitry Figure A																																																					
Item	Overvoltage Protection 過電圧保護																																																						
Object	+12V16.7A																																																						
1. Graph	<p>—△— Input Volt. 36V - - -□--- Input Volt. 48V - - -○--- Input Volt. 76V</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>15.51</td><td>15.51</td><td>15.51</td></tr> <tr> <td>-40</td><td>15.51</td><td>15.51</td><td>15.51</td></tr> <tr> <td>-20</td><td>15.50</td><td>15.50</td><td>15.50</td></tr> <tr> <td>0</td><td>15.50</td><td>15.50</td><td>15.50</td></tr> <tr> <td>25</td><td>15.50</td><td>15.50</td><td>15.50</td></tr> <tr> <td>40</td><td>15.50</td><td>15.50</td><td>15.50</td></tr> <tr> <td>60</td><td>15.49</td><td>15.49</td><td>15.49</td></tr> <tr> <td>85</td><td>15.49</td><td>15.49</td><td>15.49</td></tr> <tr> <td>100</td><td>15.42</td><td>15.42</td><td>15.42</td></tr> <tr> <td>105</td><td>15.41</td><td>15.41</td><td>15.41</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Operating Point [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-50	15.51	15.51	15.51	-40	15.51	15.51	15.51	-20	15.50	15.50	15.50	0	15.50	15.50	15.50	25	15.50	15.50	15.50	40	15.50	15.50	15.50	60	15.49	15.49	15.49	85	15.49	15.49	15.49	100	15.42	15.42	15.42	105	15.41	15.41	15.41	--	-	-	-
Ambient Temperature [°C]	Operating Point [V]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
-50	15.51	15.51	15.51																																																				
-40	15.51	15.51	15.51																																																				
-20	15.50	15.50	15.50																																																				
0	15.50	15.50	15.50																																																				
25	15.50	15.50	15.50																																																				
40	15.50	15.50	15.50																																																				
60	15.49	15.49	15.49																																																				
85	15.49	15.49	15.49																																																				
100	15.42	15.42	15.42																																																				
105	15.41	15.41	15.41																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							
(注) 斜線は定格周囲温度範囲を示す。																																																							


COSEL

CSEL

Model	CBS2004812	Temperature	25°C		
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A		
Object	+12V16.7A				
1. Graph					
Output Volt.	Load 50%	Input Volt. 36 V			
[2V/div]					
Output Volt.	Load 100%				
[2V/div]					
Input Volt.					
[10V/div]					
Time	[50mS/div]	Time	[10mS/div]		
2. Values [mS]					
Load	T _d	T _r	T _s	T _h	T _f
50 %	16.3	6.3	22.5	0.2	4.1
100 %	16.3	6.3	22.5	0.2	2.0
					



Model	CBS2004812
Item	Ambient Temperature Drift 周囲温度変動
Object	+12V16.7A



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-50	12.002	12.002	12.002
-40	12.000	12.000	12.000
-20	11.996	11.996	11.996
0	11.993	11.993	11.993
25	11.982	11.981	11.982
40	11.970	11.969	11.969
60	11.950	11.950	11.949
85	11.920	11.919	11.919
100	11.900	11.900	11.899
105	11.891	11.891	11.891
--	-	-	-



		Testing Circuitry Figure A																																							
Model	CBS2004812																																								
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧																																								
Object	+12V16.7A																																								
1. Graph			2. Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>28.1</td><td>28.7</td> </tr> <tr> <td>-40</td><td>28.1</td><td>28.7</td> </tr> <tr> <td>-20</td><td>28.1</td><td>29.1</td> </tr> <tr> <td>0</td><td>28.1</td><td>29.2</td> </tr> <tr> <td>25</td><td>28.1</td><td>29.6</td> </tr> <tr> <td>40</td><td>28.1</td><td>29.8</td> </tr> <tr> <td>60</td><td>28.3</td><td>30.0</td> </tr> <tr> <td>85</td><td>28.3</td><td>30.1</td> </tr> <tr> <td>100</td><td>28.3</td><td>30.3</td> </tr> <tr> <td>105</td><td>28.3</td><td>30.5</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	28.1	28.7	-40	28.1	28.7	-20	28.1	29.1	0	28.1	29.2	25	28.1	29.6	40	28.1	29.8	60	28.3	30.0	85	28.3	30.1	100	28.3	30.3	105	28.3	30.5	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-50	28.1	28.7																																							
-40	28.1	28.7																																							
-20	28.1	29.1																																							
0	28.1	29.2																																							
25	28.1	29.6																																							
40	28.1	29.8																																							
60	28.3	30.0																																							
85	28.3	30.1																																							
100	28.3	30.3																																							
105	28.3	30.5																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																									


COSSEL

Model	CBS2004812																																							
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																							
Object	+12V16.7A																																							
1. Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from -60 to 100 °C. Two data series are plotted: Load 50% (squares) and Load 100% (triangles). Both series show a decrease in ripple voltage as ambient temperature increases. A slanted line indicates the rated ambient temperature range.</p> <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (Load 50%)</th> <th>Ripple Voltage [mV] (Load 100%)</th> </tr> </thead> <tbody> <tr><td>-50</td><td>115</td><td>115</td></tr> <tr><td>-40</td><td>95</td><td>95</td></tr> <tr><td>-20</td><td>45</td><td>45</td></tr> <tr><td>0</td><td>20</td><td>20</td></tr> <tr><td>25</td><td>15</td><td>15</td></tr> <tr><td>40</td><td>10</td><td>10</td></tr> <tr><td>60</td><td>10</td><td>10</td></tr> <tr><td>85</td><td>10</td><td>10</td></tr> <tr><td>100</td><td>15</td><td>10</td></tr> <tr><td>105</td><td>15</td><td>15</td></tr> <tr><td>--</td><td>—</td><td>—</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV] (Load 50%)	Ripple Voltage [mV] (Load 100%)	-50	115	115	-40	95	95	-20	45	45	0	20	20	25	15	15	40	10	10	60	10	10	85	10	10	100	15	10	105	15	15	--	—	—			
Ambient Temperature [°C]	Ripple Voltage [mV] (Load 50%)	Ripple Voltage [mV] (Load 100%)																																						
-50	115	115																																						
-40	95	95																																						
-20	45	45																																						
0	20	20																																						
25	15	15																																						
40	10	10																																						
60	10	10																																						
85	10	10																																						
100	15	10																																						
105	15	15																																						
--	—	—																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>115</td><td>115</td></tr> <tr><td>-40</td><td>95</td><td>95</td></tr> <tr><td>-20</td><td>45</td><td>45</td></tr> <tr><td>0</td><td>20</td><td>20</td></tr> <tr><td>25</td><td>15</td><td>15</td></tr> <tr><td>40</td><td>10</td><td>10</td></tr> <tr><td>60</td><td>10</td><td>10</td></tr> <tr><td>85</td><td>10</td><td>10</td></tr> <tr><td>100</td><td>15</td><td>10</td></tr> <tr><td>105</td><td>15</td><td>15</td></tr> <tr><td>--</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-50	115	115	-40	95	95	-20	45	45	0	20	20	25	15	15	40	10	10	60	10	10	85	10	10	100	15	10	105	15	15	--	—	—
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-50	115	115																																						
-40	95	95																																						
-20	45	45																																						
0	20	20																																						
25	15	15																																						
40	10	10																																						
60	10	10																																						
85	10	10																																						
100	15	10																																						
105	15	15																																						
--	—	—																																						

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model	CBS2004812	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+12V16.7A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11.975</td></tr> <tr><td>0.5</td><td>11.960</td></tr> <tr><td>1.0</td><td>11.960</td></tr> <tr><td>2.0</td><td>11.960</td></tr> <tr><td>3.0</td><td>11.960</td></tr> <tr><td>4.0</td><td>11.960</td></tr> <tr><td>5.0</td><td>11.961</td></tr> <tr><td>6.0</td><td>11.961</td></tr> <tr><td>7.0</td><td>11.961</td></tr> <tr><td>8.0</td><td>11.961</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	11.975	0.5	11.960	1.0	11.960	2.0	11.960	3.0	11.960	4.0	11.960	5.0	11.961	6.0	11.961	7.0	11.961	8.0	11.961
Time since start [H]	Output Voltage [V]																								
0.0	11.975																								
0.5	11.960																								
1.0	11.960																								
2.0	11.960																								
3.0	11.960																								
4.0	11.960																								
5.0	11.961																								
6.0	11.961																								
7.0	11.961																								
8.0	11.961																								



Model	CBS2004812	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+12V16.7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 100°C

Input Voltage : 36 ~ 76V

Load Current : 0 ~ 16.7A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -40 ~ 100°C

入力電圧 : 36 ~ 76V

負荷電流 : 0 ~ 16.7A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	36	0	12.000	±53	±0.4
Minimum Voltage	100	76	16.7	11.894		



Model	CBS2004812	Testing Circuitry Figure A
Item	Condense 結露特性	
Object	+12V16.7A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	12.064	Input Volt. :48V, Load Current. :16.7A
Line Regulation [mV]	2	Input Volt. :36~76V, Load Current. :16.7A
Load Regulation [mV]	1	Input Volt. :48V, Load Current. :0~16.7A

COSEL

Model	CBS2004812	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure B
Object	+12V16.7A		

1. Conditions

- Input Voltage : 48 V
- Pulse Input Duration : 1 min. or more
- Pulse Voltage : 2000 V
- Load : 100 %
- Pulse Cycle : 16.7 ms

2. Results

Pulse Width [ns]	MODE	No protection failure should occur		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY	保護回路の誤動作がない	
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation






Figure C

C1 : 100V 33 μ F

C2 : 4700pF

C3 : 50V 0.1 μ F(-40°C ≤ T_B ≤ -20°C)

C4 : CBS2004803, 05

CBS2004812, 15

CBS2004824, 28

10V 2200 μ F × 225V 1000 μ F × 235V 470 μ F × 2(-20°C < T_B ≤ 100°C)

C4 : CBS2004803, 05

CBS2004812, 15

CBS2004824, 28

10V 2200 μ F25V 1000 μ F35V 470 μ FT_B:Base Plate Temp.