

TEST DATA OF CBS502405

(24V INPUT)

Regulated DC Power Supply

Approved by : Isao Yasuda Design Manager

Prepared by : Kouichi Kinoshita Design Engineer


**コーセル株式会社
COSEL CO.,LTD.**



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

Model	CBS502405	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation 静的入力変動																																	
Object	+5V10A																																	
1. Graph		2. Values																																
 <p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>5.075</td><td>5.075</td></tr> <tr><td>18</td><td>5.075</td><td>5.075</td></tr> <tr><td>20</td><td>5.075</td><td>5.075</td></tr> <tr><td>24</td><td>5.075</td><td>5.075</td></tr> <tr><td>30</td><td>5.075</td><td>5.075</td></tr> <tr><td>36</td><td>5.075</td><td>5.075</td></tr> <tr><td>40</td><td>5.075</td><td>5.075</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	5.075	5.075	18	5.075	5.075	20	5.075	5.075	24	5.075	5.075	30	5.075	5.075	36	5.075	5.075	40	5.075	5.075	—	—	—	—	—	—
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
17	5.075	5.075																																
18	5.075	5.075																																
20	5.075	5.075																																
24	5.075	5.075																																
30	5.075	5.075																																
36	5.075	5.075																																
40	5.075	5.075																																
—	—	—																																
—	—	—																																

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

Model	CBS502405	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object	—	—	—																																																																							
1. Graph		2. Values																																																																								
<p>The graph plots Input Current [A] on the y-axis (0.0 to 5.0) against Input Voltage [V] on the x-axis (0 to 50). Three data series are shown: Load 100% (triangles), Load 50% (squares), and Load 0% (circles). All series show a sharp increase in current from 0V to approximately 15V, followed by a gradual decrease. A slanted line is drawn through the peak of the Load 100% curve, indicating the rated input voltage range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.019</td></tr> <tr><td>12.0</td><td>0.015</td><td>0.015</td><td>0.015</td></tr> <tr><td>15.6</td><td>0.091</td><td>1.980</td><td>3.729</td></tr> <tr><td>16.0</td><td>0.090</td><td>1.918</td><td>3.765</td></tr> <tr><td>18.0</td><td>0.084</td><td>1.678</td><td>3.324</td></tr> <tr><td>20.0</td><td>0.079</td><td>1.509</td><td>2.978</td></tr> <tr><td>24.0</td><td>0.072</td><td>1.262</td><td>2.487</td></tr> <tr><td>28.0</td><td>0.066</td><td>1.089</td><td>2.134</td></tr> <tr><td>32.0</td><td>0.063</td><td>0.958</td><td>1.866</td></tr> <tr><td>36.0</td><td>0.060</td><td>0.857</td><td>1.658</td></tr> <tr><td>40.0</td><td>0.058</td><td>0.777</td><td>1.501</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.019	12.0	0.015	0.015	0.015	15.6	0.091	1.980	3.729	16.0	0.090	1.918	3.765	18.0	0.084	1.678	3.324	20.0	0.079	1.509	2.978	24.0	0.072	1.262	2.487	28.0	0.066	1.089	2.134	32.0	0.063	0.958	1.866	36.0	0.060	0.857	1.658	40.0	0.058	0.777	1.501	---	—	—	—	---	—	—	—	---	—	—	—
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
4.0	0.000	0.000	0.000																																																																							
8.0	0.000	0.000	0.019																																																																							
12.0	0.015	0.015	0.015																																																																							
15.6	0.091	1.980	3.729																																																																							
16.0	0.090	1.918	3.765																																																																							
18.0	0.084	1.678	3.324																																																																							
20.0	0.079	1.509	2.978																																																																							
24.0	0.072	1.262	2.487																																																																							
28.0	0.066	1.089	2.134																																																																							
32.0	0.063	0.958	1.866																																																																							
36.0	0.060	0.857	1.658																																																																							
40.0	0.058	0.777	1.501																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

Model	CBS502405	Temperature	25°C																																																			
Item	Input Current (by Load Current) 入力電流（負荷特性）	Testing Circuitry	Figure A																																																			
Object	—	—	—																																																			
1. Graph		2. Values																																																				
<p>The graph shows three curves representing different input voltages: 18V (solid line with triangles), 24V (dashed line with squares), and 36V (dash-dot line with circles). The x-axis is labeled "Load Current [A]" and ranges from 0 to 12. The y-axis is labeled "Input Current [A]" and ranges from 0.0 to 5.0. A diagonal slanted line is drawn across the graph, representing the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.084</td><td>0.071</td><td>0.060</td></tr> <tr><td>1.5</td><td>0.573</td><td>0.438</td><td>0.303</td></tr> <tr><td>3.0</td><td>1.047</td><td>0.791</td><td>0.544</td></tr> <tr><td>4.5</td><td>1.531</td><td>1.150</td><td>0.780</td></tr> <tr><td>6.0</td><td>2.033</td><td>1.515</td><td>1.021</td></tr> <tr><td>7.5</td><td>2.544</td><td>1.892</td><td>1.264</td></tr> <tr><td>9.0</td><td>3.070</td><td>2.274</td><td>1.512</td></tr> <tr><td>10.0</td><td>3.428</td><td>2.532</td><td>1.680</td></tr> <tr><td>11.0</td><td>3.791</td><td>2.794</td><td>1.852</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.084	0.071	0.060	1.5	0.573	0.438	0.303	3.0	1.047	0.791	0.544	4.5	1.531	1.150	0.780	6.0	2.033	1.515	1.021	7.5	2.544	1.892	1.264	9.0	3.070	2.274	1.512	10.0	3.428	2.532	1.680	11.0	3.791	2.794	1.852	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.0	0.084	0.071	0.060																																																			
1.5	0.573	0.438	0.303																																																			
3.0	1.047	0.791	0.544																																																			
4.5	1.531	1.150	0.780																																																			
6.0	2.033	1.515	1.021																																																			
7.5	2.544	1.892	1.264																																																			
9.0	3.070	2.274	1.512																																																			
10.0	3.428	2.532	1.680																																																			
11.0	3.791	2.794	1.852																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.


(注) 斜線は定格負荷電流範囲を示す。

Model	CBS502405																																																					
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	<hr/>																																																					
1. Graph																																																						
<p>The graph plots Input Power [W] on the Y-axis (0 to 100) against Load Current [A] on the X-axis (0 to 12). Three curves are shown for Input Voltages: 18V (solid line with open triangle markers), 24V (dashed line with open square markers), and 36V (dash-dot line with open circle markers). All curves start at (0,0) and increase linearly. A slanted line is drawn through the points (4.5, 27.19) and (11.0, 66.30), representing the rated load current range.</p>			2. Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.50</td><td>1.72</td><td>2.17</td></tr> <tr><td>1.5</td><td>10.25</td><td>10.47</td><td>10.94</td></tr> <tr><td>3.0</td><td>18.67</td><td>18.86</td><td>19.60</td></tr> <tr><td>4.5</td><td>27.19</td><td>27.41</td><td>28.10</td></tr> <tr><td>6.0</td><td>36.00</td><td>36.05</td><td>36.70</td></tr> <tr><td>7.5</td><td>44.90</td><td>45.00</td><td>45.50</td></tr> <tr><td>9.0</td><td>53.90</td><td>53.90</td><td>54.30</td></tr> <tr><td>10.0</td><td>60.10</td><td>59.90</td><td>60.20</td></tr> <tr><td>11.0</td><td>66.30</td><td>66.00</td><td>66.60</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	1.50	1.72	2.17	1.5	10.25	10.47	10.94	3.0	18.67	18.86	19.60	4.5	27.19	27.41	28.10	6.0	36.00	36.05	36.70	7.5	44.90	45.00	45.50	9.0	53.90	53.90	54.30	10.0	60.10	59.90	60.20	11.0	66.30	66.00	66.60	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.0	1.50	1.72	2.17																																																			
1.5	10.25	10.47	10.94																																																			
3.0	18.67	18.86	19.60																																																			
4.5	27.19	27.41	28.10																																																			
6.0	36.00	36.05	36.70																																																			
7.5	44.90	45.00	45.50																																																			
9.0	53.90	53.90	54.30																																																			
10.0	60.10	59.90	60.20																																																			
11.0	66.30	66.00	66.60																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																						

Model	CBS502405
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
16	82.5	83.3
18	83.9	84.1
20	83.9	84.3
24	83.3	84.3
30	82.4	84.0
36	81.6	83.9
40	80.9	83.7
—	—	—
—	—	—

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.0	—	—	—
1.5	73.3	71.7	68.6
3.0	80.9	80.1	77.0
4.5	83.5	82.8	80.7
6.0	84.1	84.0	82.5
7.5	84.4	84.2	83.3
9.0	84.4	84.4	83.7
10.0	84.1	84.4	83.9
11.0	83.8	84.2	83.5
--	—	—	—
--	—	—	—


Model	CBS502405	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+5V10A																																																	
1. Graph																																																		
<p>—▲— Input Volt. 18V - - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p>																																																		
2. Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>1.5</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>3.0</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>4.5</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>6.0</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>7.5</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>9.0</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>10.0</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>11.0</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	5.075	5.075	5.075	1.5	5.075	5.075	5.075	3.0	5.075	5.075	5.075	4.5	5.075	5.075	5.075	6.0	5.075	5.075	5.075	7.5	5.075	5.075	5.075	9.0	5.075	5.075	5.075	10.0	5.075	5.075	5.075	11.0	5.075	5.075	5.075	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																															
0.0	5.075	5.075	5.075																																															
1.5	5.075	5.075	5.075																																															
3.0	5.075	5.075	5.075																																															
4.5	5.075	5.075	5.075																																															
6.0	5.075	5.075	5.075																																															
7.5	5.075	5.075	5.075																																															
9.0	5.075	5.075	5.075																																															
10.0	5.075	5.075	5.075																																															
11.0	5.075	5.075	5.075																																															
—	—	—	—																																															
Note: Slanted line shows the range of the rated load current.																																																		
(注) 斜線は定格負荷電流範囲を示す。																																																		

Model	CBS502405	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Testing Circuitry	Figure A																																						
Object	+5V10A																																								
1. Graph			2. Values																																						
<p>Y-axis: Ripple Voltage [mV] (0 to 50) X-axis: Load Current [A] (0 to 12)</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>2</td><td>10</td><td>20</td></tr> <tr><td>4</td><td>10</td><td>20</td></tr> <tr><td>6</td><td>10</td><td>20</td></tr> <tr><td>8</td><td>10</td><td>20</td></tr> <tr><td>10</td><td>10</td><td>20</td></tr> <tr><td>12</td><td>10</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	5	5	2	10	20	4	10	20	6	10	20	8	10	20	10	10	20	12	10	20	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 18 [V]	Input Volt. 36 [V]																																							
0	5	5																																							
2	10	20																																							
4	10	20																																							
6	10	20																																							
8	10	20																																							
10	10	20																																							
12	10	20																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

Model	CBS502405
Item	Ripple-Noise リップルノイズ
Object	+5V10A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0	10	15
2	15	25
4	15	25
6	20	25
8	20	25
10	20	25
12	25	25
—	—	—
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。





Fig. Complex Ripple Noise Wave Form
図 リップルノイズ波形

Model	CBS502405	Temperature	25°C																																																							
Item	Overcurrent Protection 過電流保護	Testing Circuitry	Figure A																																																							
Object	+5V10A																																																									
1. Graph		————— Input Volt. 18V Input Volt. 24V Input Volt. 36V																																																								
			2. Values																																																							
Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>10.27</td><td>10.10</td><td>10.10</td></tr> <tr><td>4.75</td><td>12.78</td><td>12.66</td><td>12.67</td></tr> <tr><td>4.50</td><td>12.79</td><td>12.66</td><td>12.75</td></tr> <tr><td>4.00</td><td>12.85</td><td>12.76</td><td>12.91</td></tr> <tr><td>3.50</td><td>12.95</td><td>12.88</td><td>13.06</td></tr> <tr><td>3.00</td><td>13.02</td><td>12.97</td><td>13.25</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	5.00	10.27	10.10	10.10	4.75	12.78	12.66	12.67	4.50	12.79	12.66	12.75	4.00	12.85	12.76	12.91	3.50	12.95	12.88	13.06	3.00	13.02	12.97	13.25	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
5.00	10.27	10.10	10.10																																																							
4.75	12.78	12.66	12.67																																																							
4.50	12.79	12.66	12.75																																																							
4.00	12.85	12.76	12.91																																																							
3.50	12.95	12.88	13.06																																																							
3.00	13.02	12.97	13.25																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Model	CBS502405	Testing Circuitry Figure A																																																					
Item	Overvoltage Protection 過電圧保護																																																						
Object	+5V10A																																																						
1. Graph																																																							
<p style="text-align: center;"> —▲— Input Volt. 18V ---□--- Input Volt. 24V ---○--- Input Volt. 36V </p> <p style="text-align: center;">Operating Point [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 0%</p>																																																							
2. Values																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="text-align: left; padding-bottom: 5px;">Ambient Temperature [°C]</th> <th colspan="3" style="text-align: left; border-bottom: 1px solid black;">Operating Point [V]</th> </tr> <tr> <th style="text-align: left; padding-bottom: 5px;">Input Volt. 18[V]</th> <th style="text-align: left; padding-bottom: 5px;">Input Volt. 24[V]</th> <th style="text-align: left; padding-bottom: 5px;">Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td style="text-align: center;">6.42</td><td style="text-align: center;">6.42</td><td style="text-align: center;">6.42</td></tr> <tr> <td>-40</td><td style="text-align: center;">6.42</td><td style="text-align: center;">6.42</td><td style="text-align: center;">6.42</td></tr> <tr> <td>-20</td><td style="text-align: center;">6.42</td><td style="text-align: center;">6.42</td><td style="text-align: center;">6.42</td></tr> <tr> <td>0</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td></tr> <tr> <td>25</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td></tr> <tr> <td>40</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td></tr> <tr> <td>60</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td></tr> <tr> <td>85</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td><td style="text-align: center;">6.41</td></tr> <tr> <td>100</td><td style="text-align: center;">6.40</td><td style="text-align: center;">6.40</td><td style="text-align: center;">6.40</td></tr> <tr> <td>105</td><td style="text-align: center;">6.40</td><td style="text-align: center;">6.40</td><td style="text-align: center;">6.40</td></tr> <tr> <td>---</td><td style="text-align: center;">—</td><td style="text-align: center;">—</td><td style="text-align: center;">—</td></tr> </tbody> </table>					Ambient Temperature [°C]	Operating Point [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-50	6.42	6.42	6.42	-40	6.42	6.42	6.42	-20	6.42	6.42	6.42	0	6.41	6.41	6.41	25	6.41	6.41	6.41	40	6.41	6.41	6.41	60	6.41	6.41	6.41	85	6.41	6.41	6.41	100	6.40	6.40	6.40	105	6.40	6.40	6.40	---	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
-50	6.42	6.42	6.42																																																				
-40	6.42	6.42	6.42																																																				
-20	6.42	6.42	6.42																																																				
0	6.41	6.41	6.41																																																				
25	6.41	6.41	6.41																																																				
40	6.41	6.41	6.41																																																				
60	6.41	6.41	6.41																																																				
85	6.41	6.41	6.41																																																				
100	6.40	6.40	6.40																																																				
105	6.40	6.40	6.40																																																				
---	—	—	—																																																				

Model CBS502405

Item Dynamic Load Response
動的負荷変動

Object +5V10A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 24 V
Cycle 1000 ms


Min. Load (0A) ←→

Load 100% (10A)

200 mV/div

500 μs/div

5 ms/div





Min. Load (0A) ←→

Load 50% (5A)

200 mV/div

500 μs/div

5 ms/div





Load 10% (1A) ←→

Load 100% (10A)

200 mV/div

500 μs/div


5 ms/div



COSEL


Model	CBS502405	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+5V10A		

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		16.8	8.5	25.3	0.3	6.5	
100 %		16.5	8.5	25.0	0.2	3.4	



Model	CBS502405																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																					
Object	+5V10A																																																					
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					
	<p>—△— Input Volt. 18V</p> <p>- - -□- - Input Volt. 24V</p> <p>- · -○- · Input Volt. 36V</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>5.073</td><td>5.073</td><td>5.073</td></tr> <tr> <td>-40</td><td>5.074</td><td>5.074</td><td>5.074</td></tr> <tr> <td>-20</td><td>5.076</td><td>5.077</td><td>5.077</td></tr> <tr> <td>0</td><td>5.080</td><td>5.080</td><td>5.080</td></tr> <tr> <td>25</td><td>5.082</td><td>5.082</td><td>5.082</td></tr> <tr> <td>40</td><td>5.080</td><td>5.080</td><td>5.080</td></tr> <tr> <td>60</td><td>5.076</td><td>5.076</td><td>5.076</td></tr> <tr> <td>85</td><td>5.069</td><td>5.069</td><td>5.069</td></tr> <tr> <td>100</td><td>5.064</td><td>5.064</td><td>5.064</td></tr> <tr> <td>105</td><td>5.062</td><td>5.062</td><td>5.062</td></tr> <tr> <td>--</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-50	5.073	5.073	5.073	-40	5.074	5.074	5.074	-20	5.076	5.077	5.077	0	5.080	5.080	5.080	25	5.082	5.082	5.082	40	5.080	5.080	5.080	60	5.076	5.076	5.076	85	5.069	5.069	5.069	100	5.064	5.064	5.064	105	5.062	5.062	5.062	--	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
-50	5.073	5.073	5.073																																																			
-40	5.074	5.074	5.074																																																			
-20	5.076	5.077	5.077																																																			
0	5.080	5.080	5.080																																																			
25	5.082	5.082	5.082																																																			
40	5.080	5.080	5.080																																																			
60	5.076	5.076	5.076																																																			
85	5.069	5.069	5.069																																																			
100	5.064	5.064	5.064																																																			
105	5.062	5.062	5.062																																																			
--	—	—	—																																																			


Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Model	CBS502405
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+5V10A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-50	14.5	15.0
-40	14.5	15.0
-20	14.5	15.0
0	14.5	15.1
25	14.5	15.2
40	14.5	15.2
60	14.4	15.2
85	14.4	15.2
100	14.4	15.2
105	14.3	15.1
--	—	—

Model	CBS502405
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+5V10A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	50	50
-40	40	40
-20	30	30
0	25	30
25	15	15
40	15	15
60	15	20
85	20	20
100	20	20
105	20	20
--	--	--

COSEL

Model	CBS502405	Temperature Testing Circuitry 25°C Figure A
Item	Time Lapse Drift 経時ドリフト	
Object	+5V10A	

1. Graph

Output Voltage [V]	5.14
	5.12
	5.10
	5.08
	5.06
	5.04
	5.02
	5.00

Time since start [H]	0.0
	0.5
	1.0
	2.0
	3.0
	4.0
	5.0
	6.0
	7.0
	8.0

2. Values

Time since start [H]	Output Voltage [V]
0.0	5.077
0.5	5.075
1.0	5.075
2.0	5.075
3.0	5.076
4.0	5.076
5.0	5.076
6.0	5.076
7.0	5.076
8.0	5.076

Input Volt. 24V
Load 100%



Model	CBS502405	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5V10A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 100°C

Input Voltage : 18 ~ 36V

Load Current : 0 ~ 10A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -40 ~ 100°C

入力電圧 : 18 ~ 36V

負荷電流 : 0 ~ 10A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	18	0	5.082	±10	±0.2
Minimum Voltage	100	36	10	5.063		



Model	CBS502405	Testing Circuitry Figure A
Item	Condense 結露特性	
Object	+5V10A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.066	Input Volt.:24V, Load Current.:10A
Line Regulation [mV]	1	Input Volt.:18~36V, Load Current.:10A
Load Regulation [mV]	1	Input Volt.:24V, Load Current.:0~10A

COSSEL




Model	CBS502405	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure B
Object	+5V10A		

1. Conditions

- Input Voltage : 24 V
- Pulse Input Duration : 1 min. or more
- Pulse Voltage : 2000 V
- Load : 100 %
- Pulse Cycle : 16.7 mS

2. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY		
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation



C1 : 50V 68 μ F
 C2 : 4700pF
 C3 : 50V 0.1 μ F
 C4 : 10V 2200 μ F \times 2 ($-40^{\circ}\text{C} \leq T_B \leq -20^{\circ}\text{C}$)
 10V 2200 μ F ($-20^{\circ}\text{C} < T_B \leq 100^{\circ}\text{C}$)
 T_B : Base Plate Temp.

Figure C