



TEST DATA OF CBS502424 (24V INPUT)

Regulated DC Power Supply
Jun. 20, 2002

Approved by : Isao Yasuda _____
Isao Yasuda Design Manager

Prepared by : Kouichi Kinoshita _____
Kouichi Kinoshita Design Engineer

コーワセル株式会社
COSEL CO.,LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSEL

Model	CBS502424	Temperature	25°C																																
Item	Line Regulation 静的の入力変動	Testing Circuitry	Figure A																																
Object	+24V2.1A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>16</td> <td>24.098</td> <td>24.098</td> </tr> <tr> <td>18</td> <td>24.098</td> <td>24.098</td> </tr> <tr> <td>20</td> <td>24.098</td> <td>24.098</td> </tr> <tr> <td>24</td> <td>24.099</td> <td>24.098</td> </tr> <tr> <td>30</td> <td>24.098</td> <td>24.098</td> </tr> <tr> <td>36</td> <td>24.098</td> <td>24.098</td> </tr> <tr> <td>40</td> <td>24.098</td> <td>24.097</td> </tr> <tr> <td>---</td> <td>—</td> <td>—</td> </tr> <tr> <td>---</td> <td>—</td> <td>—</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	24.098	24.098	18	24.098	24.098	20	24.098	24.098	24	24.099	24.098	30	24.098	24.098	36	24.098	24.098	40	24.098	24.097	---	—	—	---	—	—
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	24.098	24.098																																	
18	24.098	24.098																																	
20	24.098	24.098																																	
24	24.099	24.098																																	
30	24.098	24.098																																	
36	24.098	24.098																																	
40	24.098	24.097																																	
---	—	—																																	
---	—	—																																	

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	CBS502424	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object																																																																										
1. Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>12.0</td><td>0.015</td><td>0.015</td><td>0.015</td></tr> <tr><td>15.6</td><td>0.129</td><td>1.898</td><td>3.718</td></tr> <tr><td>16.0</td><td>0.126</td><td>1.846</td><td>3.620</td></tr> <tr><td>18.0</td><td>0.116</td><td>1.638</td><td>3.198</td></tr> <tr><td>20.0</td><td>0.108</td><td>1.486</td><td>2.879</td></tr> <tr><td>24.0</td><td>0.097</td><td>1.246</td><td>2.410</td></tr> <tr><td>28.0</td><td>0.089</td><td>1.080</td><td>2.072</td></tr> <tr><td>32.0</td><td>0.085</td><td>0.954</td><td>1.820</td></tr> <tr><td>36.0</td><td>0.082</td><td>0.858</td><td>1.621</td></tr> <tr><td>40.0</td><td>0.077</td><td>0.782</td><td>1.471</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </table>			Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	12.0	0.015	0.015	0.015	15.6	0.129	1.898	3.718	16.0	0.126	1.846	3.620	18.0	0.116	1.638	3.198	20.0	0.108	1.486	2.879	24.0	0.097	1.246	2.410	28.0	0.089	1.080	2.072	32.0	0.085	0.954	1.820	36.0	0.082	0.858	1.621	40.0	0.077	0.782	1.471	---	—	—	—	---	—	—	—	---	—	—	—			
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																							
0	0.000	0.000	0.000																																																																							
4.0	0.000	0.000	0.000																																																																							
8.0	0.000	0.000	0.000																																																																							
12.0	0.015	0.015	0.015																																																																							
15.6	0.129	1.898	3.718																																																																							
16.0	0.126	1.846	3.620																																																																							
18.0	0.116	1.638	3.198																																																																							
20.0	0.108	1.486	2.879																																																																							
24.0	0.097	1.246	2.410																																																																							
28.0	0.089	1.080	2.072																																																																							
32.0	0.085	0.954	1.820																																																																							
36.0	0.082	0.858	1.621																																																																							
40.0	0.077	0.782	1.471																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							
2. Values																																																																										
	<table border="1" style="width: 100%;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>12.0</td><td>0.015</td><td>0.015</td><td>0.015</td></tr> <tr><td>15.6</td><td>0.129</td><td>1.898</td><td>3.718</td></tr> <tr><td>16.0</td><td>0.126</td><td>1.846</td><td>3.620</td></tr> <tr><td>18.0</td><td>0.116</td><td>1.638</td><td>3.198</td></tr> <tr><td>20.0</td><td>0.108</td><td>1.486</td><td>2.879</td></tr> <tr><td>24.0</td><td>0.097</td><td>1.246</td><td>2.410</td></tr> <tr><td>28.0</td><td>0.089</td><td>1.080</td><td>2.072</td></tr> <tr><td>32.0</td><td>0.085</td><td>0.954</td><td>1.820</td></tr> <tr><td>36.0</td><td>0.082</td><td>0.858</td><td>1.621</td></tr> <tr><td>40.0</td><td>0.077</td><td>0.782</td><td>1.471</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	12.0	0.015	0.015	0.015	15.6	0.129	1.898	3.718	16.0	0.126	1.846	3.620	18.0	0.116	1.638	3.198	20.0	0.108	1.486	2.879	24.0	0.097	1.246	2.410	28.0	0.089	1.080	2.072	32.0	0.085	0.954	1.820	36.0	0.082	0.858	1.621	40.0	0.077	0.782	1.471	---	—	—	—	---	—	—	—	---	—	—	—
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
4.0	0.000	0.000	0.000																																																																							
8.0	0.000	0.000	0.000																																																																							
12.0	0.015	0.015	0.015																																																																							
15.6	0.129	1.898	3.718																																																																							
16.0	0.126	1.846	3.620																																																																							
18.0	0.116	1.638	3.198																																																																							
20.0	0.108	1.486	2.879																																																																							
24.0	0.097	1.246	2.410																																																																							
28.0	0.089	1.080	2.072																																																																							
32.0	0.085	0.954	1.820																																																																							
36.0	0.082	0.858	1.621																																																																							
40.0	0.077	0.782	1.471																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。


COSEL

Model	CBS502424	Temperature Testing Circuitry	25°C Figure A																																														
Item	Input Current (by Load Current) 入力電流 (負荷特性)																																																
Object	—	2. Values																																															
1. Graph	<p>—△— Input Volt. 18V ---□--- Input Volt. 24V -○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (18V)</th> <th>Input Current [A] (24V)</th> <th>Input Current [A] (36V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.117</td><td>0.097</td><td>0.082</td></tr> <tr><td>0.40</td><td>0.715</td><td>0.551</td><td>0.391</td></tr> <tr><td>0.80</td><td>1.298</td><td>0.986</td><td>0.682</td></tr> <tr><td>1.20</td><td>1.904</td><td>1.429</td><td>0.975</td></tr> <tr><td>1.60</td><td>2.520</td><td>1.880</td><td>1.269</td></tr> <tr><td>2.00</td><td>3.154</td><td>2.338</td><td>1.566</td></tr> <tr><td>2.10</td><td>3.314</td><td>2.454</td><td>1.641</td></tr> <tr><td>2.31</td><td>3.658</td><td>2.702</td><td>1.799</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)	0.00	0.117	0.097	0.082	0.40	0.715	0.551	0.391	0.80	1.298	0.986	0.682	1.20	1.904	1.429	0.975	1.60	2.520	1.880	1.269	2.00	3.154	2.338	1.566	2.10	3.314	2.454	1.641	2.31	3.658	2.702	1.799	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)																																														
0.00	0.117	0.097	0.082																																														
0.40	0.715	0.551	0.391																																														
0.80	1.298	0.986	0.682																																														
1.20	1.904	1.429	0.975																																														
1.60	2.520	1.880	1.269																																														
2.00	3.154	2.338	1.566																																														
2.10	3.314	2.454	1.641																																														
2.31	3.658	2.702	1.799																																														
—	—	—	—																																														
—	—	—	—																																														
—	—	—	—																																														

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS502424	Temperature	25°C																																																		
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Testing Circuitry	Figure A																																																		
Object	<hr/>																																																				
1. Graph	<p>—▲— Input Volt. 18V - - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p>  <p>Input Power [W]</p> <p>Load Current [A]</p>																																																				
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>2.11</td> <td>2.34</td> <td>2.97</td> </tr> <tr> <td>0.40</td> <td>12.74</td> <td>13.18</td> <td>14.08</td> </tr> <tr> <td>0.80</td> <td>23.05</td> <td>23.48</td> <td>24.50</td> </tr> <tr> <td>1.20</td> <td>33.70</td> <td>33.94</td> <td>35.10</td> </tr> <tr> <td>1.60</td> <td>44.30</td> <td>44.60</td> <td>45.50</td> </tr> <tr> <td>2.00</td> <td>55.10</td> <td>55.30</td> <td>56.10</td> </tr> <tr> <td>2.10</td> <td>57.80</td> <td>57.90</td> <td>58.80</td> </tr> <tr> <td>2.31</td> <td>63.60</td> <td>63.60</td> <td>64.40</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Input Power [W]			18[V]	24[V]	36[V]	0.00	2.11	2.34	2.97	0.40	12.74	13.18	14.08	0.80	23.05	23.48	24.50	1.20	33.70	33.94	35.10	1.60	44.30	44.60	45.50	2.00	55.10	55.30	56.10	2.10	57.80	57.90	58.80	2.31	63.60	63.60	64.40	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	18[V]	24[V]	36[V]																																																		
0.00	2.11	2.34	2.97																																																		
0.40	12.74	13.18	14.08																																																		
0.80	23.05	23.48	24.50																																																		
1.20	33.70	33.94	35.10																																																		
1.60	44.30	44.60	45.50																																																		
2.00	55.10	55.30	56.10																																																		
2.10	57.80	57.90	58.80																																																		
2.31	63.60	63.60	64.40																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS502424	Temperature	25°C																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																																
Object	<hr/>																																		
1. Graph																																			
			2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>16</td><td>85.5</td><td>87.2</td></tr> <tr> <td>18</td><td>85.8</td><td>87.5</td></tr> <tr> <td>20</td><td>85.4</td><td>87.5</td></tr> <tr> <td>24</td><td>84.5</td><td>87.4</td></tr> <tr> <td>30</td><td>83.2</td><td>86.7</td></tr> <tr> <td>36</td><td>81.6</td><td>86.1</td></tr> <tr> <td>40</td><td>80.7</td><td>85.4</td></tr> <tr> <td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	85.5	87.2	18	85.8	87.5	20	85.4	87.5	24	84.5	87.4	30	83.2	86.7	36	81.6	86.1	40	80.7	85.4	—	—	—	—	—	—
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
16	85.5	87.2																																	
18	85.8	87.5																																	
20	85.4	87.5																																	
24	84.5	87.4																																	
30	83.2	86.7																																	
36	81.6	86.1																																	
40	80.7	85.4																																	
—	—	—																																	
—	—	—																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	CBS502424	Temperature	25°C																																																			
Item	Efficiency (by Load Current) 効率(負荷特性)	Testing Circuitry	Figure A																																																			
Object																																																						
1. Graph	<p>—△— Input Volt. 18V ---□--- Input Volt. 24V ---○--- Input Volt. 36V</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.40</td><td>76.6</td><td>73.9</td><td>69.2</td></tr> <tr><td>0.80</td><td>83.9</td><td>82.4</td><td>79.0</td></tr> <tr><td>1.20</td><td>86.1</td><td>85.5</td><td>82.7</td></tr> <tr><td>1.60</td><td>87.2</td><td>86.5</td><td>84.9</td></tr> <tr><td>2.00</td><td>87.5</td><td>87.2</td><td>85.9</td></tr> <tr><td>2.10</td><td>87.5</td><td>87.4</td><td>86.0</td></tr> <tr><td>2.31</td><td>87.5</td><td>87.5</td><td>86.4</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	—	—	—	0.40	76.6	73.9	69.2	0.80	83.9	82.4	79.0	1.20	86.1	85.5	82.7	1.60	87.2	86.5	84.9	2.00	87.5	87.2	85.9	2.10	87.5	87.4	86.0	2.31	87.5	87.5	86.4	---	—	—	—	---	—	—	—	---	—	—	—
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	—	—	—																																																			
0.40	76.6	73.9	69.2																																																			
0.80	83.9	82.4	79.0																																																			
1.20	86.1	85.5	82.7																																																			
1.60	87.2	86.5	84.9																																																			
2.00	87.5	87.2	85.9																																																			
2.10	87.5	87.4	86.0																																																			
2.31	87.5	87.5	86.4																																																			
---	—	—	—																																																			
---	—	—	—																																																			
---	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS502424	Temperature 25°C Testing Circuitry Figure A																																																	
Item	Load Regulation 靜的負荷變動																																																		
Object	+24V2.1A																																																		
1. Graph	<p>—▲— Input Volt. 18V - - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (18V)</th> <th>Output Voltage [V] (24V)</th> <th>Output Voltage [V] (36V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>0.4</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>0.8</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>1.2</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>1.6</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>2.0</td><td>24.098</td><td>24.098</td><td>24.099</td></tr> <tr><td>2.3</td><td>24.098</td><td>24.098</td><td>24.099</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (18V)	Output Voltage [V] (24V)	Output Voltage [V] (36V)	0.0	24.098	24.098	24.098	0.4	24.098	24.098	24.098	0.8	24.098	24.098	24.098	1.2	24.098	24.098	24.098	1.6	24.098	24.098	24.098	2.0	24.098	24.098	24.099	2.3	24.098	24.098	24.099																
Load Current [A]	Output Voltage [V] (18V)	Output Voltage [V] (24V)	Output Voltage [V] (36V)																																																
0.0	24.098	24.098	24.098																																																
0.4	24.098	24.098	24.098																																																
0.8	24.098	24.098	24.098																																																
1.2	24.098	24.098	24.098																																																
1.6	24.098	24.098	24.098																																																
2.0	24.098	24.098	24.099																																																
2.3	24.098	24.098	24.099																																																
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>0.4</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>0.8</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>1.2</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>1.6</td><td>24.098</td><td>24.098</td><td>24.098</td></tr> <tr><td>2.0</td><td>24.098</td><td>24.098</td><td>24.099</td></tr> <tr><td>2.1</td><td>24.098</td><td>24.098</td><td>24.099</td></tr> <tr><td>2.3</td><td>24.098</td><td>24.098</td><td>24.099</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	24.098	24.098	24.098	0.4	24.098	24.098	24.098	0.8	24.098	24.098	24.098	1.2	24.098	24.098	24.098	1.6	24.098	24.098	24.098	2.0	24.098	24.098	24.099	2.1	24.098	24.098	24.099	2.3	24.098	24.098	24.099	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																
0.0	24.098	24.098	24.098																																																
0.4	24.098	24.098	24.098																																																
0.8	24.098	24.098	24.098																																																
1.2	24.098	24.098	24.098																																																
1.6	24.098	24.098	24.098																																																
2.0	24.098	24.098	24.099																																																
2.1	24.098	24.098	24.099																																																
2.3	24.098	24.098	24.099																																																
—	—	—	—																																																
—	—	—	—																																																
Note: Slanted line shows the range of the rated load current.																																																			
(注) 斜線は定格負荷電流範囲を示す。																																																			

COSEL


Model	CBS502424																																							
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Temperature Testing Circuitry 25°C Figure A																																						
Object	+24V2.1A																																							
1. Graph																																								
<p>—△— Input Volt. 18V ---○--- Input Volt. 36V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 18V)</th> <th>Ripple Voltage [mV] (Input Volt. 36V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>10</td><td>15</td></tr> <tr><td>0.8</td><td>10</td><td>15</td></tr> <tr><td>1.3</td><td>10</td><td>15</td></tr> <tr><td>1.7</td><td>10</td><td>15</td></tr> <tr><td>2.1</td><td>10</td><td>15</td></tr> <tr><td>2.5</td><td>10</td><td>15</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 18V)	Ripple Voltage [mV] (Input Volt. 36V)	0.0	5	5	0.4	10	15	0.8	10	15	1.3	10	15	1.7	10	15	2.1	10	15	2.5	10	15															
Load Current [A]	Ripple Voltage [mV] (Input Volt. 18V)	Ripple Voltage [mV] (Input Volt. 36V)																																						
0.0	5	5																																						
0.4	10	15																																						
0.8	10	15																																						
1.3	10	15																																						
1.7	10	15																																						
2.1	10	15																																						
2.5	10	15																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>10</td><td>15</td></tr> <tr><td>0.8</td><td>10</td><td>15</td></tr> <tr><td>1.3</td><td>10</td><td>15</td></tr> <tr><td>1.7</td><td>10</td><td>15</td></tr> <tr><td>2.1</td><td>10</td><td>15</td></tr> <tr><td>2.5</td><td>10</td><td>15</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	5	5	0.4	10	15	0.8	10	15	1.3	10	15	1.7	10	15	2.1	10	15	2.5	10	15	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.0	5	5																																						
0.4	10	15																																						
0.8	10	15																																						
1.3	10	15																																						
1.7	10	15																																						
2.1	10	15																																						
2.5	10	15																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model	CBS502424
Item	Ripple-Noise リップルノイズ
Object	+24V2.1A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.0	10	15
0.4	15	25
0.8	15	25
1.3	15	25
1.7	15	25
2.1	15	25
2.5	20	25
--	--	--
--	--	--
--	--	--
--	--	--

Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。





Fig. Complex Ripple Noise Wave Form
図 リップルノイズ波形

COSEL

Model	CBS502424	Temperature Testing Circuitry 25°C Figure A																																																											
Item	Overcurrent Protection 過電流保護																																																												
Object	+24V2.1A																																																												
1. Graph	<p>— Input Volt. 18V Input Volt. 24V Input Volt. 36V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2. Values																																																											
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>24.0</td><td>2.17</td><td>2.17</td><td>2.13</td></tr> <tr><td>22.8</td><td>2.71</td><td>2.70</td><td>2.73</td></tr> <tr><td>21.6</td><td>2.72</td><td>2.71</td><td>2.75</td></tr> <tr><td>19.2</td><td>2.75</td><td>2.74</td><td>2.78</td></tr> <tr><td>16.8</td><td>2.76</td><td>2.76</td><td>2.80</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	24.0	2.17	2.17	2.13	22.8	2.71	2.70	2.73	21.6	2.72	2.71	2.75	19.2	2.75	2.74	2.78	16.8	2.76	2.76	2.80	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Output Voltage [V]	Load Current [A]																																																												
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																										
24.0	2.17	2.17	2.13																																																										
22.8	2.71	2.70	2.73																																																										
21.6	2.72	2.71	2.75																																																										
19.2	2.75	2.74	2.78																																																										
16.8	2.76	2.76	2.80																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
	<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p> <p>Intermittent operation occurs when the output voltage is from 16.8V to 0V. 16.8V～0V間は、間欠モードとなる。</p>																																																												

COSEL

Model	CBS502424	Testing Circuitry Figure A			
Item	Overvoltage Protection 過電圧保護				
Object	+24V2.1A				
1. Graph					
		—△— Input Volt. 18V - -□--- Input Volt. 24V - -○--- Input Volt. 36V			
		2. Values			
Ambient Temperature [°C]	Operating Point [V]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]		
-50	31.16	31.16	31.16		
-40	31.16	31.16	31.16		
-20	31.27	31.27	31.27		
0	31.33	31.33	31.33		
25	31.33	31.33	31.33		
40	31.44	31.44	31.44		
60	31.44	31.44	31.44		
85	31.44	31.44	31.44		
100	31.44	31.44	31.44		
105	31.44	31.44	31.44		
--	--	--	--	--	




Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model	CBS502424	Temperature Testing Circuitry 25°C Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	+24V2.1A	

Input Volt. 24 V
Cycle 1000 ms




Min. Load (0A) ↔

Load 100% (2.1A)

500 mV/div

500 μs/div





5 ms/div

Min. Load (0A) ↔

Load 50% (1.05A)

500 mV/div

500 μs/div





5 ms/div

Load 10% (0.21A) ↔

Load 100% (2.1A)

500 mV/div

500 μs/div



5 ms/div

COSEL


Model CBS502424

Item Rise and Fall Time
立上り、立下り時間

Object +24V2.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		17.0	6.3	23.3	0.7	12.9	
100 %		17.0	6.3	23.3	0.4	6.7	




COSEL

Model	CBS502424	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+24V2.1A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 18V --- □ --- Input Volt. 24V --- ○ --- Input Volt. 36V 																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>24.127</td><td>24.128</td><td>24.127</td></tr> <tr> <td>-40</td><td>24.129</td><td>24.129</td><td>24.129</td></tr> <tr> <td>-20</td><td>24.129</td><td>24.129</td><td>24.129</td></tr> <tr> <td>0</td><td>24.129</td><td>24.129</td><td>24.129</td></tr> <tr> <td>25</td><td>24.120</td><td>24.119</td><td>24.119</td></tr> <tr> <td>40</td><td>24.101</td><td>24.100</td><td>24.100</td></tr> <tr> <td>60</td><td>24.068</td><td>24.068</td><td>24.067</td></tr> <tr> <td>85</td><td>24.015</td><td>24.014</td><td>24.014</td></tr> <tr> <td>100</td><td>23.979</td><td>23.978</td><td>23.978</td></tr> <tr> <td>105</td><td>23.966</td><td>23.965</td><td>23.965</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-50	24.127	24.128	24.127	-40	24.129	24.129	24.129	-20	24.129	24.129	24.129	0	24.129	24.129	24.129	25	24.120	24.119	24.119	40	24.101	24.100	24.100	60	24.068	24.068	24.067	85	24.015	24.014	24.014	100	23.979	23.978	23.978	105	23.966	23.965	23.965	--	--	--	--
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
-50	24.127	24.128	24.127																																																				
-40	24.129	24.129	24.129																																																				
-20	24.129	24.129	24.129																																																				
0	24.129	24.129	24.129																																																				
25	24.120	24.119	24.119																																																				
40	24.101	24.100	24.100																																																				
60	24.068	24.068	24.067																																																				
85	24.015	24.014	24.014																																																				
100	23.979	23.978	23.978																																																				
105	23.966	23.965	23.965																																																				
--	--	--	--																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						
(注)	斜線は定格周囲温度範囲を示す。																																																						

COSEL

Model	CBS502424
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+24V2.1A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-50	12.7	13.0
-40	12.7	13.1
-20	12.8	13.2
0	12.9	13.3
25	13.0	13.4
40	13.0	13.5
60	13.1	13.6
85	13.1	13.7
100	13.0	13.6
105	13.0	13.6
—	—	—

COSEL

Model	CBS502424
Item	Ripple Voltage (by Ambient Temp.) リップル電圧（周囲温度特性）
Object	+24V2.1A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.
(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	50	50
-40	45	45
-20	30	30
0	20	20
25	15	15
40	15	15
60	15	15
85	15	15
100	20	20
105	20	20
—	—	—

COSEL

Model	CBS502424	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+24V2.1A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.106</td></tr> <tr><td>0.5</td><td>24.097</td></tr> <tr><td>1.0</td><td>24.098</td></tr> <tr><td>2.0</td><td>24.098</td></tr> <tr><td>3.0</td><td>24.098</td></tr> <tr><td>4.0</td><td>24.099</td></tr> <tr><td>5.0</td><td>24.099</td></tr> <tr><td>6.0</td><td>24.099</td></tr> <tr><td>7.0</td><td>24.099</td></tr> <tr><td>8.0</td><td>24.099</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.106	0.5	24.097	1.0	24.098	2.0	24.098	3.0	24.098	4.0	24.099	5.0	24.099	6.0	24.099	7.0	24.099	8.0	24.099
Time since start [H]	Output Voltage [V]																								
0.0	24.106																								
0.5	24.097																								
1.0	24.098																								
2.0	24.098																								
3.0	24.098																								
4.0	24.099																								
5.0	24.099																								
6.0	24.099																								
7.0	24.099																								
8.0	24.099																								



Model	CBS502424	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+24V2.1A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 100°C

Input Voltage : 18 ~ 36V

Load Current : 0 ~ 2.1A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -40 ~ 100°C

入力電圧 : 18 ~ 36V

負荷電流 : 0 ~ 2.1A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	36	2.1	24.129	±77	±0.3
Minimum Voltage	100	36	0	23.975		



Model	CBS502424	Testing Circuitry Figure A
Item	Condense 結露特性	
Object	+24V2.1A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	24.112	Input Volt.:24V, Load Current.:2.1A
Line Regulation [mV]	2	Input Volt.:18~36V, Load Current.:2.1A
Load Regulation [mV]	1	Input Volt.:24V, Load Current.:0~2.1A



Model	CBS502424	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure B
Object	+24V2.1A		

1. Conditions

- Input Voltage : 24 V
- Pulse Input Duration : 1 min. or more
- Pulse Voltage : 2000 V
- Load : 100 %
- Pulse Cycle : 16.7 ms

2. Results

Pulse Width [nS]	MODE	No protection failure should occur		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY	保護回路の誤動作がない	
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

COSEL

