



TEST DATA OF CDS6002428

(24V INPUT)

Regulated DC Power Supply

Sep. 4, 2001

Approved by : Kazuyoshi Shimano
Design Manager

Prepared by : Katsumi Mizui
Design Engineer

コーセル株式会社
COSEL CO., LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSSEL

Model	CDS6002428		Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+28.0V 22A																																		
1. Graph	Load 50%	Load 100%																																	
<p>[V]</p> <p>Output Voltage</p> <p>Input Voltage [V]</p>			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>28.130</td><td>28.119</td></tr> <tr><td>18</td><td>28.131</td><td>28.118</td></tr> <tr><td>21</td><td>28.130</td><td>28.121</td></tr> <tr><td>24</td><td>28.131</td><td>28.122</td></tr> <tr><td>27</td><td>28.127</td><td>28.124</td></tr> <tr><td>30</td><td>28.129</td><td>28.123</td></tr> <tr><td>33</td><td>28.128</td><td>28.124</td></tr> <tr><td>36</td><td>28.126</td><td>28.124</td></tr> <tr><td>40</td><td>28.125</td><td>28.122</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	28.130	28.119	18	28.131	28.118	21	28.130	28.121	24	28.131	28.122	27	28.127	28.124	30	28.129	28.123	33	28.128	28.124	36	28.126	28.124	40	28.125	28.122
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	28.130	28.119																																	
18	28.131	28.118																																	
21	28.130	28.121																																	
24	28.131	28.122																																	
27	28.127	28.124																																	
30	28.129	28.123																																	
33	28.128	28.124																																	
36	28.126	28.124																																	
40	28.125	28.122																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			


COSEL

Model	CDS6002428	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object	—																																																																									
1. Graph	<p>[A]</p> <p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend: Load 100% (△), Load 50% (□), Load 0% (○)</p>																																																																									
	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>3.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>9.0</td><td>0.059</td><td>0.056</td><td>0.053</td></tr> <tr><td>12.0</td><td>0.044</td><td>0.043</td><td>0.044</td></tr> <tr><td>12.3</td><td>0.169</td><td>0.039</td><td>0.038</td></tr> <tr><td>14.7</td><td>0.144</td><td>22.959</td><td>41.135</td></tr> <tr><td>15.0</td><td>0.136</td><td>22.700</td><td>42.193</td></tr> <tr><td>15.9</td><td>0.134</td><td>21.297</td><td>44.592</td></tr> <tr><td>18.0</td><td>0.120</td><td>18.880</td><td>39.159</td></tr> <tr><td>21.0</td><td>0.108</td><td>16.251</td><td>33.262</td></tr> <tr><td>24.0</td><td>0.095</td><td>14.259</td><td>29.247</td></tr> <tr><td>30.0</td><td>0.087</td><td>11.570</td><td>23.385</td></tr> <tr><td>36.0</td><td>0.079</td><td>9.791</td><td>19.730</td></tr> <tr><td>39.0</td><td>0.071</td><td>9.092</td><td>18.410</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	3.0	0.000	0.000	0.000	6.0	0.000	0.000	0.000	9.0	0.059	0.056	0.053	12.0	0.044	0.043	0.044	12.3	0.169	0.039	0.038	14.7	0.144	22.959	41.135	15.0	0.136	22.700	42.193	15.9	0.134	21.297	44.592	18.0	0.120	18.880	39.159	21.0	0.108	16.251	33.262	24.0	0.095	14.259	29.247	30.0	0.087	11.570	23.385	36.0	0.079	9.791	19.730	39.0	0.071	9.092	18.410	—	—	—	—
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0.0	0.000	0.000	0.000																																																																							
3.0	0.000	0.000	0.000																																																																							
6.0	0.000	0.000	0.000																																																																							
9.0	0.059	0.056	0.053																																																																							
12.0	0.044	0.043	0.044																																																																							
12.3	0.169	0.039	0.038																																																																							
14.7	0.144	22.959	41.135																																																																							
15.0	0.136	22.700	42.193																																																																							
15.9	0.134	21.297	44.592																																																																							
18.0	0.120	18.880	39.159																																																																							
21.0	0.108	16.251	33.262																																																																							
24.0	0.095	14.259	29.247																																																																							
30.0	0.087	11.570	23.385																																																																							
36.0	0.079	9.791	19.730																																																																							
39.0	0.071	9.092	18.410																																																																							
—	—	—	—																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model	CDS6002428																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object																																																										
1. Graph	<p style="text-align: center;">—△— Input Volt. 18V □..... Input Volt. 24V ○.... Input Volt. 36V</p> 																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.113</td><td>0.096</td><td>0.063</td></tr> <tr><td>4.0</td><td>7.197</td><td>5.562</td><td>3.926</td></tr> <tr><td>8.0</td><td>13.957</td><td>10.696</td><td>7.414</td></tr> <tr><td>12.0</td><td>21.224</td><td>16.053</td><td>10.919</td></tr> <tr><td>16.0</td><td>28.264</td><td>21.284</td><td>14.562</td></tr> <tr><td>20.0</td><td>36.428</td><td>27.137</td><td>18.439</td></tr> <tr><td>22.0</td><td>39.674</td><td>29.793</td><td>20.307</td></tr> <tr><td>24.2</td><td>44.470</td><td>33.174</td><td>22.557</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.113	0.096	0.063	4.0	7.197	5.562	3.926	8.0	13.957	10.696	7.414	12.0	21.224	16.053	10.919	16.0	28.264	21.284	14.562	20.0	36.428	27.137	18.439	22.0	39.674	29.793	20.307	24.2	44.470	33.174	22.557	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
0.0	0.113	0.096	0.063																																																							
4.0	7.197	5.562	3.926																																																							
8.0	13.957	10.696	7.414																																																							
12.0	21.224	16.053	10.919																																																							
16.0	28.264	21.284	14.562																																																							
20.0	36.428	27.137	18.439																																																							
22.0	39.674	29.793	20.307																																																							
24.2	44.470	33.174	22.557																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	CDS6002428																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Object	—																																																									
1. Graph	<p style="text-align: center;"> △ Input Volt. 18V □ Input Volt. 24V ○ Input Volt. 36V </p>																																																									
2. Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.03</td><td>2.33</td><td>2.27</td></tr> <tr><td>4.0</td><td>129.41</td><td>133.26</td><td>141.29</td></tr> <tr><td>8.0</td><td>252.12</td><td>256.57</td><td>265.85</td></tr> <tr><td>12.0</td><td>378.25</td><td>382.22</td><td>393.55</td></tr> <tr><td>16.0</td><td>508.01</td><td>511.57</td><td>523.13</td></tr> <tr><td>20.0</td><td>644.91</td><td>646.88</td><td>660.15</td></tr> <tr><td>22.0</td><td>713.82</td><td>716.45</td><td>731.36</td></tr> <tr><td>24.2</td><td>793.20</td><td>793.58</td><td>810.67</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	2.03	2.33	2.27	4.0	129.41	133.26	141.29	8.0	252.12	256.57	265.85	12.0	378.25	382.22	393.55	16.0	508.01	511.57	523.13	20.0	644.91	646.88	660.15	22.0	713.82	716.45	731.36	24.2	793.20	793.58	810.67	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
0.0	2.03	2.33	2.27																																																							
4.0	129.41	133.26	141.29																																																							
8.0	252.12	256.57	265.85																																																							
12.0	378.25	382.22	393.55																																																							
16.0	508.01	511.57	523.13																																																							
20.0	644.91	646.88	660.15																																																							
22.0	713.82	716.45	731.36																																																							
24.2	793.20	793.58	810.67																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL

Model	CDS6002428		Temperature Testing Circuitry	25°C Figure A																																	
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																																				
Object	<hr/>			<hr/>																																	
1. Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Load 50% Load 100%</p>			2. Values																																	
	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>88.3</td><td>85.8</td></tr> <tr><td>18</td><td>87.9</td><td>86.1</td></tr> <tr><td>21</td><td>87.4</td><td>85.9</td></tr> <tr><td>24</td><td>87.0</td><td>85.7</td></tr> <tr><td>27</td><td>86.3</td><td>85.4</td></tr> <tr><td>30</td><td>85.6</td><td>85.1</td></tr> <tr><td>33</td><td>85.1</td><td>84.4</td></tr> <tr><td>36</td><td>84.3</td><td>84.0</td></tr> <tr><td>40</td><td>83.3</td><td>82.7</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	88.3	85.8	18	87.9	86.1	21	87.4	85.9	24	87.0	85.7	27	86.3	85.4	30	85.6	85.1	33	85.1	84.4	36	84.3	84.0	40	83.3	82.7		
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
16	88.3	85.8																																			
18	87.9	86.1																																			
21	87.4	85.9																																			
24	87.0	85.7																																			
27	86.3	85.4																																			
30	85.6	85.1																																			
33	85.1	84.4																																			
36	84.3	84.0																																			
40	83.3	82.7																																			
	<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																				

COSEL

Model	CDS6002428																																																									
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Object	_____																																																									
1. Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>83.6</td><td>81.9</td><td>76.7</td></tr> <tr><td>8.0</td><td>87.4</td><td>85.9</td><td>82.8</td></tr> <tr><td>12.0</td><td>87.9</td><td>87.0</td><td>84.7</td></tr> <tr><td>16.0</td><td>87.4</td><td>86.8</td><td>85.1</td></tr> <tr><td>20.0</td><td>86.5</td><td>86.3</td><td>84.5</td></tr> <tr><td>22.0</td><td>86.0</td><td>85.7</td><td>84.0</td></tr> <tr><td>24.2</td><td>85.3</td><td>85.1</td><td>83.4</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	4.0	83.6	81.9	76.7	8.0	87.4	85.9	82.8	12.0	87.9	87.0	84.7	16.0	87.4	86.8	85.1	20.0	86.5	86.3	84.5	22.0	86.0	85.7	84.0	24.2	85.3	85.1	83.4	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
4.0	83.6	81.9	76.7																																																							
8.0	87.4	85.9	82.8																																																							
12.0	87.9	87.0	84.7																																																							
16.0	87.4	86.8	85.1																																																							
20.0	86.5	86.3	84.5																																																							
22.0	86.0	85.7	84.0																																																							
24.2	85.3	85.1	83.4																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL

Model	CDS6002428	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+28.0V22A																																																	
1. Graph	<p>—△— Input Volt. 18 V -□--- Input Volt. 24 V -○--- Input Volt. 36 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>28.081</td><td>28.086</td><td>28.089</td></tr> <tr> <td>4.0</td><td>28.094</td><td>28.101</td><td>28.103</td></tr> <tr> <td>8.0</td><td>28.108</td><td>28.114</td><td>28.119</td></tr> <tr> <td>12.0</td><td>28.116</td><td>28.122</td><td>28.121</td></tr> <tr> <td>16.0</td><td>28.113</td><td>28.121</td><td>28.123</td></tr> <tr> <td>20.0</td><td>28.112</td><td>28.121</td><td>28.124</td></tr> <tr> <td>22.0</td><td>28.113</td><td>28.121</td><td>28.124</td></tr> <tr> <td>24.2</td><td>28.113</td><td>28.121</td><td>28.123</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	28.081	28.086	28.089	4.0	28.094	28.101	28.103	8.0	28.108	28.114	28.119	12.0	28.116	28.122	28.121	16.0	28.113	28.121	28.123	20.0	28.112	28.121	28.124	22.0	28.113	28.121	28.124	24.2	28.113	28.121	28.123	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																															
0.0	28.081	28.086	28.089																																															
4.0	28.094	28.101	28.103																																															
8.0	28.108	28.114	28.119																																															
12.0	28.116	28.122	28.121																																															
16.0	28.113	28.121	28.123																																															
20.0	28.112	28.121	28.124																																															
22.0	28.113	28.121	28.124																																															
24.2	28.113	28.121	28.123																																															
—	—	—	—																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。


COSEL

Model	CDS6002428	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)																																								
Object	+28.0V 22A																																								
1. Graph	<p>—△— Input Volt. 18V [mV] —□— Input Volt. 36V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Volt. [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>20</td></tr> <tr><td>3.5</td><td>30</td><td>30</td></tr> <tr><td>7.0</td><td>30</td><td>30</td></tr> <tr><td>11.0</td><td>30</td><td>30</td></tr> <tr><td>14.5</td><td>30</td><td>30</td></tr> <tr><td>18.0</td><td>30</td><td>30</td></tr> <tr><td>22.0</td><td>30</td><td>30</td></tr> <tr><td>23.2</td><td>30</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Volt. [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	10	20	3.5	30	30	7.0	30	30	11.0	30	30	14.5	30	30	18.0	30	30	22.0	30	30	23.2	30	30	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Volt. [mV]																																								
	Input Volt. 18 [V]	Input Volt. 36 [V]																																							
0.0	10	20																																							
3.5	30	30																																							
7.0	30	30																																							
11.0	30	30																																							
14.5	30	30																																							
18.0	30	30																																							
22.0	30	30																																							
23.2	30	30																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>図 リップル波形図</p>																																									

CSEL

Model	CDS6002428
Item	Ripple-Noise リップルノイズ
Object	+28.0V 22A

Temperature 25°C
Testing Circuitry Figure A



2. Values

Load current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.0	30	30
3.5	50	60
7.0	60	60
11.0	60	60
14.5	60	60
18.0	60	60
22.0	60	60
23.2	60	60
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。





図 リップルノイズ波形図

COSEL

Model	CDS6002428
Item	Overcurrent Protection 過電流保護
Object	+28.0V 22A

Temperature 25°C
Testing Circuitry Figure A



2. Values

Output Voltage [V]	Load Current [A]		
	18[V]	24[V]	36[V]
28.00	25.23	25.99	27.73
26.60	25.33	26.20	27.61
25.20	25.44	26.52	27.50
22.40	25.72	26.74	27.50
19.60	26.09	27.12	27.65
16.80	26.48	27.55	27.75
14.00	—	—	—
11.20	—	—	—
8.40	—	—	—
5.60	—	—	—
2.80	—	—	—
0.00	—	—	—

Note: Slanted line shows the range of the rated load current.


Intermittent operation occurs when the output voltage is from 15V to 0V.

(注) 斜線は定格負荷電流範囲を示す。

15V～0V間は、間欠モードとなる。

COSEL

Model	CDS6002428
Item	Overvoltage Protection 過電圧保護
Object	+28.0V 22A




Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values


Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-35	34.76	34.76	34.76
-20	35.05	35.05	35.05
0	35.58	35.58	35.58
15	35.99	35.99	35.99
25	36.16	36.16	36.16
40	36.57	36.57	36.57
55	36.87	36.87	36.87
70	37.28	37.27	37.27
85	37.69	37.69	37.69
90	37.75	37.75	37.75
100	37.98	37.98	37.98

COSEL

COSEL


Model	CDS6002428	Temperature	25°C
Item	Rise and Fall Time 立ち上り、立下り時間	Testing Circuitry	Figure A
Object	+28.0V 22A		

1. Graph




2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		41.50	14.50	56.00	0.50	4.00	
100 %		41.50	14.50	56.00	0.50	2.00	



COSEL




Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-35	28.226	28.231	28.230
-20	28.208	28.213	28.213
0	28.187	28.192	28.193
15	28.174	28.179	28.180
25	28.163	28.168	28.170
40	28.138	28.142	28.144
55	28.105	28.108	28.110
70	28.063	28.066	28.067
85	28.020	28.023	28.027
90	27.999	28.001	28.007
100	27.970	27.974	27.982

COSEL

Model	CDS6002428				
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry Figure A			
Object	+28.0V22A				
1. Graph					
[V]	32.0 24.0 16.0 8.0 0.0	□ Load 50% △ Load 100%			
Input Voltage					
Ambient Temperature [°C]	-50 -10 30 70 110				
					
Note: Slanted line shows the range of the rated ambient temperature.					
(注)斜線は定格周囲温度範囲を示す。					
2. Values					
Ambient Temperature [°C]	Input Voltage [V]				
	Load 50%	Load 100%			
-35	14.0	14.8			
-20	14.1	14.8			
0	14.0	14.9			
15	14.0	15.0			
25	14.0	15.0			
40	14.0	15.0			
55	14.1	15.0			
70	14.0	15.0			
85	14.0	15.0			
90	14.0	15.0			
100	14.0	15.0			

COSSEL

Model	CDS6002428																																							
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																							
Object	+28.0 V 22A																																							
1. Graph																																								
<p>Input Volt. 24 V</p>		2. Values																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-35</td><td>50</td><td>50</td></tr> <tr><td>-20</td><td>40</td><td>50</td></tr> <tr><td>0</td><td>40</td><td>30</td></tr> <tr><td>15</td><td>30</td><td>30</td></tr> <tr><td>25</td><td>30</td><td>30</td></tr> <tr><td>40</td><td>30</td><td>30</td></tr> <tr><td>55</td><td>30</td><td>30</td></tr> <tr><td>70</td><td>20</td><td>20</td></tr> <tr><td>85</td><td>20</td><td>20</td></tr> <tr><td>90</td><td>20</td><td>20</td></tr> <tr><td>100</td><td>20</td><td>20</td></tr> </tbody> </table>	Ambient Temp. [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-35	50	50	-20	40	50	0	40	30	15	30	30	25	30	30	40	30	30	55	30	30	70	20	20	85	20	20	90	20	20	100	20	20
Ambient Temp. [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-35	50	50																																						
-20	40	50																																						
0	40	30																																						
15	30	30																																						
25	30	30																																						
40	30	30																																						
55	30	30																																						
70	20	20																																						
85	20	20																																						
90	20	20																																						
100	20	20																																						

COSEL

Model	CDS6002428	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+28.0V 22A																								
1. Graph																									
<p>[V]</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>28.155</td></tr> <tr><td>0.5</td><td>28.116</td></tr> <tr><td>1.0</td><td>28.119</td></tr> <tr><td>2.0</td><td>28.119</td></tr> <tr><td>3.0</td><td>28.120</td></tr> <tr><td>4.0</td><td>28.120</td></tr> <tr><td>5.0</td><td>28.121</td></tr> <tr><td>6.0</td><td>28.122</td></tr> <tr><td>7.0</td><td>28.121</td></tr> <tr><td>8.0</td><td>28.121</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	28.155	0.5	28.116	1.0	28.119	2.0	28.119	3.0	28.120	4.0	28.120	5.0	28.121	6.0	28.122	7.0	28.121	8.0	28.121	
Time since start [H]	Output Voltage [V]																								
0.0	28.155																								
0.5	28.116																								
1.0	28.119																								
2.0	28.119																								
3.0	28.120																								
4.0	28.120																								
5.0	28.121																								
6.0	28.122																								
7.0	28.121																								
8.0	28.121																								
<p>Output Voltage [V]</p> <p>28.400 28.300 28.200 28.100 28.000 27.900 27.800 27.700</p> <p>0 1 2 3 4 5 6 7 8 9 10</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>			2. Values																						
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>28.155</td></tr> <tr><td>0.5</td><td>28.116</td></tr> <tr><td>1.0</td><td>28.119</td></tr> <tr><td>2.0</td><td>28.119</td></tr> <tr><td>3.0</td><td>28.120</td></tr> <tr><td>4.0</td><td>28.120</td></tr> <tr><td>5.0</td><td>28.121</td></tr> <tr><td>6.0</td><td>28.122</td></tr> <tr><td>7.0</td><td>28.121</td></tr> <tr><td>8.0</td><td>28.121</td></tr> </tbody> </table>				Time since start [H]	Output Voltage [V]	0.0	28.155	0.5	28.116	1.0	28.119	2.0	28.119	3.0	28.120	4.0	28.120	5.0	28.121	6.0	28.122	7.0	28.121	8.0	28.121
Time since start [H]	Output Voltage [V]																								
0.0	28.155																								
0.5	28.116																								
1.0	28.119																								
2.0	28.119																								
3.0	28.120																								
4.0	28.120																								
5.0	28.121																								
6.0	28.122																								
7.0	28.121																								
8.0	28.121																								

COSSEL

Model	CDS6002428
Item	Output Voltage Accuracy 定電圧精度
Object	+28.0V 22A

Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~85 °C

Input Voltage: 18~ 36 V

Load Current : 0~22 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~85 °C

入力電圧 18~ 36 V

負荷電流 0~22 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	24	22	28.215	±115	±0.5
Minimum Voltage	85	36	0	27.986		



Model	CDS6002428														
Item	Condensation 結露特性	Testing Circuitry	Figure A												
Object	+28.0V22A														
1. Condensation test															
Testing procedure is as follows.															
① Keeping and cooling the unit in a tank at -10°C for an hour with the input off. ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH. ③ Testing electrical characteristics of the unit to confirm there be no fault.															
1. 結露特性試験															
入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。															
2. Values															
<table border="1"> <thead> <tr> <th>Item</th> <th>Data</th> <th>Testing Conditions</th> </tr> </thead> <tbody> <tr> <td>Output Voltage [V]</td> <td>28.122</td> <td>Input Volt.: 24V, Load Current:22A</td> </tr> <tr> <td>Line Regulation [mV]</td> <td>6</td> <td>Input Volt.: 18~36V, Load Current:22A</td> </tr> <tr> <td>Load Regulation [mV]</td> <td>36</td> <td>Input Volt.: 24V, Load Current:0~22A</td> </tr> </tbody> </table>				Item	Data	Testing Conditions	Output Voltage [V]	28.122	Input Volt.: 24V, Load Current:22A	Line Regulation [mV]	6	Input Volt.: 18~36V, Load Current:22A	Load Regulation [mV]	36	Input Volt.: 24V, Load Current:0~22A
Item	Data	Testing Conditions													
Output Voltage [V]	28.122	Input Volt.: 24V, Load Current:22A													
Line Regulation [mV]	6	Input Volt.: 18~36V, Load Current:22A													
Load Regulation [mV]	36	Input Volt.: 24V, Load Current:0~22A													



Model	CDS6002428	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure B
Object	+28.0V 22A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動	Conditions
50	COMMON	OK	no fluctuation	Input Voltage : 24 V
	NORMAL	OK	no fluctuation	Pulse Voltage : ±2000 V
1000	COMMON	OK	no fluctuation	Pulse Cycle : 10 mS
	NORMAL	OK	no fluctuation	Pulse Input Duration: 1 min. or more Load : 100 %

COSEL




Figure A





Figure B

Figure C (General Electric Characteristic)
一般電気特性