



TEST DATA OF CDS6004828  
(48V INPUT)

Regulated DC Power Supply

July 4, 2001

Approved by : Kazuyoshi Shimano  
Design Manager

Prepared by : Kimio Asano  
Design Engineer

**コーセル株式会社**  
**COSEL CO., LTD.**

## CONTENTS

1. Line Regulation . . . . .	1
静的入力変動	
2. Input Current (by Input Voltage) . . . . .	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current) . . . . .	3
入力電流 (負荷特性)	
4. Input Power (by Load Current) . . . . .	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage) . . . . .	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current) . . . . .	6
効率 (負荷特性)	
7. Load Regulation . . . . .	7
静的負荷変動	
8. Ripple Voltage (by Load Current) . . . . .	8
リップル電圧 (負荷特性)	
9. Ripple-Noise . . . . .	9
リップルノイズ	
10. Overcurrent Protection . . . . .	10
過電流保護	
11. Overvoltage Protection . . . . .	11
過電圧保護	
12. Dynamic Load Responce . . . . .	12
動的負荷変動	
13. Rise and Fall Time . . . . .	13
立上り、立下り時間	
14. Ambient Temperature Drift . . . . .	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage . . . . .	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature) . . . . .	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift . . . . .	17
経時ドリフト	
18. Output Voltage Accuracy . . . . .	18
定電圧精度	
19. Condensation . . . . .	19
結露特性	
20. Line Noise Tolerance . . . . .	20
入力雑音耐量	
21. Figure of Testing Circuitry . . . . .	21
測定回路図	

(Final Page 21 )



Model		CDS6004828	Temperature	25°C																																
Item		Line Regulation 静的入力変動	Testing Circuitry	Figure A																																
Object		+28.0V25A																																		
1. Graph			2. Values																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>28.083</td><td>28.078</td></tr> <tr><td>36</td><td>28.084</td><td>28.075</td></tr> <tr><td>40</td><td>28.083</td><td>28.072</td></tr> <tr><td>48</td><td>28.084</td><td>28.073</td></tr> <tr><td>54</td><td>28.085</td><td>28.073</td></tr> <tr><td>60</td><td>28.087</td><td>28.073</td></tr> <tr><td>68</td><td>28.088</td><td>28.076</td></tr> <tr><td>76</td><td>28.087</td><td>28.078</td></tr> <tr><td>80</td><td>28.085</td><td>28.078</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	28.083	28.078	36	28.084	28.075	40	28.083	28.072	48	28.084	28.073	54	28.085	28.073	60	28.087	28.073	68	28.088	28.076	76	28.087	28.078	80	28.085	28.078
Input Voltage [V]	Output Voltage [V]																																			
	Load 50%	Load 100%																																		
33	28.083	28.078																																		
36	28.084	28.075																																		
40	28.083	28.072																																		
48	28.084	28.073																																		
54	28.085	28.073																																		
60	28.087	28.073																																		
68	28.088	28.076																																		
76	28.087	28.078																																		
80	28.085	28.078																																		
Note: Slanted line shows the range of the rated input voltage.																																				
(注)斜線は定格入力電圧範囲を示す。																																				



Model		CDS6004828		Temperature		25°C																																																																								
Item		Input Current (by Input Voltage) 入力電流 (入力電圧特性)		Testing Circuitry		Figure A																																																																								
Object		_____																																																																												
1. Graph				2. Values																																																																										
<p>Legend:          —△— Load 100%          - - -□- - - Load 50%          - - -○- - - Load 0%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>25.0</td><td>0.025</td><td>0.023</td><td>0.024</td></tr> <tr><td>27.5</td><td>0.131</td><td>12.760</td><td>23.370</td></tr> <tr><td>30.0</td><td>0.121</td><td>13.330</td><td>25.530</td></tr> <tr><td>33.0</td><td>0.113</td><td>11.850</td><td>24.970</td></tr> <tr><td>36.0</td><td>0.109</td><td>10.820</td><td>22.530</td></tr> <tr><td>40.0</td><td>0.103</td><td>9.730</td><td>20.130</td></tr> <tr><td>48.0</td><td>0.094</td><td>8.130</td><td>16.680</td></tr> <tr><td>54.0</td><td>0.083</td><td>7.240</td><td>14.810</td></tr> <tr><td>60.0</td><td>0.071</td><td>6.540</td><td>13.330</td></tr> <tr><td>68.0</td><td>0.062</td><td>5.800</td><td>11.780</td></tr> <tr><td>76.0</td><td>0.056</td><td>5.230</td><td>10.580</td></tr> <tr><td>80.0</td><td>0.054</td><td>4.990</td><td>10.080</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	25.0	0.025	0.023	0.024	27.5	0.131	12.760	23.370	30.0	0.121	13.330	25.530	33.0	0.113	11.850	24.970	36.0	0.109	10.820	22.530	40.0	0.103	9.730	20.130	48.0	0.094	8.130	16.680	54.0	0.083	7.240	14.810	60.0	0.071	6.540	13.330	68.0	0.062	5.800	11.780	76.0	0.056	5.230	10.580	80.0	0.054	4.990	10.080	-	-	-	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Input Current [A]																																																																													
	Load 0%	Load 50%	Load 100%																																																																											
0.0	0.000	0.000	0.000																																																																											
25.0	0.025	0.023	0.024																																																																											
27.5	0.131	12.760	23.370																																																																											
30.0	0.121	13.330	25.530																																																																											
33.0	0.113	11.850	24.970																																																																											
36.0	0.109	10.820	22.530																																																																											
40.0	0.103	9.730	20.130																																																																											
48.0	0.094	8.130	16.680																																																																											
54.0	0.083	7.240	14.810																																																																											
60.0	0.071	6.540	13.330																																																																											
68.0	0.062	5.800	11.780																																																																											
76.0	0.056	5.230	10.580																																																																											
80.0	0.054	4.990	10.080																																																																											
-	-	-	-																																																																											
-	-	-	-																																																																											
-	-	-	-																																																																											
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																																																														



Model		CDS6004828		Temperature		25°C																																																								
Item		Input Current (by Load Current) 入力電流 (負荷特性)		Testing Circuitry		Figure A																																																								
Object		_____																																																												
1. Graph				2. Values																																																										
<p>                 —△— Input Volt. 36V                  - - -□- - - Input Volt. 48V                  - - -○- - - Input Volt. 76V             </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.107</td><td>0.088</td><td>0.054</td></tr> <tr><td>4.0</td><td>3.523</td><td>2.698</td><td>1.805</td></tr> <tr><td>8.0</td><td>6.860</td><td>5.220</td><td>3.398</td></tr> <tr><td>12.0</td><td>10.250</td><td>7.750</td><td>5.010</td></tr> <tr><td>16.0</td><td>13.630</td><td>10.290</td><td>6.650</td></tr> <tr><td>20.0</td><td>17.280</td><td>12.940</td><td>8.360</td></tr> <tr><td>24.0</td><td>20.900</td><td>15.760</td><td>10.080</td></tr> <tr><td>25.0</td><td>21.600</td><td>16.460</td><td>10.520</td></tr> <tr><td>27.5</td><td>24.010</td><td>18.160</td><td>11.640</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.107	0.088	0.054	4.0	3.523	2.698	1.805	8.0	6.860	5.220	3.398	12.0	10.250	7.750	5.010	16.0	13.630	10.290	6.650	20.0	17.280	12.940	8.360	24.0	20.900	15.760	10.080	25.0	21.600	16.460	10.520	27.5	24.010	18.160	11.640	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Input Current [A]																																																													
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																											
0.0	0.107	0.088	0.054																																																											
4.0	3.523	2.698	1.805																																																											
8.0	6.860	5.220	3.398																																																											
12.0	10.250	7.750	5.010																																																											
16.0	13.630	10.290	6.650																																																											
20.0	17.280	12.940	8.360																																																											
24.0	20.900	15.760	10.080																																																											
25.0	21.600	16.460	10.520																																																											
27.5	24.010	18.160	11.640																																																											
-	-	-	-																																																											
-	-	-	-																																																											
-	-	-	-																																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																														



Model		CDS6004828		Temperature	25°C																																																							
Item		Input Power (by Load Current) 入力電力 (負荷特性)		Testing Circuitry	Figure A																																																							
Object		_____																																																										
1. Graph			2. Values																																																									
<p> <input type="checkbox"/> —△— Input Volt. 36V  <input type="checkbox"/> - - -□- - - Input Volt. 48V  <input type="checkbox"/> - - -○- - - Input Volt. 76V                 </p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.80</td><td>4.20</td><td>4.10</td></tr> <tr><td>4.0</td><td>126.20</td><td>129.20</td><td>137.10</td></tr> <tr><td>8.0</td><td>246.00</td><td>249.00</td><td>257.90</td></tr> <tr><td>12.0</td><td>368.00</td><td>371.00</td><td>380.00</td></tr> <tr><td>16.0</td><td>492.00</td><td>495.00</td><td>505.00</td></tr> <tr><td>20.0</td><td>620.00</td><td>623.00</td><td>634.00</td></tr> <tr><td>24.0</td><td>750.00</td><td>753.00</td><td>765.00</td></tr> <tr><td>25.0</td><td>783.00</td><td>786.00</td><td>798.00</td></tr> <tr><td>27.5</td><td>867.00</td><td>869.00</td><td>883.00</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	3.80	4.20	4.10	4.0	126.20	129.20	137.10	8.0	246.00	249.00	257.90	12.0	368.00	371.00	380.00	16.0	492.00	495.00	505.00	20.0	620.00	623.00	634.00	24.0	750.00	753.00	765.00	25.0	783.00	786.00	798.00	27.5	867.00	869.00	883.00	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																											
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																									
0.0	3.80	4.20	4.10																																																									
4.0	126.20	129.20	137.10																																																									
8.0	246.00	249.00	257.90																																																									
12.0	368.00	371.00	380.00																																																									
16.0	492.00	495.00	505.00																																																									
20.0	620.00	623.00	634.00																																																									
24.0	750.00	753.00	765.00																																																									
25.0	783.00	786.00	798.00																																																									
27.5	867.00	869.00	883.00																																																									
—	—	—	—																																																									
—	—	—	—																																																									
—	—	—	—																																																									
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																												



Model		CDS6004828	Temperature	25°C																																
Item		Efficiency (by Input Voltage) 効率 (入力電圧特性)	Testing Circuitry	Figure A																																
Object																																				
1. Graph		<p>-----□----- Load 50%</p> <p>-----△----- Load 100%</p>	2. Values																																	
<p>Efficiency [%]</p> <p>Input Voltage [V]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>91.7</td><td>89.1</td></tr> <tr><td>36</td><td>91.7</td><td>89.6</td></tr> <tr><td>40</td><td>91.2</td><td>89.5</td></tr> <tr><td>48</td><td>90.8</td><td>89.2</td></tr> <tr><td>54</td><td>90.3</td><td>89.0</td></tr> <tr><td>60</td><td>89.8</td><td>88.7</td></tr> <tr><td>68</td><td>89.2</td><td>88.2</td></tr> <tr><td>76</td><td>88.7</td><td>87.8</td></tr> <tr><td>80</td><td>88.2</td><td>87.6</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	91.7	89.1	36	91.7	89.6	40	91.2	89.5	48	90.8	89.2	54	90.3	89.0	60	89.8	88.7	68	89.2	88.2	76	88.7	87.8	80	88.2	87.6		
	Input Voltage [V]	Efficiency [%]																																		
		Load 50%	Load 100%																																	
	33	91.7	89.1																																	
	36	91.7	89.6																																	
	40	91.2	89.5																																	
	48	90.8	89.2																																	
	54	90.3	89.0																																	
	60	89.8	88.7																																	
	68	89.2	88.2																																	
	76	88.7	87.8																																	
80	88.2	87.6																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																				



Model		CDS6004828		Temperature	25°C																																																							
Item		Efficiency (by Load Current) 効率 (負荷特性)		Testing Circuitry	Figure A																																																							
Object		_____																																																										
1. Graph			2. Values																																																									
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>88.9</td><td>86.9</td><td>81.9</td></tr> <tr><td>8.0</td><td>91.3</td><td>90.1</td><td>87.0</td></tr> <tr><td>12.0</td><td>91.5</td><td>90.8</td><td>88.5</td></tr> <tr><td>16.0</td><td>91.3</td><td>90.6</td><td>88.8</td></tr> <tr><td>20.0</td><td>90.6</td><td>90.2</td><td>88.6</td></tr> <tr><td>24.0</td><td>89.8</td><td>89.5</td><td>88.1</td></tr> <tr><td>25.0</td><td>89.6</td><td>89.3</td><td>87.9</td></tr> <tr><td>27.5</td><td>89.0</td><td>88.8</td><td>87.4</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	4.0	88.9	86.9	81.9	8.0	91.3	90.1	87.0	12.0	91.5	90.8	88.5	16.0	91.3	90.6	88.8	20.0	90.6	90.2	88.6	24.0	89.8	89.5	88.1	25.0	89.6	89.3	87.9	27.5	89.0	88.8	87.4	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																											
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																									
4.0	88.9	86.9	81.9																																																									
8.0	91.3	90.1	87.0																																																									
12.0	91.5	90.8	88.5																																																									
16.0	91.3	90.6	88.8																																																									
20.0	90.6	90.2	88.6																																																									
24.0	89.8	89.5	88.1																																																									
25.0	89.6	89.3	87.9																																																									
27.5	89.0	88.8	87.4																																																									
—	—	—	—																																																									
—	—	—	—																																																									
—	—	—	—																																																									
—	—	—	—																																																									
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																												




Model	CDS6004828
Item	Load Regulation 静的負荷変動
Object	+28.0V25A

Temperature	25°C
Testing Circuitry	Figure A

1. Graph

—△— Input Volt. 36 V  
 - - -□- - - Input Volt. 48 V  
 - - -○- - - Input Volt. 76 V



Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	28.021	28.024	28.024
4.0	28.030	28.033	28.039
8.0	28.052	28.063	28.064
12.0	28.065	28.071	28.075
16.0	28.075	28.073	28.079
20.0	28.073	28.076	28.082
24.0	28.067	28.070	28.078
25.0	28.065	28.068	28.077
27.5	28.063	28.066	28.074
—	—	—	—




Model		CDS6004828	Temperature		25°C																																						
Item		Ripple Voltage (by Load Current) リップル電圧(負荷特性)	Testing Circuitry		Figure A																																						
Object		+28.0V25A																																									
<p>1. Graph</p> <p>—△— Input Volt. 36V - - -□- - - Input Volt. 76V</p>			<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Volt. [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0</td><td>5</td></tr> <tr><td>4.0</td><td>10</td><td>20</td></tr> <tr><td>8.0</td><td>15</td><td>25</td></tr> <tr><td>12.0</td><td>15</td><td>25</td></tr> <tr><td>16.0</td><td>15</td><td>25</td></tr> <tr><td>20.0</td><td>15</td><td>25</td></tr> <tr><td>24.0</td><td>15</td><td>25</td></tr> <tr><td>25.0</td><td>15</td><td>25</td></tr> <tr><td>27.5</td><td>15</td><td>25</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Volt. [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.0	0	5	4.0	10	20	8.0	15	25	12.0	15	25	16.0	15	25	20.0	15	25	24.0	15	25	25.0	15	25	27.5	15	25	—	—	—	—	—	—
Load Current [A]	Ripple Output Volt. [mV]																																										
	Input Volt. 36 [V]	Input Volt. 76 [V]																																									
0.0	0	5																																									
4.0	10	20																																									
8.0	15	25																																									
12.0	15	25																																									
16.0	15	25																																									
20.0	15	25																																									
24.0	15	25																																									
25.0	15	25																																									
27.5	15	25																																									
—	—	—																																									
—	—	—																																									
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p-p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>図 リップル波形図</p>																																											



Model	CDS6004828	Temperature	25°C
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A
Object	+28.0V25A		

1. Graph



2. Values

Load current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	5	5
4.0	25	40
8.0	35	50
12.0	50	55
16.0	65	60
20.0	70	60
24.0	65	55
25.0	65	55
27.5	60	55
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。  
 (注) 斜線は定格負荷電流範囲を示す。




図 リップルノイズ波形図




<p>Model CDS6004828</p> <p>Item Overcurrent Protection 過電流保護</p> <p>Object +28.0V25A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																						
<p>1. Graph</p> <p>[V]</p> <p>Output Voltage</p> <p>40.0</p> <p>30.0</p> <p>20.0</p> <p>10.0</p> <p>0.0</p> <p>0 10 20 30 40</p> <p>Load Current [A]</p> <p> <span style="border-bottom: 1px solid black; width: 50px; display: inline-block;"></span> Input Volt. 36 V  <span style="border-bottom: 1px dashed black; width: 50px; display: inline-block;"></span> Input Volt. 48 V  <span style="border-bottom: 1px solid black; width: 50px; display: inline-block;"></span> Input Volt. 76 V                 </p>	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>28.00</td><td>0.00</td><td>29.45</td><td>0.00</td></tr> <tr><td>26.60</td><td>28.64</td><td>29.75</td><td>31.81</td></tr> <tr><td>25.20</td><td>28.72</td><td>29.97</td><td>32.02</td></tr> <tr><td>22.40</td><td>28.97</td><td>30.41</td><td>32.18</td></tr> <tr><td>19.60</td><td>29.27</td><td>30.89</td><td>32.29</td></tr> <tr><td>16.80</td><td>29.59</td><td>31.27</td><td>32.58</td></tr> <tr><td>14.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>11.20</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>8.40</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>5.60</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>2.80</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	28.00	0.00	29.45	0.00	26.60	28.64	29.75	31.81	25.20	28.72	29.97	32.02	22.40	28.97	30.41	32.18	19.60	29.27	30.89	32.29	16.80	29.59	31.27	32.58	14.00	—	—	—	11.20	—	—	—	8.40	—	—	—	5.60	—	—	—	2.80	—	—	—	0.00	—	—	—
Output Voltage [V]	Load Current [A]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
28.00	0.00	29.45	0.00																																																					
26.60	28.64	29.75	31.81																																																					
25.20	28.72	29.97	32.02																																																					
22.40	28.97	30.41	32.18																																																					
19.60	29.27	30.89	32.29																																																					
16.80	29.59	31.27	32.58																																																					
14.00	—	—	—																																																					
11.20	—	—	—																																																					
8.40	—	—	—																																																					
5.60	—	—	—																																																					
2.80	—	—	—																																																					
0.00	—	—	—																																																					
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 16.8V to 0V.</p> <p>(注)斜線は定格負荷電流範囲を示す。 16.8V~0V間は、間欠モードとなる。</p>																																																								



Model	CDS6004828
Item	Overvoltage Protection 過電圧保護
Object	+28.0V25A

Testing Circuitry Figure A



2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-35	35.04	34.97	34.97
-20	35.39	35.25	35.25
0	35.95	35.81	35.81
15	36.30	36.16	36.16
25	36.51	36.44	36.44
40	36.86	36.79	36.79
55	37.28	37.14	37.14
70	37.63	37.49	37.49
85	37.98	37.84	37.84
90	38.12	37.98	37.91
100	38.19	38.12	38.12


Load 0%

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Model	CDS6004828	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+28.0V25A		


Input Volt. 48 V  
Cycle 1000 ms




Min. Load (0A) ←→

Load 100% (25A)

500 mV/div



1 ms/div




100 ms/div

Min. Load (0A) ←→

Load 50% (12.5A)

500 mV/div



1 ms/div




100 ms/div


Load 10% (2.5A) ←→

Load 100% (25A)

500 mV/div



1 ms/div




1 ms/div



Model	CDS6004828	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+28.0V25A		

1. Graph


Input Volt. 36 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	42.75	13.75	56.50	0.25	3.10
100 %	42.75	13.50	56.25	0.20	1.55






Model	CDS6004828
Item	Ambient Temperature Drift 周囲温度変動
Object	+28.0V25A

Testing Circuitry Figure A

1. Graph
- △— Input Volt. 36V
  - - -□- - - Input Volt. 48V
  - - -○- - - Input Volt. 76V



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。


2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-35	28.206	28.204	28.195
-20	28.191	28.187	28.180
0	28.158	28.151	28.151
15	28.136	28.133	28.136
25	28.116	28.115	28.123
40	28.084	28.084	28.095
55	28.048	28.049	28.061
70	28.007	28.009	28.026
85	27.963	27.969	27.989
90	27.940	27.948	27.967
100	27.912	27.922	27.942



Model	CDS6004828
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+28.0V25A

Testing Circuitry Figure A



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-35	27.0	28.2
-20	27.1	28.3
0	27.2	28.4
15	27.3	28.5
25	27.3	28.7
40	27.3	28.7
55	27.3	28.8
70	27.4	28.8
85	27.3	28.9
90	27.2	28.9
100	27.2	28.9


Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。



Model	CDS6004828
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+28.0V 25A

Testing Circuitry Figure A



2. Values

Ambient Temp. [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-35	30	35
-20	30	30
0	20	20
15	15	15
25	15	15
40	10	10
55	15	10
70	15	15
85	15	15
90	15	15
100	15	15

Input Volt. 48 V

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。



<b>COSEL</b>																								
Model	CDS6004828																							
Item	Time Lapse Drift 経時ドリフト	Temperature 25°C Testing Circuitry Figure A																						
Object	+28.0V25A																							
<p>1. Graph</p> <p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>28.110</td></tr> <tr><td>0.5</td><td>28.053</td></tr> <tr><td>1.0</td><td>28.055</td></tr> <tr><td>2.0</td><td>28.056</td></tr> <tr><td>3.0</td><td>28.056</td></tr> <tr><td>4.0</td><td>28.057</td></tr> <tr><td>5.0</td><td>28.057</td></tr> <tr><td>6.0</td><td>28.057</td></tr> <tr><td>7.0</td><td>28.058</td></tr> <tr><td>8.0</td><td>28.058</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	28.110	0.5	28.053	1.0	28.055	2.0	28.056	3.0	28.056	4.0	28.057	5.0	28.057	6.0	28.057	7.0	28.058	8.0	28.058
Time since start [H]	Output Voltage [V]																							
0.0	28.110																							
0.5	28.053																							
1.0	28.055																							
2.0	28.056																							
3.0	28.056																							
4.0	28.057																							
5.0	28.057																							
6.0	28.057																							
7.0	28.058																							
8.0	28.058																							



Model		CDS6004828	Testing Circuitry Figure A
Item		Output Voltage Accuracy 定電圧精度	
Object		+28.0V25A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~85 °C

Input Voltage : 36~ 76 V

Load Current : 0~25 A

\* Output Voltage Accuracy =  $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~85 °C

入力電圧 36~ 76 V

負荷電流 0~25 A

\* 定電圧精度(変動値) =  $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

\* 定電圧精度(変動率) =  $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	-20	36	25	28.189	±135	±0.5
Minimum Voltage	85	36	0	27.921		



Model		CDS6004828	Testing Circuitry Figure A
Item		Condensation 結露特性	
Object		+28.0V25A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at  $-10^{\circ}\text{C}$  for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is  $25^{\circ}\text{C}$  and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で $-10^{\circ}\text{C}$ に冷却しておき、約1時間後に恒温槽から取り出し、室温 $25^{\circ}\text{C}$ 、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	28.073	Input Volt.: 48V, Load Current:25A
Line Regulation [mV]	6	Input Volt.: 36~76V, Load Current:25A
Load Regulation [mV]	58	Input Volt.: 48V, Load Current:0~25A



Model		CDS6004828	Temperature		25°C
Item		Line Noise Tolerance 入力雑音耐量	Testing Circuitry		Figure B
Object		+28.0V25A			

1. Results

Pulse Width [n S]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

Conditions

Input Voltage : 48 V  
 Pulse Voltage : ±2000 V  
 Pulse Cycle : 10 mS  
 Pulse Input Duration: 1 min. or more  
 Load : 100 %




Figure A




Figure B




Figure C (General Electric Characteristic)  
一般電気特性