

TEST DATA OF CHS3004812H

Regulated DC Power Supply
June 3, 2013

Approved by : Yoshimichi Hirokawa
Yoshimichi Hirokawa Design Manager

Prepared by : Ryosuke Kawai
Ryosuke Kawai Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	CHS3004812H
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
8.0	0.000	0.000	0.000
16.0	0.000	0.000	0.000
24.0	0.006	0.006	0.006
33.0	0.015	0.015	0.015
36.0	0.085	3.906	7.530
37.6	0.084	4.076	7.860
38.4	0.082	4.044	8.030
40.0	0.081	3.890	7.859
48.0	0.082	3.255	6.535
60.0	0.087	2.629	5.239
70.0	0.090	2.292	4.523
76.0	0.091	2.117	4.166
80.0	0.091	2.020	3.962
84.8	0.092	1.896	3.725
88.0	0.092	1.834	3.591
--	-	-	-
--	-	-	-

COSEL

Model	CHS3004812H
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	0.079	0.081	0.091
4.0	1.288	1.088	0.727
8.0	2.505	2.105	1.377
12.0	3.734	3.128	2.032
16.0	4.979	4.158	2.684
20.0	6.243	5.208	3.340
24.0	7.522	6.268	4.009
25.0	7.859	6.535	4.166
27.5	8.663	7.272	4.598
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL


Model CHS3004812H

Item Input Power (by Load Current)

Object _____

1.Graph

—△— Input Volt. 40V
 -□--- Input Volt. 48V
 -○--- Input Volt. 76V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	3.2	3.9	7.0
4.0	51.5	52.2	55.3
8.0	100.2	101.0	104.7
12.0	149.4	150.2	154.5
16.0	199.2	199.6	204.0
20.0	249.7	250.0	253.9
24.0	300.9	300.9	304.6
25.0	314.3	313.7	316.6
27.5	346.5	349.1	349.4
--	-	-	-
--	-	-	-

COSEL

Model	CHS3004812H
Item	Efficiency (by Input Voltage)
Object	

1. Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
40	96.5	95.5
42	96.5	95.6
46	96.3	95.8
48	96.1	95.7
55	95.6	95.6
60	95.2	95.5
70	93.6	94.8
76	93.3	94.8
80	92.9	94.7


COSEL

Model	CHS3004812H	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<p>Efficiency [%]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>4.0</td><td>93.3</td><td>92.0</td><td>86.9</td></tr> <tr> <td>8.0</td><td>95.9</td><td>95.1</td><td>91.8</td></tr> <tr> <td>12.0</td><td>96.5</td><td>96.0</td><td>93.3</td></tr> <tr> <td>16.0</td><td>96.5</td><td>96.3</td><td>94.2</td></tr> <tr> <td>20.0</td><td>96.2</td><td>96.1</td><td>94.6</td></tr> <tr> <td>24.0</td><td>95.8</td><td>95.8</td><td>94.6</td></tr> <tr> <td>25.0</td><td>95.5</td><td>95.7</td><td>94.8</td></tr> <tr> <td>27.5</td><td>95.3</td><td>94.6</td><td>94.7</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	4.0	93.3	92.0	86.9	8.0	95.9	95.1	91.8	12.0	96.5	96.0	93.3	16.0	96.5	96.3	94.2	20.0	96.2	96.1	94.6	24.0	95.8	95.8	94.6	25.0	95.5	95.7	94.8	27.5	95.3	94.6	94.7	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
4.0	93.3	92.0	86.9																																																			
8.0	95.9	95.1	91.8																																																			
12.0	96.5	96.0	93.3																																																			
16.0	96.5	96.3	94.2																																																			
20.0	96.2	96.1	94.6																																																			
24.0	95.8	95.8	94.6																																																			
25.0	95.5	95.7	94.8																																																			
27.5	95.3	94.6	94.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	CHS3004812H
Item	Line Regulation
Object	+12V25A



Temperature 25°C
Testing Circuitry Figure A

2.Values


Input Voltage [V]	Output Voltage [V]		
	Load 0%	Load 50%	Load 100%
36	11.873	11.359	11.032
38	12.012	12.011	11.724
39	12.012	12.012	12.008
40	12.012	12.012	12.008
48	12.012	12.012	12.008
55	12.012	12.012	12.008
60	12.011	12.011	12.008
70	12.011	12.011	12.007
76	12.009	12.009	12.007

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CHS3004812H	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+12V25A																																																						
1.Graph	<p>—△— Input Volt. 40V - -□--- Input Volt. 48V - -○--- Input Volt. 76V</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.012</td><td>12.012</td><td>12.009</td></tr> <tr><td>4.0</td><td>12.012</td><td>12.012</td><td>12.009</td></tr> <tr><td>8.0</td><td>12.012</td><td>12.012</td><td>12.009</td></tr> <tr><td>12.0</td><td>12.012</td><td>12.012</td><td>12.009</td></tr> <tr><td>16.0</td><td>12.012</td><td>12.012</td><td>12.008</td></tr> <tr><td>20.0</td><td>12.011</td><td>12.011</td><td>12.008</td></tr> <tr><td>24.0</td><td>12.010</td><td>12.010</td><td>12.008</td></tr> <tr><td>25.0</td><td>12.008</td><td>12.008</td><td>12.007</td></tr> <tr><td>27.5</td><td>12.008</td><td>12.008</td><td>12.007</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	12.012	12.012	12.009	4.0	12.012	12.012	12.009	8.0	12.012	12.012	12.009	12.0	12.012	12.012	12.009	16.0	12.012	12.012	12.008	20.0	12.011	12.011	12.008	24.0	12.010	12.010	12.008	25.0	12.008	12.008	12.007	27.5	12.008	12.008	12.007	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
0.0	12.012	12.012	12.009																																																				
4.0	12.012	12.012	12.009																																																				
8.0	12.012	12.012	12.009																																																				
12.0	12.012	12.012	12.009																																																				
16.0	12.012	12.012	12.008																																																				
20.0	12.011	12.011	12.008																																																				
24.0	12.010	12.010	12.008																																																				
25.0	12.008	12.008	12.007																																																				
27.5	12.008	12.008	12.007																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.


COSEL

COSEL

Model	CHS3004812H
Item	Ripple Voltage (by Load Current)
Object	+12V25A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 40 [V]	Input Volt. 76 [V]
0.0	15	25
4.0	15	25
8.0	15	25
12.0	15	25
16.0	15	25
20.0	15	25
24.0	15	25
25.0	15	25
27.5	15	25
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	CHS3004812H
Item	Ripple-Noise
Object	+12V25A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 40 [V]	Input Volt. 76 [V]
0.0	20	25
4.0	25	40
8.0	30	55
12.0	30	55
16.0	30	60
20.0	30	65
24.0	30	65
25.0	30	65
27.5	35	70
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	CHS3004812H
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V25A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	30	30
-20	30	30
0	25	30
25	25	30
40	25	30
60	30	35
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Model CHS3004812H

Item Ambient Temperature Drift

Object +12V25A

1. Graph

—△— Input Volt. 40V
 - -□--- Input Volt. 48V
 - -○--- Input Volt. 76V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	12.044	12.042	12.040
-20	12.027	12.027	12.024
0	12.018	12.017	12.015
25	12.008	12.007	12.006
40	12.003	12.003	12.002
55	12.003	12.003	12.002
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	CHS3004812H	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V25A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 40 - 76V

Load Current : 0 - 25A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	48	0	12.046	± 22	± 0.2
Minimum Voltage	40	76	25	12.002		

COSEL

Model	CHS3004812H	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+12V25A																							
1.Graph		2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.022</td></tr> <tr><td>0.5</td><td>12.011</td></tr> <tr><td>1.0</td><td>12.011</td></tr> <tr><td>2.0</td><td>12.011</td></tr> <tr><td>3.0</td><td>12.011</td></tr> <tr><td>4.0</td><td>12.011</td></tr> <tr><td>5.0</td><td>12.011</td></tr> <tr><td>6.0</td><td>12.011</td></tr> <tr><td>7.0</td><td>12.011</td></tr> <tr><td>8.0</td><td>12.011</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.022	0.5	12.011	1.0	12.011	2.0	12.011	3.0	12.011	4.0	12.011	5.0	12.011	6.0	12.011	7.0	12.011	8.0	12.011
Time since start [H]	Output Voltage [V]																							
0.0	12.022																							
0.5	12.011																							
1.0	12.011																							
2.0	12.011																							
3.0	12.011																							
4.0	12.011																							
5.0	12.011																							
6.0	12.011																							
7.0	12.011																							
8.0	12.011																							

COSEL


Model CHS3004812H

Item Rise and Fall Time

Object +12V25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		8.6	3.9	12.5	1.2	1.0	
100 %		8.5	6.6	15.1	0.6	0.8	




COSEL

Model CHS3004812H

Item Minimum Input Voltage
for Regulated Output Voltage

Object +12V25A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	36.2	36.9
-20	36.2	36.9
0	36.4	37.0
25	36.4	37.0
40	36.1	37.0
55	36.1	37.0
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Model CHS3004812H

Item Overcurrent Protection

Object +12V25A

1. Graph

— Input Volt. 40V
 — Input Volt. 48V
 — Input Volt. 76V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]
11.4	31.18	31.00	30.24
10.8	31.23	30.87	30.40
9.6	30.99	30.66	30.23
8.4	30.90	30.61	30.24
8.0	30.90	30.62	30.24
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model CHS3004812H

Item Overvoltage Protection

Object +12V25A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt.	Input Volt.
-40	48[V]	76[V]
-20	15.10	15.16
0	15.08	15.08
25	15.16	15.16
40	15.26	15.22
60	15.26	15.26
85	15.20	15.14
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B