



# TEST DATA OF CHS3004824

Regulated DC Power Supply  
September 26, 2019

Approved by : Yukihiko Takehashi  
Yukihiko Takehashi Design Manager

Prepared by : Tatsuya Nakagawa  
Tatsuya Nakagawa Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Overvoltage Protection . . . . .	18
19.Figure of Testing Circuitry . . . . .	19

(Final Page 19)




Model		CHS3004824		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object																																																																																				
1.Graph			2.Values																																																																																	
<p>Legend:          —△— Load 100%          - - - □ - - - Load 50%          - · - ○ - · - - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.008</td><td>0.008</td><td>0.008</td></tr> <tr><td>16.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>24.0</td><td>0.009</td><td>0.009</td><td>0.010</td></tr> <tr><td>33.0</td><td>0.010</td><td>0.010</td><td>0.010</td></tr> <tr><td>33.6</td><td>0.071</td><td>4.641</td><td>9.378</td></tr> <tr><td>36.0</td><td>0.072</td><td>4.347</td><td>8.796</td></tr> <tr><td>40.0</td><td>0.075</td><td>3.918</td><td>7.915</td></tr> <tr><td>42.4</td><td>0.076</td><td>3.701</td><td>7.462</td></tr> <tr><td>44.0</td><td>0.078</td><td>3.579</td><td>7.209</td></tr> <tr><td>48.0</td><td>0.080</td><td>3.288</td><td>6.611</td></tr> <tr><td>60.0</td><td>0.086</td><td>2.660</td><td>5.316</td></tr> <tr><td>70.0</td><td>0.089</td><td>2.301</td><td>4.578</td></tr> <tr><td>76.0</td><td>0.091</td><td>2.134</td><td>4.224</td></tr> <tr><td>80.0</td><td>0.092</td><td>2.035</td><td>4.028</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.008	0.008	0.008	16.0	0.009	0.009	0.009	24.0	0.009	0.009	0.010	33.0	0.010	0.010	0.010	33.6	0.071	4.641	9.378	36.0	0.072	4.347	8.796	40.0	0.075	3.918	7.915	42.4	0.076	3.701	7.462	44.0	0.078	3.579	7.209	48.0	0.080	3.288	6.611	60.0	0.086	2.660	5.316	70.0	0.089	2.301	4.578	76.0	0.091	2.134	4.224	80.0	0.092	2.035	4.028	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
8.0	0.008	0.008	0.008																																																																																	
16.0	0.009	0.009	0.009																																																																																	
24.0	0.009	0.009	0.010																																																																																	
33.0	0.010	0.010	0.010																																																																																	
33.6	0.071	4.641	9.378																																																																																	
36.0	0.072	4.347	8.796																																																																																	
40.0	0.075	3.918	7.915																																																																																	
42.4	0.076	3.701	7.462																																																																																	
44.0	0.078	3.579	7.209																																																																																	
48.0	0.080	3.288	6.611																																																																																	
60.0	0.086	2.660	5.316																																																																																	
70.0	0.089	2.301	4.578																																																																																	
76.0	0.091	2.134	4.224																																																																																	
80.0	0.092	2.035	4.028																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model	CHS3004824
Item	Input Current (by Load Current)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A



2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	0.072	0.080	0.091
2.00	1.423	1.094	0.737
4.00	2.789	2.125	1.392
6.00	4.168	3.162	2.050
8.00	5.574	4.201	2.712
10.00	6.987	5.261	3.378
12.00	8.417	6.334	4.057
12.50	8.796	6.611	4.224
13.75	9.715	7.288	4.655
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.



Model		CHS3004824		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 36V</p> <p>- - - □ - - - Input Volt. 48V</p> <p>- · - ○ - · - - Input Volt. 76V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2.6</td><td>3.8</td><td>6.9</td></tr> <tr><td>2.00</td><td>51.3</td><td>52.6</td><td>56.0</td></tr> <tr><td>4.00</td><td>100.5</td><td>102.1</td><td>105.9</td></tr> <tr><td>6.00</td><td>150.2</td><td>151.8</td><td>156.0</td></tr> <tr><td>8.00</td><td>200.7</td><td>201.9</td><td>206.3</td></tr> <tr><td>10.00</td><td>251.8</td><td>252.9</td><td>257.1</td></tr> <tr><td>12.00</td><td>303.5</td><td>304.3</td><td>308.4</td></tr> <tr><td>12.50</td><td>316.8</td><td>317.4</td><td>321.4</td></tr> <tr><td>13.75</td><td>349.8</td><td>350.1</td><td>353.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	2.6	3.8	6.9	2.00	51.3	52.6	56.0	4.00	100.5	102.1	105.9	6.00	150.2	151.8	156.0	8.00	200.7	201.9	206.3	10.00	251.8	252.9	257.1	12.00	303.5	304.3	308.4	12.50	316.8	317.4	321.4	13.75	349.8	350.1	353.9	--	-	-	-	--	-	-	-		
Load Current [A]	Input Power [W]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	2.6	3.8	6.9																																																					
2.00	51.3	52.6	56.0																																																					
4.00	100.5	102.1	105.9																																																					
6.00	150.2	151.8	156.0																																																					
8.00	200.7	201.9	206.3																																																					
10.00	251.8	252.9	257.1																																																					
12.00	303.5	304.3	308.4																																																					
12.50	316.8	317.4	321.4																																																					
13.75	349.8	350.1	353.9																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



<b>COSEL</b>																																		
Model	CHS3004824																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____																																	
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>35</td><td>96.0</td><td>94.9</td></tr> <tr><td>36</td><td>96.0</td><td>94.9</td></tr> <tr><td>40</td><td>95.7</td><td>94.8</td></tr> <tr><td>48</td><td>95.1</td><td>94.7</td></tr> <tr><td>55</td><td>94.5</td><td>94.4</td></tr> <tr><td>60</td><td>94.0</td><td>94.2</td></tr> <tr><td>70</td><td>93.1</td><td>93.8</td></tr> <tr><td>76</td><td>92.6</td><td>93.5</td></tr> <tr><td>80</td><td>92.2</td><td>93.3</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	35	96.0	94.9	36	96.0	94.9	40	95.7	94.8	48	95.1	94.7	55	94.5	94.4	60	94.0	94.2	70	93.1	93.8	76	92.6	93.5	80	92.2	93.3
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
35	96.0	94.9																																
36	96.0	94.9																																
40	95.7	94.8																																
48	95.1	94.7																																
55	94.5	94.4																																
60	94.0	94.2																																
70	93.1	93.8																																
76	92.6	93.5																																
80	92.2	93.3																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



Model		CHS3004824		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 36V - - □ - - Input Volt. 48V - · ○ - · Input Volt. 76V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>93.5</td><td>91.1</td><td>85.4</td></tr> <tr><td>4.00</td><td>95.6</td><td>94.1</td><td>90.7</td></tr> <tr><td>6.00</td><td>96.0</td><td>95.0</td><td>92.4</td></tr> <tr><td>8.00</td><td>95.8</td><td>95.2</td><td>93.2</td></tr> <tr><td>10.00</td><td>95.5</td><td>95.1</td><td>93.5</td></tr> <tr><td>12.00</td><td>95.1</td><td>94.8</td><td>93.6</td></tr> <tr><td>12.50</td><td>94.9</td><td>94.7</td><td>93.5</td></tr> <tr><td>13.75</td><td>94.6</td><td>94.5</td><td>93.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	2.00	93.5	91.1	85.4	4.00	95.6	94.1	90.7	6.00	96.0	95.0	92.4	8.00	95.8	95.2	93.2	10.00	95.5	95.1	93.5	12.00	95.1	94.8	93.6	12.50	94.9	94.7	93.5	13.75	94.6	94.5	93.4	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	-	-	-																																																					
2.00	93.5	91.1	85.4																																																					
4.00	95.6	94.1	90.7																																																					
6.00	96.0	95.0	92.4																																																					
8.00	95.8	95.2	93.2																																																					
10.00	95.5	95.1	93.5																																																					
12.00	95.1	94.8	93.6																																																					
12.50	94.9	94.7	93.5																																																					
13.75	94.6	94.5	93.4																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



<b>COSEL</b>																																			
Model	CHS3004824	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+24V12.5A																																		
<p>1. Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>35</td><td>24.061</td><td>24.072</td></tr> <tr><td>36</td><td>24.061</td><td>24.072</td></tr> <tr><td>40</td><td>24.061</td><td>24.072</td></tr> <tr><td>48</td><td>24.062</td><td>24.072</td></tr> <tr><td>55</td><td>24.063</td><td>24.073</td></tr> <tr><td>60</td><td>24.064</td><td>24.074</td></tr> <tr><td>70</td><td>24.066</td><td>24.075</td></tr> <tr><td>76</td><td>24.067</td><td>24.076</td></tr> <tr><td>80</td><td>24.068</td><td>24.076</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	35	24.061	24.072	36	24.061	24.072	40	24.061	24.072	48	24.062	24.072	55	24.063	24.073	60	24.064	24.074	70	24.066	24.075	76	24.067	24.076	80	24.068	24.076
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
35	24.061	24.072																																	
36	24.061	24.072																																	
40	24.061	24.072																																	
48	24.062	24.072																																	
55	24.063	24.073																																	
60	24.064	24.074																																	
70	24.066	24.075																																	
76	24.067	24.076																																	
80	24.068	24.076																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			




<p>Model CHS3004824</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Load Regulation</p>																																																					
<p>Object +24V12.5A</p>																																																					
<p>1.Graph</p> <p>                     —△— Input Volt. 36V                      - - - □ - - - Input Volt. 48V                      - · - ○ - · - - Input Volt. 76V                 </p> <p>                     Output Voltage [V]                      Load Current [A]                 </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>24.063</td><td>24.064</td><td>24.066</td></tr> <tr><td>2.00</td><td>24.059</td><td>24.061</td><td>24.065</td></tr> <tr><td>4.00</td><td>24.059</td><td>24.061</td><td>24.065</td></tr> <tr><td>6.00</td><td>24.060</td><td>24.062</td><td>24.067</td></tr> <tr><td>8.00</td><td>24.062</td><td>24.064</td><td>24.069</td></tr> <tr><td>10.00</td><td>24.064</td><td>24.066</td><td>24.072</td></tr> <tr><td>12.00</td><td>24.067</td><td>24.070</td><td>24.073</td></tr> <tr><td>12.50</td><td>24.072</td><td>24.072</td><td>24.076</td></tr> <tr><td>13.75</td><td>24.073</td><td>24.073</td><td>24.078</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	24.063	24.064	24.066	2.00	24.059	24.061	24.065	4.00	24.059	24.061	24.065	6.00	24.060	24.062	24.067	8.00	24.062	24.064	24.069	10.00	24.064	24.066	24.072	12.00	24.067	24.070	24.073	12.50	24.072	24.072	24.076	13.75	24.073	24.073	24.078	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	24.063	24.064	24.066																																																		
2.00	24.059	24.061	24.065																																																		
4.00	24.059	24.061	24.065																																																		
6.00	24.060	24.062	24.067																																																		
8.00	24.062	24.064	24.069																																																		
10.00	24.064	24.066	24.072																																																		
12.00	24.067	24.070	24.073																																																		
12.50	24.072	24.072	24.076																																																		
13.75	24.073	24.073	24.078																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					




Model		CHS3004824	
Item		Dynamic Load Response	
Object		+24V12.5A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 48 V  
 Cycle 10 ms




Min. Load (0A) ←→  
 Load 100% (12.5A)

1 V/div




400 us/div




400 us/div

Min. Load (0A) ←→  
 Load 50% (6.25A)

1 V/div




400 us/div




400 us/div

Load 50% (6.25A) ←→  
 Load 100% (12.5A)

1 V/div



400 us/div



400 us/div




<b>COSEL</b>																																								
Model	CHS3004824																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+24V12.5A																																							
<p>1. Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 36V</p> <p>-·-○-·- Input Volt. 76V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <div style="text-align: center;"> <p>Ripple [mVp-p]</p> </div> <p>Fig. Complex Ripple Wave Form</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>80</td><td>170</td></tr> <tr><td>3.10</td><td>80</td><td>160</td></tr> <tr><td>6.25</td><td>75</td><td>160</td></tr> <tr><td>9.30</td><td>70</td><td>160</td></tr> <tr><td>12.50</td><td>70</td><td>160</td></tr> <tr><td>13.75</td><td>70</td><td>160</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	80	170	3.10	80	160	6.25	75	160	9.30	70	160	12.50	70	160	13.75	70	160	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	80	170																																						
3.10	80	160																																						
6.25	75	160																																						
9.30	70	160																																						
12.50	70	160																																						
13.75	70	160																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



Model	CHS3004824	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure B
Object	+24V12.5A		

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	100	190
3.10	100	180
6.25	100	180
9.30	100	185
12.50	100	185
13.75	100	185
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.  
 Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form



<b>COSEL</b>																																								
Model	CHS3004824																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+24V12.5A																																							
<p>1.Graph</p> <p style="text-align: center;">Ambient Temperature [°C] Input Volt. 48V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>100</td><td>105</td></tr> <tr><td>-40</td><td>100</td><td>105</td></tr> <tr><td>0</td><td>90</td><td>100</td></tr> <tr><td>25</td><td>90</td><td>95</td></tr> <tr><td>55</td><td>90</td><td>95</td></tr> <tr><td>60</td><td>90</td><td>95</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-50	100	105	-40	100	105	0	90	100	25	90	95	55	90	95	60	90	95	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-50	100	105																																						
-40	100	105																																						
0	90	100																																						
25	90	95																																						
55	90	95																																						
60	90	95																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model CHS3004824</p>																																																						
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+24V12.5A																																																					
<p>1.Graph</p> <p>                     —△— Input Volt. 36V                      - - - □ - - - Input Volt. 48V                      · · · ○ · · · Input Volt. 76V                 </p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td> <td>23.949</td> <td>23.959</td> <td>23.975</td> </tr> <tr> <td>-20</td> <td>23.997</td> <td>24.007</td> <td>24.018</td> </tr> <tr> <td>0</td> <td>24.035</td> <td>24.041</td> <td>24.050</td> </tr> <tr> <td>25</td> <td>24.072</td> <td>24.072</td> <td>24.076</td> </tr> <tr> <td>40</td> <td>24.073</td> <td>24.076</td> <td>24.079</td> </tr> <tr> <td>55</td> <td>24.080</td> <td>24.081</td> <td>24.082</td> </tr> <tr> <td>60</td> <td>24.081</td> <td>24.081</td> <td>24.082</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-40	23.949	23.959	23.975	-20	23.997	24.007	24.018	0	24.035	24.041	24.050	25	24.072	24.072	24.076	40	24.073	24.076	24.079	55	24.080	24.081	24.082	60	24.081	24.081	24.082	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-40	23.949	23.959	23.975																																																			
-20	23.997	24.007	24.018																																																			
0	24.035	24.041	24.050																																																			
25	24.072	24.072	24.076																																																			
40	24.073	24.076	24.079																																																			
55	24.080	24.081	24.082																																																			
60	24.081	24.081	24.082																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



<b>COSEL</b>		Testing Circuitry Figure A
Model	CHS3004824	
Item	Output Voltage Accuracy	
Object	+24V12.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 12.5A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ratio) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	55	76	12.5	24.082	±74	±0.3
Minimum Voltage	-40	48	0	23.934		




<b>COSEL</b>																								
Model	CHS3004824																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+24V12.5A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.072</td></tr> <tr><td>0.5</td><td>24.072</td></tr> <tr><td>1.0</td><td>24.073</td></tr> <tr><td>2.0</td><td>24.074</td></tr> <tr><td>3.0</td><td>24.073</td></tr> <tr><td>4.0</td><td>24.074</td></tr> <tr><td>5.0</td><td>24.074</td></tr> <tr><td>6.0</td><td>24.073</td></tr> <tr><td>7.0</td><td>24.073</td></tr> <tr><td>8.0</td><td>24.073</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.072	0.5	24.072	1.0	24.073	2.0	24.074	3.0	24.073	4.0	24.074	5.0	24.074	6.0	24.073	7.0	24.073	8.0	24.073
Time since start [H]	Output Voltage [V]																							
0.0	24.072																							
0.5	24.072																							
1.0	24.073																							
2.0	24.074																							
3.0	24.073																							
4.0	24.074																							
5.0	24.074																							
6.0	24.073																							
7.0	24.073																							
8.0	24.073																							



Model		CHS3004824	Temperature		25°C
Item		Rise and Fall Time	Testing Circuitry		Figure A
Object		+24V12.5A			


1. Graph

Input Volt. 48 V



2. Values

		[ms]				
Load \ Time	Td	Tr	Ts	Th	Tf	
50 %	5.3	10.6	15.9	0.2	0.3	
100 %	5.3	10.7	16.0	0.2	0.2	





<b>COSEL</b>																																								
Model	CHS3004824																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+24V12.5A																																							
<p>1.Graph</p> <p style="text-align: center;"> <span style="margin-right: 20px;">---□---</span> Load 50%  <span>—△—</span> Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>32.4</td><td>32.5</td></tr> <tr><td>-20</td><td>32.6</td><td>32.6</td></tr> <tr><td>0</td><td>32.5</td><td>32.6</td></tr> <tr><td>25</td><td>32.6</td><td>32.8</td></tr> <tr><td>40</td><td>32.7</td><td>32.8</td></tr> <tr><td>55</td><td>32.7</td><td>32.8</td></tr> <tr><td>60</td><td>32.8</td><td>32.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	32.4	32.5	-20	32.6	32.6	0	32.5	32.6	25	32.6	32.8	40	32.7	32.8	55	32.7	32.8	60	32.8	32.9	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	32.4	32.5																																						
-20	32.6	32.6																																						
0	32.5	32.6																																						
25	32.6	32.8																																						
40	32.7	32.8																																						
55	32.7	32.8																																						
60	32.8	32.9																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model CHS3004824</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																							
<p>Item Overcurrent Protection</p>																																																									
<p>Object +24V12.5A</p>																																																									
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>— Input Volt. 36V</p> <p>— Input Volt. 48V</p> <p>— Input Volt. 76V</p> </div> </div> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>22.80</td> <td>17.96</td> <td>18.16</td> <td>18.14</td> </tr> <tr> <td>21.60</td> <td>18.27</td> <td>18.46</td> <td>18.32</td> </tr> <tr> <td>20.40</td> <td>18.41</td> <td>18.69</td> <td>18.44</td> </tr> <tr> <td>19.68</td> <td>18.62</td> <td>18.88</td> <td>18.71</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	22.80	17.96	18.16	18.14	21.60	18.27	18.46	18.32	20.40	18.41	18.69	18.44	19.68	18.62	18.88	18.71	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
22.80	17.96	18.16	18.14																																																						
21.60	18.27	18.46	18.32																																																						
20.40	18.41	18.69	18.44																																																						
19.68	18.62	18.88	18.71																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						



<b>COSEL</b>																																								
Model	CHS3004824																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+24V12.5A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Input Volt. 48V</p> <p>---○--- Input Volt. 76V</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>30.40</td><td>30.36</td></tr> <tr><td>-20</td><td>30.42</td><td>30.39</td></tr> <tr><td>0</td><td>30.45</td><td>30.41</td></tr> <tr><td>25</td><td>30.48</td><td>30.44</td></tr> <tr><td>55</td><td>30.40</td><td>30.39</td></tr> <tr><td>60</td><td>30.40</td><td>30.39</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 48[V]	Input Volt. 76[V]	-40	30.40	30.36	-20	30.42	30.39	0	30.45	30.41	25	30.48	30.44	55	30.40	30.39	60	30.40	30.39	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 48[V]	Input Volt. 76[V]																																						
-40	30.40	30.36																																						
-20	30.42	30.39																																						
0	30.45	30.41																																						
25	30.48	30.44																																						
55	30.40	30.39																																						
60	30.40	30.39																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								




Figure A




Figure B