

# TEST DATA OF CHS3804810

# Regulated DC Power Supply

## March 30, 2017

Approved by : Junichi Hatagishi  
Junichi Hatagishi                                  Design Manager

**COSEL CO.,LTD.**

## CONTENTS

1. Input Current (by Input Voltage) . . . . .	1
2. Input Current (by Load Current) . . . . .	2
3. Input Power (by Load Current) . . . . .	3
4. Efficiency (by Input Voltage) . . . . .	4
5. Efficiency (by Load Current) . . . . .	5
6. Line Regulation . . . . .	6
7. Load Regulation . . . . .	7
8. Dynamic Load Response . . . . .	8
9. Ripple Voltage (by Load Current) . . . . .	9
10. Ripple-Noise . . . . .	10
11. Ripple Voltage (by Ambient Temperature) . . . . .	11
12. Ambient Temperature Drift . . . . .	12
13. Output Voltage Accuracy . . . . .	13
14. Time Lapse Drift . . . . .	14
15. Rise and Fall Time . . . . .	15
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17. Overcurrent Protection . . . . .	17
18. Overvoltage Protection . . . . .	18
19. Figure of Testing Circuitry . . . . .	19

(Final Page 19)

**COSEL**

Model	CHS3804810	Temperature Testing Circuitry	25°C Figure A																																																																															
Item	Input Current (by Input Voltage)																																																																																	
Object	—																																																																																	
1.Graph		2.Values																																																																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.008</td><td>0.008</td><td>0.008</td></tr> <tr><td>16.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>24.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>33.0</td><td>0.010</td><td>0.010</td><td>0.010</td></tr> <tr><td>35.2</td><td>0.069</td><td>5.644</td><td>11.588</td></tr> <tr><td>36.0</td><td>0.069</td><td>5.514</td><td>11.287</td></tr> <tr><td>40.0</td><td>0.068</td><td>4.964</td><td>10.142</td></tr> <tr><td>48.0</td><td>0.069</td><td>4.152</td><td>8.426</td></tr> <tr><td>60.0</td><td>0.072</td><td>3.343</td><td>6.744</td></tr> <tr><td>70.0</td><td>0.072</td><td>2.878</td><td>5.787</td></tr> <tr><td>73.0</td><td>0.072</td><td>2.763</td><td>5.558</td></tr> <tr><td>76.0</td><td>0.072</td><td>2.658</td><td>5.339</td></tr> <tr><td>80.0</td><td>0.072</td><td>2.533</td><td>5.074</td></tr> <tr><td>84.0</td><td>0.073</td><td>2.418</td><td>4.834</td></tr> <tr><td>88.0</td><td>0.073</td><td>2.312</td><td>4.618</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.008	0.008	0.008	16.0	0.009	0.009	0.009	24.0	0.009	0.009	0.009	33.0	0.010	0.010	0.010	35.2	0.069	5.644	11.588	36.0	0.069	5.514	11.287	40.0	0.068	4.964	10.142	48.0	0.069	4.152	8.426	60.0	0.072	3.343	6.744	70.0	0.072	2.878	5.787	73.0	0.072	2.763	5.558	76.0	0.072	2.658	5.339	80.0	0.072	2.533	5.074	84.0	0.073	2.418	4.834	88.0	0.073	2.312	4.618	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
8.0	0.008	0.008	0.008																																																																															
16.0	0.009	0.009	0.009																																																																															
24.0	0.009	0.009	0.009																																																																															
33.0	0.010	0.010	0.010																																																																															
35.2	0.069	5.644	11.588																																																																															
36.0	0.069	5.514	11.287																																																																															
40.0	0.068	4.964	10.142																																																																															
48.0	0.069	4.152	8.426																																																																															
60.0	0.072	3.343	6.744																																																																															
70.0	0.072	2.878	5.787																																																																															
73.0	0.072	2.763	5.558																																																																															
76.0	0.072	2.658	5.339																																																																															
80.0	0.072	2.533	5.074																																																																															
84.0	0.073	2.418	4.834																																																																															
88.0	0.073	2.312	4.618																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

**COSSEL**

Model	CHS3804810																																																			
Item	Input Current (by Load Current)																																																			
Object	<p>1. Graph</p> <p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.069</td><td>0.069</td><td>0.072</td></tr> <tr><td>6.0</td><td>1.767</td><td>1.348</td><td>0.881</td></tr> <tr><td>12.0</td><td>3.479</td><td>2.628</td><td>1.700</td></tr> <tr><td>18.0</td><td>5.212</td><td>3.924</td><td>2.516</td></tr> <tr><td>24.0</td><td>7.003</td><td>5.249</td><td>3.350</td></tr> <tr><td>30.0</td><td>8.820</td><td>6.589</td><td>4.190</td></tr> <tr><td>36.0</td><td>10.643</td><td>7.968</td><td>5.045</td></tr> <tr><td>38.0</td><td>11.287</td><td>8.426</td><td>5.339</td></tr> <tr><td>41.8</td><td>12.504</td><td>9.309</td><td>5.887</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.069	0.069	0.072	6.0	1.767	1.348	0.881	12.0	3.479	2.628	1.700	18.0	5.212	3.924	2.516	24.0	7.003	5.249	3.350	30.0	8.820	6.589	4.190	36.0	10.643	7.968	5.045	38.0	11.287	8.426	5.339	41.8	12.504	9.309	5.887	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																			
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																	
0.0	0.069	0.069	0.072																																																	
6.0	1.767	1.348	0.881																																																	
12.0	3.479	2.628	1.700																																																	
18.0	5.212	3.924	2.516																																																	
24.0	7.003	5.249	3.350																																																	
30.0	8.820	6.589	4.190																																																	
36.0	10.643	7.968	5.045																																																	
38.0	11.287	8.426	5.339																																																	
41.8	12.504	9.309	5.887																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.

 Temperature 25°C  
 Testing Circuitry Figure A

Load Current [A]	Input Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	0.069	0.069	0.072
6.0	1.767	1.348	0.881
12.0	3.479	2.628	1.700
18.0	5.212	3.924	2.516
24.0	7.003	5.249	3.350
30.0	8.820	6.589	4.190
36.0	10.643	7.968	5.045
38.0	11.287	8.426	5.339
41.8	12.504	9.309	5.887
--	-	-	-
--	-	-	-

Model	CHS3804810	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 36V        - - □ - - Input Volt. 48V        - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.5</td><td>3.3</td><td>5.5</td></tr> <tr><td>6.0</td><td>63.6</td><td>64.7</td><td>66.9</td></tr> <tr><td>12.0</td><td>125.0</td><td>126.3</td><td>129.2</td></tr> <tr><td>18.0</td><td>187.7</td><td>188.5</td><td>191.4</td></tr> <tr><td>24.0</td><td>252.1</td><td>252.1</td><td>254.6</td></tr> <tr><td>30.0</td><td>317.0</td><td>316.7</td><td>318.6</td></tr> <tr><td>36.0</td><td>383.5</td><td>381.9</td><td>383.3</td></tr> <tr><td>38.0</td><td>406.6</td><td>404.5</td><td>405.6</td></tr> <tr><td>41.8</td><td>449.8</td><td>447.3</td><td>447.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.0	2.5	3.3	5.5	6.0	63.6	64.7	66.9	12.0	125.0	126.3	129.2	18.0	187.7	188.5	191.4	24.0	252.1	252.1	254.6	30.0	317.0	316.7	318.6	36.0	383.5	381.9	383.3	38.0	406.6	404.5	405.6	41.8	449.8	447.3	447.6	--	-	-	-	--	-	-	-			
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																			
0.0	2.5	3.3	5.5																																																			
6.0	63.6	64.7	66.9																																																			
12.0	125.0	126.3	129.2																																																			
18.0	187.7	188.5	191.4																																																			
24.0	252.1	252.1	254.6																																																			
30.0	317.0	316.7	318.6																																																			
36.0	383.5	381.9	383.3																																																			
38.0	406.6	404.5	405.6																																																			
41.8	449.8	447.3	447.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.5</td><td>3.3</td><td>5.5</td></tr> <tr><td>6.0</td><td>63.6</td><td>64.7</td><td>66.9</td></tr> <tr><td>12.0</td><td>125.0</td><td>126.3</td><td>129.2</td></tr> <tr><td>18.0</td><td>187.7</td><td>188.5</td><td>191.4</td></tr> <tr><td>24.0</td><td>252.1</td><td>252.1</td><td>254.6</td></tr> <tr><td>30.0</td><td>317.0</td><td>316.7</td><td>318.6</td></tr> <tr><td>36.0</td><td>383.5</td><td>381.9</td><td>383.3</td></tr> <tr><td>38.0</td><td>406.6</td><td>404.5</td><td>405.6</td></tr> <tr><td>41.8</td><td>449.8</td><td>447.3</td><td>447.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	2.5	3.3	5.5	6.0	63.6	64.7	66.9	12.0	125.0	126.3	129.2	18.0	187.7	188.5	191.4	24.0	252.1	252.1	254.6	30.0	317.0	316.7	318.6	36.0	383.5	381.9	383.3	38.0	406.6	404.5	405.6	41.8	449.8	447.3	447.6	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	2.5	3.3	5.5																																																			
6.0	63.6	64.7	66.9																																																			
12.0	125.0	126.3	129.2																																																			
18.0	187.7	188.5	191.4																																																			
24.0	252.1	252.1	254.6																																																			
30.0	317.0	316.7	318.6																																																			
36.0	383.5	381.9	383.3																																																			
38.0	406.6	404.5	405.6																																																			
41.8	449.8	447.3	447.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSSEL**

Model	CHS3804810	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	—																																		
1. Graph			2. Values																																
<p>The graph plots Efficiency [%] on the y-axis (72 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency remaining high (around 95%) across the input voltage range of 30V to 80V. A slanted line indicates the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>34</td> <td>95.8</td> <td>93.3</td> </tr> <tr> <td>36</td> <td>95.8</td> <td>93.5</td> </tr> <tr> <td>40</td> <td>95.7</td> <td>93.8</td> </tr> <tr> <td>48</td> <td>95.4</td> <td>94.0</td> </tr> <tr> <td>55</td> <td>95.1</td> <td>93.9</td> </tr> <tr> <td>60</td> <td>94.9</td> <td>93.9</td> </tr> <tr> <td>70</td> <td>94.4</td> <td>93.8</td> </tr> <tr> <td>76</td> <td>94.1</td> <td>93.7</td> </tr> <tr> <td>80</td> <td>93.9</td> <td>93.7</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	34	95.8	93.3	36	95.8	93.5	40	95.7	93.8	48	95.4	94.0	55	95.1	93.9	60	94.9	93.9	70	94.4	93.8	76	94.1	93.7	80	93.9	93.7
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
34	95.8	93.3																																	
36	95.8	93.5																																	
40	95.7	93.8																																	
48	95.4	94.0																																	
55	95.1	93.9																																	
60	94.9	93.9																																	
70	94.4	93.8																																	
76	94.1	93.7																																	
80	93.9	93.7																																	

Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	CHS3804810	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>The graph shows efficiency decreasing slightly as load current increases from 0 to 40A. The 36V curve is the highest, followed by 48V, and then 76V. A vertical slanted line is drawn through the curves between approximately 35A and 40A, representing the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>6.0</td><td>94.7</td><td>93.0</td><td>89.9</td></tr> <tr> <td>12.0</td><td>96.0</td><td>95.0</td><td>92.9</td></tr> <tr> <td>18.0</td><td>95.8</td><td>95.5</td><td>94.0</td></tr> <tr> <td>24.0</td><td>95.3</td><td>95.2</td><td>94.3</td></tr> <tr> <td>30.0</td><td>94.6</td><td>94.7</td><td>94.2</td></tr> <tr> <td>36.0</td><td>93.8</td><td>94.2</td><td>93.9</td></tr> <tr> <td>38.0</td><td>93.5</td><td>94.0</td><td>93.7</td></tr> <tr> <td>41.8</td><td>93.0</td><td>93.5</td><td>93.4</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	6.0	94.7	93.0	89.9	12.0	96.0	95.0	92.9	18.0	95.8	95.5	94.0	24.0	95.3	95.2	94.3	30.0	94.6	94.7	94.2	36.0	93.8	94.2	93.9	38.0	93.5	94.0	93.7	41.8	93.0	93.5	93.4	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
6.0	94.7	93.0	89.9																																																			
12.0	96.0	95.0	92.9																																																			
18.0	95.8	95.5	94.0																																																			
24.0	95.3	95.2	94.3																																																			
30.0	94.6	94.7	94.2																																																			
36.0	93.8	94.2	93.9																																																			
38.0	93.5	94.0	93.7																																																			
41.8	93.0	93.5	93.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSSEL**

Model	CHS3804810
Item	Line Regulation
Object	+10V38A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



Note: Slanted line shows the range of the rated input voltage.

## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
34	10.008	10.008
36	10.008	10.008
40	10.008	10.008
48	10.008	10.007
55	10.008	10.007
60	10.008	10.007
70	10.007	10.007
76	10.007	10.006
80	10.007	10.006

**COSSEL**

Model	CHS3804810
Item	Load Regulation
Object	+10V38A

1.Graph

Output Voltage [V]

Load Current [A]

Legend:


- Input Volt. 36V
- Input Volt. 48V
- Input Volt. 76V

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	10.008	10.008	10.007
6.0	10.008	10.008	10.007
12.0	10.008	10.008	10.007
18.0	10.008	10.008	10.007
24.0	10.008	10.008	10.007
30.0	10.008	10.008	10.007
36.0	10.008	10.008	10.006
38.0	10.008	10.007	10.006
41.8	10.007	10.007	10.006
--	-	-	-
--	-	-	-

**COSEL**

**COSEL**

Model	CHS3804810
Item	Ripple Voltage (by Load Current)
Object	+10V38A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

Temperature 25°C  
Testing Circuitry Figure B


## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	15	45
6.0	15	45
12.0	15	45
18.0	15	45
24.0	15	45
30.0	15	45
36.0	15	45
38.0	15	45
41.8	15	45
--	-	-
--	-	-

**COSEL**

Model	CHS3804810
Item	Ripple-Noise
Object	+10V38A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure B

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	25	50
6.0	30	55
12.0	30	55
18.0	40	55
24.0	40	55
30.0	45	55
36.0	45	55
38.0	45	55
41.8	45	55
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	CHS3804810
Item	Ripple Voltage (by Ambient Temp.)
Object	+10V38A

## 1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.




Fig.Complex Ripple Noise Wave Form

## Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	30	30
-20	25	25
0	25	25
25	25	25
40	35	35
55	35	35
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

**COSSEL**


Model CHS3804810

Item Ambient Temperature Drift

Object +10V38A

## 1.Graph

- △— Input Volt. 36V
- -□--- Input Volt. 48V
- -○--- Input Volt. 76V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	10.032	10.029	10.026
-20	10.024	10.022	10.020
0	10.017	10.015	10.012
25	10.008	10.007	10.006
40	10.005	10.005	10.003
55	10.002	10.003	10.003
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	CHS3804810	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+10V38A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 38A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	36	38	10.032	$\pm 15$	$\pm 0.2$
Minimum Voltage	55	36	38	10.002		

**COSEL**

Model	CHS3804810	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+10V38A																								
1.Graph			2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10.007</td></tr> <tr><td>0.5</td><td>10.007</td></tr> <tr><td>1.0</td><td>10.007</td></tr> <tr><td>2.0</td><td>10.007</td></tr> <tr><td>3.0</td><td>10.007</td></tr> <tr><td>4.0</td><td>10.007</td></tr> <tr><td>5.0</td><td>10.007</td></tr> <tr><td>6.0</td><td>10.007</td></tr> <tr><td>7.0</td><td>10.007</td></tr> <tr><td>8.0</td><td>10.007</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	10.007	0.5	10.007	1.0	10.007	2.0	10.007	3.0	10.007	4.0	10.007	5.0	10.007	6.0	10.007	7.0	10.007	8.0	10.007
Time since start [H]	Output Voltage [V]																								
0.0	10.007																								
0.5	10.007																								
1.0	10.007																								
2.0	10.007																								
3.0	10.007																								
4.0	10.007																								
5.0	10.007																								
6.0	10.007																								
7.0	10.007																								
8.0	10.007																								

COSEL

Model CHS3804810


Item Rise and Fall Time

Object +10V38A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph


Input Volt. 48 V



## 2. Values

[mS]


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	8.7	13.0	21.7	0.8	0.1
100 %	8.9	15.0	23.9	0.4	0.0





Model	CHS3804810
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+10V38A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	32.8	32.8
-20	32.8	32.8
0	32.8	32.9
25	33.0	33.0
40	33.0	33.2
55	32.9	33.4
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



Model	CHS3804810	Temperature	25°C																																																																				
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																				
Object	+10V38A																																																																						
1.Graph		Input Volt. 36V Input Volt. 48V Input Volt. 76V																																																																					
			2.Values																																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>9.5</td><td>49.73</td><td>49.79</td><td>49.77</td></tr> <tr><td>9.0</td><td>50.09</td><td>49.94</td><td>49.77</td></tr> <tr><td>8.0</td><td>49.79</td><td>50.17</td><td>50.37</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	9.5	49.73	49.79	49.77	9.0	50.09	49.94	49.77	8.0	49.79	50.17	50.37	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Output Voltage [V]	Load Current [A]																																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																				
9.5	49.73	49.79	49.77																																																																				
9.0	50.09	49.94	49.77																																																																				
8.0	49.79	50.17	50.37																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				
--	-	-	-																																																																				

Note: Slanted line shows the range of the rated load current.


**COSEL**

Model CHS3804810

Item Overvoltage Protection

Object +10V38A

## 1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-40	12.66	12.68
-20	12.68	12.70
0	12.70	12.74
25	12.72	12.76
40	12.74	12.78
55	12.76	12.80
60	12.78	12.80
--	-	-
--	-	-
--	-	-
--	-	-




Figure A

Data Acquisition/Control Unit




Figure B