



TEST DATA OF CHS60483R3

Regulated DC Power Supply
November 17, 2014

Approved by : Yoshimichi Hirokawa
Yoshimichi Hirokawa Design Manager

Prepared by : Masashi Ueda
Masashi Ueda Design Engineer

COSEL CO.,LTD.

CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

Model	CHS60483R3	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p>—△— Load 100%</p> <p>- - -□-- Load 50%</p> <p>- -○-- Load 0%</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>35</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>37.5</td><td>0.006</td><td>0.007</td><td>0.007</td></tr> <tr><td>40</td><td>0.007</td><td>0.006</td><td>0.007</td></tr> <tr><td>45</td><td>0.007</td><td>0.007</td><td>0.013</td></tr> <tr><td>50</td><td>0.007</td><td>0.007</td><td>0.010</td></tr> <tr><td>60</td><td>0.008</td><td>0.006</td><td>0.011</td></tr> <tr><td>70</td><td>0.008</td><td>0.005</td><td>0.009</td></tr> <tr><td>75</td><td>0.008</td><td>0.004</td><td>0.008</td></tr> <tr><td>80</td><td>0.008</td><td>0.004</td><td>0.007</td></tr> <tr><td>85</td><td>0.008</td><td>0.004</td><td>0.006</td></tr> <tr><td>90</td><td>0.008</td><td>0.004</td><td>0.005</td></tr> <tr><td>95</td><td>0.008</td><td>0.004</td><td>0.004</td></tr> <tr><td>100</td><td>0.008</td><td>0.004</td><td>0.003</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	35	0.000	0.000	0.000	37.5	0.006	0.007	0.007	40	0.007	0.006	0.007	45	0.007	0.007	0.013	50	0.007	0.007	0.010	60	0.008	0.006	0.011	70	0.008	0.005	0.009	75	0.008	0.004	0.008	80	0.008	0.004	0.007	85	0.008	0.004	0.006	90	0.008	0.004	0.005	95	0.008	0.004	0.004	100	0.008	0.004	0.003																						
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																																
0	0.000	0.000	0.000																																																																																
35	0.000	0.000	0.000																																																																																
37.5	0.006	0.007	0.007																																																																																
40	0.007	0.006	0.007																																																																																
45	0.007	0.007	0.013																																																																																
50	0.007	0.007	0.010																																																																																
60	0.008	0.006	0.011																																																																																
70	0.008	0.005	0.009																																																																																
75	0.008	0.004	0.008																																																																																
80	0.008	0.004	0.007																																																																																
85	0.008	0.004	0.006																																																																																
90	0.008	0.004	0.005																																																																																
95	0.008	0.004	0.004																																																																																
100	0.008	0.004	0.003																																																																																
2.	Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.006</td><td>0.007</td><td>0.006</td></tr> <tr><td>16.0</td><td>0.007</td><td>0.006</td><td>0.007</td></tr> <tr><td>24.0</td><td>0.007</td><td>0.007</td><td>0.008</td></tr> <tr><td>33.0</td><td>0.008</td><td>0.008</td><td>0.008</td></tr> <tr><td>34.6</td><td>0.040</td><td>0.930</td><td>1.891</td></tr> <tr><td>34.8</td><td>0.037</td><td>0.922</td><td>1.879</td></tr> <tr><td>36.0</td><td>0.035</td><td>0.891</td><td>1.811</td></tr> <tr><td>40.0</td><td>0.030</td><td>0.802</td><td>1.619</td></tr> <tr><td>48.0</td><td>0.029</td><td>0.672</td><td>1.349</td></tr> <tr><td>60.0</td><td>0.033</td><td>0.544</td><td>1.082</td></tr> <tr><td>70.0</td><td>0.035</td><td>0.471</td><td>0.931</td></tr> <tr><td>76.0</td><td>0.035</td><td>0.437</td><td>0.859</td></tr> <tr><td>80.0</td><td>0.036</td><td>0.417</td><td>0.819</td></tr> <tr><td>88.0</td><td>0.038</td><td>0.385</td><td>0.748</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.006	0.007	0.006	16.0	0.007	0.006	0.007	24.0	0.007	0.007	0.008	33.0	0.008	0.008	0.008	34.6	0.040	0.930	1.891	34.8	0.037	0.922	1.879	36.0	0.035	0.891	1.811	40.0	0.030	0.802	1.619	48.0	0.029	0.672	1.349	60.0	0.033	0.544	1.082	70.0	0.035	0.471	0.931	76.0	0.035	0.437	0.859	80.0	0.036	0.417	0.819	88.0	0.038	0.385	0.748	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.006	0.007	0.006																																																																																
16.0	0.007	0.006	0.007																																																																																
24.0	0.007	0.007	0.008																																																																																
33.0	0.008	0.008	0.008																																																																																
34.6	0.040	0.930	1.891																																																																																
34.8	0.037	0.922	1.879																																																																																
36.0	0.035	0.891	1.811																																																																																
40.0	0.030	0.802	1.619																																																																																
48.0	0.029	0.672	1.349																																																																																
60.0	0.033	0.544	1.082																																																																																
70.0	0.035	0.471	0.931																																																																																
76.0	0.035	0.437	0.859																																																																																
80.0	0.036	0.417	0.819																																																																																
88.0	0.038	0.385	0.748																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Note: Slanted line shows the range of the rated input voltage.


Model	CHS60483R3																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.035</td><td>0.029</td><td>0.035</td></tr> <tr> <td>3.0</td><td>0.313</td><td>0.240</td><td>0.167</td></tr> <tr> <td>6.0</td><td>0.597</td><td>0.454</td><td>0.300</td></tr> <tr> <td>9.0</td><td>0.891</td><td>0.672</td><td>0.437</td></tr> <tr> <td>12.0</td><td>1.191</td><td>0.896</td><td>0.579</td></tr> <tr> <td>15.0</td><td>1.515</td><td>1.129</td><td>0.723</td></tr> <tr> <td>18.0</td><td>1.811</td><td>1.349</td><td>0.859</td></tr> <tr> <td>19.8</td><td>2.035</td><td>1.508</td><td>0.959</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.035	0.029	0.035	3.0	0.313	0.240	0.167	6.0	0.597	0.454	0.300	9.0	0.891	0.672	0.437	12.0	1.191	0.896	0.579	15.0	1.515	1.129	0.723	18.0	1.811	1.349	0.859	19.8	2.035	1.508	0.959	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.035	0.029	0.035																																																			
3.0	0.313	0.240	0.167																																																			
6.0	0.597	0.454	0.300																																																			
9.0	0.891	0.672	0.437																																																			
12.0	1.191	0.896	0.579																																																			
15.0	1.515	1.129	0.723																																																			
18.0	1.811	1.349	0.859																																																			
19.8	2.035	1.508	0.959																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	CHS60483R3																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□--- Input Volt. 48V - - ○--- Input Volt. 76V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>1.26</td><td>1.41</td><td>2.64</td></tr> <tr> <td>3.0</td><td>11.25</td><td>11.53</td><td>12.70</td></tr> <tr> <td>6.0</td><td>21.52</td><td>21.75</td><td>22.79</td></tr> <tr> <td>9.0</td><td>32.08</td><td>32.27</td><td>33.25</td></tr> <tr> <td>12.0</td><td>42.97</td><td>43.04</td><td>43.95</td></tr> <tr> <td>15.0</td><td>54.13</td><td>53.99</td><td>54.88</td></tr> <tr> <td>18.0</td><td>65.49</td><td>65.20</td><td>65.91</td></tr> <tr> <td>19.8</td><td>72.57</td><td>72.02</td><td>72.70</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	1.26	1.41	2.64	3.0	11.25	11.53	12.70	6.0	21.52	21.75	22.79	9.0	32.08	32.27	33.25	12.0	42.97	43.04	43.95	15.0	54.13	53.99	54.88	18.0	65.49	65.20	65.91	19.8	72.57	72.02	72.70	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	1.26	1.41	2.64																																																			
3.0	11.25	11.53	12.70																																																			
6.0	21.52	21.75	22.79																																																			
9.0	32.08	32.27	33.25																																																			
12.0	42.97	43.04	43.95																																																			
15.0	54.13	53.99	54.88																																																			
18.0	65.49	65.20	65.91																																																			
19.8	72.57	72.02	72.70																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	CHS60483R3
Item	Efficiency (by Input Voltage)
Object	—

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
35	92.5	90.8
36	93.0	91.1
40	93.1	91.3
48	92.5	91.5
55	91.9	91.2
60	91.2	91.1
70	90.3	90.8
76	89.7	90.6
80	89.1	90.2


Note: Slanted line shows the range of the rated input voltage.

Model	CHS60483R3	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] (%)</th> <th>Efficiency [48V] (%)</th> <th>Efficiency [76V] (%)</th> </tr> </thead> <tbody> <tr><td>3.0</td><td>88.2</td><td>86.1</td><td>78.1</td></tr> <tr><td>6.0</td><td>92.3</td><td>91.3</td><td>87.1</td></tr> <tr><td>9.0</td><td>93.0</td><td>92.5</td><td>89.7</td></tr> <tr><td>12.0</td><td>92.6</td><td>92.4</td><td>90.5</td></tr> <tr><td>15.0</td><td>91.9</td><td>92.1</td><td>90.6</td></tr> <tr><td>18.0</td><td>91.1</td><td>91.5</td><td>90.6</td></tr> <tr><td>19.8</td><td>90.5</td><td>91.2</td><td>90.3</td></tr> </tbody> </table>			Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)	3.0	88.2	86.1	78.1	6.0	92.3	91.3	87.1	9.0	93.0	92.5	89.7	12.0	92.6	92.4	90.5	15.0	91.9	92.1	90.6	18.0	91.1	91.5	90.6	19.8	90.5	91.2	90.3																			
Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)																																																			
3.0	88.2	86.1	78.1																																																			
6.0	92.3	91.3	87.1																																																			
9.0	93.0	92.5	89.7																																																			
12.0	92.6	92.4	90.5																																																			
15.0	91.9	92.1	90.6																																																			
18.0	91.1	91.5	90.6																																																			
19.8	90.5	91.2	90.3																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>88.2</td><td>86.1</td><td>78.1</td></tr> <tr><td>6.0</td><td>92.3</td><td>91.3</td><td>87.1</td></tr> <tr><td>9.0</td><td>93.0</td><td>92.5</td><td>89.7</td></tr> <tr><td>12.0</td><td>92.6</td><td>92.4</td><td>90.5</td></tr> <tr><td>15.0</td><td>91.9</td><td>92.1</td><td>90.6</td></tr> <tr><td>18.0</td><td>91.1</td><td>91.5</td><td>90.6</td></tr> <tr><td>19.8</td><td>90.5</td><td>91.2</td><td>90.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	3.0	88.2	86.1	78.1	6.0	92.3	91.3	87.1	9.0	93.0	92.5	89.7	12.0	92.6	92.4	90.5	15.0	91.9	92.1	90.6	18.0	91.1	91.5	90.6	19.8	90.5	91.2	90.3	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
3.0	88.2	86.1	78.1																																																			
6.0	92.3	91.3	87.1																																																			
9.0	93.0	92.5	89.7																																																			
12.0	92.6	92.4	90.5																																																			
15.0	91.9	92.1	90.6																																																			
18.0	91.1	91.5	90.6																																																			
19.8	90.5	91.2	90.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	CHS60483R3
Item	Line Regulation
Object	+3.3V18A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
35	3.310	3.310
36	3.310	3.310
40	3.310	3.310
48	3.310	3.310
55	3.310	3.310
60	3.310	3.310
70	3.310	3.310
76	3.310	3.310
80	3.310	3.311

Note: Slanted line shows the range of the rated input voltage.

Model	CHS60483R3	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+3.3V18A																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□--- Input Volt. 48V - - -○--- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (36V)</th> <th>Output Voltage [V] (48V)</th> <th>Output Voltage [V] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.309</td><td>3.309</td><td>3.309</td></tr> <tr><td>3.0</td><td>3.309</td><td>3.309</td><td>3.310</td></tr> <tr><td>6.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>9.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>12.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>15.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>18.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>19.8</td><td>3.310</td><td>3.310</td><td>3.311</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)	0.0	3.309	3.309	3.309	3.0	3.309	3.309	3.310	6.0	3.310	3.310	3.310	9.0	3.310	3.310	3.310	12.0	3.310	3.310	3.310	15.0	3.310	3.310	3.310	18.0	3.310	3.310	3.310	19.8	3.310	3.310	3.311																		
Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)																																																				
0.0	3.309	3.309	3.309																																																				
3.0	3.309	3.309	3.310																																																				
6.0	3.310	3.310	3.310																																																				
9.0	3.310	3.310	3.310																																																				
12.0	3.310	3.310	3.310																																																				
15.0	3.310	3.310	3.310																																																				
18.0	3.310	3.310	3.310																																																				
19.8	3.310	3.310	3.311																																																				
2.Values																																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.309</td><td>3.309</td><td>3.309</td></tr> <tr><td>3.0</td><td>3.309</td><td>3.309</td><td>3.310</td></tr> <tr><td>6.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>9.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>12.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>15.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>18.0</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>19.8</td><td>3.310</td><td>3.310</td><td>3.311</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	3.309	3.309	3.309	3.0	3.309	3.309	3.310	6.0	3.310	3.310	3.310	9.0	3.310	3.310	3.310	12.0	3.310	3.310	3.310	15.0	3.310	3.310	3.310	18.0	3.310	3.310	3.310	19.8	3.310	3.310	3.311	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
0.0	3.309	3.309	3.309																																																				
3.0	3.309	3.309	3.310																																																				
6.0	3.310	3.310	3.310																																																				
9.0	3.310	3.310	3.310																																																				
12.0	3.310	3.310	3.310																																																				
15.0	3.310	3.310	3.310																																																				
18.0	3.310	3.310	3.310																																																				
19.8	3.310	3.310	3.311																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.

COSEL


Model	CHS60483R3
Item	Dynamic Load Response
Object	+3.3V18A

Temperature 25°C
Testing Circuitry Figure A



Input Volt. 48 V
Cycle 10 ms





Min. Load (0A) ↔
Load 100% (18A)



Min. Load (0A) ↔
Load 50% (9A)



Load 50% (9A) ↔
Load 100% (18A)




COSEL

Model	CHS60483R3
Item	Ripple Voltage (by Load Current)
Object	+3.3V18A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	5	8
3.6	5	8
7.2	5	10
10.8	5	12
14.4	5	12
18.0	10	15
19.8	10	15
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	CHS60483R3	Temperature Testing Circuitry	25°C Figure B
Item	Ripple-Noise		
Object	+3.3V18A		

1. Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	15	35
3.6	20	50
7.2	20	50
10.8	20	50
14.4	25	50
18.0	25	50
19.8	25	50
--	-	-
--	-	-
--	-	-
--	-	-



Model	CHS60483R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V18A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	10	15
-40	10	15
-20	10	10
0	10	10
25	10	10
40	10	10
60	10	10
85	10	10
--	-	-
--	-	-
--	-	-

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	CHS60483R3
Item	Ambient Temperature Drift
Object	+3.3V18A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	3.312	3.312	3.312
-20	3.311	3.310	3.311
0	3.309	3.309	3.309
25	3.310	3.310	3.310
40	3.310	3.310	3.310
60	3.310	3.310	3.310
85	3.312	3.313	3.313
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	CHS60483R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V18A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 36 - 76V

Load Current : 0 - 18A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	85	76	18	3.313	±3	±0.1
Minimum Voltage	0	36	0	3.308		

COSEL

Model	CHS60483R3
Item	Time Lapse Drift
Object	+3.3V18A

1. Graph



Temperature 25°C
Testing Circuitry Figure A

2. Values


Time since start [H]	Output Voltage [V]
0.0	3.310
0.5	3.310
1.0	3.310
2.0	3.310
3.0	3.310
4.0	3.310
5.0	3.310
6.0	3.310
7.0	3.310
8.0	3.310

COSSEL

Model	CHS60483R3
Item	Rise and Fall Time
Object	+3.3V18A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

[ms]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		3.2	4.0	7.2	0.4	0.1
100 %		3.2	4.8	8.0	0.3	0.1



Model	CHS60483R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V18A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	31.9	31.8
-20	32.0	32.0
0	32.1	32.1
25	32.2	32.2
40	32.2	32.2
60	32.3	32.3
85	32.4	32.4
--	-	-
--	-	-
--	-	-
--	-	-




Model	CHS60483R3	Temperature Testing Circuitry 25°C Figure A																																																																	
Item	Overcurrent Protection																																																																		
Object	+3.3V18A																																																																		
1.Graph	<p>— Input Volt. 36V — Input Volt. 48V — Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																																	
Note:	Slanted line shows the range of the rated load current.																																																																		
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>3.14</td><td>22.17</td><td>22.13</td><td>22.27</td></tr> <tr><td>2.97</td><td>22.28</td><td>22.31</td><td>22.58</td></tr> <tr><td>2.64</td><td>22.60</td><td>22.81</td><td>23.32</td></tr> <tr><td>2.31</td><td>22.98</td><td>23.39</td><td>24.23</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	3.14	22.17	22.13	22.27	2.97	22.28	22.31	22.58	2.64	22.60	22.81	23.32	2.31	22.98	23.39	24.23	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																																		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																
3.14	22.17	22.13	22.27																																																																
2.97	22.28	22.31	22.58																																																																
2.64	22.60	22.81	23.32																																																																
2.31	22.98	23.39	24.23																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																
--	-	-	-																																																																

Model	CHS60483R3
Item	Oversupply Protection
Object	+3.3V18A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-40	4.39	4.27
-20	4.42	4.27
0	4.43	4.32
25	4.45	4.40
40	4.56	4.42
60	4.57	4.45
85	4.58	4.49
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B