

TEST DATA OF CQHS2504850

Regulated DC Power Supply
August 25, 2014

Approved by : Yoshimichi Hirokawa
Yoshimichi Hirokawa Design Manager

Prepared by : Satoshi Shiina
Satoshi Shiina Design Engineer

COSEL CO.,LTD.



CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	CQHS2504850
Item	Input Current (by Input Voltage)
Object	_____

1.Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
25.0	0.006	0.006	0.006
30.0	0.006	0.006	0.006
33.0	0.006	0.006	0.006
35.5	0.119	3.698	7.480
36.0	0.119	3.650	7.402
40.0	0.125	3.298	6.661
48.0	0.130	2.782	5.560
60.0	0.135	2.254	4.476
68.0	0.138	2.012	3.968
76.0	0.138	1.814	3.570
80.0	0.139	1.733	3.407
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	CQHS2504850																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object																																																						
1.Graph	—△— Input Volt. 36V - - □--- Input Volt. 48V - - ○--- Input Volt. 76V																																																					
	<p>Input Current [A]</p> <p>Load Current [A]</p>	2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.119</td><td>0.130</td><td>0.138</td></tr> <tr> <td>0.8</td><td>1.266</td><td>0.988</td><td>0.677</td></tr> <tr> <td>1.6</td><td>2.402</td><td>1.840</td><td>1.217</td></tr> <tr> <td>2.4</td><td>3.548</td><td>2.702</td><td>1.761</td></tr> <tr> <td>3.2</td><td>4.710</td><td>3.562</td><td>2.314</td></tr> <tr> <td>4.0</td><td>5.890</td><td>4.437</td><td>2.866</td></tr> <tr> <td>4.8</td><td>7.080</td><td>5.330</td><td>3.430</td></tr> <tr> <td>5.0</td><td>7.400</td><td>5.560</td><td>3.570</td></tr> <tr> <td>5.5</td><td>8.170</td><td>6.120</td><td>3.932</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.119	0.130	0.138	0.8	1.266	0.988	0.677	1.6	2.402	1.840	1.217	2.4	3.548	2.702	1.761	3.2	4.710	3.562	2.314	4.0	5.890	4.437	2.866	4.8	7.080	5.330	3.430	5.0	7.400	5.560	3.570	5.5	8.170	6.120	3.932	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.119	0.130	0.138																																																			
0.8	1.266	0.988	0.677																																																			
1.6	2.402	1.840	1.217																																																			
2.4	3.548	2.702	1.761																																																			
3.2	4.710	3.562	2.314																																																			
4.0	5.890	4.437	2.866																																																			
4.8	7.080	5.330	3.430																																																			
5.0	7.400	5.560	3.570																																																			
5.5	8.170	6.120	3.932																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	Note: Slanted line shows the range of the rated load current.																																																					

COSEL


Model	CQHS2504850																																																					
Item	Input Power (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	<p style="text-align: center;"> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p>  <p style="text-align: center;">Input Power [W]</p> <p style="text-align: center;">Load Current [A]</p>																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>4.3</td><td>6.3</td><td>10.5</td></tr> <tr> <td>0.8</td><td>45.4</td><td>47.3</td><td>51.4</td></tr> <tr> <td>1.6</td><td>86.3</td><td>88.1</td><td>92.3</td></tr> <tr> <td>2.4</td><td>127.3</td><td>129.2</td><td>133.6</td></tr> <tr> <td>3.2</td><td>168.9</td><td>170.5</td><td>175.5</td></tr> <tr> <td>4.0</td><td>211.2</td><td>212.4</td><td>217.5</td></tr> <tr> <td>4.8</td><td>254.3</td><td>255.1</td><td>260.0</td></tr> <tr> <td>5.0</td><td>265.3</td><td>265.9</td><td>270.9</td></tr> <tr> <td>5.5</td><td>293.3</td><td>293.3</td><td>298.2</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	4.3	6.3	10.5	0.8	45.4	47.3	51.4	1.6	86.3	88.1	92.3	2.4	127.3	129.2	133.6	3.2	168.9	170.5	175.5	4.0	211.2	212.4	217.5	4.8	254.3	255.1	260.0	5.0	265.3	265.9	270.9	5.5	293.3	293.3	298.2	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	4.3	6.3	10.5																																																			
0.8	45.4	47.3	51.4																																																			
1.6	86.3	88.1	92.3																																																			
2.4	127.3	129.2	133.6																																																			
3.2	168.9	170.5	175.5																																																			
4.0	211.2	212.4	217.5																																																			
4.8	254.3	255.1	260.0																																																			
5.0	265.3	265.9	270.9																																																			
5.5	293.3	293.3	298.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	CQHS2504850
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
35.5	95.0	94.4
36.0	94.9	94.4
40.0	94.4	94.4
48.0	93.6	94.3
55.0	92.8	93.9
60.0	92.3	93.5
70.0	91.1	92.9
76.0	90.6	92.5
80.0	90.3	92.1

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	CQHS2504850																																																					
Item	Efficiency (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object																																																						
1.Graph	<p>1. Graph</p> <ul style="list-style-type: none"> —△— Input Volt. 36V -□--- Input Volt. 48V -○--- Input Volt. 76V <p>Efficiency [%]</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.8</td> <td>90.0</td> <td>86.4</td> <td>79.7</td> </tr> <tr> <td>1.6</td> <td>93.7</td> <td>91.8</td> <td>87.6</td> </tr> <tr> <td>2.4</td> <td>94.9</td> <td>93.5</td> <td>90.5</td> </tr> <tr> <td>3.2</td> <td>95.1</td> <td>94.2</td> <td>91.5</td> </tr> <tr> <td>4.0</td> <td>95.0</td> <td>94.5</td> <td>92.2</td> </tr> <tr> <td>4.8</td> <td>94.6</td> <td>94.3</td> <td>92.6</td> </tr> <tr> <td>5.0</td> <td>94.4</td> <td>94.3</td> <td>92.5</td> </tr> <tr> <td>5.5</td> <td>93.9</td> <td>94.0</td> <td>92.4</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	0.8	90.0	86.4	79.7	1.6	93.7	91.8	87.6	2.4	94.9	93.5	90.5	3.2	95.1	94.2	91.5	4.0	95.0	94.5	92.2	4.8	94.6	94.3	92.6	5.0	94.4	94.3	92.5	5.5	93.9	94.0	92.4	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
0.8	90.0	86.4	79.7																																																			
1.6	93.7	91.8	87.6																																																			
2.4	94.9	93.5	90.5																																																			
3.2	95.1	94.2	91.5																																																			
4.0	95.0	94.5	92.2																																																			
4.8	94.6	94.3	92.6																																																			
5.0	94.4	94.3	92.5																																																			
5.5	93.9	94.0	92.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	CQHS2504850
Item	Line Regulation
Object	+50V5A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
35.5	50.067	50.072
36.0	50.067	50.071
40.0	50.066	50.070
48.0	50.066	50.070
55.0	50.066	50.072
60.0	50.065	50.072
70.0	50.066	50.072
76.0	50.068	50.073
80.0	50.069	50.073

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CQHS2504850
Item	Load Regulation
Object	+50V5A



 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	50.065	50.069	50.071
0.8	50.058	50.063	50.067
1.6	50.055	50.059	50.065
2.4	50.054	50.058	50.065
3.2	50.056	50.059	50.066
4.0	50.060	50.062	50.069
4.8	50.067	50.067	50.071
5.0	50.071	50.070	50.073
5.5	50.075	50.074	50.075
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL




COSEL

Model	CQHS2504850
Item	Ripple Voltage (by Load Current)
Object	+50V5A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph




2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	43	188
0.8	42	183
1.6	42	186
2.4	42	188
3.2	43	188
4.0	43	189
5.0	43	189
5.5	43	189
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.
 Ripple [mVp-p]




COSEL

Model	CQHS2504850
Item	Ripple-Noise
Object	+50V5A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	72	230
0.8	73	240
1.6	75	247
2.4	78	252
3.2	78	249
4.0	78	252
5.0	80	252
5.5	80	252
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	CQHS2504850
Item	Ripple Voltage (by Ambient Temp.)
Object	+50V5A

1. Graph



Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	220	224
-20	204	202
0	168	160
25	117	119
40	101	101
50	90	90
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	CQHS2504850
Item	Ambient Temperature Drift
Object	+50V5A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	49.822	49.831	49.837
-20	49.928	49.935	49.938
0	50.005	50.011	50.012
25	50.071	50.070	50.073
40	50.092	50.092	50.089
50	50.101	50.100	50.096
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	CQHS2504850	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+50V5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 50°C

Input Voltage : 36 - 76V

Load Current : 0 - 5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	50	36	0	50.092	± 149	± 0.3
Minimum Voltage	-40	76	0	49.795		

COSEL


Model	CQHS2504850	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+50V5A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>50.041</td></tr> <tr><td>0.5</td><td>50.070</td></tr> <tr><td>1.0</td><td>50.070</td></tr> <tr><td>2.0</td><td>50.070</td></tr> <tr><td>3.0</td><td>50.070</td></tr> <tr><td>4.0</td><td>50.070</td></tr> <tr><td>5.0</td><td>50.070</td></tr> <tr><td>6.0</td><td>50.070</td></tr> <tr><td>7.0</td><td>50.070</td></tr> <tr><td>8.0</td><td>50.070</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	50.041	0.5	50.070	1.0	50.070	2.0	50.070	3.0	50.070	4.0	50.070	5.0	50.070	6.0	50.070	7.0	50.070	8.0	50.070
Time since start [H]	Output Voltage [V]																								
0.0	50.041																								
0.5	50.070																								
1.0	50.070																								
2.0	50.070																								
3.0	50.070																								
4.0	50.070																								
5.0	50.070																								
6.0	50.070																								
7.0	50.070																								
8.0	50.070																								

COSEL

Model	CQHS2504850
Item	Rise and Fall Time
Object	+50V5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		43.8	3.6	47.4	1.4	5.1	
100 %		43.8	4.4	48.2	0.8	2.6	




COSEL

Model	CQHS2504850
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+50V5A

Testing Circuitry Figure A

1. Graph




2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	32.9	33.4
-20	32.8	33.6
0	32.9	33.7
25	33.1	33.9
40	33.0	34.0
50	33.1	34.1
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	CQHS2504850
Item	Overcurrent Protection
Object	+50V5A



Note: Slanted line shows the range of the rated load current.

When the output voltage fell to less than 45.0V , the unit shuts off the output by operating low voltage protection.

Temperature 25°C
Testing Circuitry Figure A


2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
47.5	6.01	5.92	5.88
45.0	6.03	5.92	5.86
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	CQHS2504850
Item	Overvoltage Protection
Object	+50V5A

1.Graph



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-40	58.92	58.77
-20	59.01	58.91
0	59.11	59.06
25	59.20	59.20
40	59.16	59.06
50	59.11	58.92
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL





Figure A



C_i : 100V 68 μ F ×2
 C_1 : 100V 0.1 μ F
 C_o : 100V 330 μ F (-40°C ≤ Ta ≤ -20°C)
 : 100V 100 μ F (-20°C < Ta ≤ 85°C)

Figure B (Ripple and Ripple noise Characteristic)