



TEST DATA OF CQS48025-45

Regulated DC Power Supply
Sep.4, 2003

Approved by :

Kazuyoshi Shimano

Kazuyoshi Shimano

Design Manager

Prepared by :

Nobuyuki Shiraishi

Nobuyuki Shiraishi

Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	CQS48025-45	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																							
Object	_____																																																																									
1.Graph		2.Values																																																																								
<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 100% (Solid line with ▲) Load 50% (Dashed line with □) Load 0% (Dotted line with ○) 		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>33</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>34</td><td>0.089</td><td>1.834</td><td>3.684</td></tr> <tr><td>36</td><td>0.082</td><td>1.705</td><td>3.430</td></tr> <tr><td>40</td><td>0.075</td><td>1.533</td><td>3.088</td></tr> <tr><td>48</td><td>0.069</td><td>1.290</td><td>2.580</td></tr> <tr><td>60</td><td>0.066</td><td>1.045</td><td>2.075</td></tr> <tr><td>70</td><td>0.064</td><td>0.908</td><td>1.792</td></tr> <tr><td>76</td><td>0.064</td><td>0.841</td><td>1.658</td></tr> <tr><td>80</td><td>0.063</td><td>0.803</td><td>1.580</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	8	0.000	0.000	0.000	16	0.000	0.000	0.000	24	0.000	0.000	0.000	33	0.002	0.002	0.002	34	0.089	1.834	3.684	36	0.082	1.705	3.430	40	0.075	1.533	3.088	48	0.069	1.290	2.580	60	0.066	1.045	2.075	70	0.064	0.908	1.792	76	0.064	0.841	1.658	80	0.063	0.803	1.580	-	-	-	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
8	0.000	0.000	0.000																																																																							
16	0.000	0.000	0.000																																																																							
24	0.000	0.000	0.000																																																																							
33	0.002	0.002	0.002																																																																							
34	0.089	1.834	3.684																																																																							
36	0.082	1.705	3.430																																																																							
40	0.075	1.533	3.088																																																																							
48	0.069	1.290	2.580																																																																							
60	0.066	1.045	2.075																																																																							
70	0.064	0.908	1.792																																																																							
76	0.064	0.841	1.658																																																																							
80	0.063	0.803	1.580																																																																							
-	-	-	-																																																																							
-	-	-	-																																																																							
-	-	-	-																																																																							


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CQS48025-45
Item	Input Current (by Load Current)
Object	_____

1.Graph

—△— Input Volt. 36V
 - - -□- - - Input Volt. 48V
 - - ○ - - Input Volt. 76V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	0.081	0.068	0.063
8.0	0.647	0.492	0.333
16.0	1.226	0.926	0.611
24.0	1.821	1.368	0.892
32.0	2.420	1.822	1.178
40.0	3.049	2.286	1.470
45.0	3.434	2.574	1.655
49.5	3.804	2.844	1.826
-	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model	CQS48025-45	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph																																																						
			2.Values																																																			
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.9</td><td>3.3</td><td>4.8</td></tr> <tr><td>8.0</td><td>23.3</td><td>23.7</td><td>25.3</td></tr> <tr><td>16.0</td><td>44.0</td><td>44.5</td><td>46.4</td></tr> <tr><td>24.0</td><td>65.1</td><td>65.6</td><td>67.7</td></tr> <tr><td>32.0</td><td>86.8</td><td>87.2</td><td>89.3</td></tr> <tr><td>40.0</td><td>109.0</td><td>109.2</td><td>111.4</td></tr> <tr><td>45.0</td><td>123.2</td><td>123.4</td><td>125.3</td></tr> <tr><td>49.5</td><td>136.2</td><td>136.2</td><td>138.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	2.9	3.3	4.8	8.0	23.3	23.7	25.3	16.0	44.0	44.5	46.4	24.0	65.1	65.6	67.7	32.0	86.8	87.2	89.3	40.0	109.0	109.2	111.4	45.0	123.2	123.4	125.3	49.5	136.2	136.2	138.4	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	2.9	3.3	4.8																																																			
8.0	23.3	23.7	25.3																																																			
16.0	44.0	44.5	46.4																																																			
24.0	65.1	65.6	67.7																																																			
32.0	86.8	87.2	89.3																																																			
40.0	109.0	109.2	111.4																																																			
45.0	123.2	123.4	125.3																																																			
49.5	136.2	136.2	138.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	CQS48025-45
Item	Efficiency (by Input Voltage)
Object	—

1.Graph




Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
36	91.2	90.5
38	91.3	90.6
42	91.2	90.6
48	90.6	90.4
54	90.0	90.2
60	89.4	89.9
66	88.7	89.7
72	88.1	89.2
76	87.6	89.0

COSEL

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	36[V]	48[V]	76[V]
0.0	-	-	-
8.0	85.2	83.8	78.3
16.0	90.1	89.1	85.5
24.0	91.4	90.7	87.9
32.0	91.3	90.9	88.8
40.0	91.0	90.7	89.0
45.0	90.5	90.4	89.0
49.5	90.1	90.1	88.6
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	CQS48025-45
Item	Line Regulation
Object	+2.5V45A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
36	2.482	2.482
38	2.482	2.482
42	2.482	2.482
48	2.482	2.482
54	2.482	2.482
60	2.482	2.482
66	2.482	2.482
72	2.482	2.482
76	2.482	2.482

COSEL

Model	CQS48025-45	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+2.5V45A																																																					
1.Graph	<p>—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (36V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.482</td></tr> <tr><td>8.0</td><td>2.482</td></tr> <tr><td>16.0</td><td>2.482</td></tr> <tr><td>24.0</td><td>2.482</td></tr> <tr><td>32.0</td><td>2.482</td></tr> <tr><td>40.0</td><td>2.482</td></tr> <tr><td>45.0</td><td>2.482</td></tr> <tr><td>49.5</td><td>2.482</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (36V)	0.0	2.482	8.0	2.482	16.0	2.482	24.0	2.482	32.0	2.482	40.0	2.482	45.0	2.482	49.5	2.482																																	
Load Current [A]	Output Voltage [V] (36V)																																																					
0.0	2.482																																																					
8.0	2.482																																																					
16.0	2.482																																																					
24.0	2.482																																																					
32.0	2.482																																																					
40.0	2.482																																																					
45.0	2.482																																																					
49.5	2.482																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>8.0</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>16.0</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>24.0</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>32.0</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>40.0</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>45.0</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>49.5</td><td>2.482</td><td>2.482</td><td>2.482</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	2.482	2.482	2.482	8.0	2.482	2.482	2.482	16.0	2.482	2.482	2.482	24.0	2.482	2.482	2.482	32.0	2.482	2.482	2.482	40.0	2.482	2.482	2.482	45.0	2.482	2.482	2.482	49.5	2.482	2.482	2.482	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	2.482	2.482	2.482																																																			
8.0	2.482	2.482	2.482																																																			
16.0	2.482	2.482	2.482																																																			
24.0	2.482	2.482	2.482																																																			
32.0	2.482	2.482	2.482																																																			
40.0	2.482	2.482	2.482																																																			
45.0	2.482	2.482	2.482																																																			
49.5	2.482	2.482	2.482																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model CQS48025-45

Item Dynamic Load Response

Object +2.5V45A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 48 V
Cycle 10 ms

Load Current

1A/ μ s

Min. Load (0A) ↔

Load 100% (45A)

100 mV/div

100 μ s/div100 μ s/div

Min. Load (0A) ↔

Load 50% (22.5A)

100 mV/div

100 μ s/div100 μ s/div

Load 50% (22.5A) ↔

Load 100% (45A)

100 mV/div

100 μ s/div100 μ s/div


COSEL

Model CQS48025-45

Item Ripple Voltage (by Load Current)

Object +2.5V45A

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	5	6
8.0	5	6
16.0	5	6
24.0	5	7
32.0	5	7
40.0	5	7
45.0	5	8
49.5	5	8
--	-	-
--	-	-
--	-	-

COSEL


Model CQS48025-45

Item Ripple-Noise

Object +2.5V45A

Temperature 25°C
Testing Circuitry Figure B

1. Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	10	15
8.0	10	15
16.0	30	30
24.0	40	45
32.0	40	45
40.0	45	50
45.0	50	55
49.5	50	55
--	-	-
--	-	-
--	-	-




COSEL
Model CQS48025-45

Item Ripple Voltage (by Ambient Temp.)

Object +2.5V45A

1. Graph


--- □ --- Load 50%
 —△— Load 100%


Testing Circuitry Figure B
2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	6	8
-20	6	8
0	6	7
25	6	6
40	5	6
60	5	6
85	6	6
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.
Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	CQS48025-45	Testing Circuitry Figure A																																																				
Item	Ambient Temperature Drift																																																					
Object	+2.5V45A																																																					
1.Graph	<p style="text-align: center;"> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>	2.Values																																																				
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>2.484</td><td>2.484</td><td>2.483</td></tr> <tr><td>-20</td><td>2.484</td><td>2.484</td><td>2.484</td></tr> <tr><td>0</td><td>2.484</td><td>2.484</td><td>2.484</td></tr> <tr><td>25</td><td>2.483</td><td>2.482</td><td>2.482</td></tr> <tr><td>40</td><td>2.481</td><td>2.481</td><td>2.481</td></tr> <tr><td>60</td><td>2.479</td><td>2.479</td><td>2.479</td></tr> <tr><td>85</td><td>2.475</td><td>2.475</td><td>2.474</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-40	2.484	2.484	2.483	-20	2.484	2.484	2.484	0	2.484	2.484	2.484	25	2.483	2.482	2.482	40	2.481	2.481	2.481	60	2.479	2.479	2.479	85	2.475	2.475	2.474	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-40	2.484	2.484	2.483																																																			
-20	2.484	2.484	2.484																																																			
0	2.484	2.484	2.484																																																			
25	2.483	2.482	2.482																																																			
40	2.481	2.481	2.481																																																			
60	2.479	2.479	2.479																																																			
85	2.475	2.475	2.474																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated ambient temperature.



Model	CQS48025-45	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+2.5V45A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 36 - 76V

Load Current : 0 - 45A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	36	0	2.484	± 5	± 0.2
Minimum Voltage	85	76	45	2.474		

COSEL

Model	CQS48025-45
Item	Time Lapse Drift
Object	+2.5V45A

1.Graph



Input Volt. 48V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	2.483
0.5	2.482
1.0	2.482
2.0	2.482
3.0	2.482
4.0	2.482
5.0	2.482
6.0	2.482
7.0	2.482
8.0	2.482

COSEL

Model CQS48025-45


Item Rise and Fall Time

Object +2.5V45A

Temperature 25°C
Testing Circuitry Figure A

1. Graph


Input Volt. 36 V



2. Values

[mS]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		10.9	8.1	19.0	0.2	0.1
100 %		10.9	8.4	19.3	0.1	0.1



COSEL

Model	CQS48025-45
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+2.5V45A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	31.0	31.0
-20	31.2	31.2
0	31.4	31.2
25	31.3	31.4
40	31.2	31.4
60	31.4	31.4
85	31.4	31.6
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	CQS48025-45
Item	Overcurrent Protection
Object	+2.5V45A

1. Graph

Output Voltage [V]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]
0.00	0.00	0.00	0.00
0.25	0.00	0.00	0.00
0.50	0.00	0.00	0.00
0.75	0.00	0.00	0.00
1.00	0.00	0.00	0.00
1.25	53.34	54.65	56.31
1.50	52.78	54.14	55.73
1.75	52.32	53.54	55.26
2.00	52.00	53.15	54.81
2.25	51.82	52.83	54.44
2.38	51.80	52.73	54.25
2.50	47.94	47.94	47.93

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
2.50	47.94	47.94	47.93
2.38	51.80	52.73	54.25
2.25	51.82	52.83	54.44
2.00	52.00	53.15	54.81
1.75	52.32	53.54	55.26
1.50	52.78	54.14	55.73
1.25	53.34	54.65	56.31
1.00	0.00	0.00	0.00
0.75	0.00	0.00	0.00
0.50	0.00	0.00	0.00
0.25	0.00	0.00	0.00
0.00	0.00	0.00	0.00

COSEL


Model CQS48025-45

Item Overvoltage Protection

Object +2.5V45A

1. Graph

—△— Input Volt. 36V
 - - □ - - Input Volt. 48V
 - - ○ - - Input Volt. 76V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	3.04	3.04	3.04
-20	3.04	3.04	3.04
0	3.04	3.04	3.04
25	2.98	2.98	2.98
40	2.98	2.98	2.98
60	2.98	2.98	2.98
85	2.97	2.97	2.97
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL




Figure A




Figure B