



TEST DATA OF DBS100A13R8 (110V INPUT)

Regulated DC Power Supply
Feb. 3. 2003

Approved by : Isao Yasuda
Isao Yasuda Design Manager

Prepared by : Tomoaki Oiwake
Tomoaki Oiwake Design Engineer

コーセル株式会社
COSEL CO.,LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Figure of Testing Circuitry	19
測定回路図	


(Final Page 19)



Model	DBS100A13R8
Item	Line Regulation 静の入力変動
Object	+13.8V7.3A

Temperature	25°C
Testing Circuitry	Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
40	13.892	13.888
45	13.892	13.889
65	13.892	13.889
85	13.892	13.888
110	13.891	13.888
125	13.891	13.887
145	13.891	13.887
160	13.890	13.886
170	13.890	13.886




Model		DBS100A13R8		Temperature		25°C																																																																								
Item		Input Current (by Input Voltage) 入力電流 (入力電圧特性)		Testing Circuitry		Figure A																																																																								
Object		_____																																																																												
1. Graph				2. Values																																																																										
<p>Legend: —△— Load 100% - - - □ - - - Load 50% - - - ○ - - - Load 0%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>20</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>40</td><td>0.016</td><td>0.016</td><td>0.016</td></tr> <tr><td>42</td><td>0.052</td><td>1.430</td><td>2.890</td></tr> <tr><td>45</td><td>0.049</td><td>1.312</td><td>2.692</td></tr> <tr><td>60</td><td>0.039</td><td>1.015</td><td>2.011</td></tr> <tr><td>80</td><td>0.030</td><td>0.778</td><td>1.514</td></tr> <tr><td>100</td><td>0.026</td><td>0.636</td><td>1.220</td></tr> <tr><td>110</td><td>0.025</td><td>0.584</td><td>1.114</td></tr> <tr><td>130</td><td>0.022</td><td>0.505</td><td>0.949</td></tr> <tr><td>150</td><td>0.019</td><td>0.447</td><td>0.831</td></tr> <tr><td>160</td><td>0.019</td><td>0.428</td><td>0.785</td></tr> <tr><td>170</td><td>0.019</td><td>0.405</td><td>0.745</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	20	0.000	0.000	0.000	40	0.016	0.016	0.016	42	0.052	1.430	2.890	45	0.049	1.312	2.692	60	0.039	1.015	2.011	80	0.030	0.778	1.514	100	0.026	0.636	1.220	110	0.025	0.584	1.114	130	0.022	0.505	0.949	150	0.019	0.447	0.831	160	0.019	0.428	0.785	170	0.019	0.405	0.745	--	--	--	--	--	--	--	--	--	--	--	--
Input Voltage [V]	Input Current [A]																																																																													
	Load 0%	Load 50%	Load 100%																																																																											
0	0.000	0.000	0.000																																																																											
20	0.000	0.000	0.000																																																																											
40	0.016	0.016	0.016																																																																											
42	0.052	1.430	2.890																																																																											
45	0.049	1.312	2.692																																																																											
60	0.039	1.015	2.011																																																																											
80	0.030	0.778	1.514																																																																											
100	0.026	0.636	1.220																																																																											
110	0.025	0.584	1.114																																																																											
130	0.022	0.505	0.949																																																																											
150	0.019	0.447	0.831																																																																											
160	0.019	0.428	0.785																																																																											
170	0.019	0.405	0.745																																																																											
--	--	--	--																																																																											
--	--	--	--																																																																											
--	--	--	--																																																																											
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																																																														



Model	DBS100A13R8
Item	Input Current (by Load Current) 入力電流 (負荷特性)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph
- △— Input Volt. 45V
 - Input Volt. 110V
 - Input Volt. 160V



Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

2. Values


Load Current [A]	Input Current [A]		
	Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]
0.000	0.049	0.025	0.019
1.460	0.576	0.268	0.200
2.920	1.079	0.482	0.352
4.380	1.594	0.686	0.494
5.840	2.136	0.896	0.637
7.300	2.692	1.116	0.785
8.030	2.988	1.227	0.862
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--



Model	DBS100A13R8
Item	Input Power (by Load Current) 入力電力 (負荷特性)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph
- △— Input Volt. 45V
 - Input Volt. 110V
 - Input Volt. 160V



2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]
0.000	2.3	2.8	3.1
1.460	25.9	29.5	32.2
2.920	48.5	53.1	56.4
4.380	71.7	75.5	79.2
5.840	96.0	98.7	102.1
7.300	121.1	122.8	125.9
8.030	134.3	135.0	138.0
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。



Model		DBS100A13R8		Temperature		25°C																																	
Item		Efficiency (by Input Voltage) 効率 (入力電圧特性)		Testing Circuitry		Figure A																																	
Object		_____																																					
1. Graph				2. Values																																			
<p>---□--- Load 50%</p> <p>—△— Load 100%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>40</td><td>84.1</td><td>82.7</td></tr> <tr><td>45</td><td>84.3</td><td>83.6</td></tr> <tr><td>65</td><td>82.7</td><td>84.0</td></tr> <tr><td>85</td><td>80.9</td><td>83.2</td></tr> <tr><td>110</td><td>78.7</td><td>82.4</td></tr> <tr><td>125</td><td>77.3</td><td>81.9</td></tr> <tr><td>145</td><td>75.6</td><td>81.1</td></tr> <tr><td>160</td><td>74.7</td><td>80.5</td></tr> <tr><td>170</td><td>73.5</td><td>79.7</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	40	84.1	82.7	45	84.3	83.6	65	82.7	84.0	85	80.9	83.2	110	78.7	82.4	125	77.3	81.9	145	75.6	81.1	160	74.7	80.5	170	73.5	79.7
Input Voltage [V]	Efficiency [%]																																						
	Load 50%	Load 100%																																					
40	84.1	82.7																																					
45	84.3	83.6																																					
65	82.7	84.0																																					
85	80.9	83.2																																					
110	78.7	82.4																																					
125	77.3	81.9																																					
145	75.6	81.1																																					
160	74.7	80.5																																					
170	73.5	79.7																																					
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																							



Model		DBS100A13R8		Temperature	25°C																																																			
Item		Efficiency (by Load Current) 効率 (負荷特性)		Testing Circuitry	Figure A																																																			
Object		_____																																																						
1. Graph			2. Values																																																					
<p> △ Input Volt. 45V □ Input Volt. 110V ○ Input Volt. 160V </p> <p>Efficiency [%]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 45[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>1.460</td><td>78.1</td><td>68.5</td><td>62.8</td></tr> <tr><td>2.920</td><td>83.5</td><td>76.2</td><td>71.8</td></tr> <tr><td>4.380</td><td>84.7</td><td>80.4</td><td>76.7</td></tr> <tr><td>5.840</td><td>84.3</td><td>82.0</td><td>79.3</td></tr> <tr><td>7.300</td><td>83.6</td><td>82.4</td><td>80.4</td></tr> <tr><td>8.030</td><td>82.9</td><td>82.4</td><td>80.6</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.000	—	—	—	1.460	78.1	68.5	62.8	2.920	83.5	76.2	71.8	4.380	84.7	80.4	76.7	5.840	84.3	82.0	79.3	7.300	83.6	82.4	80.4	8.030	82.9	82.4	80.6	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.000	—	—	—																																																					
1.460	78.1	68.5	62.8																																																					
2.920	83.5	76.2	71.8																																																					
4.380	84.7	80.4	76.7																																																					
5.840	84.3	82.0	79.3																																																					
7.300	83.6	82.4	80.4																																																					
8.030	82.9	82.4	80.6																																																					
—	—	—	—																																																					
—	—	—	—																																																					
—	—	—	—																																																					
—	—	—	—																																																					
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																								



<p>Model DBS100A13R8</p> <p>Item Load Regulation 静的負荷変動</p> <p>Object +13.8V7.3A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																															
<p>1. Graph</p> <p>—△— Input Volt. 45V ---□--- Input Volt. 110V ---○--- Input Volt. 160V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 45[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>13.891</td><td>13.891</td><td>13.891</td></tr> <tr><td>1.460</td><td>13.890</td><td>13.891</td><td>13.890</td></tr> <tr><td>2.920</td><td>13.889</td><td>13.890</td><td>13.890</td></tr> <tr><td>4.380</td><td>13.888</td><td>13.889</td><td>13.888</td></tr> <tr><td>5.840</td><td>13.888</td><td>13.887</td><td>13.887</td></tr> <tr><td>7.300</td><td>13.887</td><td>13.886</td><td>13.885</td></tr> <tr><td>8.030</td><td>13.887</td><td>13.886</td><td>13.885</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.000	13.891	13.891	13.891	1.460	13.890	13.891	13.890	2.920	13.889	13.890	13.890	4.380	13.888	13.889	13.888	5.840	13.888	13.887	13.887	7.300	13.887	13.886	13.885	8.030	13.887	13.886	13.885	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																
	Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]																																														
0.000	13.891	13.891	13.891																																														
1.460	13.890	13.891	13.890																																														
2.920	13.889	13.890	13.890																																														
4.380	13.888	13.889	13.888																																														
5.840	13.888	13.887	13.887																																														
7.300	13.887	13.886	13.885																																														
8.030	13.887	13.886	13.885																																														
--	--	--	--																																														
--	--	--	--																																														
--	--	--	--																																														
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																	



<p>Model DBS100A13R8</p> <p>Item Ripple Voltage (by Load Current) リップル電圧 (負荷特性)</p> <p>Object +13.8V7.3A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																						
<p>1. Graph</p> <p style="text-align: center;"> —△— Input Volt. 45V ---○--- Input Volt. 160V </p> <p style="text-align: center;">Ripple Voltage [mV]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 45 [V]</th> <th>Input Volt. 160 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>10</td><td>20</td></tr> <tr><td>1.460</td><td>10</td><td>20</td></tr> <tr><td>2.920</td><td>10</td><td>20</td></tr> <tr><td>4.380</td><td>10</td><td>20</td></tr> <tr><td>5.840</td><td>10</td><td>20</td></tr> <tr><td>7.300</td><td>10</td><td>20</td></tr> <tr><td>8.030</td><td>10</td><td>20</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 45 [V]	Input Volt. 160 [V]	0.000	10	20	1.460	10	20	2.920	10	20	4.380	10	20	5.840	10	20	7.300	10	20	8.030	10	20	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 45 [V]	Input Volt. 160 [V]																																						
0.000	10	20																																						
1.460	10	20																																						
2.920	10	20																																						
4.380	10	20																																						
5.840	10	20																																						
7.300	10	20																																						
8.030	10	20																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p-p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								



<p>Model DBS100A13R8</p> <p>Item Ripple-Noise リップルノイズ</p> <p>Object +13.8V7.3A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																						
<p>1. Graph</p> <p>—△— Input Volt. 45V</p> <p>- -○- - Input Volt. 160V</p> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 45 [V]</th> <th>Input Volt. 160 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15</td><td>25</td></tr> <tr><td>1.460</td><td>20</td><td>30</td></tr> <tr><td>2.920</td><td>20</td><td>30</td></tr> <tr><td>4.380</td><td>20</td><td>35</td></tr> <tr><td>5.840</td><td>20</td><td>35</td></tr> <tr><td>7.300</td><td>20</td><td>35</td></tr> <tr><td>8.030</td><td>20</td><td>35</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 45 [V]	Input Volt. 160 [V]	0.000	15	25	1.460	20	30	2.920	20	30	4.380	20	35	5.840	20	35	7.300	20	35	8.030	20	35	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 45 [V]	Input Volt. 160 [V]																																						
0.000	15	25																																						
1.460	20	30																																						
2.920	20	30																																						
4.380	20	35																																						
5.840	20	35																																						
7.300	20	35																																						
8.030	20	35																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p-p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>Ripple Noise [mVp-p]</p>																																								
<p>Fig. Complex Ripple Noise Wave Form 図 リップルノイズ波形</p>																																								




<p>Model DBS100A13R8</p> <p>Item Overcurrent Protection 過電流保護</p> <p>Object +13.8V7.3A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																											
<p>1. Graph</p> <p> Input Volt. 45V Input Volt. 110V Input Volt. 160V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。</p> <p>Intermittent operation occurs when the output voltage is from 8.9V to 0V. 8.9V~0V間は、間欠モードとなる。</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 45[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>13.80</td><td>9.14</td><td>9.26</td><td>10.08</td></tr> <tr><td>13.11</td><td>9.28</td><td>9.44</td><td>10.14</td></tr> <tr><td>12.42</td><td>9.28</td><td>9.53</td><td>10.11</td></tr> <tr><td>11.04</td><td>9.33</td><td>10.02</td><td>10.76</td></tr> <tr><td>9.66</td><td>9.44</td><td>10.15</td><td>10.89</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]	13.80	9.14	9.26	10.08	13.11	9.28	9.44	10.14	12.42	9.28	9.53	10.11	11.04	9.33	10.02	10.76	9.66	9.44	10.15	10.89	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Output Voltage [V]	Load Current [A]																																																												
	Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																										
13.80	9.14	9.26	10.08																																																										
13.11	9.28	9.44	10.14																																																										
12.42	9.28	9.53	10.11																																																										
11.04	9.33	10.02	10.76																																																										
9.66	9.44	10.15	10.89																																																										
--	--	--	--																																																										
--	--	--	--																																																										
--	--	--	--																																																										
--	--	--	--																																																										
--	--	--	--																																																										
--	--	--	--																																																										
--	--	--	--																																																										
--	--	--	--																																																										



Model	DBS100A13R8
Item	Overvoltage Protection 過電圧保護
Object	+13.8V7.3A

Testing Circuitry Figure A

1. Graph
- △— Input Volt. 45V
 - Input Volt. 110V
 - Input Volt. 160V



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values


Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]
-35	17.45	17.45	17.45
-20	17.57	17.57	17.57
0	17.57	17.57	17.57
15	17.68	17.57	17.57
25	17.68	17.68	17.68
40	17.74	17.74	17.74
55	17.74	17.74	17.74
70	17.74	17.74	17.74
85	17.86	17.86	17.86
90	17.86	17.86	17.86
--	--	--	--



Model	DBS100A13R8	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+13.8V7.3A		


Input Volt. 110 V
Cycle 1000 ms

Load Current




Min. Load (0A) ←→
Load 100% (7.3A)

500 mV/div




5 ms/div




5 ms/div

Min. Load (0A) ←→
Load 50% (3.65A)

500 mV/div




5 ms/div




5 ms/div

Load 10% (0.73A) ←→
Load 100% (7.3A)

500 mV/div



5 ms/div




5 ms/div




Model	DBS100A13R8	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+13.8V7.3A		

1. Graph



2. Values

Load	Time [mS]				
	T _d	T _r	T _s	T _h	T _f
50 %	12.8	4.8	17.5	0.6	12.3
100 %	12.8	4.5	17.3	0.3	6.2






Model	DBS100A13R8
Item	Ambient Temperature Drift 周囲温度変動
Object	+13.8V7.3A

Testing Circuitry Figure A

1. Graph

—△— Input Volt. 45V
 - - - □ - - - Input Volt. 110V
 - - - ○ - - - Input Volt. 160V



2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 45[V]	Input Volt. 110[V]	Input Volt. 160[V]
-35	13.897	13.895	13.894
-20	13.898	13.896	13.895
0	13.897	13.896	13.895
15	13.897	13.895	13.894
25	13.894	13.893	13.892
40	13.886	13.885	13.884
55	13.877	13.876	13.875
70	13.863	13.862	13.862
85	13.846	13.846	13.844
90	13.839	13.839	13.838
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。



Model	DBS100A13R8
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+13.8V7.3A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-35	36	36
-20	35	37
0	35	37
15	35	37
25	35	38
40	35	38
55	36	38
70	36	39
85	36	39
90	36	39
--	—	—



Model	DBS100A13R8
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+13.8V7.3A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	30	30
-20	20	20
0	10	15
25	10	10
45	10	10
65	15	15
85	20	15
100	20	20
--	--	--
--	--	--
--	--	--

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。



COSEL																								
Model	DBS100A13R8																							
Item	Time Lapse Drift 経時ドリフト	Temperature 25°C Testing Circuitry Figure A																						
Object	+13.8V7.3A																							
<p>1. Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 110V Load 100%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>13.895</td></tr> <tr><td>0.5</td><td>13.885</td></tr> <tr><td>1.0</td><td>13.885</td></tr> <tr><td>2.0</td><td>13.885</td></tr> <tr><td>3.0</td><td>13.885</td></tr> <tr><td>4.0</td><td>13.885</td></tr> <tr><td>5.0</td><td>13.885</td></tr> <tr><td>6.0</td><td>13.885</td></tr> <tr><td>7.0</td><td>13.885</td></tr> <tr><td>8.0</td><td>13.885</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	13.895	0.5	13.885	1.0	13.885	2.0	13.885	3.0	13.885	4.0	13.885	5.0	13.885	6.0	13.885	7.0	13.885	8.0	13.885
Time since start [H]	Output Voltage [V]																							
0.0	13.895																							
0.5	13.885																							
1.0	13.885																							
2.0	13.885																							
3.0	13.885																							
4.0	13.885																							
5.0	13.885																							
6.0	13.885																							
7.0	13.885																							
8.0	13.885																							



COSEL		
Model	DBS100A13R8	
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry Figure A
Object	+13.8V7.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 ~ 85°C

Input Voltage : 45 ~ 160V

Load Current : 0 ~ 7.3A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -20 ~ 85°C

入力電圧 : 45 ~ 160V

負荷電流 : 0 ~ 7.3A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	45	0	13.900	±29	±0.2
Minimum Voltage	85	160	7.3	13.842		




Figure A




Figure B (General Electric Characteristic)
一般電気特性

- C1 : 0.1 μ F 250V Film capacitor
- C2 : 47 μ F 250V Electric capacitor
- C3、C4 : 2200pF 250V Ceramic capacitor
- C5 : 1000 μ F 25V Electric capacitor
- C6 : 0.1 μ F 50V Film capacitor
- LF1 : 1mH 3A Common mode Choke Coil