



TEST DATA OF DBS150A12 (DC110V INPUT)

Regulated DC Power Supply
Feb. 4. 2003

Approved by : Isao Yasuda
Isao Yasuda Design Manager

Prepared by : Tomoaki Oiwake
Tomoaki Oiwake Design Engineer

コーワセル株式会社
COSEL CO.,LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Figure of Testing Circuitry	19
測定回路図	

(Final Page 19)

COSEL

Model	DBS150A12	Temperature	25°C																																
Item	Line Regulation 静的入力変動	Testing Circuitry	Figure A																																
Object	+12V12.5A																																		
1. Graph	<p style="text-align: center;">---□--- Load 50% —△— Load 100%</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Output Voltage [V] (Load 50%)</th> <th>Output Voltage [V] (Load 100%)</th> </tr> </thead> <tbody> <tr><td>60</td><td>12.217</td><td>12.213</td></tr> <tr><td>66</td><td>12.217</td><td>12.214</td></tr> <tr><td>80</td><td>12.217</td><td>12.214</td></tr> <tr><td>95</td><td>12.217</td><td>12.214</td></tr> <tr><td>110</td><td>12.217</td><td>12.214</td></tr> <tr><td>125</td><td>12.217</td><td>12.213</td></tr> <tr><td>145</td><td>12.217</td><td>12.213</td></tr> <tr><td>160</td><td>12.217</td><td>12.213</td></tr> <tr><td>170</td><td>12.216</td><td>12.212</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V] (Load 50%)	Output Voltage [V] (Load 100%)	60	12.217	12.213	66	12.217	12.214	80	12.217	12.214	95	12.217	12.214	110	12.217	12.214	125	12.217	12.213	145	12.217	12.213	160	12.217	12.213	170	12.216	12.212		
Input Voltage [V]	Output Voltage [V] (Load 50%)	Output Voltage [V] (Load 100%)																																	
60	12.217	12.213																																	
66	12.217	12.214																																	
80	12.217	12.214																																	
95	12.217	12.214																																	
110	12.217	12.214																																	
125	12.217	12.213																																	
145	12.217	12.213																																	
160	12.217	12.213																																	
170	12.216	12.212																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>60</td><td>12.217</td><td>12.213</td></tr> <tr><td>66</td><td>12.217</td><td>12.214</td></tr> <tr><td>80</td><td>12.217</td><td>12.214</td></tr> <tr><td>95</td><td>12.217</td><td>12.214</td></tr> <tr><td>110</td><td>12.217</td><td>12.214</td></tr> <tr><td>125</td><td>12.217</td><td>12.213</td></tr> <tr><td>145</td><td>12.217</td><td>12.213</td></tr> <tr><td>160</td><td>12.217</td><td>12.213</td></tr> <tr><td>170</td><td>12.216</td><td>12.212</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	60	12.217	12.213	66	12.217	12.214	80	12.217	12.214	95	12.217	12.214	110	12.217	12.214	125	12.217	12.213	145	12.217	12.213	160	12.217	12.213	170	12.216	12.212
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
60	12.217	12.213																																	
66	12.217	12.214																																	
80	12.217	12.214																																	
95	12.217	12.214																																	
110	12.217	12.214																																	
125	12.217	12.213																																	
145	12.217	12.213																																	
160	12.217	12.213																																	
170	12.216	12.212																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	DBS150A12	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object																																																																										
1. Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% —○— Load 0% </p>																																																																									
2. Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>20</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>40</td><td>0.016</td><td>0.016</td><td>0.015</td></tr> <tr><td>59</td><td>0.044</td><td>1.486</td><td>3.054</td></tr> <tr><td>60</td><td>0.043</td><td>1.460</td><td>2.986</td></tr> <tr><td>66</td><td>0.039</td><td>1.328</td><td>2.703</td></tr> <tr><td>80</td><td>0.036</td><td>1.100</td><td>2.206</td></tr> <tr><td>100</td><td>0.030</td><td>0.885</td><td>1.758</td></tr> <tr><td>110</td><td>0.028</td><td>0.809</td><td>1.598</td></tr> <tr><td>130</td><td>0.024</td><td>0.691</td><td>1.355</td></tr> <tr><td>150</td><td>0.022</td><td>0.606</td><td>1.179</td></tr> <tr><td>160</td><td>0.022</td><td>0.572</td><td>1.115</td></tr> <tr><td>170</td><td>0.021</td><td>0.542</td><td>1.048</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	20	0.000	0.000	0.000	40	0.016	0.016	0.015	59	0.044	1.486	3.054	60	0.043	1.460	2.986	66	0.039	1.328	2.703	80	0.036	1.100	2.206	100	0.030	0.885	1.758	110	0.028	0.809	1.598	130	0.024	0.691	1.355	150	0.022	0.606	1.179	160	0.022	0.572	1.115	170	0.021	0.542	1.048	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
20	0.000	0.000	0.000																																																																							
40	0.016	0.016	0.015																																																																							
59	0.044	1.486	3.054																																																																							
60	0.043	1.460	2.986																																																																							
66	0.039	1.328	2.703																																																																							
80	0.036	1.100	2.206																																																																							
100	0.030	0.885	1.758																																																																							
110	0.028	0.809	1.598																																																																							
130	0.024	0.691	1.355																																																																							
150	0.022	0.606	1.179																																																																							
160	0.022	0.572	1.115																																																																							
170	0.021	0.542	1.048																																																																							
—	—	—	—																																																																							
—	—	—	—																																																																							
—	—	—	—																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	DBS150A12																																																					
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	<hr/>																																																					
1. Graph	<p>—▲— Input Volt. 66V ---□--- Input Volt. 110V -○--- Input Volt. 160V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (66V)</th> <th>Input Current [A] (110V)</th> <th>Input Current [A] (160V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.040</td><td>0.028</td><td>0.022</td></tr> <tr><td>2.50</td><td>0.560</td><td>0.356</td><td>0.262</td></tr> <tr><td>5.00</td><td>1.066</td><td>0.653</td><td>0.466</td></tr> <tr><td>7.50</td><td>1.593</td><td>0.962</td><td>0.677</td></tr> <tr><td>10.00</td><td>2.146</td><td>1.278</td><td>0.892</td></tr> <tr><td>12.50</td><td>2.722</td><td>1.602</td><td>1.110</td></tr> <tr><td>13.75</td><td>3.021</td><td>1.767</td><td>1.221</td></tr> </tbody> </table>			Load Current [A]	Input Current [A] (66V)	Input Current [A] (110V)	Input Current [A] (160V)	0.00	0.040	0.028	0.022	2.50	0.560	0.356	0.262	5.00	1.066	0.653	0.466	7.50	1.593	0.962	0.677	10.00	2.146	1.278	0.892	12.50	2.722	1.602	1.110	13.75	3.021	1.767	1.221																			
Load Current [A]	Input Current [A] (66V)	Input Current [A] (110V)	Input Current [A] (160V)																																																			
0.00	0.040	0.028	0.022																																																			
2.50	0.560	0.356	0.262																																																			
5.00	1.066	0.653	0.466																																																			
7.50	1.593	0.962	0.677																																																			
10.00	2.146	1.278	0.892																																																			
12.50	2.722	1.602	1.110																																																			
13.75	3.021	1.767	1.221																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 66[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.040</td><td>0.028</td><td>0.022</td></tr> <tr><td>2.50</td><td>0.560</td><td>0.356</td><td>0.262</td></tr> <tr><td>5.00</td><td>1.066</td><td>0.653</td><td>0.466</td></tr> <tr><td>7.50</td><td>1.593</td><td>0.962</td><td>0.677</td></tr> <tr><td>10.00</td><td>2.146</td><td>1.278</td><td>0.892</td></tr> <tr><td>12.50</td><td>2.722</td><td>1.602</td><td>1.110</td></tr> <tr><td>13.75</td><td>3.021</td><td>1.767</td><td>1.221</td></tr> <tr><td>---</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>---</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>---</td><td>---</td><td>---</td><td>---</td></tr> <tr><td>---</td><td>---</td><td>---</td><td>---</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	0.040	0.028	0.022	2.50	0.560	0.356	0.262	5.00	1.066	0.653	0.466	7.50	1.593	0.962	0.677	10.00	2.146	1.278	0.892	12.50	2.722	1.602	1.110	13.75	3.021	1.767	1.221	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---
Load Current [A]	Input Current [A]																																																					
	Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																			
0.00	0.040	0.028	0.022																																																			
2.50	0.560	0.356	0.262																																																			
5.00	1.066	0.653	0.466																																																			
7.50	1.593	0.962	0.677																																																			
10.00	2.146	1.278	0.892																																																			
12.50	2.722	1.602	1.110																																																			
13.75	3.021	1.767	1.221																																																			
---	---	---	---																																																			
---	---	---	---																																																			
---	---	---	---																																																			
---	---	---	---																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS150A12																																																					
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object																																																						
1. Graph	<p>—▲— Input Volt. 66V ---□--- Input Volt. 110V ---○--- Input Volt. 160V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (66V)</th> <th>Input Power [W] (110V)</th> <th>Input Power [W] (160V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2.7</td><td>3.1</td><td>3.5</td></tr> <tr><td>2.50</td><td>36.9</td><td>39.1</td><td>41.9</td></tr> <tr><td>5.00</td><td>70.2</td><td>71.7</td><td>74.5</td></tr> <tr><td>7.50</td><td>104.6</td><td>105.6</td><td>108.2</td></tr> <tr><td>10.00</td><td>140.7</td><td>140.1</td><td>142.3</td></tr> <tr><td>12.50</td><td>178.1</td><td>175.6</td><td>177.2</td></tr> <tr><td>13.75</td><td>197.4</td><td>193.6</td><td>194.9</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (66V)	Input Power [W] (110V)	Input Power [W] (160V)	0.00	2.7	3.1	3.5	2.50	36.9	39.1	41.9	5.00	70.2	71.7	74.5	7.50	104.6	105.6	108.2	10.00	140.7	140.1	142.3	12.50	178.1	175.6	177.2	13.75	197.4	193.6	194.9																			
Load Current [A]	Input Power [W] (66V)	Input Power [W] (110V)	Input Power [W] (160V)																																																			
0.00	2.7	3.1	3.5																																																			
2.50	36.9	39.1	41.9																																																			
5.00	70.2	71.7	74.5																																																			
7.50	104.6	105.6	108.2																																																			
10.00	140.7	140.1	142.3																																																			
12.50	178.1	175.6	177.2																																																			
13.75	197.4	193.6	194.9																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 66[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2.7</td><td>3.1</td><td>3.5</td></tr> <tr><td>2.50</td><td>36.9</td><td>39.1</td><td>41.9</td></tr> <tr><td>5.00</td><td>70.2</td><td>71.7</td><td>74.5</td></tr> <tr><td>7.50</td><td>104.6</td><td>105.6</td><td>108.2</td></tr> <tr><td>10.00</td><td>140.7</td><td>140.1</td><td>142.3</td></tr> <tr><td>12.50</td><td>178.1</td><td>175.6</td><td>177.2</td></tr> <tr><td>13.75</td><td>197.4</td><td>193.6</td><td>194.9</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	2.7	3.1	3.5	2.50	36.9	39.1	41.9	5.00	70.2	71.7	74.5	7.50	104.6	105.6	108.2	10.00	140.7	140.1	142.3	12.50	178.1	175.6	177.2	13.75	197.4	193.6	194.9	---	—	—	—	---	—	—	—	---	—	—	—	---	—	—	—
Load Current [A]	Input Power [W]																																																					
	Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																			
0.00	2.7	3.1	3.5																																																			
2.50	36.9	39.1	41.9																																																			
5.00	70.2	71.7	74.5																																																			
7.50	104.6	105.6	108.2																																																			
10.00	140.7	140.1	142.3																																																			
12.50	178.1	175.6	177.2																																																			
13.75	197.4	193.6	194.9																																																			
---	—	—	—																																																			
---	—	—	—																																																			
---	—	—	—																																																			
---	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS150A12	Temperature	25°C																															
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																															
Object	—	—	—																															
1. Graph																																		
			2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>60</td><td>87.0</td><td>84.5</td></tr> <tr><td>66</td><td>87.2</td><td>85.3</td></tr> <tr><td>80</td><td>86.8</td><td>86.1</td></tr> <tr><td>95</td><td>86.4</td><td>86.3</td></tr> <tr><td>110</td><td>85.9</td><td>86.6</td></tr> <tr><td>125</td><td>85.2</td><td>86.5</td></tr> <tr><td>145</td><td>84.3</td><td>86.1</td></tr> <tr><td>160</td><td>83.5</td><td>85.7</td></tr> <tr><td>170</td><td>82.8</td><td>85.3</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	60	87.0	84.5	66	87.2	85.3	80	86.8	86.1	95	86.4	86.3	110	85.9	86.6	125	85.2	86.5	145	84.3	86.1	160	83.5	85.7	170	82.8	85.3
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
60	87.0	84.5																																
66	87.2	85.3																																
80	86.8	86.1																																
95	86.4	86.3																																
110	85.9	86.6																																
125	85.2	86.5																																
145	84.3	86.1																																
160	83.5	85.7																																
170	82.8	85.3																																

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	DBS150A12																																																					
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	<hr/>																																																					
1. Graph	<p>—△— Input Volt. 66V - - - □ - Input Volt. 110V - - ○ - Input Volt. 160V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency 66V [%]</th> <th>Efficiency 110V [%]</th> <th>Efficiency 160V [%]</th> </tr> </thead> <tbody> <tr><td>3.0</td><td>84.5</td><td>78.0</td><td>72.0</td></tr> <tr><td>5.0</td><td>85.5</td><td>81.0</td><td>75.0</td></tr> <tr><td>7.5</td><td>85.5</td><td>83.0</td><td>80.0</td></tr> <tr><td>10.0</td><td>85.5</td><td>83.0</td><td>82.0</td></tr> <tr><td>12.5</td><td>85.5</td><td>83.0</td><td>82.0</td></tr> </tbody> </table>			Load Current [A]	Efficiency 66V [%]	Efficiency 110V [%]	Efficiency 160V [%]	3.0	84.5	78.0	72.0	5.0	85.5	81.0	75.0	7.5	85.5	83.0	80.0	10.0	85.5	83.0	82.0	12.5	85.5	83.0	82.0																											
Load Current [A]	Efficiency 66V [%]	Efficiency 110V [%]	Efficiency 160V [%]																																																			
3.0	84.5	78.0	72.0																																																			
5.0	85.5	81.0	75.0																																																			
7.5	85.5	83.0	80.0																																																			
10.0	85.5	83.0	82.0																																																			
12.5	85.5	83.0	82.0																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 66[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>2.50</td><td>82.5</td><td>77.8</td><td>72.5</td></tr> <tr><td>5.00</td><td>86.7</td><td>84.8</td><td>81.7</td></tr> <tr><td>7.50</td><td>87.2</td><td>86.4</td><td>84.3</td></tr> <tr><td>10.00</td><td>86.4</td><td>86.8</td><td>85.4</td></tr> <tr><td>12.50</td><td>85.4</td><td>86.6</td><td>85.8</td></tr> <tr><td>13.75</td><td>84.7</td><td>86.3</td><td>85.7</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	—	—	—	2.50	82.5	77.8	72.5	5.00	86.7	84.8	81.7	7.50	87.2	86.4	84.3	10.00	86.4	86.8	85.4	12.50	85.4	86.6	85.8	13.75	84.7	86.3	85.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																			
0.00	—	—	—																																																			
2.50	82.5	77.8	72.5																																																			
5.00	86.7	84.8	81.7																																																			
7.50	87.2	86.4	84.3																																																			
10.00	86.4	86.8	85.4																																																			
12.50	85.4	86.6	85.8																																																			
13.75	84.7	86.3	85.7																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS150A12																																																		
Item	Load Regulation 静的負荷変動	Temperature 25°C Testing Circuitry Figure A																																																	
Object	+12V12.5A																																																		
1. Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 66V Input Volt. 110V Input Volt. 160V 																																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 66[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.221</td><td>12.221</td><td>12.220</td></tr> <tr><td>2.50</td><td>12.219</td><td>12.220</td><td>12.219</td></tr> <tr><td>5.00</td><td>12.218</td><td>12.218</td><td>12.218</td></tr> <tr><td>7.50</td><td>12.216</td><td>12.217</td><td>12.216</td></tr> <tr><td>10.00</td><td>12.215</td><td>12.215</td><td>12.214</td></tr> <tr><td>12.50</td><td>12.213</td><td>12.214</td><td>12.213</td></tr> <tr><td>13.75</td><td>12.213</td><td>12.213</td><td>12.212</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	12.221	12.221	12.220	2.50	12.219	12.220	12.219	5.00	12.218	12.218	12.218	7.50	12.216	12.217	12.216	10.00	12.215	12.215	12.214	12.50	12.213	12.214	12.213	13.75	12.213	12.213	12.212	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																
0.00	12.221	12.221	12.220																																																
2.50	12.219	12.220	12.219																																																
5.00	12.218	12.218	12.218																																																
7.50	12.216	12.217	12.216																																																
10.00	12.215	12.215	12.214																																																
12.50	12.213	12.214	12.213																																																
13.75	12.213	12.213	12.212																																																
—	—	—	—																																																
—	—	—	—																																																
—	—	—	—																																																
Note: Slanted line shows the range of the rated load current.																																																			
(注) 斜線は定格負荷電流範囲を示す。																																																			

COSEL

Model	DBS150A12	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Testing Circuitry	Figure A																																						
Object	+12V12.5A																																								
1. Graph																																									
			2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 66 [V]</th> <th>Input Volt. 160 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>10</td></tr> <tr><td>2.50</td><td>5</td><td>10</td></tr> <tr><td>5.00</td><td>5</td><td>10</td></tr> <tr><td>7.50</td><td>5</td><td>10</td></tr> <tr><td>10.00</td><td>5</td><td>10</td></tr> <tr><td>12.50</td><td>10</td><td>10</td></tr> <tr><td>13.75</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Load Current [A]	Ripple Voltage [mV]		Input Volt. 66 [V]	Input Volt. 160 [V]	0.00	5	10	2.50	5	10	5.00	5	10	7.50	5	10	10.00	5	10	12.50	10	10	13.75	10	10	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 66 [V]	Input Volt. 160 [V]																																							
0.00	5	10																																							
2.50	5	10																																							
5.00	5	10																																							
7.50	5	10																																							
10.00	5	10																																							
12.50	10	10																																							
13.75	10	10																																							
--	--	--																																							
--	--	--																																							
--	--	--																																							
--	--	--																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	DBS150A12	Temperature	25°C																																				
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																																				
Object	+12V12.5A																																						
1. Graph																																							
<p>Y-axis: Ripple-Noise [mV] (0 to 160) X-axis: Load Current [A] (0 to 12)</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 66V)</th> <th>Ripple-Noise [mV] (Input Volt. 160V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>25</td></tr> <tr><td>2.50</td><td>15</td><td>25</td></tr> <tr><td>5.00</td><td>20</td><td>25</td></tr> <tr><td>7.50</td><td>20</td><td>25</td></tr> <tr><td>10.00</td><td>20</td><td>25</td></tr> <tr><td>12.50</td><td>20</td><td>30</td></tr> <tr><td>13.75</td><td>20</td><td>30</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Load Current [A]	Ripple-Noise [mV] (Input Volt. 66V)	Ripple-Noise [mV] (Input Volt. 160V)	0.00	15	25	2.50	15	25	5.00	20	25	7.50	20	25	10.00	20	25	12.50	20	30	13.75	20	30	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple-Noise [mV] (Input Volt. 66V)	Ripple-Noise [mV] (Input Volt. 160V)																																					
0.00	15	25																																					
2.50	15	25																																					
5.00	20	25																																					
7.50	20	25																																					
10.00	20	25																																					
12.50	20	30																																					
13.75	20	30																																					
--	--	--																																					
--	--	--																																					
--	--	--																																					
--	--	--																																					
Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																							
<p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>Y-axis: Ripple Noise [mVp-p]</p>																																							
<p>Fig. Complex Ripple Noise Wave Form 図 リップルノイズ波形</p>																																							

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 66 [V]	Input Volt. 160 [V]
0.00	15	25
2.50	15	25
5.00	20	25
7.50	20	25
10.00	20	25
12.50	20	30
13.75	20	30
--	--	--
--	--	--
--	--	--
--	--	--

COSEL


Model	DBS150A12	Temperature 25°C Testing Circuitry Figure A																																																													
Item	Overcurrent Protection 過電流保護																																																														
Object	+12V12.5A																																																														
1. Graph	<p>The graph plots Output Voltage [V] on the Y-axis (0 to 12) against Load Current [A] on the X-axis (0 to 20). Three solid lines represent different input voltages: 66V (top), 110V (middle), and 160V (bottom). All three lines show a horizontal plateau at approximately 12V until a certain load current is reached, after which they drop sharply. A diagonal hatched band is drawn across the graph, starting from the 110V curve at approximately 12A and extending down to the 66V curve at approximately 18A, representing the rated load current range.</p>																																																														
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 66[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>15.97</td><td>15.99</td><td>16.40</td></tr> <tr><td>11.4</td><td>16.24</td><td>16.14</td><td>16.77</td></tr> <tr><td>10.8</td><td>16.28</td><td>16.25</td><td>16.88</td></tr> <tr><td>9.6</td><td>16.38</td><td>16.46</td><td>17.08</td></tr> <tr><td>8.4</td><td>16.52</td><td>16.70</td><td>17.38</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]	12.0	15.97	15.99	16.40	11.4	16.24	16.14	16.77	10.8	16.28	16.25	16.88	9.6	16.38	16.46	17.08	8.4	16.52	16.70	17.38	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Output Voltage [V]	Load Current [A]																																																														
	Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																												
12.0	15.97	15.99	16.40																																																												
11.4	16.24	16.14	16.77																																																												
10.8	16.28	16.25	16.88																																																												
9.6	16.38	16.46	17.08																																																												
8.4	16.52	16.70	17.38																																																												
--	--	--	--																																																												
--	--	--	--																																																												
--	--	--	--																																																												
--	--	--	--																																																												
--	--	--	--																																																												
--	--	--	--																																																												
--	--	--	--																																																												
--	--	--	--																																																												
Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。																																																															
Intermittent operation occurs when the output voltage is from 7.6V to 0V. 7.6V~0V間は、間欠モードとなる。																																																															

COSEL


Model	DBS150A12																																																					
Item	Overvoltage Protection 過電圧保護																																																					
Object	+12V12.5A																																																					
1. Graph																																																						
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 66V Input Volt. 110V Input Volt. 160V 																																																						
2. Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 66[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr> <td>-35</td> <td>14.75</td> <td>14.63</td> <td>14.63</td> </tr> <tr> <td>-20</td> <td>14.75</td> <td>14.75</td> <td>14.75</td> </tr> <tr> <td>0</td> <td>14.92</td> <td>14.92</td> <td>14.92</td> </tr> <tr> <td>15</td> <td>15.05</td> <td>15.05</td> <td>15.05</td> </tr> <tr> <td>25</td> <td>15.05</td> <td>15.05</td> <td>15.05</td> </tr> <tr> <td>40</td> <td>15.17</td> <td>15.17</td> <td>15.17</td> </tr> <tr> <td>55</td> <td>15.28</td> <td>15.28</td> <td>15.28</td> </tr> <tr> <td>70</td> <td>15.34</td> <td>15.34</td> <td>15.34</td> </tr> <tr> <td>85</td> <td>15.46</td> <td>15.45</td> <td>15.45</td> </tr> <tr> <td>90</td> <td>15.46</td> <td>15.46</td> <td>15.46</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Operating Point [V]			Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]	-35	14.75	14.63	14.63	-20	14.75	14.75	14.75	0	14.92	14.92	14.92	15	15.05	15.05	15.05	25	15.05	15.05	15.05	40	15.17	15.17	15.17	55	15.28	15.28	15.28	70	15.34	15.34	15.34	85	15.46	15.45	15.45	90	15.46	15.46	15.46	--	--	--	--
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																			
-35	14.75	14.63	14.63																																																			
-20	14.75	14.75	14.75																																																			
0	14.92	14.92	14.92																																																			
15	15.05	15.05	15.05																																																			
25	15.05	15.05	15.05																																																			
40	15.17	15.17	15.17																																																			
55	15.28	15.28	15.28																																																			
70	15.34	15.34	15.34																																																			
85	15.46	15.45	15.45																																																			
90	15.46	15.46	15.46																																																			
--	--	--	--																																																			

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

COSEL



COSEL

Model	DBS150A12																																																						
Item	Ambient Temperature Drift 周囲温度変動	Testing Circuitry Figure A																																																					
Object	+12V12.5A																																																						
1. Graph																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 66[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr> <td>-35</td><td>12.239</td><td>12.239</td><td>12.239</td></tr> <tr> <td>-20</td><td>12.237</td><td>12.237</td><td>12.237</td></tr> <tr> <td>0</td><td>12.233</td><td>12.233</td><td>12.232</td></tr> <tr> <td>15</td><td>12.229</td><td>12.229</td><td>12.228</td></tr> <tr> <td>25</td><td>12.226</td><td>12.226</td><td>12.225</td></tr> <tr> <td>40</td><td>12.219</td><td>12.219</td><td>12.219</td></tr> <tr> <td>55</td><td>12.210</td><td>12.209</td><td>12.209</td></tr> <tr> <td>70</td><td>12.194</td><td>12.194</td><td>12.193</td></tr> <tr> <td>85</td><td>12.177</td><td>12.176</td><td>12.176</td></tr> <tr> <td>90</td><td>12.168</td><td>12.167</td><td>12.167</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]	-35	12.239	12.239	12.239	-20	12.237	12.237	12.237	0	12.233	12.233	12.232	15	12.229	12.229	12.228	25	12.226	12.226	12.225	40	12.219	12.219	12.219	55	12.210	12.209	12.209	70	12.194	12.194	12.193	85	12.177	12.176	12.176	90	12.168	12.167	12.167	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 66[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																				
-35	12.239	12.239	12.239																																																				
-20	12.237	12.237	12.237																																																				
0	12.233	12.233	12.232																																																				
15	12.229	12.229	12.228																																																				
25	12.226	12.226	12.225																																																				
40	12.219	12.219	12.219																																																				
55	12.210	12.209	12.209																																																				
70	12.194	12.194	12.193																																																				
85	12.177	12.176	12.176																																																				
90	12.168	12.167	12.167																																																				
—	—	—	—																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							
(注) 斜線は定格周囲温度範囲を示す。																																																							

COSEL

Model	DBS150A12																																								
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry Figure A																																							
Object	+12V12.5A																																								
1. Graph																																									
			2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-35</td><td>47</td><td>49</td> </tr> <tr> <td>-20</td><td>48</td><td>49</td> </tr> <tr> <td>0</td><td>48</td><td>50</td> </tr> <tr> <td>15</td><td>48</td><td>50</td> </tr> <tr> <td>25</td><td>48</td><td>51</td> </tr> <tr> <td>40</td><td>48</td><td>51</td> </tr> <tr> <td>55</td><td>49</td><td>52</td> </tr> <tr> <td>70</td><td>49</td><td>52</td> </tr> <tr> <td>85</td><td>49</td><td>53</td> </tr> <tr> <td>90</td><td>49</td><td>53</td> </tr> <tr> <td>--</td><td>--</td><td>--</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-35	47	49	-20	48	49	0	48	50	15	48	50	25	48	51	40	48	51	55	49	52	70	49	52	85	49	53	90	49	53	--	--	--
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-35	47	49																																							
-20	48	49																																							
0	48	50																																							
15	48	50																																							
25	48	51																																							
40	48	51																																							
55	49	52																																							
70	49	52																																							
85	49	53																																							
90	49	53																																							
--	--	--																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																									

COSEL

Model	DBS150A12																																							
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																						
Object	+12V12.5A																																							
1. Graph																																								
<p>--- □ --- Load 50%</p> <p>— △ — Load 100%</p> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 110V</p>																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>30</td><td>30</td></tr> <tr> <td>-20</td><td>20</td><td>20</td></tr> <tr> <td>0</td><td>15</td><td>15</td></tr> <tr> <td>25</td><td>10</td><td>10</td></tr> <tr> <td>45</td><td>10</td><td>10</td></tr> <tr> <td>65</td><td>10</td><td>10</td></tr> <tr> <td>85</td><td>10</td><td>10</td></tr> <tr> <td>100</td><td>10</td><td>10</td></tr> <tr> <td>--</td><td>—</td><td>—</td></tr> <tr> <td>--</td><td>—</td><td>—</td></tr> <tr> <td>--</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-40	30	30	-20	20	20	0	15	15	25	10	10	45	10	10	65	10	10	85	10	10	100	10	10	--	—	—	--	—	—	--	—	—
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-40	30	30																																						
-20	20	20																																						
0	15	15																																						
25	10	10																																						
45	10	10																																						
65	10	10																																						
85	10	10																																						
100	10	10																																						
--	—	—																																						
--	—	—																																						
--	—	—																																						


Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model	DBS150A12
Item	Time Lapse Drift 経時ドリフト
Object	+12V12.5A

1. Graph



Input Volt. 110V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	12.226
0.5	12.210
1.0	12.210
2.0	12.210
3.0	12.210
4.0	12.211
5.0	12.211
6.0	12.211
7.0	12.211
8.0	12.211



Model	DBS150A12	
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry Figure A
Object	+12V12.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 ~ 85°C

Input Voltage : 66 ~ 160V

Load Current : 0 ~ 12.5A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -20 ~ 85°C

入力電圧 : 66 ~ 160V

負荷電流 : 0 ~ 12.5A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output		Output Voltage Accuracy	
			Current [A]	Voltage [V]	Value [mV]	Ration [%]
Maximum Voltage	-20	66	0	12.243		
Minimum Voltage	85	160	12.5	12.173	±35	±0.3

COSEL





Figure B (General Electric Characteristic)
 一般電気特性

- C1 : 0.1 μ F 250V Film capacitor
- C2 : 47 μ F 250V Electric capacitor
- C3, C4 : 2200pF 250V Ceramic capacitor
- C5 : 1000 μ F 25V Electric capacitor
- C6 : 0.1 μ F 50V Film capacitor
- LF1 : 1mH 3A Common mode Choke Coil