

COSEL

TEST DATA OF DBS200B05

(280V INPUT)

Regulated DC Power Supply

Date : Apr. 16. 1999

Approved by : K. Shimano

Design Manager

Prepared by : K. Mizui

Design Engineer

コーワセル株式会社

COSEL CO., LTD.




CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Ovvervoltage Protection	11
過電圧保護	
12. Dynamic Load Responce	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雜音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 22)

COSEL

Model	DBS200B05	Temperature Testing Circuitry	25°C Figure A																															
Item	Line Regulation 静的入力変動																																	
Object	+5.0V40A																																	
1. Graph		-----□----- Load 50% -----△----- Load 100%																																
			2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>170</td><td>5.015</td><td>5.012</td></tr> <tr> <td>180</td><td>5.015</td><td>5.012</td></tr> <tr> <td>200</td><td>5.015</td><td>5.011</td></tr> <tr> <td>250</td><td>5.014</td><td>5.011</td></tr> <tr> <td>280</td><td>5.014</td><td>5.011</td></tr> <tr> <td>300</td><td>5.014</td><td>5.011</td></tr> <tr> <td>350</td><td>5.014</td><td>5.011</td></tr> <tr> <td>400</td><td>5.014</td><td>5.011</td></tr> <tr> <td>420</td><td>5.014</td><td>5.011</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	170	5.015	5.012	180	5.015	5.012	200	5.015	5.011	250	5.014	5.011	280	5.014	5.011	300	5.014	5.011	350	5.014	5.011	400	5.014	5.011	420	5.014	5.011
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
170	5.015	5.012																																
180	5.015	5.012																																
200	5.015	5.011																																
250	5.014	5.011																																
280	5.014	5.011																																
300	5.014	5.011																																
350	5.014	5.011																																
400	5.014	5.011																																
420	5.014	5.011																																
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																		

COSEL


Model	DBS200B05																																																																										
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Temperature Testing Circuitry	25°C	Figure A																																																																							
Object																																																																											
1. Graph																																																																											
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Volt. [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.003</td><td>0.002</td><td>0.002</td></tr> <tr><td>170</td><td>0.015</td><td>0.682</td><td>1.365</td></tr> <tr><td>180</td><td>0.015</td><td>0.646</td><td>1.289</td></tr> <tr><td>200</td><td>0.014</td><td>0.582</td><td>1.155</td></tr> <tr><td>250</td><td>0.013</td><td>0.468</td><td>0.922</td></tr> <tr><td>280</td><td>0.012</td><td>0.421</td><td>0.824</td></tr> <tr><td>300</td><td>0.012</td><td>0.394</td><td>0.769</td></tr> <tr><td>350</td><td>0.011</td><td>0.341</td><td>0.662</td></tr> <tr><td>400</td><td>0.011</td><td>0.303</td><td>0.582</td></tr> <tr><td>420</td><td>0.011</td><td>0.290</td><td>0.556</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Input Volt. [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.003	0.002	0.002	170	0.015	0.682	1.365	180	0.015	0.646	1.289	200	0.014	0.582	1.155	250	0.013	0.468	0.922	280	0.012	0.421	0.824	300	0.012	0.394	0.769	350	0.011	0.341	0.662	400	0.011	0.303	0.582	420	0.011	0.290	0.556	—	—	—	—	—	—	—	—	—	—	—	—
Input Volt. [V]	Input Current [A]																																																																										
	Load 0%	Load 50%	Load 100%																																																																								
0	0.000	0.000	0.000																																																																								
50	0.000	0.000	0.000																																																																								
100	0.000	0.000	0.000																																																																								
150	0.003	0.002	0.002																																																																								
170	0.015	0.682	1.365																																																																								
180	0.015	0.646	1.289																																																																								
200	0.014	0.582	1.155																																																																								
250	0.013	0.468	0.922																																																																								
280	0.012	0.421	0.824																																																																								
300	0.012	0.394	0.769																																																																								
350	0.011	0.341	0.662																																																																								
400	0.011	0.303	0.582																																																																								
420	0.011	0.290	0.556																																																																								
—	—	—	—																																																																								
—	—	—	—																																																																								
—	—	—	—																																																																								

COSEL

Model	DBS200B05
Item	Input Current (by Load Current) 入力電流 (負荷特性)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0	0.01	0.01	0.01
8	0.25	0.18	0.14
16	0.48	0.35	0.25
24	0.71	0.51	0.37
32	0.95	0.68	0.48
40	1.21	0.86	0.61
44	1.34	0.95	0.67
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

COSEL

Model	DBS200B05																																
Item	Input Power (by Load Current) 入力電力 (負荷特性)																																
Object	_____																																
1. Graph	<p>—△— Input Volt. 200V —□— Input Volt. 280V —○— Input Volt. 400V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power 200V [W]</th> <th>Input Power 280V [W]</th> <th>Input Power 400V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>8</td><td>50</td><td>52</td><td>55</td></tr> <tr><td>16</td><td>95</td><td>97</td><td>100</td></tr> <tr><td>24</td><td>142</td><td>143</td><td>146</td></tr> <tr><td>32</td><td>191</td><td>191</td><td>193</td></tr> <tr><td>40</td><td>242</td><td>241</td><td>243</td></tr> <tr><td>44</td><td>268</td><td>267</td><td>268</td></tr> </tbody> </table>	Load Current [A]	Input Power 200V [W]	Input Power 280V [W]	Input Power 400V [W]	0	0	0	0	8	50	52	55	16	95	97	100	24	142	143	146	32	191	191	193	40	242	241	243	44	268	267	268
Load Current [A]	Input Power 200V [W]	Input Power 280V [W]	Input Power 400V [W]																														
0	0	0	0																														
8	50	52	55																														
16	95	97	100																														
24	142	143	146																														
32	191	191	193																														
40	242	241	243																														
44	268	267	268																														

Temperature 25°C
 Humidity 40%RH
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0	3	3	4
8	50	52	55
16	95	97	100
24	142	143	146
32	191	191	193
40	242	241	243
44	268	267	268
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL


Model	DBS200B05	Temperature	25°C																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																																
Object																																			
1. Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (squares), Load 100% (triangles)</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>170</td> <td>85.1</td> <td>82.7</td> </tr> <tr> <td>180</td> <td>85.5</td> <td>83.3</td> </tr> <tr> <td>200</td> <td>85.6</td> <td>83.8</td> </tr> <tr> <td>250</td> <td>84.9</td> <td>83.7</td> </tr> <tr> <td>280</td> <td>84.5</td> <td>83.9</td> </tr> <tr> <td>300</td> <td>84.1</td> <td>84.1</td> </tr> <tr> <td>350</td> <td>83.0</td> <td>83.3</td> </tr> <tr> <td>400</td> <td>82.5</td> <td>83.1</td> </tr> <tr> <td>420</td> <td>82.0</td> <td>83.0</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	170	85.1	82.7	180	85.5	83.3	200	85.6	83.8	250	84.9	83.7	280	84.5	83.9	300	84.1	84.1	350	83.0	83.3	400	82.5	83.1	420	82.0	83.0
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
170	85.1	82.7																																	
180	85.5	83.3																																	
200	85.6	83.8																																	
250	84.9	83.7																																	
280	84.5	83.9																																	
300	84.1	84.1																																	
350	83.0	83.3																																	
400	82.5	83.1																																	
420	82.0	83.0																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	DBS200B05
Item	Efficiency (by Load Current) 効率(負荷特性)
Object	_____



Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
8	81.3	78.7	73.9
16	85.1	83.6	80.9
24	85.5	84.9	83.1
32	85.0	84.8	83.5
40	83.6	84.1	83.5
44	82.9	83.6	83.3
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL


Model	DBS200B05	Temperature Testing Circuitry	25°C Figure A																																															
Item	Load Regulation 靜的負荷変動																																																	
Object	+5.0V 40A																																																	
1. Graph	<p>△ Input Volt. 200V □ Input Volt. 280V ○ Input Volt. 400V</p>	2. Values																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>5.019</td><td>5.019</td><td>5.019</td></tr> <tr> <td>8</td><td>5.018</td><td>5.018</td><td>5.018</td></tr> <tr> <td>16</td><td>5.018</td><td>5.017</td><td>5.017</td></tr> <tr> <td>24</td><td>5.017</td><td>5.017</td><td>5.017</td></tr> <tr> <td>32</td><td>5.016</td><td>5.016</td><td>5.016</td></tr> <tr> <td>40</td><td>5.016</td><td>5.016</td><td>5.015</td></tr> <tr> <td>44</td><td>5.015</td><td>5.015</td><td>5.015</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	5.019	5.019	5.019	8	5.018	5.018	5.018	16	5.018	5.017	5.017	24	5.017	5.017	5.017	32	5.016	5.016	5.016	40	5.016	5.016	5.015	44	5.015	5.015	5.015	—	—	—	—	—	—	—	—	—	—	—	—	
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																															
0	5.019	5.019	5.019																																															
8	5.018	5.018	5.018																																															
16	5.018	5.017	5.017																																															
24	5.017	5.017	5.017																																															
32	5.016	5.016	5.016																																															
40	5.016	5.016	5.015																																															
44	5.015	5.015	5.015																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS200B05
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)
Object	+5.0V 40A

Temperature
Testing Circuitry 25°C
Figure A

2. Values

Load Current [A]	Ripple Output Volt. [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0	5	10
10	10	20
20	10	20
30	10	20
40	10	20
44	10	20
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。





図 リップル波形図

COSEL

Model DBS200B05

Item Ripple-Noise リップルノイズ

Object +5.0V 40A

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0	15	20
10	20	35
20	25	35
30	25	35
40	25	35
44	25	35
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図p-p値で示される。

(注)斜線は定格負荷電流範囲を示す。





図 リップルノイズ波形図

COSEL

Model	DBS200B05	Temperature Testing Circuitry 25°C Figure A																																																								
Item	Overcurrent Protection 過電流保護																																																									
Object	+5.0V 40A																																																									
1. Graph	<p>[V] Input Volt. 200 V Input Volt. 280 V Input Volt. 400 V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (Input 200V)</th> <th>Output Voltage [V] (Input 280V)</th> <th>Output Voltage [V] (Input 400V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>5.00</td><td>5.00</td><td>5.00</td></tr> <tr><td>40</td><td>5.00</td><td>5.00</td><td>5.00</td></tr> <tr><td>50</td><td>5.00</td><td>5.00</td><td>5.00</td></tr> <tr><td>55</td><td>4.50</td><td>4.50</td><td>4.50</td></tr> <tr><td>60</td><td>2.00</td><td>2.00</td><td>2.00</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 280V)	Output Voltage [V] (Input 400V)	0	5.00	5.00	5.00	40	5.00	5.00	5.00	50	5.00	5.00	5.00	55	4.50	4.50	4.50	60	2.00	2.00	2.00	2. Values																																
Load Current [A]	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 280V)	Output Voltage [V] (Input 400V)																																																							
0	5.00	5.00	5.00																																																							
40	5.00	5.00	5.00																																																							
50	5.00	5.00	5.00																																																							
55	4.50	4.50	4.50																																																							
60	2.00	2.00	2.00																																																							
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>51.40</td><td>50.85</td><td>54.60</td></tr> <tr><td>4.75</td><td>52.85</td><td>53.40</td><td>55.02</td></tr> <tr><td>4.50</td><td>53.11</td><td>53.68</td><td>55.47</td></tr> <tr><td>4.00</td><td>53.70</td><td>54.35</td><td>56.28</td></tr> <tr><td>3.50</td><td>54.31</td><td>55.13</td><td>56.99</td></tr> <tr><td>3.00</td><td>54.95</td><td>55.74</td><td>57.69</td></tr> <tr><td>2.50</td><td>55.61</td><td>56.35</td><td>58.66</td></tr> <tr><td>2.00</td><td>56.08</td><td>57.38</td><td>59.96</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	5.00	51.40	50.85	54.60	4.75	52.85	53.40	55.02	4.50	53.11	53.68	55.47	4.00	53.70	54.35	56.28	3.50	54.31	55.13	56.99	3.00	54.95	55.74	57.69	2.50	55.61	56.35	58.66	2.00	56.08	57.38	59.96	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Output Voltage [V]		Load Current [A]																																																								
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
5.00	51.40	50.85	54.60																																																							
4.75	52.85	53.40	55.02																																																							
4.50	53.11	53.68	55.47																																																							
4.00	53.70	54.35	56.28																																																							
3.50	54.31	55.13	56.99																																																							
3.00	54.95	55.74	57.69																																																							
2.50	55.61	56.35	58.66																																																							
2.00	56.08	57.38	59.96																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																										

COSEL



Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Operating Point [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-35	6.61	6.61	6.61
-20	6.54	6.54	6.54
0	6.47	6.47	6.47
15	6.47	6.47	6.47
25	6.40	6.40	6.40
40	6.40	6.40	6.40
55	6.33	6.33	6.33
70	6.33	6.33	6.33
85	6.25	6.25	6.25
90	6.25	6.25	6.25
—	—	—	—


COSEL

Model	DBS200B05	Temperature	25°C
Item	Dynamic Load Response 動的負荷變動	Testing Circuitry	Figure A
Object	+5V 40A		

Input Volt. 280 V


Cycle 1000 mS

Load Current




Min. Load (0.0A) ↔

Load 100% (40.0A)




500 mV/div




5 ms/div

Min. Load (0.0A) ↔

Load 50% (20.0A)



500 mV/div



5 ms/div

Load 10% (4.0A) ↔

Load 100% (40.0A)



500 mV/div




5 ms/div

COSEL

Model	DBS200B05
Item	Rise and Fall Time 立上り、立下り時間
Object	+5.0V 40A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		14.25	3.00	17.25	0.0	1.60	
100 %		14.75	3.00	17.75	0.0	0.80	



COSEL


Model DBS200B05

Item Ambient Temperature Drift
周囲温度変動

Object +5.0V 40A

1. Graph

△ Input Volt. 200V
□ Input Volt. 280V
○ Input Volt. 400V



Load 100%

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values


Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-35	5.107	5.107	5.107
-20	5.106	5.105	5.105
0	5.104	5.104	5.104
15	5.103	5.103	5.103
25	5.101	5.101	5.100
40	5.096	5.096	5.096
55	5.089	5.089	5.089
70	5.082	5.082	5.081
85	5.073	5.073	5.072
90	5.069	5.069	5.069
—	—	—	—

COSEL

Model	DBS200B05			
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧			
Object	+5.0V 40A			
1. Graph				
[V]				
Input Voltage	Load 50% Load 100%			
250				
200				
150				
100				
50				
0				
-50				
Ambient Temperature	[°C]			
Note: Slanted line shows the range of the rated ambient temperature.				
(注)斜線は定格周囲温度範囲を示す。				
Testing Circuitry Figure A				
2. Values				
Ambient Temp. [°C]	Input Voltage [V]			
	Load 50%	Load 100%		
-35	147	155		
-20	147	156		
0	148	158		
15	148	159		
25	148	159		
40	148	160		
55	148	161		
70	148	161		
85	148	162		
90	148	163		
—	—	—		

COSEL

Model	DBS200B05
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+5.0V 40A



(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	70	80
-20	45	45
0	25	25
25	15	15
45	15	15
65	15	15
85	20	20
100	25	25
—	—	—
—	—	—
—	—	—

COSEL

Model	DBS200B05	Temperature Testing Circuitry	25 °C Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	+5.0V 40A																								
1. Graph			2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 280V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.021</td></tr> <tr><td>0.5</td><td>5.015</td></tr> <tr><td>1.0</td><td>5.015</td></tr> <tr><td>2.0</td><td>5.015</td></tr> <tr><td>3.0</td><td>5.015</td></tr> <tr><td>4.0</td><td>5.015</td></tr> <tr><td>5.0</td><td>5.015</td></tr> <tr><td>6.0</td><td>5.015</td></tr> <tr><td>7.0</td><td>5.015</td></tr> <tr><td>8.0</td><td>5.015</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.021	0.5	5.015	1.0	5.015	2.0	5.015	3.0	5.015	4.0	5.015	5.0	5.015	6.0	5.015	7.0	5.015	8.0	5.015
Time since start [H]	Output Voltage [V]																								
0.0	5.021																								
0.5	5.015																								
1.0	5.015																								
2.0	5.015																								
3.0	5.015																								
4.0	5.015																								
5.0	5.015																								
6.0	5.015																								
7.0	5.015																								
8.0	5.015																								

COSEL

Model DBS200B05

Item Output Voltage Accuracy 定電圧精度

Object +5.0V40A

Testing Circuitry Figure A

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~85 °C

Input Voltage : 200~400 V

Load Current : 0~40 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~85 °C

入力電圧 200~400 V

負荷電流 0~40 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$\text{* 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	200	0	5.108	±19	±0.4
Minimum Voltage	85	400	40	5.070		



Model	DBS200B05	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+5.0V40A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.016	Input Volt.: 280V, Load Current:40A
Line Regulation [mV]	1	Input Volt.: 200~400V, Load Current:40A
Load Regulation [mV]	4	Input Volt.: 280V, Load Current:0~40A



Model	DBS200B05	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5.0V 40A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

Conditions

Input Voltage : 200 V
 Pulse Voltage : ±2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration: 1 min. or more
 Load : 100 %

COSEL





Figure A



COSEL





Figure C

Figure D (Line Noise Tolerance)
入力雑音耐量