



TEST DATA OF DCS1400B12

Regulated DC Power Supply
March 26, 2025

Approved by : Junichi Hatagishi
Design Manager

Prepared by : Yeongjun Lee
Design Engineer

COSEL CO.,LTD.



CONTENTS


1.Input Current (by Load Current) 1
2.Efficiency (by Load Current) 2
3.Line Regulation 3
4.Load Regulation 4
5.Ripple-Noise 4
6.Dynamic Load Response 5
7.Rise and Fall Time 6
8.Overcurrent Protection 7
9.Ambient Temperature Drift 8
10.Minimum Input Voltage for Regulated Output Voltage 8
11.Oversvoltage Protection 8
12.Figure of Testing Circuitry 9

(Final Page 9)



Model	DCS1400B12
Item	Input Current (by Load Current)
Object	+12V100A

Temperature 25°C
Testing Circuitry Figure A



2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 435[V]
0	0.048	0.035	0.024
15	0.976	0.697	0.472
30	1.900	1.370	0.902
45	2.844	2.045	1.338
60	3.803	2.730	1.780
75	4.777	3.426	2.230
90	5.766	4.133	2.686
95	6.103	4.372	2.841
100	6.439	4.612	2.995
110	7.119	5.099	3.309
--	-	-	-



<p>Model DCS1400B12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Efficiency (by Load Current)</p>																																																					
<p>Object +12V100A</p>																																																					
<p>1.Graph</p> <p> —△— Input Volt. 200V - - - □ - - - Input Volt. 280V ···○··· Input Volt. 435V </p> <p> Efficiency [%] Load Current [A] </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 435[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>15</td><td>92.4</td><td>92.4</td><td>87.7</td></tr> <tr><td>30</td><td>95.0</td><td>94.1</td><td>92.0</td></tr> <tr><td>45</td><td>95.3</td><td>94.6</td><td>93.1</td></tr> <tr><td>60</td><td>95.1</td><td>94.5</td><td>93.3</td></tr> <tr><td>75</td><td>94.6</td><td>94.2</td><td>93.2</td></tr> <tr><td>90</td><td>94.1</td><td>93.7</td><td>92.8</td></tr> <tr><td>95</td><td>93.8</td><td>93.5</td><td>92.7</td></tr> <tr><td>100</td><td>93.6</td><td>93.3</td><td>92.5</td></tr> <tr><td>110</td><td>93.1</td><td>92.9</td><td>92.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 435[V]	0	-	-	-	15	92.4	92.4	87.7	30	95.0	94.1	92.0	45	95.3	94.6	93.1	60	95.1	94.5	93.3	75	94.6	94.2	93.2	90	94.1	93.7	92.8	95	93.8	93.5	92.7	100	93.6	93.3	92.5	110	93.1	92.9	92.1	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 435[V]																																																		
0	-	-	-																																																		
15	92.4	92.4	87.7																																																		
30	95.0	94.1	92.0																																																		
45	95.3	94.6	93.1																																																		
60	95.1	94.5	93.3																																																		
75	94.6	94.2	93.2																																																		
90	94.1	93.7	92.8																																																		
95	93.8	93.5	92.7																																																		
100	93.6	93.3	92.5																																																		
110	93.1	92.9	92.1																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



COSEL																																			
Model	DCS1400B12	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V100A																																		
<p>1. Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>190</td><td>12.071</td><td>12.073</td></tr> <tr><td>200</td><td>12.071</td><td>12.073</td></tr> <tr><td>240</td><td>12.071</td><td>12.073</td></tr> <tr><td>280</td><td>12.071</td><td>12.073</td></tr> <tr><td>320</td><td>12.072</td><td>12.074</td></tr> <tr><td>380</td><td>12.072</td><td>12.074</td></tr> <tr><td>435</td><td>12.072</td><td>12.075</td></tr> <tr><td>445</td><td>12.072</td><td>12.075</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	190	12.071	12.073	200	12.071	12.073	240	12.071	12.073	280	12.071	12.073	320	12.072	12.074	380	12.072	12.074	435	12.072	12.075	445	12.072	12.075	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
190	12.071	12.073																																	
200	12.071	12.073																																	
240	12.071	12.073																																	
280	12.071	12.073																																	
320	12.072	12.074																																	
380	12.072	12.074																																	
435	12.072	12.075																																	
445	12.072	12.075																																	
--	-	-																																	



COSEL																																																					
Model	DCS1400B12	Temperature 25°C Testing Circuitry Figure A																																																			
Item	Load Regulation																																																				
Object	+12V100A																																																				
<p>1.Graph</p> <p> —△— Input Volt. 200V - - - □ - - - Input Volt. 280V - · - ○ - · - · Input Volt. 435V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 435[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>12.070</td><td>12.070</td><td>12.071</td></tr> <tr><td>15</td><td>12.071</td><td>12.071</td><td>12.071</td></tr> <tr><td>30</td><td>12.071</td><td>12.071</td><td>12.072</td></tr> <tr><td>45</td><td>12.071</td><td>12.072</td><td>12.072</td></tr> <tr><td>60</td><td>12.072</td><td>12.072</td><td>12.073</td></tr> <tr><td>75</td><td>12.072</td><td>12.072</td><td>12.073</td></tr> <tr><td>90</td><td>12.072</td><td>12.072</td><td>12.073</td></tr> <tr><td>95</td><td>12.072</td><td>12.072</td><td>12.073</td></tr> <tr><td>100</td><td>12.072</td><td>12.072</td><td>12.074</td></tr> <tr><td>110</td><td>12.073</td><td>12.073</td><td>12.074</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 435[V]	0	12.070	12.070	12.071	15	12.071	12.071	12.071	30	12.071	12.071	12.072	45	12.071	12.072	12.072	60	12.072	12.072	12.073	75	12.072	12.072	12.073	90	12.072	12.072	12.073	95	12.072	12.072	12.073	100	12.072	12.072	12.074	110	12.073	12.073	12.074	--	--	--	--
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 435[V]																																																		
0	12.070	12.070	12.071																																																		
15	12.071	12.071	12.071																																																		
30	12.071	12.071	12.072																																																		
45	12.071	12.072	12.072																																																		
60	12.072	12.072	12.073																																																		
75	12.072	12.072	12.073																																																		
90	12.072	12.072	12.073																																																		
95	12.072	12.072	12.073																																																		
100	12.072	12.072	12.074																																																		
110	12.073	12.073	12.074																																																		
--	--	--	--																																																		
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																																			
Object	+12V100A																																																				
<p>1.Graph</p> <p> Input Voltage 280V Load 100% </p> <p style="text-align: center;">50[mV/div]</p> <p style="text-align: center;">4[μs/div]</p>																																																					





Model		DCS1400B12	
Item		Dynamic Load Response	
Object		+12V100A	
		Temperature	25°C
		Testing Circuitry	Figure B

Input Volt. 280 V
Cycle 1000 ms



Response. $t_1=t_2=50\mu\text{s}$. Typ



Load 0%(0A) ←→
Load 100%(100A)



Load 50%(50A) ←→
Load 100%(100A)






Model	DCS1400B12	
Item	Rise and Fall Time	Temperature 25°C Testing Circuitry Figure A
Object	+12V100A	


1. Graph

Input Volt. 280 V



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		17.0	5.0	22.0	0.3	2.6
100 %		17.0	5.1	22.1	0.2	1.5





<p>Model DCS1400B12</p>		<p>Temperature 25°C</p>																																																								
<p>Item Overcurrent Protection</p>		<p>Testing Circuitry Figure A</p>																																																								
<p>Object +12V100A</p>																																																										
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>— Input Volt. 200V</p> <p>— Input Volt. 280V</p> <p>— Input Volt. 435V</p> </div> </div> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Hiccup mode activates when the output voltage is from 6.0 to 0V.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 435[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>103.55</td><td>103.52</td><td>103.47</td></tr> <tr><td>11.4</td><td>114.64</td><td>114.64</td><td>114.63</td></tr> <tr><td>10.8</td><td>114.64</td><td>114.63</td><td>114.63</td></tr> <tr><td>9.6</td><td>114.64</td><td>114.62</td><td>114.62</td></tr> <tr><td>8.4</td><td>114.62</td><td>114.62</td><td>114.61</td></tr> <tr><td>7.2</td><td>114.62</td><td>114.61</td><td>114.59</td></tr> <tr><td>6.0</td><td>114.61</td><td>114.60</td><td>114.58</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 435[V]	12.0	103.55	103.52	103.47	11.4	114.64	114.64	114.63	10.8	114.64	114.63	114.63	9.6	114.64	114.62	114.62	8.4	114.62	114.62	114.61	7.2	114.62	114.61	114.59	6.0	114.61	114.60	114.58	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 435[V]																																																							
12.0	103.55	103.52	103.47																																																							
11.4	114.64	114.64	114.63																																																							
10.8	114.64	114.63	114.63																																																							
9.6	114.64	114.62	114.62																																																							
8.4	114.62	114.62	114.61																																																							
7.2	114.62	114.61	114.59																																																							
6.0	114.61	114.60	114.58																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							

COSEL

COSEL		
Model	DCS1400B12	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V100A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 200V	Input Volt. 280V	Input Volt. 435V
-40	12.041	12.043	12.044
25	12.069	12.070	12.071
85	12.077	12.078	12.080

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V100A	

1.Values




Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	167	168
25	169	170
85	170	171

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+12V100A	

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 200V	Input Volt. 435V
-40	15.44	15.44
25	15.44	15.44
85	15.44	15.44



- F11 : 0505016
- L11,L12 : SCF25XV-150-1R6A010JH
- C11,C13 : 1.0uF 450V Film Capacitor
- C12 : 2.2uF 450V Film Capacitor
- CY13,CY14 : 2200pF 400V
- CY15,CY16 : 1500pF 400V
- CY21,CY22,CY23,CY24 : 0.01uF 300V (For DCS1400B65 only)