

TEST DATA OF DHS100B03

Regulated DC Power Supply
May 22, 2009

Approved by : Tatsuya Mano
Tatsuya Mano Design Manager

Prepared by : Shuuhei Sawada
Shuuhei Sawada Design Engineer

COSEL CO.,LTD.

CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	DHS100B03	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object																																																																																		
1.Graph	<p>The graph plots Input Current [A] on the y-axis (0.0 to 0.8) against Input Voltage [V] on the x-axis (0 to 500). Three curves are shown: Load 100% (triangles), Load 50% (squares), and Load 0% (circles). A slanted line indicates the rated input voltage range.</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 100% [A]</th> <th>Load 50% [A]</th> <th>Load 0% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>200</td><td>0.45</td><td>0.22</td><td>0.02</td></tr> <tr><td>250</td><td>0.32</td><td>0.18</td><td>0.02</td></tr> <tr><td>300</td><td>0.28</td><td>0.15</td><td>0.02</td></tr> <tr><td>350</td><td>0.22</td><td>0.12</td><td>0.02</td></tr> <tr><td>400</td><td>0.20</td><td>0.12</td><td>0.02</td></tr> <tr><td>450</td><td>0.18</td><td>0.10</td><td>0.02</td></tr> <tr><td>500</td><td>0.15</td><td>0.10</td><td>0.02</td></tr> </tbody> </table>			Input Voltage [V]	Load 100% [A]	Load 50% [A]	Load 0% [A]	0	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.000	0.000	0.000	200	0.45	0.22	0.02	250	0.32	0.18	0.02	300	0.28	0.15	0.02	350	0.22	0.12	0.02	400	0.20	0.12	0.02	450	0.18	0.10	0.02	500	0.15	0.10	0.02																																			
Input Voltage [V]	Load 100% [A]	Load 50% [A]	Load 0% [A]																																																																															
0	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
150	0.000	0.000	0.000																																																																															
200	0.45	0.22	0.02																																																																															
250	0.32	0.18	0.02																																																																															
300	0.28	0.15	0.02																																																																															
350	0.22	0.12	0.02																																																																															
400	0.20	0.12	0.02																																																																															
450	0.18	0.10	0.02																																																																															
500	0.15	0.10	0.02																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>170</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>180</td><td>0.022</td><td>0.231</td><td>0.467</td></tr> <tr><td>200</td><td>0.022</td><td>0.208</td><td>0.418</td></tr> <tr><td>250</td><td>0.018</td><td>0.170</td><td>0.337</td></tr> <tr><td>280</td><td>0.016</td><td>0.151</td><td>0.300</td></tr> <tr><td>300</td><td>0.013</td><td>0.144</td><td>0.284</td></tr> <tr><td>350</td><td>0.012</td><td>0.127</td><td>0.246</td></tr> <tr><td>400</td><td>0.011</td><td>0.115</td><td>0.218</td></tr> <tr><td>420</td><td>0.011</td><td>0.110</td><td>0.209</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.000	0.000	0.000	170	0.002	0.002	0.002	180	0.022	0.231	0.467	200	0.022	0.208	0.418	250	0.018	0.170	0.337	280	0.016	0.151	0.300	300	0.013	0.144	0.284	350	0.012	0.127	0.246	400	0.011	0.115	0.218	420	0.011	0.110	0.209	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
50	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
150	0.000	0.000	0.000																																																																															
170	0.002	0.002	0.002																																																																															
180	0.022	0.231	0.467																																																																															
200	0.022	0.208	0.418																																																																															
250	0.018	0.170	0.337																																																																															
280	0.016	0.151	0.300																																																																															
300	0.013	0.144	0.284																																																																															
350	0.012	0.127	0.246																																																																															
400	0.011	0.115	0.218																																																																															
420	0.011	0.110	0.209																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

COSEL

coSEL

Model	DHS100B03	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—▲— Input Volt. 200V - - - ■ - - Input Volt. 280V - - ○ - - Input Volt. 400V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>4.40</td><td>4.10</td><td>4.16</td></tr> <tr> <td>4</td><td>18.10</td><td>19.50</td><td>22.40</td></tr> <tr> <td>8</td><td>33.60</td><td>34.90</td><td>37.90</td></tr> <tr> <td>12</td><td>49.80</td><td>51.00</td><td>53.80</td></tr> <tr> <td>16</td><td>66.40</td><td>67.40</td><td>70.20</td></tr> <tr> <td>20</td><td>83.80</td><td>84.60</td><td>87.20</td></tr> <tr> <td>22</td><td>92.90</td><td>93.30</td><td>95.90</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	4.40	4.10	4.16	4	18.10	19.50	22.40	8	33.60	34.90	37.90	12	49.80	51.00	53.80	16	66.40	67.40	70.20	20	83.80	84.60	87.20	22	92.90	93.30	95.90	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	4.40	4.10	4.16																																																			
4	18.10	19.50	22.40																																																			
8	33.60	34.90	37.90																																																			
12	49.80	51.00	53.80																																																			
16	66.40	67.40	70.20																																																			
20	83.80	84.60	87.20																																																			
22	92.90	93.30	95.90																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	DHS100B03	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	_____																																		
1.Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>195</td><td>80.4</td><td>79.7</td> </tr> <tr> <td>200</td><td>80.2</td><td>79.6</td> </tr> <tr> <td>240</td><td>78.8</td><td>79.4</td> </tr> <tr> <td>280</td><td>77.5</td><td>79.0</td> </tr> <tr> <td>320</td><td>76.0</td><td>78.3</td> </tr> <tr> <td>360</td><td>74.1</td><td>77.2</td> </tr> <tr> <td>400</td><td>72.5</td><td>76.4</td> </tr> <tr> <td>420</td><td>71.6</td><td>75.9</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	80.4	79.7	200	80.2	79.6	240	78.8	79.4	280	77.5	79.0	320	76.0	78.3	360	74.1	77.2	400	72.5	76.4	420	71.6	75.9	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
195	80.4	79.7																																	
200	80.2	79.6																																	
240	78.8	79.4																																	
280	77.5	79.0																																	
320	76.0	78.3																																	
360	74.1	77.2																																	
400	72.5	76.4																																	
420	71.6	75.9																																	
--	-	-																																	
Note:	Slanted line shows the range of the rated input voltage.																																		

COSEL

Model	DHS100B03
Item	Efficiency (by Load Current)
Object	

1. Graph

Load Current [A]	Input Volt. 200V	Input Volt. 280V	Input Volt. 400V
0	-	-	-
4	73.6	68.2	59.5
8	79.4	76.2	70.1
12	80.4	78.3	74.0
16	80.3	79.1	75.7
20	79.6	79.0	76.4
22	79.1	78.7	76.5
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A


2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0	-	-	-
4	73.6	68.2	59.5
8	79.4	76.2	70.1
12	80.4	78.3	74.0
16	80.3	79.1	75.7
20	79.6	79.0	76.4
22	79.1	78.7	76.5
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	DHS100B03
Item	Line Regulation
Object	+3.3V20A

1.Graph



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
195	3.348	3.348
200	3.348	3.348
240	3.348	3.348
280	3.348	3.348
320	3.348	3.348
360	3.348	3.348
400	3.348	3.348
420	3.348	3.348
--	-	-

COSEL

Model	DHS100B03	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+3.3V20A																																																					
1.Graph	<p>—△— Input Volt. 200V - - -□-- Input Volt. 280V - · -○--- Input Volt. 400V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.350</td><td>3.350</td><td>3.350</td></tr> <tr><td>4</td><td>3.348</td><td>3.348</td><td>3.349</td></tr> <tr><td>8</td><td>3.348</td><td>3.348</td><td>3.348</td></tr> <tr><td>12</td><td>3.348</td><td>3.348</td><td>3.348</td></tr> <tr><td>16</td><td>3.348</td><td>3.348</td><td>3.348</td></tr> <tr><td>20</td><td>3.348</td><td>3.348</td><td>3.347</td></tr> <tr><td>22</td><td>3.348</td><td>3.347</td><td>3.347</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	3.350	3.350	3.350	4	3.348	3.348	3.349	8	3.348	3.348	3.348	12	3.348	3.348	3.348	16	3.348	3.348	3.348	20	3.348	3.348	3.347	22	3.348	3.347	3.347	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	3.350	3.350	3.350																																																			
4	3.348	3.348	3.349																																																			
8	3.348	3.348	3.348																																																			
12	3.348	3.348	3.348																																																			
16	3.348	3.348	3.348																																																			
20	3.348	3.348	3.347																																																			
22	3.348	3.347	3.347																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	DHS100B03	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	+3.3V20A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>10</td><td>10</td></tr> <tr><td>4</td><td>10</td><td>15</td></tr> <tr><td>8</td><td>10</td><td>15</td></tr> <tr><td>12</td><td>10</td><td>15</td></tr> <tr><td>16</td><td>15</td><td>20</td></tr> <tr><td>20</td><td>20</td><td>20</td></tr> <tr><td>22</td><td>20</td><td>20</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0	10	10	4	10	15	8	10	15	12	10	15	16	15	20	20	20	20	22	20	20	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 200 [V]	Input Volt. 400 [V]																																							
0	10	10																																							
4	10	15																																							
8	10	15																																							
12	10	15																																							
16	15	20																																							
20	20	20																																							
22	20	20																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									


COSEL

Model	DHS100B03																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V20A																																							
1.Graph																																								
<p>—▲— Input Volt. 200V ---○--- Input Volt. 400V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 200V)</th> <th>Ripple-Noise [mV] (Input Volt. 400V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>20</td><td>20</td></tr> <tr><td>5</td><td>25</td><td>25</td></tr> <tr><td>10</td><td>30</td><td>30</td></tr> <tr><td>15</td><td>30</td><td>30</td></tr> <tr><td>20</td><td>30</td><td>30</td></tr> <tr><td>22</td><td>30</td><td>30</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV] (Input Volt. 200V)	Ripple-Noise [mV] (Input Volt. 400V)	0	20	20	5	25	25	10	30	30	15	30	30	20	30	30	22	30	30																		
Load Current [A]	Ripple-Noise [mV] (Input Volt. 200V)	Ripple-Noise [mV] (Input Volt. 400V)																																						
0	20	20																																						
5	25	25																																						
10	30	30																																						
15	30	30																																						
20	30	30																																						
22	30	30																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>20</td><td>20</td></tr> <tr><td>4</td><td>25</td><td>30</td></tr> <tr><td>8</td><td>30</td><td>30</td></tr> <tr><td>12</td><td>30</td><td>30</td></tr> <tr><td>16</td><td>30</td><td>30</td></tr> <tr><td>20</td><td>30</td><td>30</td></tr> <tr><td>22</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0	20	20	4	25	30	8	30	30	12	30	30	16	30	30	20	30	30	22	30	30	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 200 [V]	Input Volt. 400 [V]																																						
0	20	20																																						
4	25	30																																						
8	30	30																																						
12	30	30																																						
16	30	30																																						
20	30	30																																						
22	30	30																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p>																																								
Fig.Complex Ripple Noise Wave Form																																								

COSEL

Model	DHS100B03
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V20A

1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	35	35
-40	35	35
-20	30	30
0	30	30
25	30	30
40	25	30
55	25	30
70	25	30
85	20	25
100	15	20
-	-	-

COSEL


Model DHS100B03

Item Ambient Temperature Drift

Object +3.3V20A

1.Graph

—△— Input Volt. 200V
 - - -□- Input Volt. 280V
 - · -○- Input Volt. 400V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-50	3.343	3.343	3.343
-40	3.344	3.344	3.343
-20	3.344	3.344	3.343
0	3.344	3.344	3.344
25	3.347	3.347	3.347
40	3.349	3.349	3.349
55	3.351	3.351	3.350
70	3.352	3.352	3.351
85	3.353	3.352	3.352
100	3.353	3.353	3.353
--	-	-	-



Model	DHS100B03	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V20A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 200 - 400V

Load Current : 0 - 20A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	100	200	0	3.356		
Minimum Voltage	-40	200	20	3.343	±7	±0.2

COSEL

Model	DHS100B03
Item	Time Lapse Drift
Object	+3.3V20A

1. Graph




Input Volt. 280V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	3.348
0.5	3.348
1.0	3.348
2.0	3.348
3.0	3.348
4.0	3.348
5.0	3.348
6.0	3.348
7.0	3.348
8.0	3.348

COSEL

coSEL


Model DHS100B03

Item Minimum Input Voltage
for Regulated Output Voltage

Object +3.3V20A

1.Graph

---□--- Load 50%
—△— Load 100%




Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-50	149	157
-40	150	158
-20	151	159
0	152	161
25	153	163
40	153	164
55	154	165
70	153	166
85	153	166
100	152	166
--	-	-

COSEL


Model	DHS100B03	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+3.3V20A																																																									
1.Graph	Input Volt. 200V Input Volt. 280V Input Volt. 400V																																																									
																																																										
	Note: Slanted line shows the range of the rated load current.																																																									
	Intermittent operation occurs when the output voltage is from 1.32V to 0V.																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>3.30</td><td>20.02</td><td>20.28</td><td>20.22</td></tr> <tr><td>3.14</td><td>24.59</td><td>24.75</td><td>25.60</td></tr> <tr><td>2.97</td><td>24.71</td><td>24.97</td><td>25.96</td></tr> <tr><td>2.64</td><td>24.96</td><td>25.42</td><td>26.20</td></tr> <tr><td>2.31</td><td>25.30</td><td>25.74</td><td>26.68</td></tr> <tr><td>1.98</td><td>25.73</td><td>26.21</td><td>27.18</td></tr> <tr><td>1.65</td><td>26.22</td><td>26.71</td><td>27.04</td></tr> <tr><td>1.32</td><td>26.74</td><td>27.33</td><td>26.96</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	3.30	20.02	20.28	20.22	3.14	24.59	24.75	25.60	2.97	24.71	24.97	25.96	2.64	24.96	25.42	26.20	2.31	25.30	25.74	26.68	1.98	25.73	26.21	27.18	1.65	26.22	26.71	27.04	1.32	26.74	27.33	26.96	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
3.30	20.02	20.28	20.22																																																							
3.14	24.59	24.75	25.60																																																							
2.97	24.71	24.97	25.96																																																							
2.64	24.96	25.42	26.20																																																							
2.31	25.30	25.74	26.68																																																							
1.98	25.73	26.21	27.18																																																							
1.65	26.22	26.71	27.04																																																							
1.32	26.74	27.33	26.96																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							

COSEL

Model DHS100B03

Item Overvoltage Protection

Object +3.3V20A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-50	5.09	5.09	5.09
-40	4.97	4.98	4.98
-20	4.97	4.98	4.98
0	4.86	4.86	4.86
25	4.74	4.74	4.74
40	4.68	4.68	4.68
55	4.56	4.56	4.56
70	4.56	4.56	4.56
85	4.44	4.44	4.44
100	4.38	4.38	4.38
--	-	-	-

COSEL





Figure A



- C1 : DHS100B24 4.7 μF
 DHS100B28 4.7 μF
 Others 10 μF
- Co : DHS100B03 2200 μF
 DHS100B05 2200 μF
 DHS100B12 470 μF
 DHS100B15 470 μF
 DHS100B24 220 μF
 DHS100B28 220 μF

Figure B