

TEST DATA OF DHS100B15

Regulated DC Power Supply
May 18, 2009

Approved by : Tatsuya Mano
Tatsuya Mano Design Manager

Prepared by : Shuuhei Sawada
Shuuhei Sawada Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)



Model		DHS100B15		Temperature		25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry		Figure A																																																																																
Object		_____																																																																																				
1. Graph				2. Values																																																																																		
<p>Legend: —△— Load 100% - - □ - - Load 50% - - ○ - - Load 0%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>170</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>180</td><td>0.030</td><td>0.324</td><td>0.616</td></tr> <tr><td>200</td><td>0.029</td><td>0.290</td><td>0.571</td></tr> <tr><td>250</td><td>0.024</td><td>0.234</td><td>0.458</td></tr> <tr><td>280</td><td>0.022</td><td>0.210</td><td>0.410</td></tr> <tr><td>300</td><td>0.018</td><td>0.199</td><td>0.385</td></tr> <tr><td>350</td><td>0.016</td><td>0.175</td><td>0.334</td></tr> <tr><td>400</td><td>0.014</td><td>0.157</td><td>0.296</td></tr> <tr><td>420</td><td>0.012</td><td>0.150</td><td>0.280</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.002	0.002	0.002	170	0.003	0.003	0.003	180	0.030	0.324	0.616	200	0.029	0.290	0.571	250	0.024	0.234	0.458	280	0.022	0.210	0.410	300	0.018	0.199	0.385	350	0.016	0.175	0.334	400	0.014	0.157	0.296	420	0.012	0.150	0.280	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																					
	Load 0%	Load 50%	Load 100%																																																																																			
0	0.000	0.000	0.000																																																																																			
50	0.000	0.000	0.000																																																																																			
100	0.000	0.000	0.000																																																																																			
150	0.002	0.002	0.002																																																																																			
170	0.003	0.003	0.003																																																																																			
180	0.030	0.324	0.616																																																																																			
200	0.029	0.290	0.571																																																																																			
250	0.024	0.234	0.458																																																																																			
280	0.022	0.210	0.410																																																																																			
300	0.018	0.199	0.385																																																																																			
350	0.016	0.175	0.334																																																																																			
400	0.014	0.157	0.296																																																																																			
420	0.012	0.150	0.280																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																						



Model		DHS100B15		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		—△— Input Volt. 200V - - - □ - - Input Volt. 280V - · - ○ - · - Input Volt. 400V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.029</td><td>0.021</td><td>0.014</td></tr> <tr><td>1.00</td><td>0.100</td><td>0.073</td><td>0.056</td></tr> <tr><td>2.00</td><td>0.182</td><td>0.133</td><td>0.103</td></tr> <tr><td>3.00</td><td>0.261</td><td>0.190</td><td>0.142</td></tr> <tr><td>4.00</td><td>0.344</td><td>0.249</td><td>0.183</td></tr> <tr><td>5.00</td><td>0.427</td><td>0.309</td><td>0.224</td></tr> <tr><td>6.00</td><td>0.512</td><td>0.368</td><td>0.267</td></tr> <tr><td>6.70</td><td>0.572</td><td>0.412</td><td>0.296</td></tr> <tr><td>7.37</td><td>0.630</td><td>0.452</td><td>0.326</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	0.029	0.021	0.014	1.00	0.100	0.073	0.056	2.00	0.182	0.133	0.103	3.00	0.261	0.190	0.142	4.00	0.344	0.249	0.183	5.00	0.427	0.309	0.224	6.00	0.512	0.368	0.267	6.70	0.572	0.412	0.296	7.37	0.630	0.452	0.326	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	0.029	0.021	0.014																																																					
1.00	0.100	0.073	0.056																																																					
2.00	0.182	0.133	0.103																																																					
3.00	0.261	0.190	0.142																																																					
4.00	0.344	0.249	0.183																																																					
5.00	0.427	0.309	0.224																																																					
6.00	0.512	0.368	0.267																																																					
6.70	0.572	0.412	0.296																																																					
7.37	0.630	0.452	0.326																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		DHS100B15		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		—△— Input Volt. 200V ---□--- Input Volt. 280V -·-○-·- Input Volt. 400V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.9</td><td>5.9</td><td>5.6</td></tr> <tr><td>1.00</td><td>20.0</td><td>20.3</td><td>22.5</td></tr> <tr><td>2.00</td><td>36.3</td><td>37.3</td><td>41.0</td></tr> <tr><td>3.00</td><td>52.2</td><td>53.3</td><td>56.9</td></tr> <tr><td>4.00</td><td>68.7</td><td>69.6</td><td>73.3</td></tr> <tr><td>5.00</td><td>85.3</td><td>86.5</td><td>89.6</td></tr> <tr><td>6.00</td><td>102.4</td><td>103.2</td><td>106.9</td></tr> <tr><td>6.70</td><td>114.3</td><td>115.3</td><td>118.7</td></tr> <tr><td>7.37</td><td>126.1</td><td>126.5</td><td>130.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	5.9	5.9	5.6	1.00	20.0	20.3	22.5	2.00	36.3	37.3	41.0	3.00	52.2	53.3	56.9	4.00	68.7	69.6	73.3	5.00	85.3	86.5	89.6	6.00	102.4	103.2	106.9	6.70	114.3	115.3	118.7	7.37	126.1	126.5	130.3	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	5.9	5.9	5.6																																																					
1.00	20.0	20.3	22.5																																																					
2.00	36.3	37.3	41.0																																																					
3.00	52.2	53.3	56.9																																																					
4.00	68.7	69.6	73.3																																																					
5.00	85.3	86.5	89.6																																																					
6.00	102.4	103.2	106.9																																																					
6.70	114.3	115.3	118.7																																																					
7.37	126.1	126.5	130.3																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model	DHS100B15
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
195	86.7	87.9
200	86.7	88.1
240	86.5	88.0
280	85.5	87.3
320	83.7	86.5
360	82.2	85.6
400	80.5	84.8
420	78.9	83.8
--	-	-



Model		DHS100B15		Temperature 25°C		
Item		Efficiency (by Load Current)		Testing Circuitry Figure A		
Object						
1. Graph		—△— Input Volt. 200V - - □ - - Input Volt. 280V - - ○ - - Input Volt. 400V		2. Values		
Efficiency [%] 	Load Current [A]		Efficiency [%]			
			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	
	0.00		-	-	-	
	1.00		75.3	74.1	67.0	
	2.00		83.1	80.8	73.5	
	3.00		86.2	84.4	79.1	
	4.00		87.4	86.2	81.8	
	5.00		88.0	86.8	83.8	
	6.00		88.0	87.4	84.3	
	6.70		88.1	87.3	84.8	
	7.37		87.8	87.6	85.0	
	--		-	-	-	
	--		-	-	-	
Note: Slanted line shows the range of the rated load current.						



COSEL																																			
Model	DHS100B15	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V6.7A																																		
<p>1. Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>195</td><td>15.020</td><td>15.019</td></tr> <tr><td>200</td><td>15.020</td><td>15.019</td></tr> <tr><td>240</td><td>15.020</td><td>15.019</td></tr> <tr><td>280</td><td>15.020</td><td>15.019</td></tr> <tr><td>320</td><td>15.020</td><td>15.020</td></tr> <tr><td>360</td><td>15.020</td><td>15.020</td></tr> <tr><td>400</td><td>15.020</td><td>15.020</td></tr> <tr><td>420</td><td>15.020</td><td>15.020</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	15.020	15.019	200	15.020	15.019	240	15.020	15.019	280	15.020	15.019	320	15.020	15.020	360	15.020	15.020	400	15.020	15.020	420	15.020	15.020	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
195	15.020	15.019																																	
200	15.020	15.019																																	
240	15.020	15.019																																	
280	15.020	15.019																																	
320	15.020	15.020																																	
360	15.020	15.020																																	
400	15.020	15.020																																	
420	15.020	15.020																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model		DHS100B15	Temperature		25°C																																																			
Item		Load Regulation	Testing Circuitry		Figure A																																																			
Object		+15V6.7A																																																						
1. Graph			2. Values																																																					
<p> —△— Input Volt. 200V ---□--- Input Volt. 280V -·-○-·- Input Volt. 400V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.030</td><td>15.030</td><td>15.032</td></tr> <tr><td>1.00</td><td>15.019</td><td>15.021</td><td>15.023</td></tr> <tr><td>2.00</td><td>15.018</td><td>15.019</td><td>15.020</td></tr> <tr><td>3.00</td><td>15.018</td><td>15.019</td><td>15.020</td></tr> <tr><td>4.00</td><td>15.019</td><td>15.019</td><td>15.020</td></tr> <tr><td>5.00</td><td>15.018</td><td>15.019</td><td>15.019</td></tr> <tr><td>6.00</td><td>15.019</td><td>15.019</td><td>15.019</td></tr> <tr><td>6.70</td><td>15.019</td><td>15.019</td><td>15.020</td></tr> <tr><td>7.37</td><td>15.019</td><td>15.019</td><td>15.019</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	15.030	15.030	15.032	1.00	15.019	15.021	15.023	2.00	15.018	15.019	15.020	3.00	15.018	15.019	15.020	4.00	15.019	15.019	15.020	5.00	15.018	15.019	15.019	6.00	15.019	15.019	15.019	6.70	15.019	15.019	15.020	7.37	15.019	15.019	15.019	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	15.030	15.030	15.032																																																					
1.00	15.019	15.021	15.023																																																					
2.00	15.018	15.019	15.020																																																					
3.00	15.018	15.019	15.020																																																					
4.00	15.019	15.019	15.020																																																					
5.00	15.018	15.019	15.019																																																					
6.00	15.019	15.019	15.019																																																					
6.70	15.019	15.019	15.020																																																					
7.37	15.019	15.019	15.019																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								




Model		DHS100B15	Temperature 25°C Testing Circuitry Figure A
Item		Dynamic Load Response	
Object		+15V6.7A	

Input Volt. 280 V
Cycle 1000 ms


Load Current 6.7A / 20µs

Min. Load (0A) ←→
Load 100% (6.7A)

500mV/div




500 µs/div




5 ms/div

Min. Load (0A) ←→
Load 50% (3.35A)

500mV/div




500 µs/div




5 ms/div

Load 10% (0.67A) ←→
Load 100% (6.7A)

500mV/div



500 µs/div




5 ms/div



Model	DHS100B15
Item	Ripple Voltage (by Load Current)
Object	+15V6.7A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.00	20	45
1.00	45	60
2.00	45	60
3.00	45	60
4.00	45	60
5.00	50	65
6.00	50	65
6.70	50	65
7.37	50	65
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form



<p>Model DHS100B15</p> <p>Item Ripple-Noise</p> <p>Object +15V6.7A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>—△— Input Volt. 200V</p> <p>-·-○-·- Input Volt. 400V</p> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>45</td></tr> <tr><td>1.00</td><td>45</td><td>60</td></tr> <tr><td>2.00</td><td>45</td><td>60</td></tr> <tr><td>3.00</td><td>45</td><td>60</td></tr> <tr><td>4.00</td><td>45</td><td>60</td></tr> <tr><td>5.00</td><td>50</td><td>65</td></tr> <tr><td>6.00</td><td>50</td><td>65</td></tr> <tr><td>6.70</td><td>50</td><td>65</td></tr> <tr><td>7.37</td><td>50</td><td>65</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	20	45	1.00	45	60	2.00	45	60	3.00	45	60	4.00	45	60	5.00	50	65	6.00	50	65	6.70	50	65	7.37	50	65	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 200 [V]	Input Volt. 400 [V]																																						
0.00	20	45																																						
1.00	45	60																																						
2.00	45	60																																						
3.00	45	60																																						
4.00	45	60																																						
5.00	50	65																																						
6.00	50	65																																						
6.70	50	65																																						
7.37	50	65																																						
--	-	-																																						
--	-	-																																						



COSEL																																								
Model	DHS100B15																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+15V6.7A																																							
<p>1.Graph</p> <p style="text-align: center;">Input Volt. 280V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>85</td><td>85</td></tr> <tr><td>-40</td><td>85</td><td>85</td></tr> <tr><td>-20</td><td>85</td><td>85</td></tr> <tr><td>0</td><td>75</td><td>75</td></tr> <tr><td>25</td><td>60</td><td>60</td></tr> <tr><td>40</td><td>60</td><td>60</td></tr> <tr><td>55</td><td>60</td><td>60</td></tr> <tr><td>70</td><td>60</td><td>60</td></tr> <tr><td>85</td><td>60</td><td>60</td></tr> <tr><td>100</td><td>50</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-50	85	85	-40	85	85	-20	85	85	0	75	75	25	60	60	40	60	60	55	60	60	70	60	60	85	60	60	100	50	50	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-50	85	85																																						
-40	85	85																																						
-20	85	85																																						
0	75	75																																						
25	60	60																																						
40	60	60																																						
55	60	60																																						
70	60	60																																						
85	60	60																																						
100	50	50																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



COSEL																																																						
Model	DHS100B15																																																					
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+15V6.7A																																																					
1.Graph	<p> </p> <p> △ Input Volt. 200V □ Input Volt. 280V ○ Input Volt. 400V </p>	2.Values																																																				
	<p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-50</td><td>14.937</td><td>14.939</td><td>14.943</td></tr> <tr><td>-40</td><td>14.952</td><td>14.954</td><td>14.958</td></tr> <tr><td>-20</td><td>14.980</td><td>14.981</td><td>14.984</td></tr> <tr><td>0</td><td>15.001</td><td>15.001</td><td>15.004</td></tr> <tr><td>25</td><td>15.018</td><td>15.019</td><td>15.019</td></tr> <tr><td>40</td><td>15.022</td><td>15.022</td><td>15.022</td></tr> <tr><td>55</td><td>15.026</td><td>15.026</td><td>15.026</td></tr> <tr><td>70</td><td>15.026</td><td>15.025</td><td>15.023</td></tr> <tr><td>85</td><td>15.023</td><td>15.023</td><td>15.021</td></tr> <tr><td>100</td><td>15.020</td><td>15.020</td><td>15.019</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-50	14.937	14.939	14.943	-40	14.952	14.954	14.958	-20	14.980	14.981	14.984	0	15.001	15.001	15.004	25	15.018	15.019	15.019	40	15.022	15.022	15.022	55	15.026	15.026	15.026	70	15.026	15.025	15.023	85	15.023	15.023	15.021	100	15.020	15.020	15.019	--	-	-	-	
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
-50	14.937	14.939	14.943																																																			
-40	14.952	14.954	14.958																																																			
-20	14.980	14.981	14.984																																																			
0	15.001	15.001	15.004																																																			
25	15.018	15.019	15.019																																																			
40	15.022	15.022	15.022																																																			
55	15.026	15.026	15.026																																																			
70	15.026	15.025	15.023																																																			
85	15.023	15.023	15.021																																																			
100	15.020	15.020	15.019																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



COSEL		
Model	DHS100B15	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+15V6.7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 200 - 400V

Load Current : 0 - 6.7A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	200	0	15.042	±45	±0.3
Minimum Voltage	-40	200	6.7	14.952		




COSEL																								
Model	DHS100B15	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+15V6.7A																							
1.Graph		2.Values																						
<p style="text-align: center;">Time [H]</p> <p>Input Volt. 280V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.019</td></tr> <tr><td>0.5</td><td>15.019</td></tr> <tr><td>1.0</td><td>15.019</td></tr> <tr><td>2.0</td><td>15.019</td></tr> <tr><td>3.0</td><td>15.019</td></tr> <tr><td>4.0</td><td>15.019</td></tr> <tr><td>5.0</td><td>15.019</td></tr> <tr><td>6.0</td><td>15.019</td></tr> <tr><td>7.0</td><td>15.019</td></tr> <tr><td>8.0</td><td>15.019</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.019	0.5	15.019	1.0	15.019	2.0	15.019	3.0	15.019	4.0	15.019	5.0	15.019	6.0	15.019	7.0	15.019	8.0	15.019
Time since start [H]	Output Voltage [V]																							
0.0	15.019																							
0.5	15.019																							
1.0	15.019																							
2.0	15.019																							
3.0	15.019																							
4.0	15.019																							
5.0	15.019																							
6.0	15.019																							
7.0	15.019																							
8.0	15.019																							




Model	DHS100B15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V6.7A		

1. Graph



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
	50 %	26.3	4.0	30.3	1.0	19.2
	100 %	26.3	4.8	31.1	0.0	0.0





COSEL																																								
Model	DHS100B15																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+15V6.7A																																							
<p>1. Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>164</td><td>170</td></tr> <tr><td>-40</td><td>164</td><td>169</td></tr> <tr><td>-20</td><td>165</td><td>171</td></tr> <tr><td>0</td><td>167</td><td>174</td></tr> <tr><td>25</td><td>169</td><td>176</td></tr> <tr><td>40</td><td>170</td><td>177</td></tr> <tr><td>55</td><td>171</td><td>179</td></tr> <tr><td>70</td><td>170</td><td>178</td></tr> <tr><td>85</td><td>171</td><td>178</td></tr> <tr><td>100</td><td>170</td><td>178</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	164	170	-40	164	169	-20	165	171	0	167	174	25	169	176	40	170	177	55	171	179	70	170	178	85	171	178	100	170	178	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-50	164	170																																						
-40	164	169																																						
-20	165	171																																						
0	167	174																																						
25	169	176																																						
40	170	177																																						
55	171	179																																						
70	170	178																																						
85	171	178																																						
100	170	178																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model		DHS100B15	Temperature		25°C																																																							
Item		Overcurrent Protection	Testing Circuitry		Figure A																																																							
Object		+15V6.7A																																																										
1. Graph			2. Values																																																									
<p>Legend: ——— Input Volt. 200V ——— Input Volt. 280V ——— Input Volt. 400V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>6.71</td><td>6.70</td><td>6.73</td></tr> <tr><td>14.3</td><td>8.25</td><td>8.41</td><td>8.82</td></tr> <tr><td>13.5</td><td>8.28</td><td>8.47</td><td>8.89</td></tr> <tr><td>12.0</td><td>8.39</td><td>8.64</td><td>9.07</td></tr> <tr><td>10.5</td><td>8.53</td><td>8.81</td><td>9.22</td></tr> <tr><td>9.0</td><td>8.69</td><td>8.98</td><td>9.35</td></tr> <tr><td>7.5</td><td>8.86</td><td>9.15</td><td>9.52</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	15.0	6.71	6.70	6.73	14.3	8.25	8.41	8.82	13.5	8.28	8.47	8.89	12.0	8.39	8.64	9.07	10.5	8.53	8.81	9.22	9.0	8.69	8.98	9.35	7.5	8.86	9.15	9.52	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																									
15.0	6.71	6.70	6.73																																																									
14.3	8.25	8.41	8.82																																																									
13.5	8.28	8.47	8.89																																																									
12.0	8.39	8.64	9.07																																																									
10.5	8.53	8.81	9.22																																																									
9.0	8.69	8.98	9.35																																																									
7.5	8.86	9.15	9.52																																																									
--	-	-	-																																																									
--	-	-	-																																																									
--	-	-	-																																																									
--	-	-	-																																																									
--	-	-	-																																																									
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 7V to 0V.</p>																																																												



COSEL																																																						
Model	DHS100B15	Testing Circuitry Figure A																																																				
Item	Overvoltage Protection																																																					
Object	+15V6.7A																																																					
1.Graph	<p> </p> <p> △ Input Volt. 200V □ Input Volt. 280V ○ Input Volt. 400V </p>	2.Values																																																				
<p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p>		<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-50</td><td>18.33</td><td>18.33</td><td>18.33</td></tr> <tr><td>-40</td><td>18.48</td><td>18.47</td><td>18.47</td></tr> <tr><td>-20</td><td>18.69</td><td>18.69</td><td>18.69</td></tr> <tr><td>0</td><td>18.97</td><td>18.97</td><td>18.96</td></tr> <tr><td>25</td><td>19.24</td><td>19.25</td><td>19.24</td></tr> <tr><td>40</td><td>19.46</td><td>19.46</td><td>19.46</td></tr> <tr><td>55</td><td>19.67</td><td>19.67</td><td>19.67</td></tr> <tr><td>70</td><td>19.81</td><td>19.81</td><td>19.81</td></tr> <tr><td>85</td><td>20.02</td><td>20.02</td><td>20.02</td></tr> <tr><td>100</td><td>20.16</td><td>20.16</td><td>20.16</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-50	18.33	18.33	18.33	-40	18.48	18.47	18.47	-20	18.69	18.69	18.69	0	18.97	18.97	18.96	25	19.24	19.25	19.24	40	19.46	19.46	19.46	55	19.67	19.67	19.67	70	19.81	19.81	19.81	85	20.02	20.02	20.02	100	20.16	20.16	20.16	--	-	-	-
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
-50	18.33	18.33	18.33																																																			
-40	18.48	18.47	18.47																																																			
-20	18.69	18.69	18.69																																																			
0	18.97	18.97	18.96																																																			
25	19.24	19.25	19.24																																																			
40	19.46	19.46	19.46																																																			
55	19.67	19.67	19.67																																																			
70	19.81	19.81	19.81																																																			
85	20.02	20.02	20.02																																																			
100	20.16	20.16	20.16																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						





Figure A



- C1 : DHS100B24 4.7uF
- DHS100B28 4.7uF
- Others 10uF
- Co : DHS100B03 2200uF
- DHS100B05 2200uF
- DHS100B12 470uF
- DHS100B15 470uF
- DHS100B24 220uF
- DHS100B28 220uF

Figure B