



**FETA3000BC series Reliability test results**

May 8, 2023  
New Product Development Dept.2

Approved : Takashi Yamamine

Prepared : Masahiro Miyake

No.	Test Item	Testing conditions	Conditions of acceptability	Number of samples	Number of failures
1	Heat cycle test	(1) - 40°C to 125°C 30minutes each (2) 800 cycles	(1)No degradation of electric characteristics after test. (2)No crack at solder joint.	1	0
2	High temperature/ High humidity bias test	(1) Ta = 85°C, RH = 85% (2) At rated input (3) Load 0% (4) 1000 hours	(1)No degradation of electric characteristics after test.	1	0
3	Vibration test	(1) f = 10 - 55Hz, 19.6 m/s <sup>2</sup> (2G) (2) 3 minutes period (3) 60 minutes along X, Y and Z axis	(1)No degradation of electric characteristics after test. (2)No crack at solder joint. (3)No mechanical damage of appearance.	3	0
4	Impact test	(1) 196.1 m/s <sup>2</sup> (20G), 11 ms (2) Once each X, Y and Z axis	(1)No degradation of electric characteristics after test. (2)No crack at solder joint. (3)No thermal damage of appearance.	3	0
5	Electrostatic discharge immunity test	(1) Applied voltage ±8kV (2) At rated input and load	(1)No protection circuit fail. (2)No output voltage drop with control circuit fail. (3)No function fail.	1	0