

# TEST DATA OF GHA700F-56-J1

Regulated DC Power Supply  
February 1, 2023

Approved by : \_\_\_\_\_  
Jun Uchida  
Design Manager

Prepared by : \_\_\_\_\_  
Kasumi Izumi  
Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Efficiency (by Load Current) . . . . .	2
3.Power Factor (by Load Current) . . . . .	3
4.Inrush Current . . . . .	4
5.Leakage Current . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Ripple-Noise . . . . .	7
9.Dynamic Load Response . . . . .	8
10.Rise and Fall Time . . . . .	9
11.Hold-Up Time . . . . .	10
12.Instantaneous Interruption Compensation . . . . .	11
13.Overcurrent Protection . . . . .	12
14.Ambient Temperature Drift . . . . .	13
15.Minimum Input Voltage for Regulated Output Voltage . . . . .	13
16.Overvoltage Protection . . . . .	13
17.Figure of Testing Circuitry . . . . .	14

(Final Page 15)

**COSEL**


Model	GHA700F-56-J1																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 115V</li> <li>Input Volt. 230V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.105</td><td>0.103</td><td>0.135</td></tr> <tr><td>2.50</td><td>1.503</td><td>1.316</td><td>0.781</td></tr> <tr><td>5.00</td><td>3.013</td><td>2.588</td><td>1.380</td></tr> <tr><td>7.50</td><td>4.540</td><td>3.920</td><td>1.995</td></tr> <tr><td>10.00</td><td>6.090</td><td>5.260</td><td>2.630</td></tr> <tr><td>12.50</td><td>-</td><td>6.620</td><td>3.282</td></tr> <tr><td>13.75</td><td>-</td><td>7.320</td><td>3.620</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.105	0.103	0.135	2.50	1.503	1.316	0.781	5.00	3.013	2.588	1.380	7.50	4.540	3.920	1.995	10.00	6.090	5.260	2.630	12.50	-	6.620	3.282	13.75	-	7.320	3.620	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.105	0.103	0.135																																																			
2.50	1.503	1.316	0.781																																																			
5.00	3.013	2.588	1.380																																																			
7.50	4.540	3.920	1.995																																																			
10.00	6.090	5.260	2.630																																																			
12.50	-	6.620	3.282																																																			
13.75	-	7.320	3.620																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	GHA700F-56-J1			
Item	Efficiency (by Load Current)	Temperature 25°C	Testing Circuitry Figure A	
Object	<u>  </u>			
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 115V</li> <li>Input Volt. 230V</li> </ul> <p>Efficiency [%]</p> <p>Load Current [A]</p>			
2.Values	Load Current [A]	Efficiency [%]		
		Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	-	-	-	-
2.50	93.6	93.9	95.4	
5.00	93.6	94.5	96.1	
7.50	93.2	94.0	96.2	
10.00	92.5	93.4	95.8	
12.50	-	92.7	95.5	
13.75	-	92.2	95.2	
--	-	-	-	-
--	-	-	-	-
--	-	-	-	-
--	-	-	-	-




Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	GHA700F-56-J1																																																					
Item	Power Factor (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p style="text-align: center;"> <span style="display: inline-block; width: 1em; height: 1em; vertical-align: middle;"></span> Input Volt. 100V  <span style="display: inline-block; width: 1em; height: 1em; vertical-align: middle; border: 1px dashed black;"></span> Input Volt. 115V  <span style="display: inline-block; width: 1em; height: 1em; vertical-align: middle; border: 1px dashed black; border-radius: 50%;"></span> Input Volt. 230V         </p>  <p>Note: Slanted line shows the range of the rated load current.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.402</td><td>0.327</td><td>0.093</td></tr> <tr><td>2.50</td><td>0.982</td><td>0.972</td><td>0.807</td></tr> <tr><td>5.00</td><td>0.988</td><td>0.991</td><td>0.912</td></tr> <tr><td>7.50</td><td>0.991</td><td>0.989</td><td>0.948</td></tr> <tr><td>10.00</td><td>0.993</td><td>0.990</td><td>0.965</td></tr> <tr><td>12.50</td><td>-</td><td>0.991</td><td>0.971</td></tr> <tr><td>13.75</td><td>-</td><td>0.992</td><td>0.971</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.402	0.327	0.093	2.50	0.982	0.972	0.807	5.00	0.988	0.991	0.912	7.50	0.991	0.989	0.948	10.00	0.993	0.990	0.965	12.50	-	0.991	0.971	13.75	-	0.992	0.971	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.402	0.327	0.093																																																			
2.50	0.982	0.972	0.807																																																			
5.00	0.988	0.991	0.912																																																			
7.50	0.991	0.989	0.948																																																			
10.00	0.993	0.990	0.965																																																			
12.50	-	0.991	0.971																																																			
13.75	-	0.992	0.971																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

**COSEL**

Model	GHA700F-56-J1	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	_____		





Model	GHA700F-56-J1	Temperature Testing Circuitry	25°C Figure C	
Item	Leakage Current			
Object	_____			

## 1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	240 [V]	264 [V]	
DEN-AN	Figure C-1	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.24	0.26	Stand by
IEC62368-1	Figure C-2	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.24	0.25	Stand by
	Figure C-3	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.23	0.26	Stand by
IEC60601-1	Figure C-4	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.24	0.26	Stand by

The value for "One of phases" is the reference value only.

## 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	GHA700F-56-J1
Item	Line Regulation
Object	+56V12.5A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values



Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	56.253	56.246
100	56.253	56.247
115	56.254	56.248
200	56.254	56.249
230	56.254	56.251
264	56.255	56.252
280	56.256	56.252
--	-	-
--	-	-

※1: Load 75%

※2: Load 87.5%

Note: Slanted line shows the range of the rated input voltage.



**COSEL**

Model	GHA700F-56-J1	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+56V12.5A																																																					
1.Graph	<p>—△— Input Volt. 100V        - - -□- Input Volt. 115V        - - -○- Input Volt. 230V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>56.266</td><td>56.263</td><td>56.257</td></tr> <tr> <td>2.50</td><td>56.262</td><td>56.258</td><td>56.253</td></tr> <tr> <td>5.00</td><td>56.260</td><td>56.255</td><td>56.252</td></tr> <tr> <td>7.50</td><td>56.257</td><td>56.252</td><td>56.251</td></tr> <tr> <td>10.00</td><td>56.256</td><td>56.251</td><td>56.249</td></tr> <tr> <td>12.50</td><td>-</td><td>56.248</td><td>56.247</td></tr> <tr> <td>13.75</td><td>-</td><td>56.247</td><td>56.245</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	56.266	56.263	56.257	2.50	56.262	56.258	56.253	5.00	56.260	56.255	56.252	7.50	56.257	56.252	56.251	10.00	56.256	56.251	56.249	12.50	-	56.248	56.247	13.75	-	56.247	56.245	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	56.266	56.263	56.257																																																			
2.50	56.262	56.258	56.253																																																			
5.00	56.260	56.255	56.252																																																			
7.50	56.257	56.252	56.251																																																			
10.00	56.256	56.251	56.249																																																			
12.50	-	56.248	56.247																																																			
13.75	-	56.247	56.245																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+56V12.5A	Testing Circuitry	Figure B																																																			
1.Graph	<p>Input Voltage 230V        Load 100%</p> 																																																					

**COSEL**

Model	GHA700F-56-J1	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+56V12.5A		

Input Volt. 115 V  
 Cycle 1000 ms

Response.  $t_1=t_2=50\mu\text{s}$ . Typ

Load 0%(0A)  $\longleftrightarrow$   
 Load 100%(12.5A)

500[mV/div]

10[ms/div]

10[ms/div]

Load 50%(6.25A)  $\longleftrightarrow$   
 Load 100%(12.5A)

500[mV/div]


10[ms/div]

10[ms/div]

**COSEL**


Model	GHA700F-56-J1	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+56V12.5A		

## 1. Graph



## 2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
115 V		460.5	5.0	465.5	13.8	2.3	
230 V		460.5	5.0	465.5	13.8	2.2	



**COSEL**

Model	GHA700F-56-J1																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+56V12.5A																																	
1. Graph																																		
<p>Graph showing Hold-Up Time [ms] vs Input Voltage [V]. The Y-axis is logarithmic from 1 to 1000 ms. The X-axis ranges from 50 to 300 V. Two series are shown: Load 50% (dashed line with squares) and Load 100% (solid line with triangles). Both series show a minimum hold-up time around 200-250V. A slanted line indicates the rated input voltage range.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>27</td> <td>14 ※1</td> </tr> <tr> <td>100</td> <td>27</td> <td>14 ※2</td> </tr> <tr> <td>115</td> <td>27</td> <td>14</td> </tr> <tr> <td>200</td> <td>27</td> <td>13</td> </tr> <tr> <td>230</td> <td>27</td> <td>14</td> </tr> <tr> <td>264</td> <td>27</td> <td>14</td> </tr> <tr> <td>280</td> <td>27</td> <td>14</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	27	14 ※1	100	27	14 ※2	115	27	14	200	27	13	230	27	14	264	27	14	280	27	14	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
85	27	14 ※1																																
100	27	14 ※2																																
115	27	14																																
200	27	13																																
230	27	14																																
264	27	14																																
280	27	14																																
--	-	-																																
--	-	-																																
※1: Load 75% ※2: Load 87.5%																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**

Model	GHA700F-56-J1																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+56V12.5A																																																					
1.Graph																																																						
<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 115V</li> <li>Input Volt. 230V</li> </ul>			2.Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>55</td><td>60</td><td>60</td></tr> <tr><td>5.00</td><td>32</td><td>32</td><td>32</td></tr> <tr><td>7.50</td><td>21</td><td>21</td><td>21</td></tr> <tr><td>10.00</td><td>15</td><td>15</td><td>16</td></tr> <tr><td>12.50</td><td>-</td><td>12</td><td>12</td></tr> <tr><td>13.75</td><td>-</td><td>11</td><td>11</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	2.50	55	60	60	5.00	32	32	32	7.50	21	21	21	10.00	15	15	16	12.50	-	12	12	13.75	-	11	11	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
2.50	55	60	60																																																			
5.00	32	32	32																																																			
7.50	21	21	21																																																			
10.00	15	15	16																																																			
12.50	-	12	12																																																			
13.75	-	11	11																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

Model	GHA700F-56-J1		
Item	Overcurrent Protection	Temperature	25°C
Object	+56V12.5A	Testing Circuitry	Figure A
1.Graph			
Note: Slanted line shows the range of the rated load current.			
Overcurrent protection is Hiccup mode.			
2.Values			
Output Voltage [V]	Load Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
56	15.01	15.09	15.09
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	GHA700F-56-J1	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+56V12.5A	

## 1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 115V	Input Volt. 230V
-20	55.975	55.987	56.011
25	56.243	56.248	56.265
50	56.338	56.341	56.353

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A	
Object	+56V12.5A		

## 1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	76	77
25	76	77
50	76	77

Item	Overvoltage Protection	Testing Circuitry Figure A	
Object	+56V12.5A		

## 1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 115V	Input Volt. 230V
-20	72.40	72.40
25	72.69	72.69
50	72.87	72.87

COSEL




Figure A




Figure B

$$C1 = 0.1 \mu F \\ (\text{Ceramic capacitor})$$

$$C2 = 22 \mu F \\ (\text{Electrolytic capacitor})$$




Figure C-1 ( DEN-AN )

**COSEL**




Figure C-2 ( IEC62368-1 refer to IEC60990 Fig.4 )




Figure C-3 ( IEC62368-1 refer to IEC60990 Fig.5 )




Figure C-4 ( IEC60601-1 )