



TEST DATA OF HFA3500TF-48

Regulated DC Power Supply

Approved by : Takashi Yamamine
Design Manager

Prepared by : Yusuke Sasaki
Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Efficiency (by Load Current)	2
3. Power Factor (by Load Current)	3
4. Inrush Current	4
5. Leakage Current	5
6. Line Regulation	6
7. Load Regulation	7
8. Ripple-Noise	7
9. Dynamic Load Response	8
10. Rise and Fall Time	9
11. Hold-Up Time	10
12. Instantaneous Interruption Compensation	11
13. Overcurrent Protection	12
14. Ambient Temperature Drift	13
15. Minimum Input Voltage for Regulated Output Voltage	13
16. Overvoltage Protection	13
17. Figure of Testing Circuitry	14

(Final Page 15)

coSEL

Model	HFA3500TF-48	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	+48V73A																																																					
1.Graph		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Voltage 200[V]</th> <th>Input Voltage 400[V]</th> <th>Input Voltage 480[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.126</td><td>0.116</td><td>0.109</td></tr> <tr><td>10.0</td><td>1.739</td><td>0.909</td><td>0.794</td></tr> <tr><td>20.0</td><td>3.274</td><td>1.662</td><td>1.421</td></tr> <tr><td>30.0</td><td>4.729</td><td>2.375</td><td>2.017</td></tr> <tr><td>40.0</td><td>6.288</td><td>3.143</td><td>2.679</td></tr> <tr><td>50.0</td><td>7.876</td><td>3.932</td><td>3.354</td></tr> <tr><td>60.0</td><td>9.474</td><td>4.723</td><td>4.018</td></tr> <tr><td>70.0</td><td>11.098</td><td>5.523</td><td>4.683</td></tr> <tr><td>73.0</td><td>11.599</td><td>5.764</td><td>4.887</td></tr> <tr><td>80.3</td><td>12.813</td><td>6.350</td><td>5.375</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]	0.0	0.126	0.116	0.109	10.0	1.739	0.909	0.794	20.0	3.274	1.662	1.421	30.0	4.729	2.375	2.017	40.0	6.288	3.143	2.679	50.0	7.876	3.932	3.354	60.0	9.474	4.723	4.018	70.0	11.098	5.523	4.683	73.0	11.599	5.764	4.887	80.3	12.813	6.350	5.375	-	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]																																																			
0.0	0.126	0.116	0.109																																																			
10.0	1.739	0.909	0.794																																																			
20.0	3.274	1.662	1.421																																																			
30.0	4.729	2.375	2.017																																																			
40.0	6.288	3.143	2.679																																																			
50.0	7.876	3.932	3.354																																																			
60.0	9.474	4.723	4.018																																																			
70.0	11.098	5.523	4.683																																																			
73.0	11.599	5.764	4.887																																																			
80.3	12.813	6.350	5.375																																																			
-	-	-	-																																																			

Note: Hatched line shows the range of the rated load current.

coSEL

Model	HFA3500TF-48	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	+48V73A																																																					
1.Graph		2.Values																																																				
<p>Efficiency [%]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — ▲ — Input Voltage 200V - - ■ - - Input Voltage 400V - · ○ - - Input Voltage 480V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Voltage 200[V]</th> <th>Input Voltage 400[V]</th> <th>Input Voltage 480[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>10.0</td><td>86.5</td><td>87.3</td><td>87.6</td></tr> <tr> <td>20.0</td><td>90.1</td><td>90.8</td><td>90.9</td></tr> <tr> <td>30.0</td><td>92.9</td><td>94.1</td><td>94.3</td></tr> <tr> <td>40.0</td><td>93.0</td><td>94.0</td><td>94.3</td></tr> <tr> <td>50.0</td><td>92.8</td><td>94.0</td><td>94.2</td></tr> <tr> <td>60.0</td><td>92.6</td><td>94.0</td><td>94.2</td></tr> <tr> <td>70.0</td><td>92.3</td><td>93.8</td><td>94.1</td></tr> <tr> <td>73.0</td><td>92.2</td><td>93.7</td><td>94.0</td></tr> <tr> <td>80.3</td><td>91.9</td><td>93.5</td><td>93.8</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]	0.0	-	-	-	10.0	86.5	87.3	87.6	20.0	90.1	90.8	90.9	30.0	92.9	94.1	94.3	40.0	93.0	94.0	94.3	50.0	92.8	94.0	94.2	60.0	92.6	94.0	94.2	70.0	92.3	93.8	94.1	73.0	92.2	93.7	94.0	80.3	91.9	93.5	93.8	-	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]																																																			
0.0	-	-	-																																																			
10.0	86.5	87.3	87.6																																																			
20.0	90.1	90.8	90.9																																																			
30.0	92.9	94.1	94.3																																																			
40.0	93.0	94.0	94.3																																																			
50.0	92.8	94.0	94.2																																																			
60.0	92.6	94.0	94.2																																																			
70.0	92.3	93.8	94.1																																																			
73.0	92.2	93.7	94.0																																																			
80.3	91.9	93.5	93.8																																																			
-	-	-	-																																																			




Note: Hatched line shows the range of the rated load current.

COSEL

Model	HFA3500TF-48	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	+48V73A																																																					
1.Graph		2.Values																																																				
<p>1. Graph</p> <ul style="list-style-type: none"> — ▲ — Input Voltage 200V - - - ■ - - Input Voltage 400V - · - ○ - - Input Voltage 480V <p>Power Factor</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Voltage 200[V]</th> <th>Input Voltage 400[V]</th> <th>Input Voltage 480[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.602</td><td>0.319</td><td>0.252</td></tr> <tr><td>10.0</td><td>0.953</td><td>0.913</td><td>0.870</td></tr> <tr><td>20.0</td><td>0.955</td><td>0.941</td><td>0.918</td></tr> <tr><td>30.0</td><td>0.956</td><td>0.946</td><td>0.929</td></tr> <tr><td>40.0</td><td>0.957</td><td>0.949</td><td>0.929</td></tr> <tr><td>50.0</td><td>0.957</td><td>0.949</td><td>0.926</td></tr> <tr><td>60.0</td><td>0.957</td><td>0.948</td><td>0.927</td></tr> <tr><td>70.0</td><td>0.957</td><td>0.947</td><td>0.928</td></tr> <tr><td>73.0</td><td>0.957</td><td>0.947</td><td>0.929</td></tr> <tr><td>80.3</td><td>0.958</td><td>0.947</td><td>0.930</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]	0.0	0.602	0.319	0.252	10.0	0.953	0.913	0.870	20.0	0.955	0.941	0.918	30.0	0.956	0.946	0.929	40.0	0.957	0.949	0.929	50.0	0.957	0.949	0.926	60.0	0.957	0.948	0.927	70.0	0.957	0.947	0.928	73.0	0.957	0.947	0.929	80.3	0.958	0.947	0.930	-	-	-	-
Load Current [A]	Power Factor																																																					
	Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]																																																			
0.0	0.602	0.319	0.252																																																			
10.0	0.953	0.913	0.870																																																			
20.0	0.955	0.941	0.918																																																			
30.0	0.956	0.946	0.929																																																			
40.0	0.957	0.949	0.929																																																			
50.0	0.957	0.949	0.926																																																			
60.0	0.957	0.948	0.927																																																			
70.0	0.957	0.947	0.928																																																			
73.0	0.957	0.947	0.929																																																			
80.3	0.958	0.947	0.930																																																			
-	-	-	-																																																			
<p>Note: Hatched line shows the range of the rated load current.</p>																																																						

COSEL

Model	HFA3500TF-48
Item	Inrush Current
Object	+48V73A

Temperature 25°C
Testing Circuitry Figure A

※ The specification of the primary inrush current means that the surge current to a built-in noise filter (0.2msec or less : waveform ③) is excluded.



Model	HFA3500TF-48
Item	Leakage Current
Object	+48V73A

Temperature 25°C
Testing Circuitry Figure B

1. Results

Standards	Testing Circuitry	Phase	Input Voltage			Note
			200[V]	400[V]	480[V]	
IEC62368-1	FigureB-1	Full phase	0.80	1.80	2.00	
		Phase loss	0.01	0.01	0.01	
	FigureB-2	Full phase	0.80	1.80	2.00	
		Phase loss	0.01	0.01	0.01	

2. Condition


Leakage current value is concluded after measuring all phase of AC input and choosing the largest one.

COSEL

Model	HFA3500TF-48
Item	Line Regulation
Object	+48V73A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
180	48.242	48.232
200	48.247	48.235
264	48.245	48.231
400	48.250	48.237
480	48.246	48.236
528	48.248	48.234
-	-	-
-	-	-
-	-	-

Note: Hatched line shows the range of the rated input voltage.


COSEL

Model	HFA3500TF-48
Item	Load Regulation
Object	+48V73A

Temperature 25°C
Testing Circuitry Figure A

1.Graph

— ▲ — Input Voltage 200V
 - - - □ - - Input Voltage 400V
 - - ○ - - Input Voltage 480V



Note: Hatched line shows the range of the rated load current.

2.Values


Load Current [A]	Output Voltage [V]		
	Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]
0.0	48.242	48.241	48.240
10.0	48.240	48.244	48.237
20.0	48.253	48.255	48.249
30.0	48.253	48.255	48.252
40.0	48.247	48.250	48.246
50.0	48.244	48.247	48.245
60.0	48.239	48.245	48.241
70.0	48.238	48.243	48.236
73.0	48.235	48.237	48.236
80.3	48.238	48.244	48.234
-	-	-	-

Item	Ripple-Noise
Object	+48V73A

Temperature 25°C
Testing Circuitry Figure C

1.Graph

Input Voltage 400V
 Load 100%



COSEL

Model	HFA3500TF-48
Item	Dynamic Load Response
Object	+48V73A

Temperature 25°C
Testing Circuitry Figure A



Input Volt.

400 V


Response. t1=t2=50μs. Typ

Cycle

1000 ms

Load 0%(0A) ←→
Load 100%(73A)

1[V/div]




10[ms/div]

10[ms/div]

Load 50%(36.5A) ←→
Load 100%(73A)

1[V/div]



10[ms/div]


10[ms/div]

coSEL

Model	HFA3500TF-48
Item	Rise and Fall Time
Object	+48V73A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
200 V		334.0	88.5	422.5	11.0	8.2	
400 V		327.5	87.0	414.5	10.8	8.1	




coSEL

Model	HFA3500TF-48
Item	Hold-Up Time
Object	+48V73A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
180	31	12
200	31	12
264	31	12
400	31	12
480	31	12
528	31	12
--	-	-
--	-	-
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage drops to 95% of the rated voltage.

Note: Hatched line shows the range of the rated input voltage.

coSEL

Model	HFA3500TF-48
Item	Instantaneous Interruption Compensation
Object	+48V73A

 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Load Current [A]	Time [ms]		
	Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]
0.0	-	-	-
10.0	118	119	120
20.0	59	59	59
30.0	38	38	39
40.0	26	27	27
50.0	19	20	20
60.0	15	15	15
70.0	11	11	11
73.0	10	10	10
80.3	8	8	8
--	-	-	-

Note: Hatched line shows the range of the rated load current.

COSEL

Model	HFA3500TF-48	Temperature	25°C																																																											
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																											
Object	+48V73A																																																													
1.Graph		2.Values																																																												
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Hatched line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Voltage 200[V]</th> <th>Input Voltage 400[V]</th> <th>Input Voltage 480[V]</th> </tr> </thead> <tbody> <tr><td>48</td><td>83.21</td><td>83.20</td><td>83.14</td></tr> <tr><td>43.2</td><td>83.82</td><td>82.87</td><td>82.81</td></tr> <tr><td>38.4</td><td>82.58</td><td>82.63</td><td>82.60</td></tr> <tr><td>33.6</td><td>82.45</td><td>82.50</td><td>82.50</td></tr> <tr><td>28.8</td><td>82.38</td><td>82.43</td><td>82.43</td></tr> <tr><td>24</td><td>82.33</td><td>82.38</td><td>82.39</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]	48	83.21	83.20	83.14	43.2	83.82	82.87	82.81	38.4	82.58	82.63	82.60	33.6	82.45	82.50	82.50	28.8	82.38	82.43	82.43	24	82.33	82.38	82.39	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																													
	Input Voltage 200[V]	Input Voltage 400[V]	Input Voltage 480[V]																																																											
48	83.21	83.20	83.14																																																											
43.2	83.82	82.87	82.81																																																											
38.4	82.58	82.63	82.60																																																											
33.6	82.45	82.50	82.50																																																											
28.8	82.38	82.43	82.43																																																											
24	82.33	82.38	82.39																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											



Model	HFA3500TF-48	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+48V73A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Voltage 200V	Input Voltage 400V	Input Voltage 480V
-10	48.308	48.309	48.306
25	48.235	48.237	48.236
50	48.098	48.105	48.103

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+48V73A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-10	170	168
25	171	170
50	171	170




Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+48V73A	

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Voltage 200V	Input Voltage 400V
-10	58.15	58.15
25	58.28	58.28
70	58.40	58.40

coSEL




COSEL

Figure C