

Approved : Yukihiro Takehashi
Yukihiro TakehashiPrepared : Seiya Shimada
Seiya Shimada

| No. | Test item | Test Conditions | Conditions of acceptability | Result |
|-----|---|--|--|--------|
| 1 | High temp./Overload test | (1) Rated input AC115V, AC230V (2) Overload (3) Ambient temp. 60°C (4) Test period 48 hours | (1) Power supply is not failed. | ok |
| 2 | No ventilation test | (1) Rated input AC115V (2) Rated output (3) Ambient temp. 25±10°C (4) Test period 48 hours | (1) No smoke, no fire. | ok |
| 3 | Capacitance reduction test | (1) Rated input AC115V (2) Rated output (3) Ambient temp. 25±10°C | (1) No smoke, no fire. (2) No rise of the output voltage. | ok |
| 4 | Low voltage input test | (1) Input : Min. regulation voltage AC63V (2) Rated output (3) Ambient temp. 25±10°C (4) Test period 48 hours | (1) Power supply is not failed. | ok |
| 5 | Input On/Off test | (1) Input : Max voltage AC264V T= 2sec Duty= 50% (2) Rated output (3) Ambient temp. 70°C (4) On/Off period 1,000 times | (1) Power supply is not failed. (2) The surge current of each components should not exceed the rated value. | ok |
| 6 | Output On/Off test | (1) Rated input AC230V (2) Output 0%←→100% T= 2sec Duty= 50% (3) Ambient temp. 25±10°C (4) On/Off period 1,000 times | (1) Power supply is not failed. | ok |
| 7 | Output-Short start test | (1) Rated input AC230V (2) Output : Short start (3) Ambient temp. 25±10°C | (1) Power supply is not failed. | ok |
| 8 | Output short test | (1) Rated input AC230V (2) Output : Short (3) Ambient temp. 25±10°C (4) Test period 48 hours | (1) Power supply is not failed. | ok |
| 9 | Withstand voltage test (High-pot test) | (1) Input : Not applied (2) Ambient temp. 25±10°C (3) The applied voltage is 1.4 times of specifications. | (1) Insulation breakdown, flashover or electric arc is not occurred. | ok |
| 10 | Isolation resistance test | (1) Input : Not applied (2) Ambient temp. 25±10°C | (1) When a regulation voltage is applied, isolation resistance is 1.4 times of specifications. | ok |
| 11 | Vibration/Impact test | Vibration: (1) f=10~150Hz : 29.4m/s ² (2) 3 minutes period (3) 60 minutes Z axis Impact: (1) 294.2m/s ² 11ms (2) Once each X, Y and Z axis | (1) No degradation of electric characteristics after test. (2) No crack at solder joint. (3) No marked damage of appearance. | ok |
| 12 | Line noise tolerance test | (1) Input AC230V (2) Rated Output (3) Ambient temp 25±10°C (4) Test Voltage ±3 kV (5) Pulse width 50~1000ns (6) Mode : Normal and Common | (1) No protection circuit failure. (2) No output voltage drop with control circuit failure. (3) No any other function failure. | ok |