



TEST DATA OF LCA100S-15

(100V INPUT)

Regulated DC Power Supply

Date : Aug. 25. 1999

Approved by : H. Yamaguchi
Design Manager

Prepared by : S. Taniguchi
Design Engineer

コーワセル株式会社
COSEL CO., LTD.




C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. O vervoltage Protection	12
過電圧保護	
13. Inrush Current	13
突入電流	
14. Dynamic Load Responce	14
動的負荷変動	
15. Rise and Fall Time	15
立ち上り、立下がり時間	
16. Ambient Temperature Drift	16
周囲温度変動	
17. Minimum Input Voltage for Regulated Output Voltage .	17
最低レギュレーション電圧	
18. Ripple Voltage (by Ambient Temperature)	18
リップル電圧 (周囲温度特性)	
19. Time Lapse Drift	19
経時ドリフト	
20. Output Voltage Accuracy	20
定電圧精度	
21. Condensation	21
結露特性	
22. Leakage Current	22
漏洩電流	
23. Line Noise Tolerance	23
入力雜音耐量	
24. Conducted Emission	24
雜音端子電圧	
25. Figure of Testing Circuitry	25
測定回路図	

(Final Page 26)

COSEL

Model	LCA100S-15
Item	Line Regulation 静的入力変動
Object	+15.0V 7A



Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。


Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	15.132	15.132
80	15.132	15.132
85	15.132	15.132
90	15.132	15.132
100	15.131	15.132
110	15.131	15.132
120	15.131	15.131
132	15.131	15.131
140	15.131	15.131

COSEL

Model	LCA100S-15
Item	Input Current (by Load Current) 入力電流 (負荷特性)
Output	—



Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	0.078	0.086	0.095
1.0	0.563	0.521	0.460
2.0	0.954	0.867	0.739
3.0	1.315	1.189	1.002
4.0	1.665	1.499	1.255
5.0	2.015	1.809	1.508
6.0	2.351	2.105	1.748
7.0	2.693	2.406	1.991
7.7	2.922	2.606	2.155
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA100S-15
Item	Input Power (by Load Current) 入力電力 (負荷特性)
Output	—




Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	2.28	2.85	3.94
1.0	20.45	21.29	23.20
2.0	37.54	38.22	39.90
3.0	54.64	55.13	56.70
4.0	72.00	72.20	73.60
5.0	90.20	90.10	91.10
6.0	108.20	107.80	108.30
7.0	127.10	126.30	126.30
7.7	140.10	139.00	138.60
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

COSEL

Model	LCA100S-15																																																									
Item	Efficiency (by Load Current) 効率(負荷電流特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	—																																																									
1. Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V (Triangle) Input Volt. 100V (Square) Input Volt. 132V (Circle) 																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>1.0</td><td>74.7</td><td>72.4</td><td>66.7</td></tr> <tr><td>2.0</td><td>81.3</td><td>80.1</td><td>76.8</td></tr> <tr><td>3.0</td><td>83.3</td><td>82.8</td><td>80.5</td></tr> <tr><td>4.0</td><td>84.1</td><td>84.0</td><td>82.4</td></tr> <tr><td>5.0</td><td>84.3</td><td>84.5</td><td>83.5</td></tr> <tr><td>6.0</td><td>84.1</td><td>84.5</td><td>84.1</td></tr> <tr><td>7.0</td><td>83.8</td><td>84.4</td><td>84.4</td></tr> <tr><td>7.7</td><td>83.5</td><td>84.2</td><td>84.5</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	1.0	74.7	72.4	66.7	2.0	81.3	80.1	76.8	3.0	83.3	82.8	80.5	4.0	84.1	84.0	82.4	5.0	84.3	84.5	83.5	6.0	84.1	84.5	84.1	7.0	83.8	84.4	84.4	7.7	83.5	84.2	84.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
1.0	74.7	72.4	66.7																																																							
2.0	81.3	80.1	76.8																																																							
3.0	83.3	82.8	80.5																																																							
4.0	84.1	84.0	82.4																																																							
5.0	84.3	84.5	83.5																																																							
6.0	84.1	84.5	84.1																																																							
7.0	83.8	84.4	84.4																																																							
7.7	83.5	84.2	84.5																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA100S-15		Temperature	25°C																															
Item	Hold-Up Time 出力保持時間		Testing Circuitry	Figure A																															
Object	+15.0V 7A																																		
1. Graph				2. Values																															
	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>22</td><td>8</td></tr> <tr><td>80</td><td>28</td><td>12</td></tr> <tr><td>85</td><td>35</td><td>15</td></tr> <tr><td>90</td><td>42</td><td>19</td></tr> <tr><td>100</td><td>58</td><td>27</td></tr> <tr><td>110</td><td>76</td><td>35</td></tr> <tr><td>120</td><td>95</td><td>45</td></tr> <tr><td>132</td><td>121</td><td>58</td></tr> <tr><td>140</td><td>139</td><td>67</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	22	8	80	28	12	85	35	15	90	42	19	100	58	27	110	76	35	120	95	45	132	121	58	140	139	67
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	22	8																																	
80	28	12																																	
85	35	15																																	
90	42	19																																	
100	58	27																																	
110	76	35																																	
120	95	45																																	
132	121	58																																	
140	139	67																																	
	<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																		

COSEL

Model	LCA100S-15	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																						
Object	+15.0V 7A																																																						
1. Graph	<p>[mS]</p> <p>Instantaneous Compensation Time [mS]</p> <p>Load Current [A]</p> <p>Input Volt. 85 V</p> <p>Input Volt. 100 V</p> <p>Input Volt. 132 V</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>1.0</td><td>106</td><td>178</td><td>365</td></tr> <tr> <td>2.0</td><td>54</td><td>94</td><td>197</td></tr> <tr> <td>3.0</td><td>35</td><td>62</td><td>134</td></tr> <tr> <td>4.0</td><td>22</td><td>45</td><td>96</td></tr> <tr> <td>5.0</td><td>19</td><td>35</td><td>80</td></tr> <tr> <td>6.0</td><td>14</td><td>29</td><td>65</td></tr> <tr> <td>7.0</td><td>12</td><td>22</td><td>56</td></tr> <tr> <td>7.7</td><td>10</td><td>21</td><td>48</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	1.0	106	178	365	2.0	54	94	197	3.0	35	62	134	4.0	22	45	96	5.0	19	35	80	6.0	14	29	65	7.0	12	22	56	7.7	10	21	48	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.0	—	—	—																																																				
1.0	106	178	365																																																				
2.0	54	94	197																																																				
3.0	35	62	134																																																				
4.0	22	45	96																																																				
5.0	19	35	80																																																				
6.0	14	29	65																																																				
7.0	12	22	56																																																				
7.7	10	21	48																																																				
—	—	—	—																																																				
—	—	—	—																																																				
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																							


COSEL

Model	LCA100S-15																																																	
Item	Load Regulation 靜的負荷変動	Temperature 25°C	Testing Circuitry Figure A																																															
Object	+ 15.0V 7A																																																	
1. Graph																																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>15.131</td><td>15.131</td><td>15.131</td></tr> <tr> <td>1.0</td><td>15.131</td><td>15.131</td><td>15.130</td></tr> <tr> <td>2.0</td><td>15.131</td><td>15.131</td><td>15.130</td></tr> <tr> <td>3.0</td><td>15.131</td><td>15.131</td><td>15.130</td></tr> <tr> <td>4.0</td><td>15.131</td><td>15.131</td><td>15.130</td></tr> <tr> <td>5.0</td><td>15.131</td><td>15.131</td><td>15.130</td></tr> <tr> <td>6.0</td><td>15.132</td><td>15.132</td><td>15.131</td></tr> <tr> <td>7.0</td><td>15.132</td><td>15.132</td><td>15.131</td></tr> <tr> <td>7.7</td><td>15.132</td><td>15.132</td><td>15.131</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	15.131	15.131	15.131	1.0	15.131	15.131	15.130	2.0	15.131	15.131	15.130	3.0	15.131	15.131	15.130	4.0	15.131	15.131	15.130	5.0	15.131	15.131	15.130	6.0	15.132	15.132	15.131	7.0	15.132	15.132	15.131	7.7	15.132	15.132	15.131	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.0	15.131	15.131	15.131																																															
1.0	15.131	15.131	15.130																																															
2.0	15.131	15.131	15.130																																															
3.0	15.131	15.131	15.130																																															
4.0	15.131	15.131	15.130																																															
5.0	15.131	15.131	15.130																																															
6.0	15.132	15.132	15.131																																															
7.0	15.132	15.132	15.131																																															
7.7	15.132	15.132	15.131																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	10	10
1.00	15	20
2.00	20	20
3.00	20	20
4.00	25	20
5.00	25	25
6.00	30	25
6.70	30	30
7.00	35	30
7.40	35	30
—	—	—

COSEL

Model	LCA100S-15	Temperature Testing Circuitry 25°C Figure A																																
Item	Ripple-Noise リップルノイズ																																	
Object	+15.0V 6.7A																																	
1. Graph	<p style="text-align: center;">□ Input Volt. 85V [mV] ▲ Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise 85V [mV]</th> <th>Ripple-Noise 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>30</td></tr> <tr><td>1.00</td><td>25</td><td>40</td></tr> <tr><td>2.00</td><td>45</td><td>45</td></tr> <tr><td>3.00</td><td>55</td><td>50</td></tr> <tr><td>4.00</td><td>55</td><td>55</td></tr> <tr><td>5.00</td><td>55</td><td>55</td></tr> <tr><td>6.00</td><td>55</td><td>60</td></tr> <tr><td>6.70</td><td>60</td><td>70</td></tr> <tr><td>7.00</td><td>60</td><td>70</td></tr> <tr><td>7.40</td><td>60</td><td>75</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]	0.00	15	30	1.00	25	40	2.00	45	45	3.00	55	50	4.00	55	55	5.00	55	55	6.00	55	60	6.70	60	70	7.00	60	70	7.40	60	75
Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]																																
0.00	15	30																																
1.00	25	40																																
2.00	45	45																																
3.00	55	50																																
4.00	55	55																																
5.00	55	55																																
6.00	55	60																																
6.70	60	70																																
7.00	60	70																																
7.40	60	75																																
2. Values																																		

Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.00	15	30
1.00	25	40
2.00	45	45
3.00	55	50
4.00	55	55
5.00	55	55
6.00	55	60
6.70	60	70
7.00	60	70
7.40	60	75
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line

入力商用周期

T2: Due to Switching

スイッチング周期





Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
15.00	8.61	8.52	8.47
14.25	8.63	8.55	8.51
13.50	8.65	8.57	8.53
12.00	8.70	8.62	8.57
10.50	8.73	8.65	8.62
9.00	8.76	8.67	8.62
7.50	8.76	8.70	8.61
6.00	8.73	8.69	8.62
4.50	8.75	8.70	8.65
3.00	8.77	8.72	8.63
1.50	8.66	8.58	8.50
0.00	8.57	8.57	8.62

COSEL

Model LCA100S-15


Item Overvoltage Protection
過電圧保護

Object +15.0V 7A

1. Graph

—▲— Input Volt. 85 V
—□— Input Volt. 100 V
—○— Input Volt. 132 V

[V]



Load 0%

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values


Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	18.56	18.57	18.57
-10	18.74	18.69	18.69
0	18.86	18.87	18.87
10	18.98	18.99	18.99
20	19.10	19.10	19.11
25	19.16	19.16	19.16
30	19.27	19.28	19.28
40	19.39	19.39	19.40
50	19.51	19.51	19.52
60	19.68	19.63	19.64
—	—	—	—

COSEL

Model	LCA100S-15	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current 突入電流		
Object	_____		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current
 ① 13.20 [A]
 ② 8.80 [A]



COSEL

Model	LCA100S-15	Temperature Testing Circuitry 25°C Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	+15.0V7A	



Input Volt. 100 V

Cycle 1000 mS





Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %



100 mV/div


10 mS/div

COSEL

Model	LCA100S-15
Item	Rise and Fall Time 立上り、立下り時間
Object	+15.0V7A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load \ Time	T d	T r	T s	T h	T f	[mS]
50 %	148.8	31.5	180.3	35.4	32.7	
100 %	148.8	31.3	180.0	14.9	16.7	



COSEL


Model LCA100S-15

Item Ambient Temperature Drift
周囲温度変動

Object +15.0V 7A

1. Graph

—△— Input Volt. 85V
 —□— Input Volt. 100V
 —○— Input Volt. 132V



Load 100%

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values

Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	15.135	15.135	15.134
-10	15.136	15.136	15.136
0	15.136	15.136	15.136
10	15.136	15.136	15.135
20	15.133	15.133	15.133
25	15.132	15.132	15.131
30	15.131	15.131	15.130
40	15.127	15.126	15.126
50	15.123	15.123	15.122
60	15.118	15.119	15.118
--	--	--	--



Model	LCA100S-15
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+15.0V7A



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	60	66
-10	58	65
0	58	65
10	58	65
20	58	65
25	58	65
30	58	65
40	58	65
50	58	65
60	58	65
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model

LCA100S-15


Item

Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object

+15.0V7A

1. Graph



(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry

Figure A

2. Values

Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]
-20	45	55
-10	35	45
0	30	40
10	25	35
20	25	30
25	25	30
30	20	25
40	20	25
50	20	25
60	15	20
—	—	—

COSSEL

Model	LCA100S-15	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift 経時ドリフト																							
Object	+ 15.0V 7A																							
1. Graph		2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.142</td></tr> <tr><td>0.5</td><td>15.139</td></tr> <tr><td>1.0</td><td>15.139</td></tr> <tr><td>2.0</td><td>15.139</td></tr> <tr><td>3.0</td><td>15.139</td></tr> <tr><td>4.0</td><td>15.139</td></tr> <tr><td>5.0</td><td>15.139</td></tr> <tr><td>6.0</td><td>15.139</td></tr> <tr><td>7.0</td><td>15.139</td></tr> <tr><td>8.0</td><td>15.139</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.142	0.5	15.139	1.0	15.139	2.0	15.139	3.0	15.139	4.0	15.139	5.0	15.139	6.0	15.139	7.0	15.139	8.0	15.139
Time since start [H]	Output Voltage [V]																							
0.0	15.142																							
0.5	15.139																							
1.0	15.139																							
2.0	15.139																							
3.0	15.139																							
4.0	15.139																							
5.0	15.139																							
6.0	15.139																							
7.0	15.139																							
8.0	15.139																							



Model	LCA100S-15		
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry	Figure A
Object	+15.0V 7A		

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~7 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~7 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132	7	15.138		
Minimum Voltage	50	132	0	15.123	±8	±0.1



Model	LCA100S-15		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+15.0V 7A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	15.132	Input Volt.: 100V, Load Current:7A
Line Regulation [mV]	2	Input Volt.: 85~132V, Load Current:7A
Load Regulation [mV]	4	Input Volt.: 100V, Load Current:0~7A



Model	LCA100S-15	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	_____	_____	_____

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.18	0.22	0.31
(B) IEC60950	0.20	0.23	0.32

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	LCA100S-15	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	+ 15.0V7A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LCA100S-15	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	<hr/>		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

規格 1 : [VCCI] Class B(平均値)

規格 2 : [VCCI] Class B(QP)



規格 1 : [FCC Part15] Class B



COSEL





Figure B (DENTORI)




Figure B (IEC 60950)

COSSEL




Figure C




Figure D




Figure E