



TEST DATA OF LCA10S-5 (100V INPUT)

Regulated DC Power Supply

Date : June 16. 1999

Approved by : K. Yamaguchi
Design Manager

Prepared by : S. Taniguchi
Design Engineer

コーセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Dynamic Load Responce	13
動的負荷変動	
14. Rise and Fall Time	14
立上り、立下がり時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift	18
経時ドリフト	
19. Output Voltage Accuracy	19
定電圧精度	
20. Condensation	20
結露特性	
21. Leakage Current	21
漏洩電流	
22. Line Noise Tolerance	22
入力雑音耐量	
23. Conducted Emission	23
雑音端子電圧	
24. Figure of Testing Circuitry	24
測定回路図	

(Final Page 25)

COSEL

Model	LCA10S-5	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+5.0V2A																																		
1. Graph	<p>Load 50% </p> <p>Load 100% </p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>5.091</td><td>5.089</td></tr> <tr><td>80</td><td>5.091</td><td>5.090</td></tr> <tr><td>85</td><td>5.091</td><td>5.090</td></tr> <tr><td>90</td><td>5.091</td><td>5.090</td></tr> <tr><td>100</td><td>5.091</td><td>5.090</td></tr> <tr><td>110</td><td>5.091</td><td>5.090</td></tr> <tr><td>120</td><td>5.091</td><td>5.090</td></tr> <tr><td>132</td><td>5.091</td><td>5.090</td></tr> <tr><td>140</td><td>5.091</td><td>5.090</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	5.091	5.089	80	5.091	5.090	85	5.091	5.090	90	5.091	5.090	100	5.091	5.090	110	5.091	5.090	120	5.091	5.090	132	5.091	5.090	140	5.091	5.090
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	5.091	5.089																																	
80	5.091	5.090																																	
85	5.091	5.090																																	
90	5.091	5.090																																	
100	5.091	5.090																																	
110	5.091	5.090																																	
120	5.091	5.090																																	
132	5.091	5.090																																	
140	5.091	5.090																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LCA10S-5																																																										
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature 25°C Testing Circuitry Figure A																																																									
Output	—																																																										
1. Graph	<p>—△— Input Volt. 85V —□— Input Volt. 100V —○— Input Volt. 132V</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.046</td><td>0.049</td><td>0.054</td></tr> <tr><td>0.4</td><td>0.105</td><td>0.099</td><td>0.094</td></tr> <tr><td>0.8</td><td>0.157</td><td>0.145</td><td>0.130</td></tr> <tr><td>1.2</td><td>0.205</td><td>0.188</td><td>0.164</td></tr> <tr><td>1.6</td><td>0.251</td><td>0.229</td><td>0.198</td></tr> <tr><td>2.0</td><td>0.299</td><td>0.270</td><td>0.232</td></tr> <tr><td>2.2</td><td>0.322</td><td>0.290</td><td>0.247</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.046	0.049	0.054	0.4	0.105	0.099	0.094	0.8	0.157	0.145	0.130	1.2	0.205	0.188	0.164	1.6	0.251	0.229	0.198	2.0	0.299	0.270	0.232	2.2	0.322	0.290	0.247	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
0.0	0.046	0.049	0.054																																																								
0.4	0.105	0.099	0.094																																																								
0.8	0.157	0.145	0.130																																																								
1.2	0.205	0.188	0.164																																																								
1.6	0.251	0.229	0.198																																																								
2.0	0.299	0.270	0.232																																																								
2.2	0.322	0.290	0.247																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
Note:	Slanted line shows the range of the rated load current																																																										
(注)	斜線は定格負荷電流範囲を示す。																																																										

COSEL

Model	LCA10S-5																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	<hr/>																																																									
1. Graph	<p>Input Volt. 85V Input Volt. 100V Input Volt. 132V</p> <table> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (85V)</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.58</td><td>1.89</td><td>2.64</td></tr> <tr><td>0.4</td><td>4.15</td><td>4.42</td><td>5.12</td></tr> <tr><td>0.8</td><td>6.74</td><td>6.97</td><td>7.57</td></tr> <tr><td>1.2</td><td>9.31</td><td>9.52</td><td>10.06</td></tr> <tr><td>1.6</td><td>11.92</td><td>12.10</td><td>12.61</td></tr> <tr><td>2.0</td><td>14.71</td><td>14.81</td><td>15.25</td></tr> <tr><td>2.2</td><td>16.08</td><td>16.14</td><td>16.52</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)	0.0	1.58	1.89	2.64	0.4	4.15	4.42	5.12	0.8	6.74	6.97	7.57	1.2	9.31	9.52	10.06	1.6	11.92	12.10	12.61	2.0	14.71	14.81	15.25	2.2	16.08	16.14	16.52	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)																																																							
0.0	1.58	1.89	2.64																																																							
0.4	4.15	4.42	5.12																																																							
0.8	6.74	6.97	7.57																																																							
1.2	9.31	9.52	10.06																																																							
1.6	11.92	12.10	12.61																																																							
2.0	14.71	14.81	15.25																																																							
2.2	16.08	16.14	16.52																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.58</td><td>1.89</td><td>2.64</td></tr> <tr><td>0.4</td><td>4.15</td><td>4.42</td><td>5.12</td></tr> <tr><td>0.8</td><td>6.74</td><td>6.97</td><td>7.57</td></tr> <tr><td>1.2</td><td>9.31</td><td>9.52</td><td>10.06</td></tr> <tr><td>1.6</td><td>11.92</td><td>12.10</td><td>12.61</td></tr> <tr><td>2.0</td><td>14.71</td><td>14.81</td><td>15.25</td></tr> <tr><td>2.2</td><td>16.08</td><td>16.14</td><td>16.52</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	1.58	1.89	2.64	0.4	4.15	4.42	5.12	0.8	6.74	6.97	7.57	1.2	9.31	9.52	10.06	1.6	11.92	12.10	12.61	2.0	14.71	14.81	15.25	2.2	16.08	16.14	16.52	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	1.58	1.89	2.64																																																							
0.4	4.15	4.42	5.12																																																							
0.8	6.74	6.97	7.57																																																							
1.2	9.31	9.52	10.06																																																							
1.6	11.92	12.10	12.61																																																							
2.0	14.71	14.81	15.25																																																							
2.2	16.08	16.14	16.52																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA10S-5																																	
Item	Efficiency 効率	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: □ Load 50% △ Load 100%</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>65.0</td><td>70.0</td></tr> <tr> <td>80</td><td>64.7</td><td>70.0</td></tr> <tr> <td>85</td><td>63.8</td><td>69.9</td></tr> <tr> <td>90</td><td>63.6</td><td>69.8</td></tr> <tr> <td>100</td><td>62.1</td><td>69.5</td></tr> <tr> <td>110</td><td>61.0</td><td>68.9</td></tr> <tr> <td>120</td><td>59.5</td><td>68.4</td></tr> <tr> <td>132</td><td>58.1</td><td>67.5</td></tr> <tr> <td>140</td><td>57.2</td><td>67.1</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	65.0	70.0	80	64.7	70.0	85	63.8	69.9	90	63.6	69.8	100	62.1	69.5	110	61.0	68.9	120	59.5	68.4	132	58.1	67.5	140	57.2	67.1
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	65.0	70.0																																
80	64.7	70.0																																
85	63.8	69.9																																
90	63.6	69.8																																
100	62.1	69.5																																
110	61.0	68.9																																
120	59.5	68.4																																
132	58.1	67.5																																
140	57.2	67.1																																

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LCA10S-5																																																									
Item	Efficiency (by Load Current) 効率(負荷電流特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	<hr/>																																																									
1. Graph	<p>The graph plots Efficiency [%] on the y-axis (40 to 90) against Load Current [A] on the x-axis (0 to 2.5). Three data series are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). All three curves show an increasing trend of efficiency with load current. A slanted line is drawn across the graph, starting from approximately (0.4, 48) and ending at (2.0, 70), indicating the range of the rated load current.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.4</td><td>50.0</td><td>47.2</td><td>40.8</td></tr> <tr><td>0.8</td><td>61.0</td><td>59.4</td><td>54.4</td></tr> <tr><td>1.2</td><td>66.3</td><td>64.5</td><td>61.1</td></tr> <tr><td>1.6</td><td>68.9</td><td>67.7</td><td>64.9</td></tr> <tr><td>2.0</td><td>69.8</td><td>69.4</td><td>67.4</td></tr> <tr><td>2.2</td><td>70.0</td><td>69.8</td><td>68.4</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.4	50.0	47.2	40.8	0.8	61.0	59.4	54.4	1.2	66.3	64.5	61.1	1.6	68.9	67.7	64.9	2.0	69.8	69.4	67.4	2.2	70.0	69.8	68.4	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.4	50.0	47.2	40.8																																																							
0.8	61.0	59.4	54.4																																																							
1.2	66.3	64.5	61.1																																																							
1.6	68.9	67.7	64.9																																																							
2.0	69.8	69.4	67.4																																																							
2.2	70.0	69.8	68.4																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LCA10S-5																																		
Item	Hold-Up Time 出力保持時間	Temperature Testing Circuitry 25°C Figure A																																	
Object	+5.0V2A																																		
1. Graph	<p>1. Graph</p> <p>Load 50% (squares)</p> <p>Load 100% (triangles)</p> <p>Hold-Up Time [mS]</p> <p>Input Voltage [V]</p>																																		
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>31</td><td>12</td></tr> <tr><td>80</td><td>35</td><td>15</td></tr> <tr><td>85</td><td>40</td><td>18</td></tr> <tr><td>90</td><td>45</td><td>21</td></tr> <tr><td>100</td><td>57</td><td>27</td></tr> <tr><td>110</td><td>69</td><td>34</td></tr> <tr><td>120</td><td>82</td><td>42</td></tr> <tr><td>132</td><td>99</td><td>52</td></tr> <tr><td>140</td><td>112</td><td>59</td></tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	31	12	80	35	15	85	40	18	90	45	21	100	57	27	110	69	34	120	82	42	132	99	52	140	112	59
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	31	12																																	
80	35	15																																	
85	40	18																																	
90	45	21																																	
100	57	27																																	
110	69	34																																	
120	82	42																																	
132	99	52																																	
140	112	59																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL


Model	LCA10S-5																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障	Temperature	25°C																																																			
Object	+5.0V 2A																																																					
1. Graph	<p>[mS]</p> <p>Instantaneous Compensation Time</p> <p>Load Current [A]</p> <p>Input Volt. 85 V</p> <p>Input Volt. 100 V</p> <p>Input Volt. 132 V</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.4</td><td>82</td><td>112</td><td>189</td></tr> <tr><td>0.8</td><td>45</td><td>65</td><td>115</td></tr> <tr><td>1.2</td><td>28</td><td>40</td><td>79</td></tr> <tr><td>1.6</td><td>18</td><td>28</td><td>57</td></tr> <tr><td>2.0</td><td>11</td><td>20</td><td>45</td></tr> <tr><td>2.2</td><td>5</td><td>14</td><td>38</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	0.4	82	112	189	0.8	45	65	115	1.2	28	40	79	1.6	18	28	57	2.0	11	20	45	2.2	5	14	38	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	—	—	—																																																			
0.4	82	112	189																																																			
0.8	45	65	115																																																			
1.2	28	40	79																																																			
1.6	18	28	57																																																			
2.0	11	20	45																																																			
2.2	5	14	38																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

COSEL


COSEL

Model	LCA10S-5																																							
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Temperature Testing Circuitry 25°C Figure A																																						
Object	+5.0V2A																																							
1. Graph	-----□----- Input Volt. 85V [mV] -----△----- Input Volt. 132V	2. Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>5</td></tr> <tr><td>0.40</td><td>10</td><td>5</td></tr> <tr><td>0.80</td><td>10</td><td>10</td></tr> <tr><td>1.00</td><td>10</td><td>10</td></tr> <tr><td>1.20</td><td>10</td><td>10</td></tr> <tr><td>1.40</td><td>10</td><td>10</td></tr> <tr><td>1.60</td><td>15</td><td>15</td></tr> <tr><td>1.80</td><td>15</td><td>15</td></tr> <tr><td>2.00</td><td>20</td><td>15</td></tr> <tr><td>2.20</td><td>25</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	10	5	0.40	10	5	0.80	10	10	1.00	10	10	1.20	10	10	1.40	10	10	1.60	15	15	1.80	15	15	2.00	20	15	2.20	25	15	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.00	10	5																																						
0.40	10	5																																						
0.80	10	10																																						
1.00	10	10																																						
1.20	10	10																																						
1.40	10	10																																						
1.60	15	15																																						
1.80	15	15																																						
2.00	20	15																																						
2.20	25	15																																						
—	—	—																																						
	Ripple Voltage is shown as p-p in the figure below.																																							
	Note: Slanted line shows the range of the rated load current.																																							
	リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。																																							
	<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																							
	Ripple [mVp-p] 																																							
	Fig. Complex Ripple Wave Form 図 リップル波形詳細図																																							

COSEL

Model	LCA10S-5	Temperature Testing Circuitry	25°C Figure A
Item	Ripple-Noise リップルノイズ		
Object	+5.0V2A		
1. Graph	-----□----- Input Volt. 85V [mV] -----△----- Input Volt. 132V		
<p>The graph shows two sets of data points for Ripple-Noise (mV) versus Load Current (A). The first set, represented by squares, corresponds to an input voltage of 85V. The second set, represented by triangles, corresponds to an input voltage of 132V. Both sets show a relatively flat noise level around 15-20 mV for low load currents (up to ~1.5A), followed by a sharp increase as the load current approaches the rated value of 2A. A diagonal line is drawn through the data points at approximately 15-20 mV, representing the rated load current range.</p>			
2. Values			
Load current	Input Volt. 85 [V]	Input Volt. 132 [V]	
[A]	Ripple-Noise [mV]	Ripple-Noise [mV]	
0.00	15	10	
0.40	15	10	
0.80	15	15	
1.00	15	15	
1.20	15	15	
1.40	15	15	
1.60	20	20	
1.80	30	20	
2.00	40	25	
2.20	50	30	
—	—	—	

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
 入力商用周期
T2: Due to Switching
 スイッチング周期





Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model	LCA10S-5																																																									
Item	Overcurrent Protection 過電流保護																																																									
Object	+5.0V 2A																																																									
1. Graph	<p>[V] Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>2.74</td><td>2.87</td><td>2.82</td></tr> <tr><td>4.75</td><td>2.74</td><td>2.85</td><td>2.79</td></tr> <tr><td>4.50</td><td>2.73</td><td>2.84</td><td>2.76</td></tr> <tr><td>4.00</td><td>2.71</td><td>2.79</td><td>2.69</td></tr> <tr><td>3.50</td><td>2.67</td><td>2.72</td><td>2.59</td></tr> <tr><td>3.00</td><td>2.60</td><td>2.62</td><td>2.48</td></tr> <tr><td>2.50</td><td>2.50</td><td>2.50</td><td>2.35</td></tr> <tr><td>2.00</td><td>2.37</td><td>2.35</td><td>2.23</td></tr> <tr><td>1.50</td><td>2.20</td><td>2.17</td><td>2.07</td></tr> <tr><td>1.00</td><td>1.99</td><td>1.97</td><td>1.91</td></tr> <tr><td>0.50</td><td>1.74</td><td>1.74</td><td>1.73</td></tr> <tr><td>0.00</td><td>1.44</td><td>1.48</td><td>1.69</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	5.00	2.74	2.87	2.82	4.75	2.74	2.85	2.79	4.50	2.73	2.84	2.76	4.00	2.71	2.79	2.69	3.50	2.67	2.72	2.59	3.00	2.60	2.62	2.48	2.50	2.50	2.50	2.35	2.00	2.37	2.35	2.23	1.50	2.20	2.17	2.07	1.00	1.99	1.97	1.91	0.50	1.74	1.74	1.73	0.00	1.44	1.48	1.69
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
5.00	2.74	2.87	2.82																																																							
4.75	2.74	2.85	2.79																																																							
4.50	2.73	2.84	2.76																																																							
4.00	2.71	2.79	2.69																																																							
3.50	2.67	2.72	2.59																																																							
3.00	2.60	2.62	2.48																																																							
2.50	2.50	2.50	2.35																																																							
2.00	2.37	2.35	2.23																																																							
1.50	2.20	2.17	2.07																																																							
1.00	1.99	1.97	1.91																																																							
0.50	1.74	1.74	1.73																																																							
0.00	1.44	1.48	1.69																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																										

COSEL

COSEL

Model	LCA10S-5	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	+5.0V2A	



Input Volt. 100 V

Cycle 1000 mS





Load 0% ←→

Load 100 %



Load 0% ←→

Load 50 %



200 mV/div


10 mS/div

COSEL

Model	LCA10S-5	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time 立上り、立下り時間		
Object	+5.0V2A		

1. Graph


Input Volt. 85 V



2. Values

[mS]

Load	Time	T _d	T _r	T _s	T _h	T _f
50 %		2.5	4.8	7.3	40.3	28.8
100 %		2.5	6.0	8.5	17.8	24.5



COSEL

Model	LCA10S-5																																																						
Item	Ambient Temperature Drift 周囲温度変動	Testing Circuitry Figure A																																																					
Object	+5.0V2A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>5.089</td><td>5.091</td><td>5.092</td></tr> <tr> <td>-10</td><td>5.092</td><td>5.093</td><td>5.093</td></tr> <tr> <td>0</td><td>5.092</td><td>5.093</td><td>5.093</td></tr> <tr> <td>10</td><td>5.092</td><td>5.092</td><td>5.092</td></tr> <tr> <td>20</td><td>5.090</td><td>5.091</td><td>5.091</td></tr> <tr> <td>25</td><td>5.090</td><td>5.090</td><td>5.090</td></tr> <tr> <td>30</td><td>5.089</td><td>5.089</td><td>5.089</td></tr> <tr> <td>40</td><td>5.087</td><td>5.087</td><td>5.087</td></tr> <tr> <td>50</td><td>5.085</td><td>5.085</td><td>5.085</td></tr> <tr> <td>60</td><td>5.082</td><td>5.082</td><td>5.082</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	5.089	5.091	5.092	-10	5.092	5.093	5.093	0	5.092	5.093	5.093	10	5.092	5.092	5.092	20	5.090	5.091	5.091	25	5.090	5.090	5.090	30	5.089	5.089	5.089	40	5.087	5.087	5.087	50	5.085	5.085	5.085	60	5.082	5.082	5.082	—	—	—	—
Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	5.089	5.091	5.092																																																				
-10	5.092	5.093	5.093																																																				
0	5.092	5.093	5.093																																																				
10	5.092	5.092	5.092																																																				
20	5.090	5.091	5.091																																																				
25	5.090	5.090	5.090																																																				
30	5.089	5.089	5.089																																																				
40	5.087	5.087	5.087																																																				
50	5.085	5.085	5.085																																																				
60	5.082	5.082	5.082																																																				
—	—	—	—																																																				

COSEL

Model	LCA10S-5																																								
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧																																								
Object	+5.0V2A																																								
1. Graph	<p>Load 50% Load 100%</p> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>36</td><td>61</td></tr> <tr><td>-10</td><td>35</td><td>60</td></tr> <tr><td>0</td><td>35</td><td>60</td></tr> <tr><td>10</td><td>34</td><td>60</td></tr> <tr><td>20</td><td>34</td><td>59</td></tr> <tr><td>25</td><td>34</td><td>59</td></tr> <tr><td>30</td><td>34</td><td>59</td></tr> <tr><td>40</td><td>34</td><td>59</td></tr> <tr><td>50</td><td>34</td><td>59</td></tr> <tr><td>60</td><td>34</td><td>59</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	36	61	-10	35	60	0	35	60	10	34	60	20	34	59	25	34	59	30	34	59	40	34	59	50	34	59	60	34	59	—	—	—
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	36	61																																							
-10	35	60																																							
0	35	60																																							
10	34	60																																							
20	34	59																																							
25	34	59																																							
30	34	59																																							
40	34	59																																							
50	34	59																																							
60	34	59																																							
—	—	—																																							

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	LCA10S-5																																								
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																							
Object	+5.0V2A																																								
1. Graph	<p>1. Graph</p> <p>Input Volt. 100 V</p> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Load 50% (dashed line with open squares)</p> <p>Load 100% (solid line with open triangles)</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>50</td><td>100</td></tr> <tr><td>-10</td><td>30</td><td>60</td></tr> <tr><td>0</td><td>20</td><td>40</td></tr> <tr><td>10</td><td>15</td><td>30</td></tr> <tr><td>20</td><td>15</td><td>20</td></tr> <tr><td>25</td><td>15</td><td>20</td></tr> <tr><td>30</td><td>10</td><td>20</td></tr> <tr><td>40</td><td>10</td><td>20</td></tr> <tr><td>50</td><td>5</td><td>15</td></tr> <tr><td>60</td><td>5</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temp. [°C]	Load 50%	Load 100%	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	-20	50	100	-10	30	60	0	20	40	10	15	30	20	15	20	25	15	20	30	10	20	40	10	20	50	5	15	60	5	15	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
-20	50	100																																							
-10	30	60																																							
0	20	40																																							
10	15	30																																							
20	15	20																																							
25	15	20																																							
30	10	20																																							
40	10	20																																							
50	5	15																																							
60	5	15																																							
—	—	—																																							
Note:	Slanted line shows the range of the rated ambient temperature.																																								
(注)	斜線は定格周囲温度範囲を示す。																																								

COSEL

Model	LCA10S-5	Temperature Testing Circuitry	25°C Figure A																					
Item	Time Lapse Drift 経時ドリフト																							
Object	+5.0V2A																							
1. Graph			2. Values																					
<p>[V]</p> <p>Output Voltage [V]</p> <p>Input Volt. 100V</p> <p>Load 100%</p> <table> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.092</td></tr> <tr><td>0.5</td><td>5.091</td></tr> <tr><td>1.0</td><td>5.091</td></tr> <tr><td>2.0</td><td>5.091</td></tr> <tr><td>3.0</td><td>5.091</td></tr> <tr><td>4.0</td><td>5.091</td></tr> <tr><td>5.0</td><td>5.091</td></tr> <tr><td>6.0</td><td>5.091</td></tr> <tr><td>7.0</td><td>5.091</td></tr> <tr><td>8.0</td><td>5.091</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	5.092	0.5	5.091	1.0	5.091	2.0	5.091	3.0	5.091	4.0	5.091	5.0	5.091	6.0	5.091	7.0	5.091	8.0	5.091
Time since start [H]	Output Voltage [V]																							
0.0	5.092																							
0.5	5.091																							
1.0	5.091																							
2.0	5.091																							
3.0	5.091																							
4.0	5.091																							
5.0	5.091																							
6.0	5.091																							
7.0	5.091																							
8.0	5.091																							



Model	LCA10S-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5.0V2A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~2 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~2 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132	0	5.097		
Minimum Voltage	50	132	2	5.085	±6	±0.2



Model	LCA10S-5		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+5.0V2A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.091	Input Volt.:100V, Load Current:2A
Line Regulation [mV]	2	Input Volt.:85~132V, Load Current:2A
Load Regulation [mV]	6	Input Volt.:100V, Load Current:0~2A



Model	LCA10S-5	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.07	0.08	0.10
(B) IEC60950	0.07	0.08	0.10

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	LCA10S-5	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5.0V2A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LCA10S-5	Temperature Testing Circuitry	25°C Figure D
Item	Conducted Emission 雜音端子電圧		
Object	<hr/>		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

規格1：[VCCI] Class B(平均値)

規格2：[VCCI] Class B(QP)



規格2：[FCC Part15] Class B







Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E