



# TEST DATA OF LCA50S-24-H

(100V INPUT)

Regulated DC Power Supply

Nov. 5, 1999

Approved by : X. Yamaguchi  
Design Manager

Prepared by : J. Asano  
Design Engineer

コーワセル株式会社  
COSEL CO., LTD.



## C O N T E N T S

1. Line Regulation . . . . .	1
静的入力変動	
2. Input Current (by Load Current) . . . . .	2
入力電流 (負荷特性)	
3. Input Power (by Load Current) . . . . .	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage) . . . . .	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current) . . . . .	5
効率 (負荷特性)	
6. Hold-Up Time . . . . .	6
出力保持時間	
7. Instantaneous Interruption Compensation . . . . .	7
瞬時停電保護	
8. Load Regulation . . . . .	8
静的負荷変動	
9. Ripple Voltage (by Load Current) . . . . .	9
リップル電圧 (負荷特性)	
10. Ripple-Noise . . . . .	10
リップルノイズ	
11. Overcurrent Protection . . . . .	11
過電流保護	
12. Overvoltage Protection . . . . .	12
過電圧保護	
13. Inrush Current . . . . .	13
突入電流	
14. Dynamic Load Responce . . . . .	14
動的負荷変動	
15. Rise and Fall Time . . . . .	15
立ち上り、立ち下り時間	
16. Ambient Temperature Drift . . . . .	16
周囲温度変動	
17. Minimum Input Voltage for Regulated Output Voltage . . . . .	17
最低レギュレーション電圧	
18. Ripple Voltage (by Ambient Temperature) . . . . .	18
リップル電圧 (周囲温度特性)	
19. Time Lapse Drift . . . . .	19
経時ドリフト	
20. Output Voltage Accuracy . . . . .	20
定電圧精度	
21. Figure of Testing Circuitry . . . . .	21
測定回路図	

(Final Page 22 )

**COSEL**


Model	LCA50S-24-H																																	
Item	Line Regulation 靜的入力変動	Temperature Testing Circuitry 25°C Figure A																																
Object	+24.0V 2.5A																																	
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>24.173</td><td>24.173</td></tr> <tr><td>80</td><td>24.173</td><td>24.173</td></tr> <tr><td>85</td><td>24.173</td><td>24.173</td></tr> <tr><td>90</td><td>24.173</td><td>24.173</td></tr> <tr><td>100</td><td>24.173</td><td>24.173</td></tr> <tr><td>110</td><td>24.173</td><td>24.173</td></tr> <tr><td>120</td><td>24.173</td><td>24.173</td></tr> <tr><td>132</td><td>24.173</td><td>24.172</td></tr> <tr><td>140</td><td>24.173</td><td>24.172</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	24.173	24.173	80	24.173	24.173	85	24.173	24.173	90	24.173	24.173	100	24.173	24.173	110	24.173	24.173	120	24.173	24.173	132	24.173	24.172	140	24.173	24.172
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	24.173	24.173																																
80	24.173	24.173																																
85	24.173	24.173																																
90	24.173	24.173																																
100	24.173	24.173																																
110	24.173	24.173																																
120	24.173	24.173																																
132	24.173	24.172																																
140	24.173	24.172																																
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																		

**COSEL**

Model	LCA50S-24-H																																																												
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																										
Output	_____																																																												
1. Graph																																																													
<p>The graph plots Input Current [A] on the Y-axis (0 to 2) against Load Current [A] on the X-axis (0 to 3). Three curves are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). All curves show a positive linear relationship between input and load currents. A slanted line is drawn across the graph, representing the rated load current range.</p>																																																													
2. Values			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.055</td><td>0.057</td><td>0.062</td></tr> <tr><td>0.40</td><td>0.299</td><td>0.275</td><td>0.241</td></tr> <tr><td>0.80</td><td>0.523</td><td>0.470</td><td>0.396</td></tr> <tr><td>1.20</td><td>0.744</td><td>0.663</td><td>0.550</td></tr> <tr><td>1.60</td><td>0.962</td><td>0.853</td><td>0.701</td></tr> <tr><td>2.00</td><td>1.181</td><td>1.042</td><td>0.852</td></tr> <tr><td>2.40</td><td>1.403</td><td>1.235</td><td>1.005</td></tr> <tr><td>2.50</td><td>1.458</td><td>1.282</td><td>1.041</td></tr> <tr><td>2.75</td><td>1.597</td><td>1.393</td><td>1.127</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.055	0.057	0.062	0.40	0.299	0.275	0.241	0.80	0.523	0.470	0.396	1.20	0.744	0.663	0.550	1.60	0.962	0.853	0.701	2.00	1.181	1.042	0.852	2.40	1.403	1.235	1.005	2.50	1.458	1.282	1.041	2.75	1.597	1.393	1.127	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																												
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																										
0.00	0.055	0.057	0.062																																																										
0.40	0.299	0.275	0.241																																																										
0.80	0.523	0.470	0.396																																																										
1.20	0.744	0.663	0.550																																																										
1.60	0.962	0.853	0.701																																																										
2.00	1.181	1.042	0.852																																																										
2.40	1.403	1.235	1.005																																																										
2.50	1.458	1.282	1.041																																																										
2.75	1.597	1.393	1.127																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
Note: Slanted line shows the range of the rated load current																																																													
(注)斜線は定格負荷電流範囲を示す。																																																													

COSEL

Model	LCA50S-24-H																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Output	—																																																									
1. Graph	<p>—△— Input Volt. 85V        —□— Input Volt. 100V        —○— Input Volt. 132V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.86</td><td>2.19</td><td>2.98</td></tr> <tr><td>0.40</td><td>13.30</td><td>13.86</td><td>15.02</td></tr> <tr><td>0.80</td><td>24.67</td><td>25.06</td><td>26.14</td></tr> <tr><td>1.20</td><td>36.11</td><td>36.38</td><td>37.36</td></tr> <tr><td>1.60</td><td>47.71</td><td>47.79</td><td>48.50</td></tr> <tr><td>2.00</td><td>59.61</td><td>59.45</td><td>59.90</td></tr> <tr><td>2.40</td><td>72.04</td><td>71.55</td><td>71.60</td></tr> <tr><td>2.50</td><td>75.08</td><td>74.50</td><td>74.50</td></tr> <tr><td>2.75</td><td>83.10</td><td>82.35</td><td>82.10</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	1.86	2.19	2.98	0.40	13.30	13.86	15.02	0.80	24.67	25.06	26.14	1.20	36.11	36.38	37.36	1.60	47.71	47.79	48.50	2.00	59.61	59.45	59.90	2.40	72.04	71.55	71.60	2.50	75.08	74.50	74.50	2.75	83.10	82.35	82.10	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	1.86	2.19	2.98																																																							
0.40	13.30	13.86	15.02																																																							
0.80	24.67	25.06	26.14																																																							
1.20	36.11	36.38	37.36																																																							
1.60	47.71	47.79	48.50																																																							
2.00	59.61	59.45	59.90																																																							
2.40	72.04	71.55	71.60																																																							
2.50	75.08	74.50	74.50																																																							
2.75	83.10	82.35	82.10																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

**COSEL**

Temperature 25°C  
Testing Circuitry Figure A


**COSEL**

Model LCA50S-24-H

Item Efficiency (by Load Current)  
効率 (負荷特性)

Output \_\_\_\_\_

## 1. Graph



Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.40	73.5	70.4	65.0
0.80	78.8	77.6	74.4
1.20	81.0	80.4	78.2
1.60	81.5	81.4	80.2
2.00	81.4	81.7	81.0
2.40	80.9	81.5	81.5
2.50	80.8	81.5	81.5
2.75	80.4	81.1	81.3
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

**COSSEL**


Model	LCA50S-24-H		Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+24.0V 2.5A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>16</td><td>6</td></tr> <tr><td>80</td><td>21</td><td>9</td></tr> <tr><td>85</td><td>27</td><td>11</td></tr> <tr><td>90</td><td>32</td><td>14</td></tr> <tr><td>100</td><td>45</td><td>21</td></tr> <tr><td>110</td><td>59</td><td>28</td></tr> <tr><td>120</td><td>75</td><td>36</td></tr> <tr><td>132</td><td>96</td><td>47</td></tr> <tr><td>140</td><td>110</td><td>55</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	16	6	80	21	9	85	27	11	90	32	14	100	45	21	110	59	28	120	75	36	132	96	47	140	110	55
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	16	6																																	
80	21	9																																	
85	27	11																																	
90	32	14																																	
100	45	21																																	
110	59	28																																	
120	75	36																																	
132	96	47																																	
140	110	55																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	LCA50S-24-H
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+24.0V 2.5A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

## 2. Values


Load Current [A]	Time [mS]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	—	—	—
0.40	88	140	281
0.80	37	64	143
1.20	22	43	97
1.60	14	31	72
2.00	12	22	56
2.40	5	19	47
2.50	5	14	44
2.75	5	14	39
—	—	—	—
—	—	—	—

**COSEL**

Model	LCA50S-24-H																																																	
Item	Load Regulation 靜的負荷変動	Temperature Testing Circuitry	25°C Figure A																																															
Object	+24.0V 2.5A																																																	
1. Graph																																																		
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85 V (solid line)</li> <li>Input Volt. 100 V (dashed line)</li> <li>Input Volt. 132 V (dotted line)</li> </ul>																																																		
2. Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>24.177</td><td>24.177</td><td>24.176</td></tr> <tr> <td>0.40</td><td>24.176</td><td>24.176</td><td>24.175</td></tr> <tr> <td>0.80</td><td>24.175</td><td>24.175</td><td>24.175</td></tr> <tr> <td>1.20</td><td>24.175</td><td>24.175</td><td>24.175</td></tr> <tr> <td>1.60</td><td>24.175</td><td>24.175</td><td>24.174</td></tr> <tr> <td>2.00</td><td>24.175</td><td>24.175</td><td>24.174</td></tr> <tr> <td>2.40</td><td>24.175</td><td>24.175</td><td>24.174</td></tr> <tr> <td>2.50</td><td>24.175</td><td>24.175</td><td>24.174</td></tr> <tr> <td>2.75</td><td>24.175</td><td>24.174</td><td>24.174</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	24.177	24.177	24.176	0.40	24.176	24.176	24.175	0.80	24.175	24.175	24.175	1.20	24.175	24.175	24.175	1.60	24.175	24.175	24.174	2.00	24.175	24.175	24.174	2.40	24.175	24.175	24.174	2.50	24.175	24.175	24.174	2.75	24.175	24.174	24.174	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.00	24.177	24.177	24.176																																															
0.40	24.176	24.176	24.175																																															
0.80	24.175	24.175	24.175																																															
1.20	24.175	24.175	24.175																																															
1.60	24.175	24.175	24.174																																															
2.00	24.175	24.175	24.174																																															
2.40	24.175	24.175	24.174																																															
2.50	24.175	24.175	24.174																																															
2.75	24.175	24.174	24.174																																															
—	—	—	—																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																		

COSEL

Model	LCA50S-24-H
Item	Ripple Voltage(by Load Current) リップル電圧(負荷特性)
Object	+24.0V 2.5A

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple Output Voltage [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	10	10
0.4	20	20
0.8	25	25
1.2	25	25
1.6	25	25
2.0	30	30
2.5	40	30
3.0	40	30
—	—	—
—	—	—
—	—	—

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line  
入力商用周期

T2: Due to Switching  
スイッチング周期





Fig. Complex Ripple Wave Form

図 リップル波形詳細図

**COSEL**

Model	LCA50S-24-H
Item	Ripple-Noise リップルノイズ
Object	+24.0V 2.5A

 Temperature 25°C  
 Testing Circuitry Figure A


## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	10	10
0.4	25	25
0.8	30	35
1.2	35	35
1.6	35	35
2.0	40	35
2.5	45	40
3.0	45	40
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図p-p値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line

入力商用周期

T2: Due to Switching

スイッチング周期




Fig. Complex Ripple Wave Form

図 リップル波形詳細図


**COSEL**

Model LCA50S-24-H

Item Overcurrent Protection  
過電流保護

Object +24.0V 2.5A

## 1. Graph



Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
24.00	3.511	3.514	3.554
22.80	3.530	3.527	3.566
21.60	3.540	3.535	3.574
19.20	3.553	3.550	3.595
16.80	3.571	3.562	3.614
14.40	3.572	3.580	3.633
12.00	3.582	3.595	3.649
9.60	3.589	3.606	3.657
7.20	3.587	3.605	3.650
4.80	3.561	3.575	3.611
2.40	3.478	3.487	3.535
0.00	3.976	4.121	4.503

**COSSEL**

Model	LCA50S-24-H																																																					
Item	Overvoltage Protection 過電圧保護																																																					
Object	+24.0V 2.5A																																																					
Testing Circuitry      Figure A																																																						
1. Graph																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>30.10</td><td>30.10</td><td>30.10</td></tr> <tr><td>-10</td><td>30.34</td><td>30.34</td><td>30.34</td></tr> <tr><td>0</td><td>30.63</td><td>30.63</td><td>30.63</td></tr> <tr><td>10</td><td>30.87</td><td>30.87</td><td>30.87</td></tr> <tr><td>20</td><td>31.17</td><td>31.17</td><td>31.17</td></tr> <tr><td>25</td><td>31.29</td><td>31.29</td><td>31.29</td></tr> <tr><td>30</td><td>31.41</td><td>31.41</td><td>31.41</td></tr> <tr><td>40</td><td>31.65</td><td>31.65</td><td>31.71</td></tr> <tr><td>50</td><td>31.95</td><td>31.95</td><td>31.95</td></tr> <tr><td>60</td><td>32.18</td><td>32.18</td><td>32.18</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	30.10	30.10	30.10	-10	30.34	30.34	30.34	0	30.63	30.63	30.63	10	30.87	30.87	30.87	20	31.17	31.17	31.17	25	31.29	31.29	31.29	30	31.41	31.41	31.41	40	31.65	31.65	31.71	50	31.95	31.95	31.95	60	32.18	32.18	32.18	—	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	30.10	30.10	30.10																																																			
-10	30.34	30.34	30.34																																																			
0	30.63	30.63	30.63																																																			
10	30.87	30.87	30.87																																																			
20	31.17	31.17	31.17																																																			
25	31.29	31.29	31.29																																																			
30	31.41	31.41	31.41																																																			
40	31.65	31.65	31.71																																																			
50	31.95	31.95	31.95																																																			
60	32.18	32.18	32.18																																																			
—	—	—	—																																																			
<p style="text-align: center;">Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																																						

**COSEL**

Model LCA50S-24-H

Item Inrush Current 突入電流


Object

Temperature  
Testing Circuitry25°C  
Figure AInput  
Current

[20A/div]

Input  
Voltage

[200V/div]



Input Voltage 100 V


Frequency 60 Hz


Load 100 %


Inrush Current

① 23.58 [A]

② 3.98 [A]



**COSEL**


**COSEL**

**COSEL**

Model	LCA50S-24-H
Item	Rise and Fall Time 立上り、立下り時間
Object	+24.0V 2.5A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		126.5	18.5	145.0	26.7	32.7	
100 %		126.8	18.5	145.3	11.4	16.8	



**COSEL**

Model	LCA50S-24-H
Item	Ambient Temperature Drift 周囲温度変動
Object	+24.0V 2.5A



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	24.214	24.214	24.214
-10	24.210	24.210	24.210
0	24.204	24.203	24.203
10	24.194	24.194	24.193
20	24.182	24.182	24.182
25	24.176	24.176	24.175
30	24.168	24.168	24.167
40	24.152	24.152	24.151
50	24.135	24.135	24.134
60	24.118	24.118	24.117
—	—	—	—

**COSEL**

Model	LCA50S-24-H
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+24.0V 2.5A



Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	65	71
-10	62	69
0	62	68
10	62	68
20	62	69
25	61	69
30	61	69
40	61	69
50	61	69
60	61	69
—	—	—

**COSEL**



Testing Circuitry Figure A

**COSEL**

Model	LCA50S-24-H	Temperature Testing Circuitry	25°C Figure A																					
Item	Time Lapse Drift 経時ドリフト																							
Object	+24.0V 2.5A																							
1. Graph			2. Values																					
<p>[V]</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Time [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.188</td></tr> <tr><td>0.5</td><td>24.178</td></tr> <tr><td>1.0</td><td>24.178</td></tr> <tr><td>2.0</td><td>24.178</td></tr> <tr><td>3.0</td><td>24.178</td></tr> <tr><td>4.0</td><td>24.178</td></tr> <tr><td>5.0</td><td>24.178</td></tr> <tr><td>6.0</td><td>24.178</td></tr> <tr><td>7.0</td><td>24.178</td></tr> <tr><td>8.0</td><td>24.178</td></tr> </tbody> </table>			Time [H]	Output Voltage [V]	0.0	24.188	0.5	24.178	1.0	24.178	2.0	24.178	3.0	24.178	4.0	24.178	5.0	24.178	6.0	24.178	7.0	24.178	8.0	24.178
Time [H]	Output Voltage [V]																							
0.0	24.188																							
0.5	24.178																							
1.0	24.178																							
2.0	24.178																							
3.0	24.178																							
4.0	24.178																							
5.0	24.178																							
6.0	24.178																							
7.0	24.178																							
8.0	24.178																							
<p>Output Voltage [V]</p> <p>Input Volt. 100V Load 100%</p>																								



Model	LCA50S-24-H
Item	Output Voltage Accuracy 定電圧精度
Object	+24.0V 2.5A

Testing Circuitry

Figure A

## 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage: 85~132 V

Load Current : 0~2.5 A

$$* \text{ Output Voltage Accuracy} = \pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

## 1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~2.5 A

$$* \text{ 定電圧精度(変動値)} = \pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$$

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

## 2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	-10	132	0.0	24.213		
Minimum Voltage	50	132	2.5	24.132	±41	±0.2

COSEL






Figure B (IEC 60950)

**COSSEL**




Figure C




Figure D




Figure E