



TEST DATA OF LDA150W-3

(200V INPUT)

Regulated DC Power Supply

Nov. 27, 2001

Approved by : K. Shibusaki
Design Manager

Prepared by : M. Hamaguchi
Design Engineer

コーセル株式会社

COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Overvoltage Protection	14
過電圧保護	
15. Inrush Current	15
突入電流	
16. Rise and Fall Time	16
立ち上り、立下り時間	
17. Ambient Temperature Drift	17
周囲温度変動	
18. Minimum Input Voltage for Regulated Output Voltage	18
最低レギュレーション電圧	
19. Ripple Voltage (by Ambient Temperature)	19
リップル電圧 (周囲温度特性)	
20. Output Voltage Accuracy	20
定電圧精度	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSEL

Model	LDA150W-3		Temperature Testing Circuitry 25°C Figure A																															
Item	Line Regulation 静的の入力変動																																	
Object	+3.0V 30A																																	
1. Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (□), Load 100% (△)</p>			2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>3.047</td><td>3.046</td></tr> <tr><td>160</td><td>3.047</td><td>3.046</td></tr> <tr><td>170</td><td>3.047</td><td>3.046</td></tr> <tr><td>180</td><td>3.047</td><td>3.046</td></tr> <tr><td>200</td><td>3.047</td><td>3.046</td></tr> <tr><td>220</td><td>3.047</td><td>3.045</td></tr> <tr><td>240</td><td>3.047</td><td>3.046</td></tr> <tr><td>264</td><td>3.047</td><td>3.046</td></tr> <tr><td>280</td><td>3.047</td><td>3.045</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	150	3.047	3.046	160	3.047	3.046	170	3.047	3.046	180	3.047	3.046	200	3.047	3.046	220	3.047	3.045	240	3.047	3.046	264	3.047	3.046	280	3.047	3.045
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
150	3.047	3.046																																
160	3.047	3.046																																
170	3.047	3.046																																
180	3.047	3.046																																
200	3.047	3.046																																
220	3.047	3.045																																
240	3.047	3.046																																
264	3.047	3.046																																
280	3.047	3.045																																
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																		

COSEL

Model	LDA150W-3																																																									
Item	Input Current (by Load Current)	Temperature	25°C																																																							
Object	入力電流（負荷特性） Testing Circuitry Figure A																																																									
1. Graph	<p>Input Volt. 170V Input Volt. 200V Input Volt. 264V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.068</td><td>0.074</td><td>0.082</td></tr> <tr><td>6</td><td>0.317</td><td>0.291</td><td>0.260</td></tr> <tr><td>12</td><td>0.561</td><td>0.503</td><td>0.427</td></tr> <tr><td>18</td><td>0.813</td><td>0.724</td><td>0.601</td></tr> <tr><td>24</td><td>1.070</td><td>0.947</td><td>0.779</td></tr> <tr><td>30</td><td>1.328</td><td>1.169</td><td>0.954</td></tr> <tr><td>33</td><td>1.453</td><td>1.244</td><td>1.009</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	0.068	0.074	0.082	6	0.317	0.291	0.260	12	0.561	0.503	0.427	18	0.813	0.724	0.601	24	1.070	0.947	0.779	30	1.328	1.169	0.954	33	1.453	1.244	1.009	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0	0.068	0.074	0.082																																																							
6	0.317	0.291	0.260																																																							
12	0.561	0.503	0.427																																																							
18	0.813	0.724	0.601																																																							
24	1.070	0.947	0.779																																																							
30	1.328	1.169	0.954																																																							
33	1.453	1.244	1.009																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							


Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA150W-3																																																									
Item	Input Power (by Load Current) 入力電力（負荷特性）	Temperature 25°C	Testing Circuitry Figure A																																																							
Object	_____																																																									
1. Graph	<p>Legend: Input Volt. 170V (triangle), Input Volt. 200V (square), Input Volt. 264V (circle)</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170V [W]</th> <th>Input Volt. 200V [W]</th> <th>Input Volt. 264V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.80</td><td>4.70</td><td>5.90</td></tr> <tr><td>6</td><td>25.70</td><td>26.70</td><td>29.40</td></tr> <tr><td>12</td><td>48.00</td><td>48.80</td><td>51.30</td></tr> <tr><td>18</td><td>71.10</td><td>71.80</td><td>74.00</td></tr> <tr><td>24</td><td>95.00</td><td>95.70</td><td>97.50</td></tr> <tr><td>30</td><td>119.90</td><td>120.40</td><td>121.90</td></tr> <tr><td>33</td><td>132.80</td><td>133.50</td><td>134.70</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170V [W]	Input Volt. 200V [W]	Input Volt. 264V [W]	0	3.80	4.70	5.90	6	25.70	26.70	29.40	12	48.00	48.80	51.30	18	71.10	71.80	74.00	24	95.00	95.70	97.50	30	119.90	120.40	121.90	33	132.80	133.50	134.70																							
Load Current [A]	Input Volt. 170V [W]	Input Volt. 200V [W]	Input Volt. 264V [W]																																																							
0	3.80	4.70	5.90																																																							
6	25.70	26.70	29.40																																																							
12	48.00	48.80	51.30																																																							
18	71.10	71.80	74.00																																																							
24	95.00	95.70	97.50																																																							
30	119.90	120.40	121.90																																																							
33	132.80	133.50	134.70																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.80</td><td>4.70</td><td>5.90</td></tr> <tr><td>6</td><td>25.70</td><td>26.70</td><td>29.40</td></tr> <tr><td>12</td><td>48.00</td><td>48.80</td><td>51.30</td></tr> <tr><td>18</td><td>71.10</td><td>71.80</td><td>74.00</td></tr> <tr><td>24</td><td>95.00</td><td>95.70</td><td>97.50</td></tr> <tr><td>30</td><td>119.90</td><td>120.40</td><td>121.90</td></tr> <tr><td>33</td><td>132.80</td><td>133.50</td><td>134.70</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	3.80	4.70	5.90	6	25.70	26.70	29.40	12	48.00	48.80	51.30	18	71.10	71.80	74.00	24	95.00	95.70	97.50	30	119.90	120.40	121.90	33	132.80	133.50	134.70	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0	3.80	4.70	5.90																																																							
6	25.70	26.70	29.40																																																							
12	48.00	48.80	51.30																																																							
18	71.10	71.80	74.00																																																							
24	95.00	95.70	97.50																																																							
30	119.90	120.40	121.90																																																							
33	132.80	133.50	134.70																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note: Slanted line shows the range of the rated load current.																																																										
(注) 斜線は定格負荷電流範囲を示す。																																																										

COSEL

Model	LDA150W-3		Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																																			
Object	<hr/>																																			
1. Graph	<p style="text-align: center;">Load 50% □ Load 100% ▲</p> 																																			
2. Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>77.7</td><td>75.6</td></tr> <tr><td>160</td><td>77.3</td><td>76.2</td></tr> <tr><td>170</td><td>76.9</td><td>76.3</td></tr> <tr><td>180</td><td>76.7</td><td>76.3</td></tr> <tr><td>200</td><td>75.9</td><td>76.3</td></tr> <tr><td>220</td><td>75.2</td><td>76.1</td></tr> <tr><td>240</td><td>74.2</td><td>76.0</td></tr> <tr><td>264</td><td>73.1</td><td>75.4</td></tr> <tr><td>280</td><td>72.3</td><td>75.1</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	77.7	75.6	160	77.3	76.2	170	76.9	76.3	180	76.7	76.3	200	75.9	76.3	220	75.2	76.1	240	74.2	76.0	264	73.1	75.4	280	72.3	75.1
Input Voltage [V]	Efficiency [%]																																			
	Load 50%	Load 100%																																		
150	77.7	75.6																																		
160	77.3	76.2																																		
170	76.9	76.3																																		
180	76.7	76.3																																		
200	75.9	76.3																																		
220	75.2	76.1																																		
240	74.2	76.0																																		
264	73.1	75.4																																		
280	72.3	75.1																																		
Note:	Slanted line shows the range of the rated input voltage.																																			
(注)	(注)斜線は定格入力電圧範囲を示す。																																			

COSEL

Model	LDA150W-3	Temperature 25°C Testing Circuitry Figure A																																																							
Item	Efficiency (by Load Current) 効率(負荷特性)																																																								
Object	_____																																																								
1. Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend: Input Volt. 170V (triangle), Input Volt. 200V (square), Input Volt. 264V (circle)</p>	2. Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>6</td><td>71.3</td><td>68.6</td><td>62.3</td></tr> <tr><td>12</td><td>76.3</td><td>75.1</td><td>71.4</td></tr> <tr><td>18</td><td>77.4</td><td>76.7</td><td>74.4</td></tr> <tr><td>24</td><td>77.2</td><td>76.7</td><td>75.2</td></tr> <tr><td>30</td><td>76.5</td><td>76.1</td><td>75.2</td></tr> <tr><td>33</td><td>75.9</td><td>75.4</td><td>74.7</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	6	71.3	68.6	62.3	12	76.3	75.1	71.4	18	77.4	76.7	74.4	24	77.2	76.7	75.2	30	76.5	76.1	75.2	33	75.9	75.4	74.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																								
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																						
6	71.3	68.6	62.3																																																						
12	76.3	75.1	71.4																																																						
18	77.4	76.7	74.4																																																						
24	77.2	76.7	75.2																																																						
30	76.5	76.1	75.2																																																						
33	75.9	75.4	74.7																																																						
—	—	—	—																																																						
—	—	—	—																																																						
—	—	—	—																																																						
—	—	—	—																																																						
—	—	—	—																																																						
—	—	—	—																																																						
Note: Slanted line shows the range of the rated load current.																																																									
(注)斜線は定格負荷電流範囲を示す。																																																									

COSEL

Model	LDA150W-3		Temperature 25°C Testing Circuitry Figure A																																
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)																																		
Object																																			
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>0.53</td><td>0.57</td></tr> <tr><td>160</td><td>0.52</td><td>0.54</td></tr> <tr><td>170</td><td>0.52</td><td>0.54</td></tr> <tr><td>180</td><td>0.51</td><td>0.53</td></tr> <tr><td>200</td><td>0.50</td><td>0.51</td></tr> <tr><td>220</td><td>0.49</td><td>0.50</td></tr> <tr><td>240</td><td>0.48</td><td>0.49</td></tr> <tr><td>264</td><td>0.47</td><td>0.48</td></tr> <tr><td>280</td><td>0.46</td><td>0.47</td></tr> </tbody> </table>	Input Voltage [V]	Power Factor		Load 50%	Load 100%	150	0.53	0.57	160	0.52	0.54	170	0.52	0.54	180	0.51	0.53	200	0.50	0.51	220	0.49	0.50	240	0.48	0.49	264	0.47	0.48	280	0.46	0.47
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
150	0.53	0.57																																	
160	0.52	0.54																																	
170	0.52	0.54																																	
180	0.51	0.53																																	
200	0.50	0.51																																	
220	0.49	0.50																																	
240	0.48	0.49																																	
264	0.47	0.48																																	
280	0.46	0.47																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA150W-3	Temperature 25°C Testing Circuitry Figure A																																																									
Item	Power Factor (by Load Current) 力率(負荷特性)																																																										
Object	—																																																										
1. Graph																																																											
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.33</td><td>0.32</td><td>0.27</td></tr> <tr><td>6</td><td>0.48</td><td>0.46</td><td>0.43</td></tr> <tr><td>12</td><td>0.50</td><td>0.49</td><td>0.46</td></tr> <tr><td>18</td><td>0.52</td><td>0.50</td><td>0.47</td></tr> <tr><td>24</td><td>0.52</td><td>0.51</td><td>0.47</td></tr> <tr><td>30</td><td>0.53</td><td>0.51</td><td>0.48</td></tr> <tr><td>33</td><td>0.54</td><td>0.53</td><td>0.50</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	0.33	0.32	0.27	6	0.48	0.46	0.43	12	0.50	0.49	0.46	18	0.52	0.50	0.47	24	0.52	0.51	0.47	30	0.53	0.51	0.48	33	0.54	0.53	0.50	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Power Factor																																																										
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																								
0	0.33	0.32	0.27																																																								
6	0.48	0.46	0.43																																																								
12	0.50	0.49	0.46																																																								
18	0.52	0.50	0.47																																																								
24	0.52	0.51	0.47																																																								
30	0.53	0.51	0.48																																																								
33	0.54	0.53	0.50																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
Note:	Slanted line shows the range of the rated load current.																																																										
(注)	斜線は定格負荷電流範囲を示す。																																																										

COSEL

Model	LDA150W-3	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																	
Object	+3.0V 30A																																	
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p>	2. Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>53</td><td>25</td></tr> <tr><td>160</td><td>63</td><td>30</td></tr> <tr><td>170</td><td>74</td><td>35</td></tr> <tr><td>180</td><td>86</td><td>41</td></tr> <tr><td>200</td><td>111</td><td>54</td></tr> <tr><td>220</td><td>138</td><td>68</td></tr> <tr><td>240</td><td>168</td><td>83</td></tr> <tr><td>264</td><td>208</td><td>103</td></tr> <tr><td>280</td><td>236</td><td>118</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	150	53	25	160	63	30	170	74	35	180	86	41	200	111	54	220	138	68	240	168	83	264	208	103	280	236	118
Input Voltage [V]	Hold-Up Time [mS]																																	
	Load 50%	Load 100%																																
150	53	25																																
160	63	30																																
170	74	35																																
180	86	41																																
200	111	54																																
220	138	68																																
240	168	83																																
264	208	103																																
280	236	118																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																		

COSEL

Model	LDA150W-3	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																					
Object	+3.0V 30A																																																					
1. Graph	<p>—△— Input Volt. 170 V -□- Input Volt. 200 V -○- Input Volt. 264 V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>170[V] [ms]</th> <th>200[V] [ms]</th> <th>264[V] [ms]</th> </tr> </thead> <tbody> <tr><td>5</td><td>~150</td><td>~200</td><td>~300</td></tr> <tr><td>10</td><td>~100</td><td>~150</td><td>~250</td></tr> <tr><td>20</td><td>~60</td><td>~80</td><td>~120</td></tr> <tr><td>30</td><td>~40</td><td>~60</td><td>~100</td></tr> <tr><td>33</td><td>~35</td><td>~50</td><td>~80</td></tr> </tbody> </table>			Load Current [A]	170[V] [ms]	200[V] [ms]	264[V] [ms]	5	~150	~200	~300	10	~100	~150	~250	20	~60	~80	~120	30	~40	~60	~100	33	~35	~50	~80																											
Load Current [A]	170[V] [ms]	200[V] [ms]	264[V] [ms]																																																			
5	~150	~200	~300																																																			
10	~100	~150	~250																																																			
20	~60	~80	~120																																																			
30	~40	~60	~100																																																			
33	~35	~50	~80																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>6</td><td>187</td><td>273</td><td>496</td></tr> <tr><td>12</td><td>95</td><td>140</td><td>264</td></tr> <tr><td>18</td><td>63</td><td>94</td><td>178</td></tr> <tr><td>24</td><td>46</td><td>69</td><td>131</td></tr> <tr><td>30</td><td>35</td><td>54</td><td>104</td></tr> <tr><td>33</td><td>31</td><td>48</td><td>93</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	—	—	—	6	187	273	496	12	95	140	264	18	63	94	178	24	46	69	131	30	35	54	104	33	31	48	93	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0	—	—	—																																																			
6	187	273	496																																																			
12	95	140	264																																																			
18	63	94	178																																																			
24	46	69	131																																																			
30	35	54	104																																																			
33	31	48	93																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																						

COSEL

Model	LDA150W-3	Temperature Testing Circuitry	25°C																																															
Item	Load Regulation 静的負荷変動		Figure A																																															
Object	+3.0V 30A	2. Values																																																
1. Graph	<p>—△— Input Volt. 170 V —□— Input Volt. 200 V —○— Input Volt. 264 V</p>																																																	
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>3.049</td> <td>3.049</td> <td>3.049</td> </tr> <tr> <td>6</td> <td>3.048</td> <td>3.048</td> <td>3.048</td> </tr> <tr> <td>12</td> <td>3.048</td> <td>3.048</td> <td>3.048</td> </tr> <tr> <td>18</td> <td>3.047</td> <td>3.047</td> <td>3.047</td> </tr> <tr> <td>24</td> <td>3.046</td> <td>3.046</td> <td>3.046</td> </tr> <tr> <td>30</td> <td>3.046</td> <td>3.046</td> <td>3.046</td> </tr> <tr> <td>33</td> <td>3.045</td> <td>3.045</td> <td>3.045</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	3.049	3.049	3.049	6	3.048	3.048	3.048	12	3.048	3.048	3.048	18	3.047	3.047	3.047	24	3.046	3.046	3.046	30	3.046	3.046	3.046	33	3.045	3.045	3.045	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																															
0	3.049	3.049	3.049																																															
6	3.048	3.048	3.048																																															
12	3.048	3.048	3.048																																															
18	3.047	3.047	3.047																																															
24	3.046	3.046	3.046																																															
30	3.046	3.046	3.046																																															
33	3.045	3.045	3.045																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															


Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA150W-3	Temperature Testing Circuitry	25°C Figure A																																					
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)																																							
Object	+3.0V30A																																							
1. Graph	—△— Input Volt. 170V [mV] —○— Input Volt. 264V	2. Values																																						
<p>The graph shows two sets of data points for Ripple Voltage (mV) versus Load Current (A). The first set, represented by triangles, corresponds to an input voltage of 170V. The second set, represented by circles, corresponds to an input voltage of 264V. Both sets show an increase in ripple voltage as load current increases, with a slight dip around 30A. A dashed line indicates the range of the rated load current.</p>																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 170 [V]</th> <th>Input Volt. 264 [V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>10</td> <td>10</td> </tr> <tr> <td>4</td> <td>20</td> <td>25</td> </tr> <tr> <td>8</td> <td>20</td> <td>30</td> </tr> <tr> <td>12</td> <td>25</td> <td>35</td> </tr> <tr> <td>16</td> <td>30</td> <td>40</td> </tr> <tr> <td>20</td> <td>30</td> <td>40</td> </tr> <tr> <td>24</td> <td>35</td> <td>45</td> </tr> <tr> <td>28</td> <td>35</td> <td>45</td> </tr> <tr> <td>30</td> <td>40</td> <td>50</td> </tr> <tr> <td>33</td> <td>45</td> <td>55</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 170 [V]	Input Volt. 264 [V]	0	10	10	4	20	25	8	20	30	12	25	35	16	30	40	20	30	40	24	35	45	28	35	45	30	40	50	33	45	55	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																							
	Input Volt. 170 [V]	Input Volt. 264 [V]																																						
0	10	10																																						
4	20	25																																						
8	20	30																																						
12	25	35																																						
16	30	40																																						
20	30	40																																						
24	35	45																																						
28	35	45																																						
30	40	50																																						
33	45	55																																						
—	—	—																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p> <p>Fig. Complex Ripple Wave Form</p> <p>図 リップル波形詳細図</p>																																								

LDA150W-3		Temperature Testing Circuitry	25°C Figure A
Model	LDA150W-3		
Item	Ripple-Noise リップルノイズ		



Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 $p - p$ 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
 入力商用周期

T2: Due to Switching
 スイッチング周期






Fig. Complex Ripple Wave Form
図 リップル波形詳細図

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 170 [V]	Input Volt. 264 [V]
0	20	25
4	40	45
8	45	50
12	50	60
16	50	65
20	55	70
24	55	75
28	60	80
30	70	90
33	75	95
—	—	—

COSSEL


Model	LDA150W-3	Temperature Testing Circuitry 25°C Figure A																																																									
Item	Overcurrent Protection 過電流保護																																																										
Object	+3.0V 30A																																																										
1. Graph																																																											
[V]		Input Volt. 170 V Input Volt. 200 V Input Volt. 264 V																																																									
Output Voltage [V]																																																											
Load Current [A]																																																											
Note: Slanted line shows the range of the rated load current.																																																											
(注) 斜線は定格負荷電流範囲を示す。																																																											
2. Values			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>3.00</td> <td>38.97</td> <td>39.13</td> <td>39.16</td> </tr> <tr> <td>2.85</td> <td>39.22</td> <td>39.18</td> <td>39.36</td> </tr> <tr> <td>2.70</td> <td>39.25</td> <td>39.27</td> <td>39.46</td> </tr> <tr> <td>2.40</td> <td>39.37</td> <td>39.53</td> <td>39.71</td> </tr> <tr> <td>2.10</td> <td>39.60</td> <td>39.69</td> <td>39.96</td> </tr> <tr> <td>1.80</td> <td>39.82</td> <td>39.92</td> <td>40.22</td> </tr> <tr> <td>1.50</td> <td>40.02</td> <td>40.09</td> <td>40.10</td> </tr> <tr> <td>1.20</td> <td>40.29</td> <td>40.09</td> <td>40.63</td> </tr> <tr> <td>0.90</td> <td>40.53</td> <td>40.54</td> <td>40.52</td> </tr> <tr> <td>0.60</td> <td>40.45</td> <td>40.34</td> <td>40.13</td> </tr> <tr> <td>0.30</td> <td>39.93</td> <td>39.67</td> <td>38.86</td> </tr> <tr> <td>0.00</td> <td>39.21</td> <td>38.91</td> <td>38.20</td> </tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	3.00	38.97	39.13	39.16	2.85	39.22	39.18	39.36	2.70	39.25	39.27	39.46	2.40	39.37	39.53	39.71	2.10	39.60	39.69	39.96	1.80	39.82	39.92	40.22	1.50	40.02	40.09	40.10	1.20	40.29	40.09	40.63	0.90	40.53	40.54	40.52	0.60	40.45	40.34	40.13	0.30	39.93	39.67	38.86	0.00	39.21	38.91	38.20
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																								
3.00	38.97	39.13	39.16																																																								
2.85	39.22	39.18	39.36																																																								
2.70	39.25	39.27	39.46																																																								
2.40	39.37	39.53	39.71																																																								
2.10	39.60	39.69	39.96																																																								
1.80	39.82	39.92	40.22																																																								
1.50	40.02	40.09	40.10																																																								
1.20	40.29	40.09	40.63																																																								
0.90	40.53	40.54	40.52																																																								
0.60	40.45	40.34	40.13																																																								
0.30	39.93	39.67	38.86																																																								
0.00	39.21	38.91	38.20																																																								

COSEL

Model	LDA150W-3	Testing Circuitry Figure A					
Item	Overvoltage Protection 過電圧保護						
Object	+3.0V 30A						
1. Graph							
		Input Volt. 170 V  Input Volt. 200 V  Input Volt. 264 V 					
	[V]						
							
		Load 0%					
Note: Slanted line shows the range of the rated ambient temperature.							
(注) 斜線は定格周囲温度範囲を示す。							
2. Values							
Ambient Temperature [°C]	Operating Point [V]						
	Input Volt.	Input Volt.	Input Volt.				
170[V]	200[V]	264[V]					
-20	4.92	4.92	4.92				
-10	4.85	4.85	4.85				
0	4.86	4.85	4.85				
10	4.79	4.79	4.79				
20	4.72	4.72	4.72				
25	4.72	4.72	4.71				
30	4.71	4.71	4.71				
40	4.65	4.65	4.65				
50	4.65	4.64	4.64				
60	4.58	4.57	4.57				
—	—	—	—				


COSEL

Model	LDA150W-3	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object			



Input Voltage 200 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current

- ① 33.54 [A]
- ② 3.14 [A]




COSSEL

Model	LDA150W-3
Item	Rise and Fall Time 立上り、立下り時間
Object	+3.0V 30A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		117.5	1.3	118.8	73.8	4.9	
100 %		117.5	1.5	119.0	35.3	2.6	




COSEL

Model	LDA150W-3	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+3.0V 30A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>3.038</td> <td>3.038</td> <td>3.038</td> </tr> <tr> <td>-10</td> <td>3.040</td> <td>3.040</td> <td>3.040</td> </tr> <tr> <td>0</td> <td>3.041</td> <td>3.041</td> <td>3.041</td> </tr> <tr> <td>10</td> <td>3.043</td> <td>3.043</td> <td>3.043</td> </tr> <tr> <td>20</td> <td>3.044</td> <td>3.044</td> <td>3.044</td> </tr> <tr> <td>25</td> <td>3.045</td> <td>3.045</td> <td>3.045</td> </tr> <tr> <td>30</td> <td>3.045</td> <td>3.045</td> <td>3.045</td> </tr> <tr> <td>40</td> <td>3.046</td> <td>3.046</td> <td>3.046</td> </tr> <tr> <td>50</td> <td>3.046</td> <td>3.046</td> <td>3.046</td> </tr> <tr> <td>60</td> <td>3.047</td> <td>3.047</td> <td>3.047</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-20	3.038	3.038	3.038	-10	3.040	3.040	3.040	0	3.041	3.041	3.041	10	3.043	3.043	3.043	20	3.044	3.044	3.044	25	3.045	3.045	3.045	30	3.045	3.045	3.045	40	3.046	3.046	3.046	50	3.046	3.046	3.046	60	3.047	3.047	3.047	--	--	--	--
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
-20	3.038	3.038	3.038																																																				
-10	3.040	3.040	3.040																																																				
0	3.041	3.041	3.041																																																				
10	3.043	3.043	3.043																																																				
20	3.044	3.044	3.044																																																				
25	3.045	3.045	3.045																																																				
30	3.045	3.045	3.045																																																				
40	3.046	3.046	3.046																																																				
50	3.046	3.046	3.046																																																				
60	3.047	3.047	3.047																																																				
--	--	--	--																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						
(注)	斜線は定格周囲温度範囲を示す。																																																						

COSEL

Model	LDA150W-3			
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧			
Object	+3.0V 30A			
1. Graph				
[V]		□ Load 50%	△ Load 100%	
Note: Slanted line shows the range of the rated ambient temperature.				
(注) 斜線は定格周囲温度範囲を示す。				
Testing Circuitry Figure A				
2. Values				
Ambient Temperature [°C]	Input Voltage [V]			
	Load	50%	Load	100%
-20	48	56		
-10	48	56		
0	47	56		
10	47	55		
20	46	55		
25	46	55		
30	46	55		
40	46	55		
50	46	55		
60	46	55		
—	—	—	—	—

COSEL



Testing Circuitry Figure A



Model	LDA150W-3	
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry Figure A
Object	+3.0V 30A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 170~264 V

Load Current : 0~30 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 170~264 V

負荷電流 0~30 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	50	200	0	3.050		
Minimum Voltage	-10	170	30	3.040	±5	±0.2


COSEL

Figure A