



TEST DATA OF LDA15F-12

(100V INPUT)

Regulated DC Power Supply

Date : June 23. 1999

Approved by : H. Yamaguchi
Design Manager

Prepared by : T. Ashihara
Design Engineer

コーワセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
10. Ripple-Noise	10
リップルノイズ	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Dynamic Load Response	13
動的負荷変動	
14. Rise and Fall Time	14
立ち上り、立下がり時間	
15. Ambient Temperature Drift	15
周囲温度変動	
16. Minimum Input Voltage for Regulated Output Voltage	16
最低レギュレーション電圧	
17. Ripple Voltage (by Ambient Temperature)	17
リップル電圧 (周囲温度特性)	
18. Time Lapse Drift	18
経時ドリフト	
19. Output Voltage Accuracy	19
定電圧精度	
20. Condensation	20
結露特性	
21. Leakage Current	21
漏洩電流	
22. Line Noise Tolerance	22
入力雑音耐量	
23. Conducted Emission	23
雑音端子電圧	
24. Figure of Testing Circuitry	24
測定回路図	

(Final Page 25)

COSEL

Model	LDA15F-12		Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation 靜的入力変動																																		
Object	+12.0V 1.3A																																		
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>12.072</td><td>12.066</td></tr> <tr><td>80</td><td>12.072</td><td>12.067</td></tr> <tr><td>85</td><td>12.072</td><td>12.067</td></tr> <tr><td>90</td><td>12.072</td><td>12.067</td></tr> <tr><td>100</td><td>12.071</td><td>12.067</td></tr> <tr><td>110</td><td>12.071</td><td>12.067</td></tr> <tr><td>120</td><td>12.071</td><td>12.067</td></tr> <tr><td>132</td><td>12.071</td><td>12.067</td></tr> <tr><td>140</td><td>12.071</td><td>12.067</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	12.072	12.066	80	12.072	12.067	85	12.072	12.067	90	12.072	12.067	100	12.071	12.067	110	12.071	12.067	120	12.071	12.067	132	12.071	12.067	140	12.071	12.067
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	12.072	12.066																																	
80	12.072	12.067																																	
85	12.072	12.067																																	
90	12.072	12.067																																	
100	12.071	12.067																																	
110	12.071	12.067																																	
120	12.071	12.067																																	
132	12.071	12.067																																	
140	12.071	12.067																																	


Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA15F-12
Item	Input Current (by Load Current) 入力電流 (負荷特性)
Output	—

1. Graph



Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	0.025	0.024	0.024
0.20	0.087	0.080	0.071
0.40	0.140	0.127	0.109
0.60	0.196	0.174	0.145
0.80	0.253	0.223	0.183
1.00	0.310	0.271	0.220
1.20	0.368	0.321	0.258
1.30	0.399	0.346	0.278
1.43	0.439	0.380	0.304
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	LDA15F-12																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																							
Output	_____																																																									
1. Graph	<p style="text-align: center;"> △ Input Volt. 85V □ Input Volt. 100V ○ Input Volt. 132V </p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power 85V [W]</th> <th>Input Power 100V [W]</th> <th>Input Power 132V [W]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.83</td><td>0.90</td><td>1.13</td></tr> <tr><td>0.20</td><td>3.82</td><td>3.94</td><td>4.27</td></tr> <tr><td>0.40</td><td>6.70</td><td>6.77</td><td>7.10</td></tr> <tr><td>0.60</td><td>9.76</td><td>9.74</td><td>9.92</td></tr> <tr><td>0.80</td><td>12.95</td><td>12.82</td><td>12.85</td></tr> <tr><td>1.00</td><td>16.16</td><td>15.89</td><td>15.77</td></tr> <tr><td>1.20</td><td>19.50</td><td>19.11</td><td>18.81</td></tr> <tr><td>1.30</td><td>21.23</td><td>20.75</td><td>20.37</td></tr> <tr><td>1.43</td><td>23.57</td><td>22.98</td><td>22.43</td></tr> </tbody> </table>			Load Current [A]	Input Power 85V [W]	Input Power 100V [W]	Input Power 132V [W]	0.00	0.83	0.90	1.13	0.20	3.82	3.94	4.27	0.40	6.70	6.77	7.10	0.60	9.76	9.74	9.92	0.80	12.95	12.82	12.85	1.00	16.16	15.89	15.77	1.20	19.50	19.11	18.81	1.30	21.23	20.75	20.37	1.43	23.57	22.98	22.43															
Load Current [A]	Input Power 85V [W]	Input Power 100V [W]	Input Power 132V [W]																																																							
0.00	0.83	0.90	1.13																																																							
0.20	3.82	3.94	4.27																																																							
0.40	6.70	6.77	7.10																																																							
0.60	9.76	9.74	9.92																																																							
0.80	12.95	12.82	12.85																																																							
1.00	16.16	15.89	15.77																																																							
1.20	19.50	19.11	18.81																																																							
1.30	21.23	20.75	20.37																																																							
1.43	23.57	22.98	22.43																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.83</td><td>0.90</td><td>1.13</td></tr> <tr><td>0.20</td><td>3.82</td><td>3.94</td><td>4.27</td></tr> <tr><td>0.40</td><td>6.70</td><td>6.77</td><td>7.10</td></tr> <tr><td>0.60</td><td>9.76</td><td>9.74</td><td>9.92</td></tr> <tr><td>0.80</td><td>12.95</td><td>12.82</td><td>12.85</td></tr> <tr><td>1.00</td><td>16.16</td><td>15.89</td><td>15.77</td></tr> <tr><td>1.20</td><td>19.50</td><td>19.11</td><td>18.81</td></tr> <tr><td>1.30</td><td>21.23</td><td>20.75</td><td>20.37</td></tr> <tr><td>1.43</td><td>23.57</td><td>22.98</td><td>22.43</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.83	0.90	1.13	0.20	3.82	3.94	4.27	0.40	6.70	6.77	7.10	0.60	9.76	9.74	9.92	0.80	12.95	12.82	12.85	1.00	16.16	15.89	15.77	1.20	19.50	19.11	18.81	1.30	21.23	20.75	20.37	1.43	23.57	22.98	22.43	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.00	0.83	0.90	1.13																																																							
0.20	3.82	3.94	4.27																																																							
0.40	6.70	6.77	7.10																																																							
0.60	9.76	9.74	9.92																																																							
0.80	12.95	12.82	12.85																																																							
1.00	16.16	15.89	15.77																																																							
1.20	19.50	19.11	18.81																																																							
1.30	21.23	20.75	20.37																																																							
1.43	23.57	22.98	22.43																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA15F-12																																	
Item	Efficiency 効率	Temperature 25°C Testing Circuitry Figure A																																
Object	_____																																	
1. Graph																																		
<p>[%]</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>74.8</td><td>72.0</td></tr> <tr><td>80</td><td>74.9</td><td>73.4</td></tr> <tr><td>85</td><td>75.3</td><td>74.3</td></tr> <tr><td>90</td><td>75.5</td><td>75.1</td></tr> <tr><td>100</td><td>75.7</td><td>76.1</td></tr> <tr><td>110</td><td>75.6</td><td>76.8</td></tr> <tr><td>120</td><td>75.2</td><td>77.3</td></tr> <tr><td>132</td><td>74.6</td><td>77.6</td></tr> <tr><td>140</td><td>74.0</td><td>77.6</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	75	74.8	72.0	80	74.9	73.4	85	75.3	74.3	90	75.5	75.1	100	75.7	76.1	110	75.6	76.8	120	75.2	77.3	132	74.6	77.6	140	74.0	77.6			
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
75	74.8	72.0																																
80	74.9	73.4																																
85	75.3	74.3																																
90	75.5	75.1																																
100	75.7	76.1																																
110	75.6	76.8																																
120	75.2	77.3																																
132	74.6	77.6																																
140	74.0	77.6																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>74.8</td><td>72.0</td></tr> <tr><td>80</td><td>74.9</td><td>73.4</td></tr> <tr><td>85</td><td>75.3</td><td>74.3</td></tr> <tr><td>90</td><td>75.5</td><td>75.1</td></tr> <tr><td>100</td><td>75.7</td><td>76.1</td></tr> <tr><td>110</td><td>75.6</td><td>76.8</td></tr> <tr><td>120</td><td>75.2</td><td>77.3</td></tr> <tr><td>132</td><td>74.6</td><td>77.6</td></tr> <tr><td>140</td><td>74.0</td><td>77.6</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	74.8	72.0	80	74.9	73.4	85	75.3	74.3	90	75.5	75.1	100	75.7	76.1	110	75.6	76.8	120	75.2	77.3	132	74.6	77.6	140	74.0	77.6
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	74.8	72.0																																
80	74.9	73.4																																
85	75.3	74.3																																
90	75.5	75.1																																
100	75.7	76.1																																
110	75.6	76.8																																
120	75.2	77.3																																
132	74.6	77.6																																
140	74.0	77.6																																

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model	LDA15F-12																																																									
Item	Efficiency (by Load Current) 効率(負荷電流特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Output	_____																																																									
1. Graph	<p>Legend: Input Volt. 85V (△), Input Volt. 100V (□), Input Volt. 132V (○)</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.20</td><td>63.6</td><td>61.9</td><td>57.1</td></tr> <tr><td>0.40</td><td>72.7</td><td>72.0</td><td>68.8</td></tr> <tr><td>0.60</td><td>74.9</td><td>75.1</td><td>73.8</td></tr> <tr><td>0.80</td><td>75.3</td><td>76.2</td><td>75.9</td></tr> <tr><td>1.00</td><td>75.1</td><td>76.4</td><td>77.0</td></tr> <tr><td>1.20</td><td>74.6</td><td>76.1</td><td>77.4</td></tr> <tr><td>1.30</td><td>74.3</td><td>76.0</td><td>77.4</td></tr> <tr><td>1.43</td><td>73.7</td><td>75.6</td><td>77.4</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.20	63.6	61.9	57.1	0.40	72.7	72.0	68.8	0.60	74.9	75.1	73.8	0.80	75.3	76.2	75.9	1.00	75.1	76.4	77.0	1.20	74.6	76.1	77.4	1.30	74.3	76.0	77.4	1.43	73.7	75.6	77.4																			
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.20	63.6	61.9	57.1																																																							
0.40	72.7	72.0	68.8																																																							
0.60	74.9	75.1	73.8																																																							
0.80	75.3	76.2	75.9																																																							
1.00	75.1	76.4	77.0																																																							
1.20	74.6	76.1	77.4																																																							
1.30	74.3	76.0	77.4																																																							
1.43	73.7	75.6	77.4																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.20</td><td>63.6</td><td>61.9</td><td>57.1</td></tr> <tr><td>0.40</td><td>72.7</td><td>72.0</td><td>68.8</td></tr> <tr><td>0.60</td><td>74.9</td><td>75.1</td><td>73.8</td></tr> <tr><td>0.80</td><td>75.3</td><td>76.2</td><td>75.9</td></tr> <tr><td>1.00</td><td>75.1</td><td>76.4</td><td>77.0</td></tr> <tr><td>1.20</td><td>74.6</td><td>76.1</td><td>77.4</td></tr> <tr><td>1.30</td><td>74.3</td><td>76.0</td><td>77.4</td></tr> <tr><td>1.43</td><td>73.7</td><td>75.6</td><td>77.4</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.20	63.6	61.9	57.1	0.40	72.7	72.0	68.8	0.60	74.9	75.1	73.8	0.80	75.3	76.2	75.9	1.00	75.1	76.4	77.0	1.20	74.6	76.1	77.4	1.30	74.3	76.0	77.4	1.43	73.7	75.6	77.4	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.20	63.6	61.9	57.1																																																							
0.40	72.7	72.0	68.8																																																							
0.60	74.9	75.1	73.8																																																							
0.80	75.3	76.2	75.9																																																							
1.00	75.1	76.4	77.0																																																							
1.20	74.6	76.1	77.4																																																							
1.30	74.3	76.0	77.4																																																							
1.43	73.7	75.6	77.4																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA15F-12		Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+12.0V 1.3A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>28</td><td>9</td></tr> <tr><td>80</td><td>33</td><td>12</td></tr> <tr><td>85</td><td>38</td><td>15</td></tr> <tr><td>90</td><td>43</td><td>17</td></tr> <tr><td>100</td><td>54</td><td>23</td></tr> <tr><td>110</td><td>67</td><td>30</td></tr> <tr><td>120</td><td>81</td><td>38</td></tr> <tr><td>132</td><td>100</td><td>48</td></tr> <tr><td>140</td><td>113</td><td>55</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	28	9	80	33	12	85	38	15	90	43	17	100	54	23	110	67	30	120	81	38	132	100	48	140	113	55
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	28	9																																	
80	33	12																																	
85	38	15																																	
90	43	17																																	
100	54	23																																	
110	67	30																																	
120	81	38																																	
132	100	48																																	
140	113	55																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model	LDA15F-12	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障	Testing Circuitry	Figure A																																																			
Object	+12.0V 1.3A																																																					
1. Graph		2. Values																																																				
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.20</td><td>118</td><td>165</td><td>288</td></tr> <tr><td>0.40</td><td>61</td><td>89</td><td>163</td></tr> <tr><td>0.60</td><td>37</td><td>56</td><td>107</td></tr> <tr><td>0.80</td><td>23</td><td>39</td><td>79</td></tr> <tr><td>1.00</td><td>14</td><td>28</td><td>60</td></tr> <tr><td>1.20</td><td>10</td><td>20</td><td>46</td></tr> <tr><td>1.30</td><td>5</td><td>14</td><td>39</td></tr> <tr><td>1.43</td><td>4</td><td>13</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.20	118	165	288	0.40	61	89	163	0.60	37	56	107	0.80	23	39	79	1.00	14	28	60	1.20	10	20	46	1.30	5	14	39	1.43	4	13	35	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	—	—	—																																																			
0.20	118	165	288																																																			
0.40	61	89	163																																																			
0.60	37	56	107																																																			
0.80	23	39	79																																																			
1.00	14	28	60																																																			
1.20	10	20	46																																																			
1.30	5	14	39																																																			
1.43	4	13	35																																																			
—	—	—	—																																																			
—	—	—	—																																																			

COSSEL

Model	LDA15F-12	Temperature	25°C																																															
Item	Load Regulation 靜的負荷変動	Testing Circuitry	Figure A																																															
Object	+12.0V 1.3A																																																	
1. Graph		2. Values																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>12.071</td><td>12.071</td><td>12.071</td></tr> <tr> <td>0.20</td><td>12.070</td><td>12.070</td><td>12.070</td></tr> <tr> <td>0.40</td><td>12.069</td><td>12.069</td><td>12.069</td></tr> <tr> <td>0.60</td><td>12.068</td><td>12.068</td><td>12.068</td></tr> <tr> <td>0.80</td><td>12.067</td><td>12.067</td><td>12.067</td></tr> <tr> <td>1.00</td><td>12.067</td><td>12.066</td><td>12.066</td></tr> <tr> <td>1.20</td><td>12.065</td><td>12.066</td><td>12.065</td></tr> <tr> <td>1.30</td><td>12.065</td><td>12.065</td><td>12.065</td></tr> <tr> <td>1.43</td><td>12.064</td><td>12.064</td><td>12.064</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	12.071	12.071	12.071	0.20	12.070	12.070	12.070	0.40	12.069	12.069	12.069	0.60	12.068	12.068	12.068	0.80	12.067	12.067	12.067	1.00	12.067	12.066	12.066	1.20	12.065	12.066	12.065	1.30	12.065	12.065	12.065	1.43	12.064	12.064	12.064	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.00	12.071	12.071	12.071																																															
0.20	12.070	12.070	12.070																																															
0.40	12.069	12.069	12.069																																															
0.60	12.068	12.068	12.068																																															
0.80	12.067	12.067	12.067																																															
1.00	12.067	12.066	12.066																																															
1.20	12.065	12.066	12.065																																															
1.30	12.065	12.065	12.065																																															
1.43	12.064	12.064	12.064																																															
—	—	—	—																																															
Note: Slanted line shows the range of the rated load current.																																																		
(注)斜線は定格負荷電流範囲を示す。																																																		

COSEL

Model	LDA15F-12	Temperature Testing Circuitry 25°C Figure A																																			
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)																																				
Object	+12.0V 1.3A																																				
1. Graph	<p style="text-align: center;">□ Input Volt. 85V [mV] —△— Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 85V [mV]</th> <th>Ripple Output Volt. 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.13</td><td>10</td><td>10</td></tr> <tr><td>0.26</td><td>10</td><td>10</td></tr> <tr><td>0.39</td><td>10</td><td>10</td></tr> <tr><td>0.52</td><td>10</td><td>10</td></tr> <tr><td>0.65</td><td>10</td><td>10</td></tr> <tr><td>0.78</td><td>10</td><td>10</td></tr> <tr><td>0.91</td><td>10</td><td>10</td></tr> <tr><td>1.30</td><td>25</td><td>10</td></tr> <tr><td>1.43</td><td>45</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]	0.00	10	10	0.13	10	10	0.26	10	10	0.39	10	10	0.52	10	10	0.65	10	10	0.78	10	10	0.91	10	10	1.30	25	10	1.43	45	10	—	—	—
Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]																																			
0.00	10	10																																			
0.13	10	10																																			
0.26	10	10																																			
0.39	10	10																																			
0.52	10	10																																			
0.65	10	10																																			
0.78	10	10																																			
0.91	10	10																																			
1.30	25	10																																			
1.43	45	10																																			
—	—	—																																			
2. Values																																					
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																			
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																			
0.00	10	10																																			
0.13	10	10																																			
0.26	10	10																																			
0.39	10	10																																			
0.52	10	10																																			
0.65	10	10																																			
0.78	10	10																																			
0.91	10	10																																			
1.30	25	10																																			
1.43	45	10																																			
—	—	—																																			

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line

入力商用周期

T2: Due to Switching

スイッチング周期




Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model	LDA15F-12	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																							
Object	+12.0V 1.3A																																							
1. Graph	<p style="text-align: center;">□ Input Volt. 85V [mV] △ Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise 85V [mV]</th> <th>Ripple-Noise 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.13</td><td>15</td><td>15</td></tr> <tr><td>0.26</td><td>15</td><td>15</td></tr> <tr><td>0.39</td><td>15</td><td>15</td></tr> <tr><td>0.52</td><td>15</td><td>15</td></tr> <tr><td>0.65</td><td>20</td><td>15</td></tr> <tr><td>0.78</td><td>30</td><td>20</td></tr> <tr><td>0.91</td><td>30</td><td>20</td></tr> <tr><td>1.30</td><td>45</td><td>25</td></tr> <tr><td>1.43</td><td>65</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]	0.00	15	15	0.13	15	15	0.26	15	15	0.39	15	15	0.52	15	15	0.65	20	15	0.78	30	20	0.91	30	20	1.30	45	25	1.43	65	30	—	—	—			
Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]																																						
0.00	15	15																																						
0.13	15	15																																						
0.26	15	15																																						
0.39	15	15																																						
0.52	15	15																																						
0.65	20	15																																						
0.78	30	20																																						
0.91	30	20																																						
1.30	45	25																																						
1.43	65	30																																						
—	—	—																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.13</td><td>15</td><td>15</td></tr> <tr><td>0.26</td><td>15</td><td>15</td></tr> <tr><td>0.39</td><td>15</td><td>15</td></tr> <tr><td>0.52</td><td>15</td><td>15</td></tr> <tr><td>0.65</td><td>20</td><td>15</td></tr> <tr><td>0.78</td><td>30</td><td>20</td></tr> <tr><td>0.91</td><td>30</td><td>20</td></tr> <tr><td>1.30</td><td>45</td><td>25</td></tr> <tr><td>1.43</td><td>65</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	15	15	0.13	15	15	0.26	15	15	0.39	15	15	0.52	15	15	0.65	20	15	0.78	30	20	0.91	30	20	1.30	45	25	1.43	65	30	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.00	15	15																																						
0.13	15	15																																						
0.26	15	15																																						
0.39	15	15																																						
0.52	15	15																																						
0.65	20	15																																						
0.78	30	20																																						
0.91	30	20																																						
1.30	45	25																																						
1.43	65	30																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSSEL


Model	LDA15F-12																																																								
Item	Overcurrent Protection 過電流保護	Temperature 25°C	Testing Circuitry Figure A																																																						
Object	+12.0V 1.3A																																																								
1. Graph	<p>Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V [V]</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																								
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>1.57</td><td>1.77</td><td>1.82</td></tr> <tr><td>11.40</td><td>1.62</td><td>1.80</td><td>1.84</td></tr> <tr><td>10.80</td><td>1.67</td><td>1.84</td><td>1.87</td></tr> <tr><td>9.60</td><td>1.77</td><td>1.92</td><td>1.92</td></tr> <tr><td>8.40</td><td>1.86</td><td>2.00</td><td>1.97</td></tr> <tr><td>7.20</td><td>1.95</td><td>2.06</td><td>2.00</td></tr> <tr><td>6.00</td><td>2.03</td><td>2.12</td><td>2.02</td></tr> <tr><td>4.80</td><td>2.09</td><td>2.15</td><td>2.02</td></tr> <tr><td>3.60</td><td>2.11</td><td>2.13</td><td>1.98</td></tr> <tr><td>2.40</td><td>2.05</td><td>2.04</td><td>1.88</td></tr> <tr><td>1.20</td><td>1.86</td><td>1.84</td><td>1.69</td></tr> <tr><td>0.00</td><td>1.50</td><td>1.47</td><td>1.38</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	12.00	1.57	1.77	1.82	11.40	1.62	1.80	1.84	10.80	1.67	1.84	1.87	9.60	1.77	1.92	1.92	8.40	1.86	2.00	1.97	7.20	1.95	2.06	2.00	6.00	2.03	2.12	2.02	4.80	2.09	2.15	2.02	3.60	2.11	2.13	1.98	2.40	2.05	2.04	1.88	1.20	1.86	1.84	1.69	0.00	1.50	1.47	1.38
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																						
12.00	1.57	1.77	1.82																																																						
11.40	1.62	1.80	1.84																																																						
10.80	1.67	1.84	1.87																																																						
9.60	1.77	1.92	1.92																																																						
8.40	1.86	2.00	1.97																																																						
7.20	1.95	2.06	2.00																																																						
6.00	2.03	2.12	2.02																																																						
4.80	2.09	2.15	2.02																																																						
3.60	2.11	2.13	1.98																																																						
2.40	2.05	2.04	1.88																																																						
1.20	1.86	1.84	1.69																																																						
0.00	1.50	1.47	1.38																																																						

Note: Slanted line shows the range of the rated load current.


(注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	LDA15F-12	Temperature Testing Circuitry	25°C
Item	Inrush Current 突入電流		Figure A
Object	_____		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current
 ① 8.42 [A]
 ② 1.22 [A]




COSEL

Model	LDA15F-12	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	+12.0V 1.3A	



Input Volt. 100 V

Cycle 1000 mS





Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %




200 mV/div

10 mS/div

COSEL


Model	LDA15F-12	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+12.0V 1.3A		

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		2.8	7.3	10.0	38.0	46.5	
100 %		2.8	10.3	13.0	14.3	31.5	



COSEL

Model	LDA15F-12	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+12.0V 1.3A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	2. Values																																																					
	<p>—△— Input Volt. 85V</p> <p>—□— Input Volt. 100V</p> <p>—○— Input Volt. 132V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>12.085</td><td>12.086</td><td>12.086</td></tr> <tr><td>-10</td><td>12.081</td><td>12.082</td><td>12.082</td></tr> <tr><td>0</td><td>12.077</td><td>12.078</td><td>12.078</td></tr> <tr><td>10</td><td>12.074</td><td>12.074</td><td>12.074</td></tr> <tr><td>20</td><td>12.070</td><td>12.070</td><td>12.070</td></tr> <tr><td>25</td><td>12.068</td><td>12.068</td><td>12.068</td></tr> <tr><td>30</td><td>12.064</td><td>12.064</td><td>12.063</td></tr> <tr><td>40</td><td>12.057</td><td>12.057</td><td>12.057</td></tr> <tr><td>50</td><td>12.049</td><td>12.049</td><td>12.048</td></tr> <tr><td>60</td><td>12.037</td><td>12.037</td><td>12.036</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	12.085	12.086	12.086	-10	12.081	12.082	12.082	0	12.077	12.078	12.078	10	12.074	12.074	12.074	20	12.070	12.070	12.070	25	12.068	12.068	12.068	30	12.064	12.064	12.063	40	12.057	12.057	12.057	50	12.049	12.049	12.048	60	12.037	12.037	12.036	—	—	—	—
Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	12.085	12.086	12.086																																																				
-10	12.081	12.082	12.082																																																				
0	12.077	12.078	12.078																																																				
10	12.074	12.074	12.074																																																				
20	12.070	12.070	12.070																																																				
25	12.068	12.068	12.068																																																				
30	12.064	12.064	12.063																																																				
40	12.057	12.057	12.057																																																				
50	12.049	12.049	12.048																																																				
60	12.037	12.037	12.036																																																				
—	—	—	—																																																				

COSSEL


Model	LDA15F-12	
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	
Object	+12.0V 1.3A	
1. Graph		
[V]		
Input Voltage [V]	Load 50% Load 100%	
Ambient Temperature [°C]	-30 -10 10 30 50 70	
Note: Slanted line shows the range of the rated ambient temperature.		
(注) 斜線は定格周囲温度範囲を示す。		
Testing Circuitry Figure A		
2. Values		
Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	44	69
-10	43	69
0	43	69
10	43	69
20	43	69
25	43	69
30	43	69
40	44	70
50	44	70
60	44	70
—	—	—

COSEL

Model	LDA15F~12
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+12.0V 1.3A

Testing Circuitry

Figure A



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	10	45
-10	10	30
0	10	20
10	10	15
20	10	15
25	10	15
30	10	10
40	10	10
50	10	10
60	10	10
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	LDA15F-12	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+12.0V 1.3A																								
1. Graph			2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.068</td></tr> <tr><td>0.5</td><td>12.053</td></tr> <tr><td>1.0</td><td>12.053</td></tr> <tr><td>2.0</td><td>12.053</td></tr> <tr><td>3.0</td><td>12.053</td></tr> <tr><td>4.0</td><td>12.054</td></tr> <tr><td>5.0</td><td>12.054</td></tr> <tr><td>6.0</td><td>12.054</td></tr> <tr><td>7.0</td><td>12.054</td></tr> <tr><td>8.0</td><td>12.054</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.068	0.5	12.053	1.0	12.053	2.0	12.053	3.0	12.053	4.0	12.054	5.0	12.054	6.0	12.054	7.0	12.054	8.0	12.054
Time since start [H]	Output Voltage [V]																								
0.0	12.068																								
0.5	12.053																								
1.0	12.053																								
2.0	12.053																								
3.0	12.053																								
4.0	12.054																								
5.0	12.054																								
6.0	12.054																								
7.0	12.054																								
8.0	12.054																								



Model	LDA15F-12	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+12.0V 1.3A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~1.3 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~1.3 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132	0.0	12.088	±23	±0.2
Minimum Voltage	50	132	1.3	12.043		



Model	LDA15F-12		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+12.0V 1.3A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	12.07	Input Volt.: 100V, Load Current: 1.3A
Line Regulation [mV]	5	Input Volt.: 85~132V, Load Current: 1.3A
Load Regulation [mV]	17	Input Volt.: 100V, Load Current: 0~1.3A



Model	LDA15F-12	Temperature Testing Circuitry Figure B
Item	Leakage Current 漏洩電流	
Object	_____	

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.12	0.16	0.24
(B) IEC60950	0.12	0.16	0.25

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	LDA15F-12	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+12.0V 1.3A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	LDA15F-12	Temperature	25°C
Item	Conducted Emission 雜音端子電圧	Testing Circuitry	Figure D
Object	<hr/>		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

規格 1: [VCCI] Class B(平均値)

規格 2: [VCCI] Class B(QP)



規格 2: [FCC Part15] Class B







Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E