



TEST DATA OF LDA30F-3

(100V INPUT)

Regulated DC Power Supply

Nov. 28, 2001

Approved by : H. Shibutani
Design Manager

Prepared by : M. Yamaguchi
Design Engineer

コーセル株式会社

COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Overvoltage Protection	14
過電圧保護	
15. Inrush Current	15
突入電流	
16. Rise and Fall Time	16
立上り、立下り時間	
17. Ambient Temperature Drift	17
周囲温度変動	
18. Minimum Input Voltage for Regulated Output Voltage	18
最低レギュレーション電圧	
19. Ripple Voltage (by Ambient Temperature)	19
リップル電圧 (周囲温度特性)	
20. Output Voltage Accuracy	20
定電圧精度	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSEL

Model	LDA30F-3		Temperature Testing Circuitry 25°C Figure A																																	
Item	Line Regulation 静的入力変動																																			
Object	+3.0V 6A																																			
1. Graph			2. Values																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>3.060</td><td>3.059</td></tr> <tr><td>80</td><td>3.060</td><td>3.059</td></tr> <tr><td>85</td><td>3.060</td><td>3.059</td></tr> <tr><td>90</td><td>3.060</td><td>3.058</td></tr> <tr><td>100</td><td>3.060</td><td>3.059</td></tr> <tr><td>110</td><td>3.060</td><td>3.059</td></tr> <tr><td>120</td><td>3.060</td><td>3.058</td></tr> <tr><td>132</td><td>3.060</td><td>3.059</td></tr> <tr><td>140</td><td>3.060</td><td>3.059</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	3.060	3.059	80	3.060	3.059	85	3.060	3.059	90	3.060	3.058	100	3.060	3.059	110	3.060	3.059	120	3.060	3.058	132	3.060	3.059	140	3.060	3.059	
Input Voltage [V]	Output Voltage [V]																																			
	Load 50%	Load 100%																																		
75	3.060	3.059																																		
80	3.060	3.059																																		
85	3.060	3.059																																		
90	3.060	3.058																																		
100	3.060	3.059																																		
110	3.060	3.059																																		
120	3.060	3.058																																		
132	3.060	3.059																																		
140	3.060	3.059																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																				

COSEL

Model	LDA30F-3																																																									
Item	Input Current (by Load Current) 入力電流（負荷特性）	Temperature Testing Circuitry	25°C Figure A																																																							
Object	—																																																									
1. Graph	<p>Input Volt. 85V Input Volt. 100V Input Volt. 132V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.038</td><td>0.039</td><td>0.042</td></tr> <tr><td>1.0</td><td>0.117</td><td>0.109</td><td>0.098</td></tr> <tr><td>2.0</td><td>0.192</td><td>0.174</td><td>0.151</td></tr> <tr><td>3.0</td><td>0.268</td><td>0.241</td><td>0.203</td></tr> <tr><td>4.0</td><td>0.347</td><td>0.309</td><td>0.257</td></tr> <tr><td>5.0</td><td>0.427</td><td>0.378</td><td>0.312</td></tr> <tr><td>6.0</td><td>0.508</td><td>0.447</td><td>0.366</td></tr> <tr><td>6.6</td><td>0.557</td><td>0.481</td><td>0.392</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.038	0.039	0.042	1.0	0.117	0.109	0.098	2.0	0.192	0.174	0.151	3.0	0.268	0.241	0.203	4.0	0.347	0.309	0.257	5.0	0.427	0.378	0.312	6.0	0.508	0.447	0.366	6.6	0.557	0.481	0.392	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	0.038	0.039	0.042																																																							
1.0	0.117	0.109	0.098																																																							
2.0	0.192	0.174	0.151																																																							
3.0	0.268	0.241	0.203																																																							
4.0	0.347	0.309	0.257																																																							
5.0	0.427	0.378	0.312																																																							
6.0	0.508	0.447	0.366																																																							
6.6	0.557	0.481	0.392																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL

Model	LDA30F-3																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	—																																																									
1. Graph	<p style="text-align: center;">△ Input Volt. 85V □ Input Volt. 100V ○ Input Volt. 132V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.38</td><td>1.59</td><td>2.17</td></tr> <tr><td>1.0</td><td>5.09</td><td>5.33</td><td>5.93</td></tr> <tr><td>2.0</td><td>8.91</td><td>9.14</td><td>9.73</td></tr> <tr><td>3.0</td><td>12.91</td><td>13.09</td><td>13.60</td></tr> <tr><td>4.0</td><td>17.10</td><td>17.24</td><td>17.70</td></tr> <tr><td>5.0</td><td>21.49</td><td>21.55</td><td>21.91</td></tr> <tr><td>6.0</td><td>26.00</td><td>26.00</td><td>26.25</td></tr> <tr><td>6.6</td><td>28.87</td><td>28.94</td><td>29.07</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	1.38	1.59	2.17	1.0	5.09	5.33	5.93	2.0	8.91	9.14	9.73	3.0	12.91	13.09	13.60	4.0	17.10	17.24	17.70	5.0	21.49	21.55	21.91	6.0	26.00	26.00	26.25	6.6	28.87	28.94	29.07	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	1.38	1.59	2.17																																																							
1.0	5.09	5.33	5.93																																																							
2.0	8.91	9.14	9.73																																																							
3.0	12.91	13.09	13.60																																																							
4.0	17.10	17.24	17.70																																																							
5.0	21.49	21.55	21.91																																																							
6.0	26.00	26.00	26.25																																																							
6.6	28.87	28.94	29.07																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-3																																			
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)		Temperature Testing Circuitry	25°C Figure A																																
Object																																				
1. Graph	<p>Load 50% Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>71.9</td><td>70.0</td></tr> <tr><td>80</td><td>71.4</td><td>70.7</td></tr> <tr><td>85</td><td>71.2</td><td>70.9</td></tr> <tr><td>90</td><td>71.0</td><td>70.9</td></tr> <tr><td>100</td><td>70.3</td><td>71.0</td></tr> <tr><td>110</td><td>69.6</td><td>70.9</td></tr> <tr><td>120</td><td>68.6</td><td>70.7</td></tr> <tr><td>132</td><td>67.6</td><td>70.3</td></tr> <tr><td>140</td><td>66.7</td><td>70.0</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	71.9	70.0	80	71.4	70.7	85	71.2	70.9	90	71.0	70.9	100	70.3	71.0	110	69.6	70.9	120	68.6	70.7	132	67.6	70.3	140	66.7	70.0
Input Voltage [V]	Efficiency [%]																																			
	Load 50%	Load 100%																																		
75	71.9	70.0																																		
80	71.4	70.7																																		
85	71.2	70.9																																		
90	71.0	70.9																																		
100	70.3	71.0																																		
110	69.6	70.9																																		
120	68.6	70.7																																		
132	67.6	70.3																																		
140	66.7	70.0																																		

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL


Model	LDA30F-3																																																									
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	——																																																									
1. Graph																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>1.0</td><td>60.0</td><td>57.2</td><td>51.4</td></tr> <tr><td>2.0</td><td>68.8</td><td>67.0</td><td>63.0</td></tr> <tr><td>3.0</td><td>71.3</td><td>70.4</td><td>67.7</td></tr> <tr><td>4.0</td><td>72.0</td><td>71.4</td><td>69.5</td></tr> <tr><td>5.0</td><td>71.6</td><td>71.4</td><td>70.2</td></tr> <tr><td>6.0</td><td>70.9</td><td>70.9</td><td>70.2</td></tr> <tr><td>6.6</td><td>70.3</td><td>70.1</td><td>69.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	1.0	60.0	57.2	51.4	2.0	68.8	67.0	63.0	3.0	71.3	70.4	67.7	4.0	72.0	71.4	69.5	5.0	71.6	71.4	70.2	6.0	70.9	70.9	70.2	6.6	70.3	70.1	69.8	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
1.0	60.0	57.2	51.4																																																							
2.0	68.8	67.0	63.0																																																							
3.0	71.3	70.4	67.7																																																							
4.0	72.0	71.4	69.5																																																							
5.0	71.6	71.4	70.2																																																							
6.0	70.9	70.9	70.2																																																							
6.6	70.3	70.1	69.8																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-3
Item	Power Factor (by Input Voltage) 力率(入力電圧特性)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA30F-3																																																									
Item	Power Factor (by Load Current) 力率 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object																																																										
1. Graph	<p style="text-align: center;">△ Input Volt. 85V □ Input Volt. 100V ○ Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Power Factor at 85V</th> <th>Power Factor at 100V</th> <th>Power Factor at 132V</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.42</td><td>0.40</td><td>0.39</td></tr> <tr><td>1.0</td><td>0.51</td><td>0.49</td><td>0.46</td></tr> <tr><td>2.0</td><td>0.55</td><td>0.52</td><td>0.49</td></tr> <tr><td>3.0</td><td>0.57</td><td>0.54</td><td>0.51</td></tr> <tr><td>4.0</td><td>0.58</td><td>0.56</td><td>0.52</td></tr> <tr><td>5.0</td><td>0.59</td><td>0.57</td><td>0.53</td></tr> <tr><td>6.0</td><td>0.60</td><td>0.58</td><td>0.54</td></tr> <tr><td>6.6</td><td>0.61</td><td>0.60</td><td>0.56</td></tr> </tbody> </table>			Load Current [A]	Power Factor at 85V	Power Factor at 100V	Power Factor at 132V	0.0	0.42	0.40	0.39	1.0	0.51	0.49	0.46	2.0	0.55	0.52	0.49	3.0	0.57	0.54	0.51	4.0	0.58	0.56	0.52	5.0	0.59	0.57	0.53	6.0	0.60	0.58	0.54	6.6	0.61	0.60	0.56																			
Load Current [A]	Power Factor at 85V	Power Factor at 100V	Power Factor at 132V																																																							
0.0	0.42	0.40	0.39																																																							
1.0	0.51	0.49	0.46																																																							
2.0	0.55	0.52	0.49																																																							
3.0	0.57	0.54	0.51																																																							
4.0	0.58	0.56	0.52																																																							
5.0	0.59	0.57	0.53																																																							
6.0	0.60	0.58	0.54																																																							
6.6	0.61	0.60	0.56																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.42</td><td>0.40</td><td>0.39</td></tr> <tr><td>1.0</td><td>0.51</td><td>0.49</td><td>0.46</td></tr> <tr><td>2.0</td><td>0.55</td><td>0.52</td><td>0.49</td></tr> <tr><td>3.0</td><td>0.57</td><td>0.54</td><td>0.51</td></tr> <tr><td>4.0</td><td>0.58</td><td>0.56</td><td>0.52</td></tr> <tr><td>5.0</td><td>0.59</td><td>0.57</td><td>0.53</td></tr> <tr><td>6.0</td><td>0.60</td><td>0.58</td><td>0.54</td></tr> <tr><td>6.6</td><td>0.61</td><td>0.60</td><td>0.56</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.42	0.40	0.39	1.0	0.51	0.49	0.46	2.0	0.55	0.52	0.49	3.0	0.57	0.54	0.51	4.0	0.58	0.56	0.52	5.0	0.59	0.57	0.53	6.0	0.60	0.58	0.54	6.6	0.61	0.60	0.56	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Power Factor																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	0.42	0.40	0.39																																																							
1.0	0.51	0.49	0.46																																																							
2.0	0.55	0.52	0.49																																																							
3.0	0.57	0.54	0.51																																																							
4.0	0.58	0.56	0.52																																																							
5.0	0.59	0.57	0.53																																																							
6.0	0.60	0.58	0.54																																																							
6.6	0.61	0.60	0.56																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.


(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-3	Temperature Testing Circuitry	25°C Figure A																																	
Item	Hold-Up Time 出力保持時間																																			
Object	+3.0V 6A																																			
1. Graph		2. Values																																		
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>39</td><td>17</td></tr> <tr><td>80</td><td>47</td><td>21</td></tr> <tr><td>85</td><td>56</td><td>26</td></tr> <tr><td>90</td><td>65</td><td>30</td></tr> <tr><td>100</td><td>86</td><td>41</td></tr> <tr><td>110</td><td>108</td><td>52</td></tr> <tr><td>120</td><td>132</td><td>64</td></tr> <tr><td>132</td><td>164</td><td>81</td></tr> <tr><td>140</td><td>187</td><td>92</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	39	17	80	47	21	85	56	26	90	65	30	100	86	41	110	108	52	120	132	64	132	164	81	140	187	92	
Input Voltage [V]	Hold-Up Time [mS]																																			
	Load 50%	Load 100%																																		
75	39	17																																		
80	47	21																																		
85	56	26																																		
90	65	30																																		
100	86	41																																		
110	108	52																																		
120	132	64																																		
132	164	81																																		
140	187	92																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																				

COSEL


Model	LDA30F-3
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+3.0V 6A

Temperature 25°C
Testing Circuitry Figure A

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。
(注)斜線は定格負荷電流範囲を示す。


COSEL

Model	LDA30F-3	Temperature 25°C Testing Circuitry Figure A																																																	
Item	Load Regulation 静的負荷変動																																																		
Object	+3.0V 6A																																																		
1. Graph	<p>—△— Input Volt. 85 V -□- Input Volt. 100 V -○- Input Volt. 132 V</p> 																																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>3.061</td> <td>3.061</td> <td>3.061</td> </tr> <tr> <td>1.0</td> <td>3.060</td> <td>3.060</td> <td>3.060</td> </tr> <tr> <td>2.0</td> <td>3.060</td> <td>3.060</td> <td>3.060</td> </tr> <tr> <td>3.0</td> <td>3.060</td> <td>3.060</td> <td>3.060</td> </tr> <tr> <td>4.0</td> <td>3.059</td> <td>3.059</td> <td>3.059</td> </tr> <tr> <td>5.0</td> <td>3.058</td> <td>3.059</td> <td>3.059</td> </tr> <tr> <td>6.0</td> <td>3.058</td> <td>3.058</td> <td>3.058</td> </tr> <tr> <td>6.6</td> <td>3.058</td> <td>3.058</td> <td>3.058</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	3.061	3.061	3.061	1.0	3.060	3.060	3.060	2.0	3.060	3.060	3.060	3.0	3.060	3.060	3.060	4.0	3.059	3.059	3.059	5.0	3.058	3.059	3.059	6.0	3.058	3.058	3.058	6.6	3.058	3.058	3.058	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
0.0	3.061	3.061	3.061																																																
1.0	3.060	3.060	3.060																																																
2.0	3.060	3.060	3.060																																																
3.0	3.060	3.060	3.060																																																
4.0	3.059	3.059	3.059																																																
5.0	3.058	3.059	3.059																																																
6.0	3.058	3.058	3.058																																																
6.6	3.058	3.058	3.058																																																
—	—	—	—																																																
—	—	—	—																																																

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL


Model	LDA30F-3																																																										
Item	Overcurrent Protection 過電流保護			Temperature Testing Circuitry	25°C Figure A																																																						
Object	+3.0V 6A																																																										
1. Graph	[V]	Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V																																																									
																																																											
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>3.00</td><td>7.85</td><td>7.82</td><td>7.78</td></tr> <tr><td>2.85</td><td>7.87</td><td>7.84</td><td>7.80</td></tr> <tr><td>2.70</td><td>7.88</td><td>7.86</td><td>7.81</td></tr> <tr><td>2.40</td><td>7.92</td><td>7.89</td><td>7.90</td></tr> <tr><td>2.10</td><td>7.95</td><td>7.91</td><td>7.87</td></tr> <tr><td>1.80</td><td>7.97</td><td>7.97</td><td>7.88</td></tr> <tr><td>1.50</td><td>8.02</td><td>7.93</td><td>7.88</td></tr> <tr><td>1.20</td><td>7.99</td><td>7.94</td><td>7.87</td></tr> <tr><td>0.90</td><td>8.01</td><td>7.95</td><td>7.85</td></tr> <tr><td>0.60</td><td>8.01</td><td>7.93</td><td>7.80</td></tr> <tr><td>0.30</td><td>7.97</td><td>7.86</td><td>7.65</td></tr> <tr><td>0.00</td><td>7.88</td><td>7.72</td><td>7.39</td></tr> </tbody> </table>					Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	3.00	7.85	7.82	7.78	2.85	7.87	7.84	7.80	2.70	7.88	7.86	7.81	2.40	7.92	7.89	7.90	2.10	7.95	7.91	7.87	1.80	7.97	7.97	7.88	1.50	8.02	7.93	7.88	1.20	7.99	7.94	7.87	0.90	8.01	7.95	7.85	0.60	8.01	7.93	7.80	0.30	7.97	7.86	7.65	0.00	7.88	7.72	7.39
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
3.00	7.85	7.82	7.78																																																								
2.85	7.87	7.84	7.80																																																								
2.70	7.88	7.86	7.81																																																								
2.40	7.92	7.89	7.90																																																								
2.10	7.95	7.91	7.87																																																								
1.80	7.97	7.97	7.88																																																								
1.50	8.02	7.93	7.88																																																								
1.20	7.99	7.94	7.87																																																								
0.90	8.01	7.95	7.85																																																								
0.60	8.01	7.93	7.80																																																								
0.30	7.97	7.86	7.65																																																								
0.00	7.88	7.72	7.39																																																								
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																											

COSEL

Model	LDA30F-3																																																					
Item	Overvoltage Protection 過電圧保護																																																					
Object	+3.0V 6A																																																					
Testing Circuitry Figure A																																																						
1. Graph																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>4.83</td><td>4.83</td><td>4.83</td></tr> <tr> <td>-10</td><td>4.76</td><td>4.83</td><td>4.83</td></tr> <tr> <td>0</td><td>4.76</td><td>4.76</td><td>4.76</td></tr> <tr> <td>10</td><td>4.69</td><td>4.69</td><td>4.69</td></tr> <tr> <td>20</td><td>4.69</td><td>4.69</td><td>4.68</td></tr> <tr> <td>25</td><td>4.62</td><td>4.69</td><td>4.68</td></tr> <tr> <td>30</td><td>4.62</td><td>4.62</td><td>4.62</td></tr> <tr> <td>40</td><td>4.55</td><td>4.62</td><td>4.62</td></tr> <tr> <td>50</td><td>4.55</td><td>4.55</td><td>4.54</td></tr> <tr> <td>60</td><td>4.48</td><td>4.48</td><td>4.48</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	4.83	4.83	4.83	-10	4.76	4.83	4.83	0	4.76	4.76	4.76	10	4.69	4.69	4.69	20	4.69	4.69	4.68	25	4.62	4.69	4.68	30	4.62	4.62	4.62	40	4.55	4.62	4.62	50	4.55	4.55	4.54	60	4.48	4.48	4.48	—	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	4.83	4.83	4.83																																																			
-10	4.76	4.83	4.83																																																			
0	4.76	4.76	4.76																																																			
10	4.69	4.69	4.69																																																			
20	4.69	4.69	4.68																																																			
25	4.62	4.69	4.68																																																			
30	4.62	4.62	4.62																																																			
40	4.55	4.62	4.62																																																			
50	4.55	4.55	4.54																																																			
60	4.48	4.48	4.48																																																			
—	—	—	—																																																			
Note:	Slanted line shows the range of the rated ambient temperature.																																																					
(注)斜線は定格周囲温度範囲を示す。																																																						

COSSEL

Model	LDA30F-3	Temperature Testing Circuitry	25°C Figure A
Item	Inrush Current 突入電流		
Object	_____		



Input Voltage 100 V


Frequency 60 Hz


Load 100 %

Inrush Current


① 10.40 [A]


② 1.20 [A]



COSSEL

COSEL

Model	LDA30F-3																																																						
Item	Ambient Temperature Drift 周囲温度変動		Testing Circuitry Figure A																																																				
Object	+3.0V 6A																																																						
1. Graph																																																							
<p style="text-align: center;">—△— Input Volt. 85V □..... Input Volt. 100V ○..... Input Volt. 132V</p>		2. Values																																																					
 <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>3.061</td><td>3.061</td><td>3.061</td></tr> <tr><td>-10</td><td>3.061</td><td>3.061</td><td>3.061</td></tr> <tr><td>0</td><td>3.061</td><td>3.061</td><td>3.061</td></tr> <tr><td>10</td><td>3.061</td><td>3.061</td><td>3.061</td></tr> <tr><td>20</td><td>3.060</td><td>3.060</td><td>3.060</td></tr> <tr><td>25</td><td>3.060</td><td>3.060</td><td>3.060</td></tr> <tr><td>30</td><td>3.059</td><td>3.059</td><td>3.059</td></tr> <tr><td>40</td><td>3.058</td><td>3.058</td><td>3.058</td></tr> <tr><td>50</td><td>3.056</td><td>3.056</td><td>3.056</td></tr> <tr><td>60</td><td>3.055</td><td>3.055</td><td>3.055</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	3.061	3.061	3.061	-10	3.061	3.061	3.061	0	3.061	3.061	3.061	10	3.061	3.061	3.061	20	3.060	3.060	3.060	25	3.060	3.060	3.060	30	3.059	3.059	3.059	40	3.058	3.058	3.058	50	3.056	3.056	3.056	60	3.055	3.055	3.055	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	3.061	3.061	3.061																																																				
-10	3.061	3.061	3.061																																																				
0	3.061	3.061	3.061																																																				
10	3.061	3.061	3.061																																																				
20	3.060	3.060	3.060																																																				
25	3.060	3.060	3.060																																																				
30	3.059	3.059	3.059																																																				
40	3.058	3.058	3.058																																																				
50	3.056	3.056	3.056																																																				
60	3.055	3.055	3.055																																																				
—	—	—	—																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							
(注)斜線は定格周囲温度範囲を示す。																																																							

COSSEL

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	52	57
-10	51	56
0	50	56
10	50	55
20	49	55
25	49	55
30	49	55
40	49	54
50	48	54
60	48	54
—	—	—



Model LDA30F-3																																							
Item Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																						
Object +3V6A																																							
<p>1. Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100V</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																							
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>60</td> <td>70</td> </tr> <tr> <td>-10</td> <td>30</td> <td>40</td> </tr> <tr> <td>0</td> <td>25</td> <td>30</td> </tr> <tr> <td>10</td> <td>25</td> <td>30</td> </tr> <tr> <td>20</td> <td>20</td> <td>25</td> </tr> <tr> <td>25</td> <td>20</td> <td>25</td> </tr> <tr> <td>30</td> <td>20</td> <td>25</td> </tr> <tr> <td>40</td> <td>15</td> <td>20</td> </tr> <tr> <td>50</td> <td>15</td> <td>20</td> </tr> <tr> <td>60</td> <td>15</td> <td>20</td> </tr> <tr> <td>--</td> <td>—</td> <td>—</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	60	70	-10	30	40	0	25	30	10	25	30	20	20	25	25	20	25	30	20	25	40	15	20	50	15	20	60	15	20	--	—	—
Ambient Temperature [°C]	Ripple Voltage [mV]																																						
	Load 50%	Load 100%																																					
-20	60	70																																					
-10	30	40																																					
0	25	30																																					
10	25	30																																					
20	20	25																																					
25	20	25																																					
30	20	25																																					
40	15	20																																					
50	15	20																																					
60	15	20																																					
--	—	—																																					



Model	LDA30F-3	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+3.0V 6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~6 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~6 A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	100	0	3.063		
Minimum Voltage	50	132	6	3.056	±4	±0.2




Figure A