



TEST DATA OF LDA30F-3

(200V INPUT)

Regulated DC Power Supply

Nov. 28, 2001

Approved by : K. Shibutani
Design Manager

Prepared by : M. Yamaguchi
Design Engineer

コーセル株式会社

COSEL CO., LTD.



C O N T E N T S


1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Overvoltage Protection	14
過電圧保護	
15. Inrush Current	15
突入電流	
16. Rise and Fall Time	16
立上り、立下り時間	
17. Ambient Temperature Drift	17
周囲温度変動	
18. Minimum Input Voltage for Regulated Output Voltage	18
最低レギュレーション電圧	
19. Ripple Voltage (by Ambient Temperature)	19
リップル電圧 (周囲温度特性)	
20. Output Voltage Accuracy	20
定電圧精度	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSEL

Model	LDA30F-3
Item	Line Regulation 静的入力変動
Object	+3.0V 6A

Temperature 25°C
Testing Circuitry Figure A



2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
150	3.060	3.058
160	3.060	3.058
170	3.060	3.058
180	3.060	3.058
200	3.060	3.058
220	3.060	3.058
240	3.060	3.058
264	3.060	3.058
280	3.060	3.058

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LDA30F-3	Temperature	25°C																																																							
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Testing Circuitry	Figure A																																																							
Object	_____																																																									
1. Graph	—△— Input Volt. 170V -□- Input Volt. 200V -○- Input Volt. 264V																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.047</td><td>0.046</td><td>0.054</td></tr> <tr><td>1.0</td><td>0.093</td><td>0.091</td><td>0.093</td></tr> <tr><td>2.0</td><td>0.136</td><td>0.129</td><td>0.123</td></tr> <tr><td>3.0</td><td>0.179</td><td>0.167</td><td>0.153</td></tr> <tr><td>4.0</td><td>0.223</td><td>0.205</td><td>0.183</td></tr> <tr><td>5.0</td><td>0.267</td><td>0.244</td><td>0.214</td></tr> <tr><td>6.0</td><td>0.312</td><td>0.282</td><td>0.244</td></tr> <tr><td>6.6</td><td>0.338</td><td>0.299</td><td>0.258</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	0.047	0.046	0.054	1.0	0.093	0.091	0.093	2.0	0.136	0.129	0.123	3.0	0.179	0.167	0.153	4.0	0.223	0.205	0.183	5.0	0.267	0.244	0.214	6.0	0.312	0.282	0.244	6.6	0.338	0.299	0.258	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	0.047	0.046	0.054																																																							
1.0	0.093	0.091	0.093																																																							
2.0	0.136	0.129	0.123																																																							
3.0	0.179	0.167	0.153																																																							
4.0	0.223	0.205	0.183																																																							
5.0	0.267	0.244	0.214																																																							
6.0	0.312	0.282	0.244																																																							
6.6	0.338	0.299	0.258																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

COSEL

Model	LDA30F-3																																																									
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	—																																																									
1. Graph	<p style="text-align: center;">—△— Input Volt. 170V —□— Input Volt. 200V —○— Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170V [W]</th> <th>Input Volt. 200V [W]</th> <th>Input Volt. 264V [W]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.00</td><td>3.20</td><td>4.70</td></tr> <tr><td>1.0</td><td>6.90</td><td>7.60</td><td>9.50</td></tr> <tr><td>2.0</td><td>10.60</td><td>11.40</td><td>13.30</td></tr> <tr><td>3.0</td><td>14.40</td><td>15.30</td><td>17.20</td></tr> <tr><td>4.0</td><td>18.40</td><td>19.20</td><td>21.20</td></tr> <tr><td>5.0</td><td>22.60</td><td>23.30</td><td>25.20</td></tr> <tr><td>6.0</td><td>26.80</td><td>27.60</td><td>29.50</td></tr> <tr><td>6.6</td><td>29.60</td><td>30.30</td><td>32.20</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170V [W]	Input Volt. 200V [W]	Input Volt. 264V [W]	0.0	3.00	3.20	4.70	1.0	6.90	7.60	9.50	2.0	10.60	11.40	13.30	3.0	14.40	15.30	17.20	4.0	18.40	19.20	21.20	5.0	22.60	23.30	25.20	6.0	26.80	27.60	29.50	6.6	29.60	30.30	32.20																			
Load Current [A]	Input Volt. 170V [W]	Input Volt. 200V [W]	Input Volt. 264V [W]																																																							
0.0	3.00	3.20	4.70																																																							
1.0	6.90	7.60	9.50																																																							
2.0	10.60	11.40	13.30																																																							
3.0	14.40	15.30	17.20																																																							
4.0	18.40	19.20	21.20																																																							
5.0	22.60	23.30	25.20																																																							
6.0	26.80	27.60	29.50																																																							
6.6	29.60	30.30	32.20																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.00</td><td>3.20</td><td>4.70</td></tr> <tr><td>1.0</td><td>6.90</td><td>7.60</td><td>9.50</td></tr> <tr><td>2.0</td><td>10.60</td><td>11.40</td><td>13.30</td></tr> <tr><td>3.0</td><td>14.40</td><td>15.30</td><td>17.20</td></tr> <tr><td>4.0</td><td>18.40</td><td>19.20</td><td>21.20</td></tr> <tr><td>5.0</td><td>22.60</td><td>23.30</td><td>25.20</td></tr> <tr><td>6.0</td><td>26.80</td><td>27.60</td><td>29.50</td></tr> <tr><td>6.6</td><td>29.60</td><td>30.30</td><td>32.20</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	3.00	3.20	4.70	1.0	6.90	7.60	9.50	2.0	10.60	11.40	13.30	3.0	14.40	15.30	17.20	4.0	18.40	19.20	21.20	5.0	22.60	23.30	25.20	6.0	26.80	27.60	29.50	6.6	29.60	30.30	32.20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	3.00	3.20	4.70																																																							
1.0	6.90	7.60	9.50																																																							
2.0	10.60	11.40	13.30																																																							
3.0	14.40	15.30	17.20																																																							
4.0	18.40	19.20	21.20																																																							
5.0	22.60	23.30	25.20																																																							
6.0	26.80	27.60	29.50																																																							
6.6	29.60	30.30	32.20																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-3		Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																																			
Object																																				
1. Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Load 50% (Squares)</p> <p>Load 100% (Triangles)</p>																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>150</td> <td>66.3</td> <td>69.6</td> </tr> <tr> <td>160</td> <td>64.9</td> <td>69.0</td> </tr> <tr> <td>170</td> <td>63.9</td> <td>68.5</td> </tr> <tr> <td>180</td> <td>62.6</td> <td>68.0</td> </tr> <tr> <td>200</td> <td>60.6</td> <td>66.8</td> </tr> <tr> <td>220</td> <td>58.3</td> <td>65.6</td> </tr> <tr> <td>240</td> <td>55.8</td> <td>64.4</td> </tr> <tr> <td>264</td> <td>53.2</td> <td>62.7</td> </tr> <tr> <td>280</td> <td>51.4</td> <td>61.5</td> </tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	66.3	69.6	160	64.9	69.0	170	63.9	68.5	180	62.6	68.0	200	60.6	66.8	220	58.3	65.6	240	55.8	64.4	264	53.2	62.7	280	51.4	61.5
Input Voltage [V]	Efficiency [%]																																			
	Load 50%	Load 100%																																		
150	66.3	69.6																																		
160	64.9	69.0																																		
170	63.9	68.5																																		
180	62.6	68.0																																		
200	60.6	66.8																																		
220	58.3	65.6																																		
240	55.8	64.4																																		
264	53.2	62.7																																		
280	51.4	61.5																																		
Note:	Slanted line shows the range of the rated input voltage.																																			
(注)	(注) 斜線は定格入力電圧範囲を示す。																																			

COSEL

Model	LDA30F-3																																																										
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature 25°C Testing Circuitry Figure A																																																									
Object	—																																																										
1. Graph	<p>The graph plots Efficiency [%] on the y-axis (20 to 80) against Load Current [A] on the x-axis (0 to 8). Three curves are shown for Input Volt. 170V (triangles), Input Volt. 200V (squares), and Input Volt. 264V (circles). All curves show efficiency increasing with load current. A slanted line on the right side of the graph indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency 170[V] [%]</th> <th>Efficiency 200[V] [%]</th> <th>Efficiency 264[V] [%]</th> </tr> </thead> <tbody> <tr><td>1.0</td><td>44.2</td><td>40.2</td><td>32.1</td></tr> <tr><td>2.0</td><td>57.8</td><td>53.8</td><td>46.1</td></tr> <tr><td>3.0</td><td>64.0</td><td>60.2</td><td>53.5</td></tr> <tr><td>4.0</td><td>66.9</td><td>64.1</td><td>58.0</td></tr> <tr><td>5.0</td><td>68.1</td><td>66.0</td><td>61.1</td></tr> <tr><td>6.0</td><td>68.8</td><td>66.8</td><td>62.5</td></tr> <tr><td>6.6</td><td>68.6</td><td>66.9</td><td>63.0</td></tr> </tbody> </table>			Load Current [A]	Efficiency 170[V] [%]	Efficiency 200[V] [%]	Efficiency 264[V] [%]	1.0	44.2	40.2	32.1	2.0	57.8	53.8	46.1	3.0	64.0	60.2	53.5	4.0	66.9	64.1	58.0	5.0	68.1	66.0	61.1	6.0	68.8	66.8	62.5	6.6	68.6	66.9	63.0																								
Load Current [A]	Efficiency 170[V] [%]	Efficiency 200[V] [%]	Efficiency 264[V] [%]																																																								
1.0	44.2	40.2	32.1																																																								
2.0	57.8	53.8	46.1																																																								
3.0	64.0	60.2	53.5																																																								
4.0	66.9	64.1	58.0																																																								
5.0	68.1	66.0	61.1																																																								
6.0	68.8	66.8	62.5																																																								
6.6	68.6	66.9	63.0																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>1.0</td><td>44.2</td><td>40.2</td><td>32.1</td></tr> <tr><td>2.0</td><td>57.8</td><td>53.8</td><td>46.1</td></tr> <tr><td>3.0</td><td>64.0</td><td>60.2</td><td>53.5</td></tr> <tr><td>4.0</td><td>66.9</td><td>64.1</td><td>58.0</td></tr> <tr><td>5.0</td><td>68.1</td><td>66.0</td><td>61.1</td></tr> <tr><td>6.0</td><td>68.8</td><td>66.8</td><td>62.5</td></tr> <tr><td>6.6</td><td>68.6</td><td>66.9</td><td>63.0</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	1.0	44.2	40.2	32.1	2.0	57.8	53.8	46.1	3.0	64.0	60.2	53.5	4.0	66.9	64.1	58.0	5.0	68.1	66.0	61.1	6.0	68.8	66.8	62.5	6.6	68.6	66.9	63.0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																										
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																								
1.0	44.2	40.2	32.1																																																								
2.0	57.8	53.8	46.1																																																								
3.0	64.0	60.2	53.5																																																								
4.0	66.9	64.1	58.0																																																								
5.0	68.1	66.0	61.1																																																								
6.0	68.8	66.8	62.5																																																								
6.6	68.6	66.9	63.0																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
Note:	Slanted line shows the range of the rated load current.																																																										
(注)	(注) 斜線は定格負荷電流範囲を示す。																																																										

COSEL

Model	LDA30F-3		Temperature Testing Circuitry 25°C Figure A																																
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)																																		
Object	<hr/>																																		
1. Graph		Load 50% A graph plotting Power Factor (Y-axis, 0.20 to 0.80) against Input Voltage [V] (X-axis, 140 to 300). Two sets of data points are shown: Load 50% (squares) and Load 100% (triangles). Both series show a slight decrease in power factor as input voltage increases. A horizontal dashed line at approximately 0.48 represents the rated power factor. Two slanted lines indicate the range of the rated input voltage, roughly between 170V and 270V. Note: Slanted line shows the range of the rated input voltage.																																	
2. Values			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>0.49</td><td>0.53</td></tr> <tr><td>160</td><td>0.48</td><td>0.52</td></tr> <tr><td>170</td><td>0.48</td><td>0.51</td></tr> <tr><td>180</td><td>0.47</td><td>0.50</td></tr> <tr><td>200</td><td>0.46</td><td>0.49</td></tr> <tr><td>220</td><td>0.45</td><td>0.47</td></tr> <tr><td>240</td><td>0.44</td><td>0.46</td></tr> <tr><td>264</td><td>0.43</td><td>0.45</td></tr> <tr><td>280</td><td>0.42</td><td>0.45</td></tr> </tbody> </table>	Input Voltage [V]	Power Factor		Load 50%	Load 100%	150	0.49	0.53	160	0.48	0.52	170	0.48	0.51	180	0.47	0.50	200	0.46	0.49	220	0.45	0.47	240	0.44	0.46	264	0.43	0.45	280	0.42	0.45
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
150	0.49	0.53																																	
160	0.48	0.52																																	
170	0.48	0.51																																	
180	0.47	0.50																																	
200	0.46	0.49																																	
220	0.45	0.47																																	
240	0.44	0.46																																	
264	0.43	0.45																																	
280	0.42	0.45																																	

COSEL

Model	LDA30F-3	Temperature	25°C																																																							
Item	Power Factor (by Load Current) 力率 (負荷特性)	Testing Circuitry	Figure A																																																							
Object																																																										
1. Graph	<p style="text-align: center;">—△— Input Volt. 170V □..... Input Volt. 200V ○..... Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170V</th> <th>Input Volt. 200V</th> <th>Input Volt. 264V</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.38</td><td>0.35</td><td>0.33</td></tr> <tr><td>1.0</td><td>0.44</td><td>0.42</td><td>0.39</td></tr> <tr><td>2.0</td><td>0.46</td><td>0.44</td><td>0.41</td></tr> <tr><td>3.0</td><td>0.47</td><td>0.46</td><td>0.42</td></tr> <tr><td>4.0</td><td>0.48</td><td>0.47</td><td>0.44</td></tr> <tr><td>5.0</td><td>0.50</td><td>0.48</td><td>0.44</td></tr> <tr><td>6.0</td><td>0.50</td><td>0.49</td><td>0.46</td></tr> <tr><td>6.6</td><td>0.51</td><td>0.50</td><td>0.47</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170V	Input Volt. 200V	Input Volt. 264V	0.0	0.38	0.35	0.33	1.0	0.44	0.42	0.39	2.0	0.46	0.44	0.41	3.0	0.47	0.46	0.42	4.0	0.48	0.47	0.44	5.0	0.50	0.48	0.44	6.0	0.50	0.49	0.46	6.6	0.51	0.50	0.47																			
Load Current [A]	Input Volt. 170V	Input Volt. 200V	Input Volt. 264V																																																							
0.0	0.38	0.35	0.33																																																							
1.0	0.44	0.42	0.39																																																							
2.0	0.46	0.44	0.41																																																							
3.0	0.47	0.46	0.42																																																							
4.0	0.48	0.47	0.44																																																							
5.0	0.50	0.48	0.44																																																							
6.0	0.50	0.49	0.46																																																							
6.6	0.51	0.50	0.47																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.38</td><td>0.35</td><td>0.33</td></tr> <tr><td>1.0</td><td>0.44</td><td>0.42</td><td>0.39</td></tr> <tr><td>2.0</td><td>0.46</td><td>0.44</td><td>0.41</td></tr> <tr><td>3.0</td><td>0.47</td><td>0.46</td><td>0.42</td></tr> <tr><td>4.0</td><td>0.48</td><td>0.47</td><td>0.44</td></tr> <tr><td>5.0</td><td>0.50</td><td>0.48</td><td>0.44</td></tr> <tr><td>6.0</td><td>0.50</td><td>0.49</td><td>0.46</td></tr> <tr><td>6.6</td><td>0.51</td><td>0.50</td><td>0.47</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	0.38	0.35	0.33	1.0	0.44	0.42	0.39	2.0	0.46	0.44	0.41	3.0	0.47	0.46	0.42	4.0	0.48	0.47	0.44	5.0	0.50	0.48	0.44	6.0	0.50	0.49	0.46	6.6	0.51	0.50	0.47	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Power Factor																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	0.38	0.35	0.33																																																							
1.0	0.44	0.42	0.39																																																							
2.0	0.46	0.44	0.41																																																							
3.0	0.47	0.46	0.42																																																							
4.0	0.48	0.47	0.44																																																							
5.0	0.50	0.48	0.44																																																							
6.0	0.50	0.49	0.46																																																							
6.6	0.51	0.50	0.47																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.


(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-3																																			
Item	Hold-Up Time 出力保持時間		Temperature Testing Circuitry	25°C Figure A																																
Object	+3.0V6A																																			
1. Graph□..... Load 50%	Load 100%	2. Values																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>218</td><td>108</td></tr> <tr><td>160</td><td>249</td><td>125</td></tr> <tr><td>170</td><td>283</td><td>142</td></tr> <tr><td>180</td><td>318</td><td>161</td></tr> <tr><td>200</td><td>393</td><td>202</td></tr> <tr><td>220</td><td>474</td><td>247</td></tr> <tr><td>240</td><td>561</td><td>295</td></tr> <tr><td>264</td><td>672</td><td>359</td></tr> <tr><td>280</td><td>750</td><td>404</td></tr> </tbody> </table>					Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	150	218	108	160	249	125	170	283	142	180	318	161	200	393	202	220	474	247	240	561	295	264	672	359	280	750	404
Input Voltage [V]	Hold-Up Time [mS]																																			
	Load 50%	Load 100%																																		
150	218	108																																		
160	249	125																																		
170	283	142																																		
180	318	161																																		
200	393	202																																		
220	474	247																																		
240	561	295																																		
264	672	359																																		
280	750	404																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																				

COSEL

Model	LDA30F-3
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+3.0V 6A

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Time [mS]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0.0	—	—	—
1.0	669	876	1428
2.0	415	600	950
3.0	329	455	665
4.0	214	297	515
5.0	180	246	425
6.0	140	199	269
6.6	126	169	194
—	—	—	—
—	—	—	—
—	—	—	—

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-3																																																	
Item	Load Regulation 静的負荷変動	Temperature Testing Circuitry	25°C Figure A																																															
Object	+3.0V 6A																																																	
1. Graph																																																		
<p>—△— Input Volt. 170 V —□— Input Volt. 200 V —○— Input Volt. 264 V</p>			2. Values																																															
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>3.061</td> <td>3.061</td> <td>3.061</td> </tr> <tr> <td>1.0</td> <td>3.061</td> <td>3.061</td> <td>3.060</td> </tr> <tr> <td>2.0</td> <td>3.060</td> <td>3.060</td> <td>3.060</td> </tr> <tr> <td>3.0</td> <td>3.060</td> <td>3.060</td> <td>3.060</td> </tr> <tr> <td>4.0</td> <td>3.059</td> <td>3.059</td> <td>3.059</td> </tr> <tr> <td>5.0</td> <td>3.059</td> <td>3.059</td> <td>3.059</td> </tr> <tr> <td>6.0</td> <td>3.058</td> <td>3.058</td> <td>3.058</td> </tr> <tr> <td>6.6</td> <td>3.058</td> <td>3.058</td> <td>3.058</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	3.061	3.061	3.061	1.0	3.061	3.061	3.060	2.0	3.060	3.060	3.060	3.0	3.060	3.060	3.060	4.0	3.059	3.059	3.059	5.0	3.059	3.059	3.059	6.0	3.058	3.058	3.058	6.6	3.058	3.058	3.058	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																															
0.0	3.061	3.061	3.061																																															
1.0	3.061	3.061	3.060																																															
2.0	3.060	3.060	3.060																																															
3.0	3.060	3.060	3.060																																															
4.0	3.059	3.059	3.059																																															
5.0	3.059	3.059	3.059																																															
6.0	3.058	3.058	3.058																																															
6.6	3.058	3.058	3.058																																															
—	—	—	—																																															
—	—	—	—																																															


Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LDA30F-3
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)
Object	+3V6A

1. Graph



Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form
図 リップル波形詳細図

Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 170 [V]	Input Volt. 264 [V]
0.0	10	15
1.0	15	15
2.0	15	15
3.0	15	20
4.0	15	20
5.0	20	25
6.0	20	30
6.6	30	40
--	--	--
--	--	--
--	--	--

COSEL

Model	LDA30F-3
Item	Ripple-Noise リップルノイズ
Object	+3V10A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 170 [V]	Input Volt. 264 [V]
0.0	15	15
1.0	20	20
2.0	25	25
3.0	25	30
4.0	30	35
5.0	30	40
6.0	35	45
6.6	45	50
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line

入力商用周期

T2: Due to Switching

スイッチング周期




Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSSEL


Model	LDA30F-3																																																										
Item	Overcurrent Protection 過電流保護	Temperature 25°C Testing Circuitry Figure A																																																									
Object	+3.0V 6A																																																										
1. Graph	<p>Input Volt. 170 V Input Volt. 200 V [V] Input Volt. 264 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>3.00</td><td>7.84</td><td>7.74</td><td>7.75</td></tr> <tr><td>2.85</td><td>7.79</td><td>7.77</td><td>7.80</td></tr> <tr><td>2.70</td><td>7.79</td><td>7.78</td><td>7.81</td></tr> <tr><td>2.40</td><td>7.81</td><td>7.80</td><td>7.84</td></tr> <tr><td>2.10</td><td>7.82</td><td>7.82</td><td>7.87</td></tr> <tr><td>1.80</td><td>7.83</td><td>7.83</td><td>7.89</td></tr> <tr><td>1.50</td><td>7.83</td><td>7.83</td><td>7.89</td></tr> <tr><td>1.20</td><td>7.82</td><td>7.81</td><td>7.86</td></tr> <tr><td>0.90</td><td>7.78</td><td>7.75</td><td>7.76</td></tr> <tr><td>0.60</td><td>7.68</td><td>7.62</td><td>7.53</td></tr> <tr><td>0.30</td><td>7.46</td><td>7.32</td><td>7.12</td></tr> <tr><td>0.00</td><td>7.06</td><td>6.82</td><td>6.34</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	3.00	7.84	7.74	7.75	2.85	7.79	7.77	7.80	2.70	7.79	7.78	7.81	2.40	7.81	7.80	7.84	2.10	7.82	7.82	7.87	1.80	7.83	7.83	7.89	1.50	7.83	7.83	7.89	1.20	7.82	7.81	7.86	0.90	7.78	7.75	7.76	0.60	7.68	7.62	7.53	0.30	7.46	7.32	7.12	0.00	7.06	6.82	6.34
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																								
3.00	7.84	7.74	7.75																																																								
2.85	7.79	7.77	7.80																																																								
2.70	7.79	7.78	7.81																																																								
2.40	7.81	7.80	7.84																																																								
2.10	7.82	7.82	7.87																																																								
1.80	7.83	7.83	7.89																																																								
1.50	7.83	7.83	7.89																																																								
1.20	7.82	7.81	7.86																																																								
0.90	7.78	7.75	7.76																																																								
0.60	7.68	7.62	7.53																																																								
0.30	7.46	7.32	7.12																																																								
0.00	7.06	6.82	6.34																																																								
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																											

COSEL

Model	LDA30F-3	Testing Circuitry Figure A																																																					
Item	Overvoltage Protection 過電圧保護																																																						
Object	+3.0V 6A																																																						
1. Graph	<p style="text-align: center;">—△— Input Volt. 170 V —□— Input Volt. 200 V —○— Input Volt. 264 V</p> <p style="text-align: center;">[V]</p> <p style="text-align: center;">Operating Point [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>4.83</td><td>4.83</td><td>4.83</td></tr> <tr><td>-10</td><td>4.83</td><td>4.83</td><td>4.83</td></tr> <tr><td>0</td><td>4.77</td><td>4.76</td><td>4.76</td></tr> <tr><td>10</td><td>4.69</td><td>4.69</td><td>4.69</td></tr> <tr><td>20</td><td>4.69</td><td>4.69</td><td>4.69</td></tr> <tr><td>25</td><td>4.63</td><td>4.62</td><td>4.62</td></tr> <tr><td>30</td><td>4.62</td><td>4.62</td><td>4.62</td></tr> <tr><td>40</td><td>4.62</td><td>4.62</td><td>4.62</td></tr> <tr><td>50</td><td>4.55</td><td>4.55</td><td>4.55</td></tr> <tr><td>60</td><td>4.48</td><td>4.48</td><td>4.48</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Operating Point [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-20	4.83	4.83	4.83	-10	4.83	4.83	4.83	0	4.77	4.76	4.76	10	4.69	4.69	4.69	20	4.69	4.69	4.69	25	4.63	4.62	4.62	30	4.62	4.62	4.62	40	4.62	4.62	4.62	50	4.55	4.55	4.55	60	4.48	4.48	4.48	—	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
-20	4.83	4.83	4.83																																																				
-10	4.83	4.83	4.83																																																				
0	4.77	4.76	4.76																																																				
10	4.69	4.69	4.69																																																				
20	4.69	4.69	4.69																																																				
25	4.63	4.62	4.62																																																				
30	4.62	4.62	4.62																																																				
40	4.62	4.62	4.62																																																				
50	4.55	4.55	4.55																																																				
60	4.48	4.48	4.48																																																				
—	—	—	—																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						
(注)	斜線は定格周囲温度範囲を示す。																																																						

COSEL

Model	LDA30F-3	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	<hr/>		



Input Voltage 200 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 22.40 [A]

② 1.20 [A]




COSEL

Model	LDA30F-3
Item	Rise and Fall Time 立上り、立下り時間
Object	+3.0V 6A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		40.8	1.5	42.3	287.8	6.0	
100 %		41.0	1.8	42.8	141.8	3.0	



COSEL


Model	LDA30F-3	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+3.0V6A																																																						
1. Graph	<p style="text-align: center;"> △ Input Volt. 170V □ Input Volt. 200V ○ Input Volt. 264V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>																																																						
2. Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="text-align: center;">Ambient Temperature [°C]</th> <th colspan="3" style="text-align: center;">Output Voltage [V]</th> </tr> <tr> <th style="text-align: center;">Input Volt. 170[V]</th> <th style="text-align: center;">Input Volt. 200[V]</th> <th style="text-align: center;">Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">-20</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td></tr> <tr> <td style="text-align: center;">-10</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td></tr> <tr> <td style="text-align: center;">0</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td></tr> <tr> <td style="text-align: center;">10</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td><td style="text-align: center;">3.061</td></tr> <tr> <td style="text-align: center;">20</td><td style="text-align: center;">3.060</td><td style="text-align: center;">3.060</td><td style="text-align: center;">3.060</td></tr> <tr> <td style="text-align: center;">25</td><td style="text-align: center;">3.059</td><td style="text-align: center;">3.059</td><td style="text-align: center;">3.059</td></tr> <tr> <td style="text-align: center;">30</td><td style="text-align: center;">3.059</td><td style="text-align: center;">3.059</td><td style="text-align: center;">3.059</td></tr> <tr> <td style="text-align: center;">40</td><td style="text-align: center;">3.057</td><td style="text-align: center;">3.057</td><td style="text-align: center;">3.057</td></tr> <tr> <td style="text-align: center;">50</td><td style="text-align: center;">3.056</td><td style="text-align: center;">3.056</td><td style="text-align: center;">3.056</td></tr> <tr> <td style="text-align: center;">60</td><td style="text-align: center;">3.054</td><td style="text-align: center;">3.054</td><td style="text-align: center;">3.054</td></tr> <tr> <td style="text-align: center;">—</td><td style="text-align: center;">—</td><td style="text-align: center;">—</td><td style="text-align: center;">—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-20	3.061	3.061	3.061	-10	3.061	3.061	3.061	0	3.061	3.061	3.061	10	3.061	3.061	3.061	20	3.060	3.060	3.060	25	3.059	3.059	3.059	30	3.059	3.059	3.059	40	3.057	3.057	3.057	50	3.056	3.056	3.056	60	3.054	3.054	3.054	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
-20	3.061	3.061	3.061																																																				
-10	3.061	3.061	3.061																																																				
0	3.061	3.061	3.061																																																				
10	3.061	3.061	3.061																																																				
20	3.060	3.060	3.060																																																				
25	3.059	3.059	3.059																																																				
30	3.059	3.059	3.059																																																				
40	3.057	3.057	3.057																																																				
50	3.056	3.056	3.056																																																				
60	3.054	3.054	3.054																																																				
—	—	—	—																																																				

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model	LDA30F-3
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+3.0V 6A



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	52	57
-10	51	56
0	50	55
10	50	55
20	49	55
25	49	55
30	49	55
40	49	54
50	48	54
60	48	54
—	—	—

COSEL

Model	LDA30F-3																																							
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																						
Object	+3V6A																																							
1. Graph																																								
			2. Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>60</td> <td>70</td> </tr> <tr> <td>-10</td> <td>30</td> <td>40</td> </tr> <tr> <td>0</td> <td>25</td> <td>30</td> </tr> <tr> <td>10</td> <td>25</td> <td>30</td> </tr> <tr> <td>20</td> <td>20</td> <td>25</td> </tr> <tr> <td>25</td> <td>20</td> <td>25</td> </tr> <tr> <td>30</td> <td>20</td> <td>25</td> </tr> <tr> <td>40</td> <td>15</td> <td>20</td> </tr> <tr> <td>50</td> <td>15</td> <td>20</td> </tr> <tr> <td>60</td> <td>15</td> <td>20</td> </tr> <tr> <td>--</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-20	60	70	-10	30	40	0	25	30	10	25	30	20	20	25	25	20	25	30	20	25	40	15	20	50	15	20	60	15	20	--	—	—
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-20	60	70																																						
-10	30	40																																						
0	25	30																																						
10	25	30																																						
20	20	25																																						
25	20	25																																						
30	20	25																																						
40	15	20																																						
50	15	20																																						
60	15	20																																						
--	—	—																																						

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。



Model	LDA30F-3	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+3.0V 6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 170~264 V

Load Current : 0~6 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 170~264 V

負荷電流 0~6 A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	-10	170	0	3.063		
Minimum Voltage	50	264	6	3.055	±4	±0.2

COSEL




Figure A