


RADIATED EMISSION

Model Name :LDA50F-3
 Model No. :
 Serial No. :
 Points :2
 Detector :PEAK/QP
 Polarization :Hori.&Vert.
 Limit:[CISPR 22] Class B<3m>

Power Supply :230V(1 Phase) 50Hz
 Temp. :25degC
 Humi. :44%
 Date :2001/2/22
 Test Equip. :R3132,ESPC
 Comment :




Frequency [MHz]	Meter Reading (QP) [dBuV]	Antena Factor [dBuV]	Cable & Preamp [dB]	Level (Qp) [dBuV]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]
990.718	12.8	25.4	-23.4	14.8	19	101	Hori.	47.0	32.2
997.918	13.0	25.3	-24.3	14.0	150	134	Vert.	47.0	33.0



LINE CONDUCTION

Model Name	:LDA50F-3	Power Supply	:230V(1 Phase) 50Hz
Model No.	:	Temp.	:25degC
Serial No.	:	Humi.	:44%
Points	:4	Date	:2001/2/22
Detector	:PEAK/QP/Ave.	Test Equip.	:R3132,ESPC
Line Mode	:VA/VB	Comment	:
Limit1:[CISPR Pub22] Class B(QP)			
Limit2:[CISPR Pub22] Class B(Ave.)			



Frequency [MHz]	Meter Reading (QP) [dBuV]	Meter Reading (Ave.) [dBuV]	Factor [dB]	Level (QP) [dBuV]	Level (Ave.) [dBuV]	Line	Limit (QP) [dBuV]	Limit (Ave.) [dBuV]	Margin (QP) [dB]	Margin (Ave.) [dB]
0.1511	41.1	16.0	9.8	50.9	25.8	VA	66.0	56.0	15.1	30.2
0.1741	38.1	14.2	9.8	47.9	24.0	VA	64.8	54.8	16.9	30.8
16.6016	30.8	30.2	10.2	41.0	40.4	VA	50.0	50.0	19.0	9.6
0.4143	32.4	32.7	9.8	42.2	42.5	VB	47.6	47.6	15.4	5.1