



TEST DATA OF LEB100F-0524
(100V INPUT)

Regulated DC Power Supply

Mar. 16, 2000

Approved by : T. Miura
Design Manager

Prepared by : T. Koide
Design Engineer

コーセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Power)	2
入力電流 (負荷特性)	
3. Input Power (by Load Power)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Power)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Power)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	10
瞬時停電保障	
10. Load Regulation	12
静的負荷変動	
11. Ripple Voltage (by Load Current)	13
リップル電圧 (負荷特性)	
12. Ripple-Noise	15
リップルノイズ	
13. Overcurrent Protection	17
過電流保護	
14. Overvoltage Protection	18
過電圧保護	
15. Inrush Current	19
突入電流	
16. Dynamic Load Response	20
動的負荷変動	
17. Rise and Fall Time	22
立上り、立下り時間	
18. Ambient Temperature Drift	24
周囲温度変動	
19. Minimum Input Voltage for Regulated Output Voltage	25
最低レギュレーション電圧	
20. Ripple Voltage (by Ambient Temperature)	26
リップル電圧 (周囲温度特性)	
21. Time Lapse Drift	27
経時ドリフト	
22. Output Voltage Accuracy	28
定電圧精度	
23. Harmonic Current	29
高調波電流	
24. Oscillator Frequency	31
発振周波数	
25. Condensation	32
結露特性	
26. Leakage Current	33
漏洩電流	
27. Line Noise Tolerance	34
入力雑音耐量	
28. Conducted Emission	35
雑音端子電圧	
29. Figure of Testing Circuitry	36
測定回路図	

(Final Page 37)

COSEL


Model LEB100F-0524

Item Line Regulation
静的の入力変動

Object V1: +5.0V 5A

1. Graph

□ Load 50%
 △ Load 100%

Temperature
Testing Circuitry25°C
Figure A


2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	5.047	5.036
80	5.047	5.037
85	5.047	5.037
90	5.047	5.037
100	5.047	5.037
110	5.047	5.037
120	5.047	5.037
132	5.047	5.037
140	5.047	5.037

Object V2: +24.0V 4A

1. Graph

□ Load 50%
 △ Load 100%



2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	24.154	24.148
80	24.153	24.149
85	24.153	24.149
90	24.153	24.149
100	24.153	24.149
110	24.153	24.149
120	24.153	24.149
132	24.153	24.149
140	24.153	24.149

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LEB100F-0524																																																									
Item	Input Current (by Load Power) 入力電流（負荷特性）	Temperature Testing Circuitry	25°C Figure A																																																							
Output	——																																																									
1. Graph																																																										
<p>Input Current [A]</p> <p>Load Power [W]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V Input Volt. 100V Input Volt. 132V 																																																										
2. Values																																																										
<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.112</td><td>0.098</td><td>0.083</td></tr> <tr><td>20</td><td>0.446</td><td>0.383</td><td>0.299</td></tr> <tr><td>40</td><td>0.719</td><td>0.613</td><td>0.472</td></tr> <tr><td>60</td><td>0.994</td><td>0.844</td><td>0.643</td></tr> <tr><td>80</td><td>1.274</td><td>1.079</td><td>0.820</td></tr> <tr><td>100</td><td>1.560</td><td>1.318</td><td>0.996</td></tr> <tr><td>110</td><td>1.706</td><td>1.442</td><td>1.087</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Power [W]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.112	0.098	0.083	20	0.446	0.383	0.299	40	0.719	0.613	0.472	60	0.994	0.844	0.643	80	1.274	1.079	0.820	100	1.560	1.318	0.996	110	1.706	1.442	1.087	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Power [W]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	0.112	0.098	0.083																																																							
20	0.446	0.383	0.299																																																							
40	0.719	0.613	0.472																																																							
60	0.994	0.844	0.643																																																							
80	1.274	1.079	0.820																																																							
100	1.560	1.318	0.996																																																							
110	1.706	1.442	1.087																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
<p>Note: Slanted line shows the range of the rated load power.</p> <p>(注)斜線は定格出力電力範囲を示す。</p>																																																										

COSEL

Model	LEB100F-0524	Temperature 25°C Testing Circuitry Figure A																																																								
Item	Input Power (by Load Power) 入力電力 (負荷特性)																																																									
Output	—																																																									
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> △ Input Volt. 85V □ Input Volt. 100V ○ Input Volt. 132V <table border="1"> <thead> <tr> <th>Load Power [W]</th> <th>Input Power 85V [W]</th> <th>Input Power 100V [W]</th> <th>Input Power 132V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>7.74</td><td>7.67</td><td>7.75</td></tr> <tr><td>20</td><td>35.80</td><td>35.70</td><td>35.42</td></tr> <tr><td>40</td><td>59.20</td><td>58.90</td><td>58.30</td></tr> <tr><td>60</td><td>82.90</td><td>82.30</td><td>81.30</td></tr> <tr><td>80</td><td>106.90</td><td>106.10</td><td>104.90</td></tr> <tr><td>100</td><td>131.90</td><td>130.20</td><td>128.60</td></tr> <tr><td>110</td><td>144.30</td><td>142.80</td><td>140.50</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Power [W]	Input Power 85V [W]	Input Power 100V [W]	Input Power 132V [W]	0	7.74	7.67	7.75	20	35.80	35.70	35.42	40	59.20	58.90	58.30	60	82.90	82.30	81.30	80	106.90	106.10	104.90	100	131.90	130.20	128.60	110	144.30	142.80	140.50	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
Load Power [W]	Input Power 85V [W]	Input Power 100V [W]	Input Power 132V [W]																																																							
0	7.74	7.67	7.75																																																							
20	35.80	35.70	35.42																																																							
40	59.20	58.90	58.30																																																							
60	82.90	82.30	81.30																																																							
80	106.90	106.10	104.90																																																							
100	131.90	130.20	128.60																																																							
110	144.30	142.80	140.50																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>7.74</td><td>7.67</td><td>7.75</td></tr> <tr><td>20</td><td>35.80</td><td>35.70</td><td>35.42</td></tr> <tr><td>40</td><td>59.20</td><td>58.90</td><td>58.30</td></tr> <tr><td>60</td><td>82.90</td><td>82.30</td><td>81.30</td></tr> <tr><td>80</td><td>106.90</td><td>106.10</td><td>104.90</td></tr> <tr><td>100</td><td>131.90</td><td>130.20</td><td>128.60</td></tr> <tr><td>110</td><td>144.30</td><td>142.80</td><td>140.50</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Power [W]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	7.74	7.67	7.75	20	35.80	35.70	35.42	40	59.20	58.90	58.30	60	82.90	82.30	81.30	80	106.90	106.10	104.90	100	131.90	130.20	128.60	110	144.30	142.80	140.50	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Power [W]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	7.74	7.67	7.75																																																							
20	35.80	35.70	35.42																																																							
40	59.20	58.90	58.30																																																							
60	82.90	82.30	81.30																																																							
80	106.90	106.10	104.90																																																							
100	131.90	130.20	128.60																																																							
110	144.30	142.80	140.50																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load power.

(注)斜線は定格出力電力範囲を示す。

COSEL


Model	LEB100F-0524	Temperature	25°C																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																																
Object																																			
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>70.8</td><td>75.7</td></tr> <tr><td>80</td><td>71.0</td><td>76.3</td></tr> <tr><td>85</td><td>71.2</td><td>76.7</td></tr> <tr><td>90</td><td>71.4</td><td>77.1</td></tr> <tr><td>100</td><td>71.6</td><td>77.8</td></tr> <tr><td>110</td><td>71.8</td><td>78.1</td></tr> <tr><td>120</td><td>72.1</td><td>78.4</td></tr> <tr><td>132</td><td>72.2</td><td>78.6</td></tr> <tr><td>140</td><td>72.3</td><td>78.7</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	75	70.8	75.7	80	71.0	76.3	85	71.2	76.7	90	71.4	77.1	100	71.6	77.8	110	71.8	78.1	120	72.1	78.4	132	72.2	78.6	140	72.3	78.7		
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																	
75	70.8	75.7																																	
80	71.0	76.3																																	
85	71.2	76.7																																	
90	71.4	77.1																																	
100	71.6	77.8																																	
110	71.8	78.1																																	
120	72.1	78.4																																	
132	72.2	78.6																																	
140	72.3	78.7																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>70.8</td><td>75.7</td></tr> <tr><td>80</td><td>71.0</td><td>76.3</td></tr> <tr><td>85</td><td>71.2</td><td>76.7</td></tr> <tr><td>90</td><td>71.4</td><td>77.1</td></tr> <tr><td>100</td><td>71.6</td><td>77.8</td></tr> <tr><td>110</td><td>71.8</td><td>78.1</td></tr> <tr><td>120</td><td>72.1</td><td>78.4</td></tr> <tr><td>132</td><td>72.2</td><td>78.6</td></tr> <tr><td>140</td><td>72.3</td><td>78.7</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	70.8	75.7	80	71.0	76.3	85	71.2	76.7	90	71.4	77.1	100	71.6	77.8	110	71.8	78.1	120	72.1	78.4	132	72.2	78.6	140	72.3	78.7
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	70.8	75.7																																	
80	71.0	76.3																																	
85	71.2	76.7																																	
90	71.4	77.1																																	
100	71.6	77.8																																	
110	71.8	78.1																																	
120	72.1	78.4																																	
132	72.2	78.6																																	
140	72.3	78.7																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LEB100F-0524
Item	Efficiency (by Load Power) 効率(負荷特性)
Output	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Power [W]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
20	56.5	56.5	56.9
40	68.2	68.5	69.4
60	73.2	73.7	74.7
80	75.7	76.2	77.1
100	76.7	77.8	78.6
110	77.0	78.0	79.1
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load power.

(注) 斜線は定格出力電力範囲を示す。

COSEL

Model	LEB100F-0524																																	
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.98</td><td>1.00</td></tr> <tr><td>80</td><td>0.98</td><td>1.00</td></tr> <tr><td>85</td><td>0.98</td><td>0.99</td></tr> <tr><td>90</td><td>0.98</td><td>0.99</td></tr> <tr><td>100</td><td>0.97</td><td>0.99</td></tr> <tr><td>110</td><td>0.96</td><td>0.99</td></tr> <tr><td>120</td><td>0.96</td><td>0.98</td></tr> <tr><td>132</td><td>0.95</td><td>0.98</td></tr> <tr><td>140</td><td>0.94</td><td>0.97</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.98	1.00	80	0.98	1.00	85	0.98	0.99	90	0.98	0.99	100	0.97	0.99	110	0.96	0.99	120	0.96	0.98	132	0.95	0.98	140	0.94	0.97
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.98	1.00																																
80	0.98	1.00																																
85	0.98	0.99																																
90	0.98	0.99																																
100	0.97	0.99																																
110	0.96	0.99																																
120	0.96	0.98																																
132	0.95	0.98																																
140	0.94	0.97																																
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																		


COSEL

Model LEB100F-0524

Item Power Factor (by Load Power)
力率 (負荷特性)

Output _____

1. Graph



Note: Slanted line shows the range of the rated load power.

(注)斜線は定格出力電力範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Power [W]	Power Factor		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	0.81	0.78	0.71
20	0.94	0.93	0.90
40	0.97	0.96	0.94
60	0.98	0.98	0.96
80	0.99	0.98	0.97
100	0.99	0.99	0.98
110	1.00	0.99	0.98
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	LEB100F-0524	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	V1: +5.0V 5A	2. Values																																	
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p>																																		
	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>—</td><td>—</td></tr> <tr><td>80</td><td>96</td><td>34</td></tr> <tr><td>85</td><td>98</td><td>37</td></tr> <tr><td>90</td><td>100</td><td>39</td></tr> <tr><td>100</td><td>102</td><td>41</td></tr> <tr><td>110</td><td>104</td><td>43</td></tr> <tr><td>120</td><td>105</td><td>44</td></tr> <tr><td>132</td><td>107</td><td>45</td></tr> <tr><td>140</td><td>107</td><td>46</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	—	—	80	96	34	85	98	37	90	100	39	100	102	41	110	104	43	120	105	44	132	107	45	140	107	46
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	—	—																																	
80	96	34																																	
85	98	37																																	
90	100	39																																	
100	102	41																																	
110	104	43																																	
120	105	44																																	
132	107	45																																	
140	107	46																																	
	<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。 (注)斜線は定格入力電圧範囲を示す。</p>																																		

COSEL

Model	LEB100F-0524	Temperature	25°C																																
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																
Object	V2: +24.0V 4A																																		
1. Graph	<p>Load 50% Load 100%</p> <p>[mS]</p> <p>1000</p> <p>100</p> <p>10</p> <p>1</p> <p>Hold-Up Time</p> <p>Input Voltage [V]</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>—</td> <td>—</td> </tr> <tr> <td>80</td> <td>35</td> <td>19</td> </tr> <tr> <td>85</td> <td>38</td> <td>20</td> </tr> <tr> <td>90</td> <td>39</td> <td>21</td> </tr> <tr> <td>100</td> <td>41</td> <td>24</td> </tr> <tr> <td>110</td> <td>43</td> <td>25</td> </tr> <tr> <td>120</td> <td>44</td> <td>27</td> </tr> <tr> <td>132</td> <td>45</td> <td>28</td> </tr> <tr> <td>140</td> <td>46</td> <td>28</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	—	—	80	35	19	85	38	20	90	39	21	100	41	24	110	43	25	120	44	27	132	45	28	140	46	28
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	—	—																																	
80	35	19																																	
85	38	20																																	
90	39	21																																	
100	41	24																																	
110	43	25																																	
120	44	27																																	
132	45	28																																	
140	46	28																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。


(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	LEB100F-0524
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	V1: +5.0V5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Time [mS]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	—	—	—
0.8	257	263	269
1.6	147	154	160
2.4	100	106	112
3.2	71	79	85
4.0	47	54	61
4.8	29	34	39
5.0	27	31	37
5.5	20	24	28
—	—	—	—
—	—	—	—

Instantaneous Compensation Time

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated load current.


瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。
(注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	LEB100F-0524
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	V2: +24.0 V 4A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load Current [A]	Time [mS]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	—	—	—
0.8	56	64	73
1.6	42	47	55
2.4	31	37	42
3.2	22	28	32
4.0	16	21	26
4.4	14	19	23
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。
(注)斜線は定格負荷電流範囲を示す。

COSSEL


Model	LEB100F-0524
Item	Load Regulation 静的負荷変動
Object	V1: +5.0V5A



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	5.056	5.056	5.056
0.8	5.053	5.053	5.053
1.6	5.050	5.050	5.050
2.4	5.048	5.048	5.048
3.2	5.045	5.045	5.045
4.0	5.041	5.041	5.041
4.8	5.038	5.038	5.038
5.0	5.037	5.037	5.037
5.5	5.034	5.034	5.035
—	—	—	—



2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	24.158	24.158	24.158
0.8	24.155	24.155	24.155
1.6	24.153	24.153	24.153
2.4	24.152	24.152	24.152
3.2	24.150	24.150	24.150
4.0	24.148	24.148	24.148
4.4	24.148	24.147	24.148
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	LEB100F-0524																																							
Item	Ripple Voltage(by Load Current) リップル電圧(負荷特性)	Temperature Testing Circuitry 25°C Figure A																																						
Object	V1: +5.0 V 5A																																							
1. Graph																																								
		2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>15</td></tr> <tr><td>1.0</td><td>20</td><td>20</td></tr> <tr><td>2.0</td><td>20</td><td>20</td></tr> <tr><td>3.0</td><td>20</td><td>20</td></tr> <tr><td>4.0</td><td>20</td><td>20</td></tr> <tr><td>5.0</td><td>20</td><td>20</td></tr> <tr><td>5.5</td><td>20</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	15	15	1.0	20	20	2.0	20	20	3.0	20	20	4.0	20	20	5.0	20	20	5.5	20	20	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	15	15																																						
1.0	20	20																																						
2.0	20	20																																						
3.0	20	20																																						
4.0	20	20																																						
5.0	20	20																																						
5.5	20	20																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p> <p>図 リップル波形詳細図</p>																																								

COSEL


Model	LEB100F-0524	Temperature	25°C																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷特性)	Testing Circuitry	Figure A																																						
Object	V2: +24.0V 4A																																								
1. Graph																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>25</td><td>25</td></tr> <tr><td>0.8</td><td>35</td><td>35</td></tr> <tr><td>1.6</td><td>40</td><td>40</td></tr> <tr><td>2.4</td><td>40</td><td>40</td></tr> <tr><td>3.2</td><td>45</td><td>45</td></tr> <tr><td>4.0</td><td>45</td><td>45</td></tr> <tr><td>4.4</td><td>45</td><td>45</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	25	25	0.8	35	35	1.6	40	40	2.4	40	40	3.2	45	45	4.0	45	45	4.4	45	45	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	25	25																																							
0.8	35	35																																							
1.6	40	40																																							
2.4	40	40																																							
3.2	45	45																																							
4.0	45	45																																							
4.4	45	45																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p – p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	LEB100F-0524	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	V1: +5.0V 5A																																								
1. Graph	<p>—△— Input Volt. 85V ○ Input Volt. 132V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>40</td><td>40</td></tr> <tr><td>1.0</td><td>50</td><td>50</td></tr> <tr><td>2.0</td><td>50</td><td>50</td></tr> <tr><td>3.0</td><td>50</td><td>50</td></tr> <tr><td>4.0</td><td>60</td><td>60</td></tr> <tr><td>5.0</td><td>65</td><td>65</td></tr> <tr><td>5.5</td><td>65</td><td>65</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	40	40	1.0	50	50	2.0	50	50	3.0	50	50	4.0	60	60	5.0	65	65	5.5	65	65	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	40	40																																							
1.0	50	50																																							
2.0	50	50																																							
3.0	50	50																																							
4.0	60	60																																							
5.0	65	65																																							
5.5	65	65																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	LEB100F-0524
Item	Ripple-Noise リップルノイズ
Object	V2: +24.0V 4A



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	50	50
0.8	70	70
1.6	85	85
2.4	85	85
3.2	90	90
4.0	95	95
4.4	100	100
—	—	—
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期





Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSEL


Model	LEB100F-0524
Item	Overcurrent Protection 過電流保護
Object	V1: +5.0V5A

Temperature 25°C
Testing Circuitry Figure A

Note: Slanted line shows the range of the rated load current.

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
5.00	6.77	6.90	7.04
4.75	6.66	6.79	6.91
4.50	6.50	6.62	6.74
4.00	6.25	6.34	6.44
3.50	5.93	6.02	6.10
3.00	5.62	5.70	5.77
2.50	5.27	5.33	5.40
2.00	4.89	4.94	5.00
1.50	4.50	4.55	4.59
1.00	4.01	4.05	4.10
0.50	3.53	3.57	3.62
0.00	4.64	4.72	4.82



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 16.8V to 0V.


2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
24.00	8.50	8.51	8.51
22.80	8.52	8.53	8.54
21.60	8.55	8.57	8.57
19.20	8.61	8.60	8.58
16.80	8.67	8.67	8.67
14.40	—	—	—
12.00	—	—	—
9.60	—	—	—
7.20	—	—	—
4.80	—	—	—
2.40	—	—	—
0.00	—	—	—

COSEL

Model	LEB100F-0524
Item	Overvoltage Protection 過電圧保護
Object	V2: +24.0V 4A

Testing Circuitry Figure A



2. Values


Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	29.7	29.7	29.7
-10	29.9	29.9	29.9
0	30.1	30.1	30.1
10	30.3	30.3	30.3
20	30.5	30.5	30.5
25	30.6	30.6	30.6
30	30.7	30.7	30.7
40	30.9	30.9	30.9
50	31.2	31.2	31.2
70	31.6	31.6	31.6
--	--	--	--

Note: Slanted line shows the range of the rated ambient temperature.


(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	LEB100F-0524	Temperature Testing Circuitry	25°C Figure A
Item	Inrush Current 突入電流		
Object	_____		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current
 ① 11.62 [A]
 ② 9.28 [A]




COSEL

Model		LEB100F-0524	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Responce 動的負荷變動			
Object	V1: +5.0V 5A			



Input Volt. 100 V
Cycle 1000 mS



Min. Load \longleftrightarrow
Load 100 %



Min. Load \longleftrightarrow
Load 50 %




COSEL



Model	LEB100F-0524	Temperature Testing Circuitry 25°C Figure A
Item	Dynamic Load Response 動的負荷變動	
Object	V2: +24.0V 4A	

Input Volt. 100 V
 Cycle 1000 mS


Load Current




Min. Load ↔
 Load 100 %



Min. Load ↔
 Load 50 %



100 mV/div



10 ms/div



COSEL

Model	LEB100F-0524
Item	Rise and Fall Time 立上り、立下り時間
Object	_____

Temperature 25°C
Testing Circuitry Figure A


Load Power 100 %
Input Volt. 100 V

1. Graph



2. Values

Output	Time	T d	T r	T s	T h	T f	[mS]
V1		28.0	11.5	39.5	50.8	60.2	
V2		340.0	12.0	352.0	28.2	18.8	
-		-	-	-	-	-	
-		-	-	-	-	-	





COSEL

Model	LEB100F-0524
Item	Rise and Fall Time 立上り、立下り時間
Object	—


Temperature 25°C
Testing Circuitry Figure ALoad Power 50 %
Input Volt. 100 V

1. Graph



2. Values

Output	Time	T d	T r	T s	T h	T f	[mS]
V1		27.2	8.2	35.4	113.4	31.0	
V2		339.5	12.0	351.5	49.6	31.0	
—		—	—	—	—	—	
—		—	—	—	—	—	




COSEL

Model	LEB100F-0524
Item	Ambient Temperature Drift 周囲温度変動
Object	V1: +5.0V5A

Testing Circuitry Figure A


1. Graph



2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	5.024	5.024	5.024
-10	5.027	5.027	5.027
0	5.029	5.029	5.029
10	5.031	5.031	5.032
20	5.034	5.034	5.034
25	5.036	5.036	5.036
30	5.037	5.038	5.038
40	5.038	5.038	5.038
50	5.037	5.038	5.038
70	5.034	5.034	5.034
—	—	—	—

1. Graph




2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	24.071	24.071	24.072
-10	24.086	24.086	24.086
0	24.101	24.101	24.101
10	24.117	24.117	24.118
20	24.135	24.135	24.135
25	24.142	24.143	24.143
30	24.148	24.149	24.149
40	24.158	24.158	24.159
50	24.163	24.163	24.164
70	24.163	24.163	24.163
—	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。

COSEL

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	57	74
-10	57	74
0	57	74
10	57	74
20	57	74
25	57	74
30	57	74
40	57	74
50	57	74
70	57	74
—	—	—



Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	73	74
-10	73	74
0	73	74
10	73	74
20	73	74
25	73	74
30	73	74
40	73	74
50	73	74
70	73	74
—	—	—


Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL


Model	LEB100F-0524
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	V1: +5.0V 5A

Testing Circuitry Figure A



2. Values

Ambient Temperature [°C]	Ripple Output Voltage [mV]	
	Load 50%	Load 100%
-20	25	30
-10	25	30
0	20	20
10	20	20
20	20	20
25	20	20
30	15	15
40	15	15
50	15	15
70	15	15
—	—	—





2. Values

Ambient Temperature [°C]	Ripple Output Voltage [mV]	
	Load 50%	Load 100%
-20	90	110
-10	80	90
0	75	75
10	55	60
20	45	45
25	40	45
30	40	40
40	40	40
50	40	40
70	35	35
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	LEB100F-0524	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	V1: +5.0V5A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.033</td></tr> <tr><td>0.5</td><td>5.035</td></tr> <tr><td>1.0</td><td>5.035</td></tr> <tr><td>2.0</td><td>5.035</td></tr> <tr><td>3.0</td><td>5.035</td></tr> <tr><td>4.0</td><td>5.035</td></tr> <tr><td>5.0</td><td>5.035</td></tr> <tr><td>6.0</td><td>5.035</td></tr> <tr><td>7.0</td><td>5.035</td></tr> <tr><td>8.0</td><td>5.035</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.033	0.5	5.035	1.0	5.035	2.0	5.035	3.0	5.035	4.0	5.035	5.0	5.035	6.0	5.035	7.0	5.035	8.0	5.035
Time since start [H]	Output Voltage [V]																								
0.0	5.033																								
0.5	5.035																								
1.0	5.035																								
2.0	5.035																								
3.0	5.035																								
4.0	5.035																								
5.0	5.035																								
6.0	5.035																								
7.0	5.035																								
8.0	5.035																								
Object																									
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.130</td></tr> <tr><td>0.5</td><td>24.134</td></tr> <tr><td>1.0</td><td>24.134</td></tr> <tr><td>2.0</td><td>24.135</td></tr> <tr><td>3.0</td><td>24.135</td></tr> <tr><td>4.0</td><td>24.135</td></tr> <tr><td>5.0</td><td>24.135</td></tr> <tr><td>6.0</td><td>24.135</td></tr> <tr><td>7.0</td><td>24.135</td></tr> <tr><td>8.0</td><td>24.135</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.130	0.5	24.134	1.0	24.134	2.0	24.135	3.0	24.135	4.0	24.135	5.0	24.135	6.0	24.135	7.0	24.135	8.0	24.135
Time since start [H]	Output Voltage [V]																								
0.0	24.130																								
0.5	24.134																								
1.0	24.134																								
2.0	24.135																								
3.0	24.135																								
4.0	24.135																								
5.0	24.135																								
6.0	24.135																								
7.0	24.135																								
8.0	24.135																								



Model	LEB100F-0524	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85~132 V

Load Current (V1) : 0~5 A

(V2) : 0~4 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage — Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 (V1) 0~5 A

(V2) 0~4 A

* 定電圧精度(変動値) = ±(出力電圧の最高値—出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$


2. Values

Object	V1:+5.0V5A					
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	50	132	0	5.057	±15	±0.3
Minimum Voltage	-10	85	5	5.027		
Object	V2:+24.0V4A					
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	50	85	0	24.171	±42	±0.2
Minimum Voltage	-10	85	4	24.088		


COSEL

Model	LEB100F-0524	Temperature	25°C
Item	Harmonic Current 高調波電流	Testing Circuitry	Figure E
Object	_____		

1. Input Current Waveform




2. Harmonic Current



COSEL


Model	LEB100F-0524	Temperature Testing Circuitry	25°C Figure E
Item	Harmonic Current 高調波電流		
Object	_____		

1. Input Current Waveform



Conditions	Values
Input Voltage [V]	100.1
Input Current [A]	0.709
Active Power [W]	68.7
Apparent Power [VA]	71.1
Frequency [Hz]	60
Power Factor	0.966
Output Power [W]	50


2. Harmonic Current



Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	0.68620
2	—	0.00060
3	5.28472	0.16630
4	—	0.00010
5	2.61938	0.06410
6	—	0.00000
7	1.76923	0.00820
8	—	0.00010
9	0.91908	0.01440
10	—	0.00000
11	0.75824	0.01170
12	—	0.00000
13	0.48252	0.00300
14	—	0.00000
15	0.34466	0.00570
16	—	0.00010
17	0.30411	0.00820
18	—	0.00010
19	0.27210	0.00670
20	—	0.00010
21	0.24618	0.00490
22	—	0.00000
23	0.22478	0.00640
24	—	0.00010
25	0.20679	0.00600
26	—	0.00010
27	0.19148	0.00350
28	—	0.00010
29	0.17827	0.00220
30	—	0.00010
31	0.16677	0.00220
32	—	0.00000
33	0.15666	0.00050
34	—	0.00000
35	0.14771	0.00210
36	—	0.00000
37	0.13973	0.00300
38	—	0.00000
39	0.13256	0.00260
40	—	0.00000

COSEL

Model	LEB100F-0524
Item	Oscillator Frequency 発振周波数
Object	V1: +5.0V 5A



Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Oscillator Frequency [KHz]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.8	368	370	371
1.6	263	264	265
2.4	202	204	204
3.2	161	164	165
4.0	134	138	139
4.8	116	118	118
5.0	113	115	116
5.5	104	106	107
—	—	—	—
—	—	—	—
—	—	—	—



Model	LEB100F-0524	Testing Circuitry Figure A
Item	Condensation 結露特性	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Object	V1: +5.0V 5A
--------	--------------

Item	Data	Testing Conditions
Output Voltage [V]	5.029	Input Volt.: 100V, Load Current:5A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:5A
Load Regulation [mV]	14	Input Volt.: 100V, Load Current:0~5A

Object	V2: +24.0V 4A
--------	---------------

Item	Data	Testing Conditions
Output Voltage [V]	24.099	Input Volt.: 100V, Load Current:4A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:4A
Load Regulation [mV]	9	Input Volt.: 100V, Load Current:0~4A



Model	LEB100F-0524
Item	Leakage Current 漏洩電流
Object	_____

Temperature 25°C
Testing Circuitry Figure B

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.17	0.19	0.25
(B) IEC60950	0.17	0.20	0.25

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	LEB100F-0524	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	V1: +5.0V5A		

1. Results

Conditions

Input Voltage : 100 V Pulse Input Duration: 1 min. or more
 Pulse Voltage : 2000 V Load : 100 %
 Pulse Cycle : 10 mS

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY		
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

Object	V2: +24.0V4A
--------	--------------

1. Results

Conditions

Input Voltage : 100 V Pulse Input Duration: 1 min. or more
 Pulse Voltage : 2000 V Load : 100 %
 Pulse Cycle : 10 mS

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY		
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

COSEL

Model	LEB100F-0524	Temperature Testing Circuitry Figure D	25°C
Item	Conducted Emission 雜音端子電壓		
Object	_____		

1. Graph


Remarks

Input Volt. 100 V (VCCI Class B)


120 V (FCC Class B)

Load 100 %

Limit1: [VCCI] Class B(QP)
 Limit2: [VCCI] Class B(Ave.)



Limit1: [FCC Part15] Class B



COSEL






Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E