

TEST DATA OF LFA300F-12-TY

Regulated DC Power Supply
December 20, 2010

Approved by : Yoshaki Shimizu Design Manager
Yoshaki Shimizu

Prepared by : Tomoyuki Mukaiyama Design Engineer
Tomoyuki Mukaiyama

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	LFA300F-12-TY																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	—	—	—																																																			
1.Graph	<p>— ▲ — Input Volt. 100V --- ■ --- Input Volt. 200V -·○-· Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.176</td><td>0.206</td><td>0.226</td></tr> <tr> <td>4.0</td><td>0.730</td><td>0.458</td><td>0.428</td></tr> <tr> <td>8.0</td><td>1.272</td><td>0.708</td><td>0.646</td></tr> <tr> <td>12.0</td><td>1.832</td><td>0.948</td><td>0.870</td></tr> <tr> <td>16.0</td><td>2.408</td><td>1.218</td><td>1.084</td></tr> <tr> <td>20.0</td><td>3.004</td><td>1.496</td><td>1.316</td></tr> <tr> <td>24.0</td><td>3.604</td><td>1.780</td><td>1.560</td></tr> <tr> <td>27.0</td><td>4.070</td><td>1.994</td><td>1.745</td></tr> <tr> <td>29.7</td><td>4.500</td><td>2.190</td><td>1.914</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.176	0.206	0.226	4.0	0.730	0.458	0.428	8.0	1.272	0.708	0.646	12.0	1.832	0.948	0.870	16.0	2.408	1.218	1.084	20.0	3.004	1.496	1.316	24.0	3.604	1.780	1.560	27.0	4.070	1.994	1.745	29.7	4.500	2.190	1.914	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.176	0.206	0.226																																																			
4.0	0.730	0.458	0.428																																																			
8.0	1.272	0.708	0.646																																																			
12.0	1.832	0.948	0.870																																																			
16.0	2.408	1.218	1.084																																																			
20.0	3.004	1.496	1.316																																																			
24.0	3.604	1.780	1.560																																																			
27.0	4.070	1.994	1.745																																																			
29.7	4.500	2.190	1.914																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model LFA300F-12-TY

Item Input Power (by Load Current)

Object _____

1. Graph

—△— Input Volt. 100V
 - -□--- Input Volt. 200V
 - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	9.6	9.0	9.0
4.0	68.7	67.0	67.0
8.0	124.2	121.0	121.0
12.0	180.9	176.0	175.0
16.0	238.7	231.0	230.0
20.0	298.0	288.0	286.0
24.0	358.2	346.0	344.0
27.0	405.0	389.0	387.0
29.7	448.0	429.0	427.0
--	-	-	-
--	-	-	-

Model	LFA300F-12-TY
Item	Efficiency (by Input Voltage)
Object	_____

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	78.7	76.4
85	79.6	78.4
100	80.5	80.4
120	81.1	81.5
200	82.4	83.6
230	83.2	84.1
264	83.7	84.5
280	83.7	84.5
--	-	-

COSEL

Model	LFA300F-12-TY																																																					
Item	Efficiency (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	—	—	—																																																			
1.Graph	—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V																																																					
	2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.0</td> <td>69.5</td> <td>71.3</td> <td>71.3</td> </tr> <tr> <td>8.0</td> <td>77.3</td> <td>79.3</td> <td>79.3</td> </tr> <tr> <td>12.0</td> <td>79.7</td> <td>81.9</td> <td>82.4</td> </tr> <tr> <td>16.0</td> <td>80.6</td> <td>83.3</td> <td>83.7</td> </tr> <tr> <td>20.0</td> <td>80.9</td> <td>83.7</td> <td>84.3</td> </tr> <tr> <td>24.0</td> <td>80.7</td> <td>83.6</td> <td>84.1</td> </tr> <tr> <td>27.0</td> <td>80.4</td> <td>83.6</td> <td>84.1</td> </tr> <tr> <td>29.7</td> <td>79.9</td> <td>83.4</td> <td>83.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	4.0	69.5	71.3	71.3	8.0	77.3	79.3	79.3	12.0	79.7	81.9	82.4	16.0	80.6	83.3	83.7	20.0	80.9	83.7	84.3	24.0	80.7	83.6	84.1	27.0	80.4	83.6	84.1	29.7	79.9	83.4	83.8	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
4.0	69.5	71.3	71.3																																																			
8.0	77.3	79.3	79.3																																																			
12.0	79.7	81.9	82.4																																																			
16.0	80.6	83.3	83.7																																																			
20.0	80.9	83.7	84.3																																																			
24.0	80.7	83.6	84.1																																																			
27.0	80.4	83.6	84.1																																																			
29.7	79.9	83.4	83.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	Note: Slanted line shows the range of the rated load current.																																																					

Model	LFA300F-12-TY																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	<hr/>																																	
1. Graph																																		
<p>Legend:</p> <ul style="list-style-type: none"> Load 50% (dashed line with squares) Load 100% (solid line with triangles) <p>Input Voltage [V]</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.995</td><td>0.998</td> </tr> <tr> <td>85</td><td>0.992</td><td>0.998</td> </tr> <tr> <td>100</td><td>0.989</td><td>0.995</td> </tr> <tr> <td>120</td><td>0.983</td><td>0.994</td> </tr> <tr> <td>200</td><td>0.938</td><td>0.975</td> </tr> <tr> <td>230</td><td>0.894</td><td>0.965</td> </tr> <tr> <td>264</td><td>0.847</td><td>0.948</td> </tr> <tr> <td>280</td><td>0.819</td><td>0.923</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.995	0.998	85	0.992	0.998	100	0.989	0.995	120	0.983	0.994	200	0.938	0.975	230	0.894	0.965	264	0.847	0.948	280	0.819	0.923	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.995	0.998																																
85	0.992	0.998																																
100	0.989	0.995																																
120	0.983	0.994																																
200	0.938	0.975																																
230	0.894	0.965																																
264	0.847	0.948																																
280	0.819	0.923																																
--	-	-																																

COSEL

Model	LFA300F-12-TY																																																						
Item	Power Factor (by Load Current)	Temperature	25°C																																																				
Object	—	Testing Circuitry	Figure A																																																				
1.Graph	<p>—△— Input Volt. 100V - - -□-- Input Volt. 200V - - -○-- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V</th> <th>Input Volt. 200V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.545</td><td>0.220</td><td>0.173</td></tr> <tr><td>4.0</td><td>0.942</td><td>0.728</td><td>0.684</td></tr> <tr><td>8.0</td><td>0.977</td><td>0.858</td><td>0.812</td></tr> <tr><td>12.0</td><td>0.989</td><td>0.931</td><td>0.875</td></tr> <tr><td>16.0</td><td>0.993</td><td>0.951</td><td>0.924</td></tr> <tr><td>20.0</td><td>0.994</td><td>0.963</td><td>0.944</td></tr> <tr><td>24.0</td><td>0.995</td><td>0.972</td><td>0.958</td></tr> <tr><td>27.0</td><td>0.995</td><td>0.975</td><td>0.965</td></tr> <tr><td>29.7</td><td>0.998</td><td>0.979</td><td>0.970</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V	0	0.545	0.220	0.173	4.0	0.942	0.728	0.684	8.0	0.977	0.858	0.812	12.0	0.989	0.931	0.875	16.0	0.993	0.951	0.924	20.0	0.994	0.963	0.944	24.0	0.995	0.972	0.958	27.0	0.995	0.975	0.965	29.7	0.998	0.979	0.970	--	-	-	-	--	-	-	-						
Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V																																																				
0	0.545	0.220	0.173																																																				
4.0	0.942	0.728	0.684																																																				
8.0	0.977	0.858	0.812																																																				
12.0	0.989	0.931	0.875																																																				
16.0	0.993	0.951	0.924																																																				
20.0	0.994	0.963	0.944																																																				
24.0	0.995	0.972	0.958																																																				
27.0	0.995	0.975	0.965																																																				
29.7	0.998	0.979	0.970																																																				
--	-	-	-																																																				
--	-	-	-																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.545</td><td>0.220</td><td>0.173</td></tr> <tr><td>4.0</td><td>0.942</td><td>0.728</td><td>0.684</td></tr> <tr><td>8.0</td><td>0.977</td><td>0.858</td><td>0.812</td></tr> <tr><td>12.0</td><td>0.989</td><td>0.931</td><td>0.875</td></tr> <tr><td>16.0</td><td>0.993</td><td>0.951</td><td>0.924</td></tr> <tr><td>20.0</td><td>0.994</td><td>0.963</td><td>0.944</td></tr> <tr><td>24.0</td><td>0.995</td><td>0.972</td><td>0.958</td></tr> <tr><td>27.0</td><td>0.995</td><td>0.975</td><td>0.965</td></tr> <tr><td>29.7</td><td>0.998</td><td>0.979</td><td>0.970</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.545	0.220	0.173	4.0	0.942	0.728	0.684	8.0	0.977	0.858	0.812	12.0	0.989	0.931	0.875	16.0	0.993	0.951	0.924	20.0	0.994	0.963	0.944	24.0	0.995	0.972	0.958	27.0	0.995	0.975	0.965	29.7	0.998	0.979	0.970	--	-	-	-	--	-	-	-			
Load Current [A]	Power Factor																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	0.545	0.220	0.173																																																				
4.0	0.942	0.728	0.684																																																				
8.0	0.977	0.858	0.812																																																				
12.0	0.989	0.931	0.875																																																				
16.0	0.993	0.951	0.924																																																				
20.0	0.994	0.963	0.944																																																				
24.0	0.995	0.972	0.958																																																				
27.0	0.995	0.975	0.965																																																				
29.7	0.998	0.979	0.970																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						


COSEL

Model LFA300F-12-TY

Temperature 25°C
Testing Circuitry Figure A


Item Inrush Current

Object _____

Input
Current
[20A/div]


Input Voltage 100 V
Frequency 60 Hz
Load 100 %

Primary inrush current : 11.4 A
Secondary inrush current : 8.4 A

Input
Voltage
[100V/div]Input
Current
[20A/div]

Input Voltage 230 V
Frequency 60 Hz
Load 100 %

Primary inrush current : 24.6 A
Secondary inrush current : 3.9 A

Input
Voltage
[200V/div]



Model	LFA300F-12-TY	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.33	0.53	0.60	Operation
	One of phases	0.34	0.70	0.83	Stand by
IEC60950-1	Both phases	0.24	0.50	0.57	Operation
	One of phases	0.32	0.68	0.74	Stand by

The value for "One of phases" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

Model	LFA300F-12-TY
Item	Line Regulation
Object	+12V27A

1. Graph

--- □ --- Load 50%
— △ — Load 100%



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	12.094	12.093
85	12.095	12.093
100	12.095	12.093
120	12.094	12.092
200	12.095	12.093
230	12.095	12.093
264	12.095	12.093
280	12.095	12.092
--	-	-



Model	LFA300F-12-TY																																																					
Item	Load Regulation																																																					
Object	+12V27A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- Input Volt. 200V - - ○- Input Volt. 230V</p> <table border="1"> <caption>Data points from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (100V)</th> <th>Output Voltage [V] (200V)</th> <th>Output Voltage [V] (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>12.099</td><td>12.099</td><td>12.099</td></tr> <tr><td>4.0</td><td>12.097</td><td>12.097</td><td>12.097</td></tr> <tr><td>8.0</td><td>12.096</td><td>12.096</td><td>12.096</td></tr> <tr><td>12.0</td><td>12.095</td><td>12.096</td><td>12.095</td></tr> <tr><td>16.0</td><td>12.095</td><td>12.095</td><td>12.095</td></tr> <tr><td>20.0</td><td>12.094</td><td>12.094</td><td>12.094</td></tr> <tr><td>24.0</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr><td>27.0</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr><td>29.7</td><td>12.092</td><td>12.092</td><td>12.092</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (100V)	Output Voltage [V] (200V)	Output Voltage [V] (230V)	0	12.099	12.099	12.099	4.0	12.097	12.097	12.097	8.0	12.096	12.096	12.096	12.0	12.095	12.096	12.095	16.0	12.095	12.095	12.095	20.0	12.094	12.094	12.094	24.0	12.093	12.093	12.093	27.0	12.093	12.093	12.093	29.7	12.092	12.092	12.092	--	-	-	-	--	-	-	-			
Load Current [A]	Output Voltage [V] (100V)	Output Voltage [V] (200V)	Output Voltage [V] (230V)																																																			
0	12.099	12.099	12.099																																																			
4.0	12.097	12.097	12.097																																																			
8.0	12.096	12.096	12.096																																																			
12.0	12.095	12.096	12.095																																																			
16.0	12.095	12.095	12.095																																																			
20.0	12.094	12.094	12.094																																																			
24.0	12.093	12.093	12.093																																																			
27.0	12.093	12.093	12.093																																																			
29.7	12.092	12.092	12.092																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.099</td><td>12.099</td><td>12.099</td></tr> <tr><td>4.0</td><td>12.097</td><td>12.097</td><td>12.097</td></tr> <tr><td>8.0</td><td>12.096</td><td>12.096</td><td>12.096</td></tr> <tr><td>12.0</td><td>12.095</td><td>12.096</td><td>12.095</td></tr> <tr><td>16.0</td><td>12.095</td><td>12.095</td><td>12.095</td></tr> <tr><td>20.0</td><td>12.094</td><td>12.094</td><td>12.094</td></tr> <tr><td>24.0</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr><td>27.0</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr><td>29.7</td><td>12.092</td><td>12.092</td><td>12.092</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	12.099	12.099	12.099	4.0	12.097	12.097	12.097	8.0	12.096	12.096	12.096	12.0	12.095	12.096	12.095	16.0	12.095	12.095	12.095	20.0	12.094	12.094	12.094	24.0	12.093	12.093	12.093	27.0	12.093	12.093	12.093	29.7	12.092	12.092	12.092	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	12.099	12.099	12.099																																																			
4.0	12.097	12.097	12.097																																																			
8.0	12.096	12.096	12.096																																																			
12.0	12.095	12.096	12.095																																																			
16.0	12.095	12.095	12.095																																																			
20.0	12.094	12.094	12.094																																																			
24.0	12.093	12.093	12.093																																																			
27.0	12.093	12.093	12.093																																																			
29.7	12.092	12.092	12.092																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


COSEL

COSEL

Model	LFA300F-12-TY
Item	Ripple Voltage (by Load Current)
Object	+12V27A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.0	10	10
4.0	15	15
8.0	15	15
12.0	20	20
16.0	20	20
20.0	25	25
24.0	30	30
27.0	30	30
29.7	30	30
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

COSEL


Model LFA300F-12-TY

Item Ripple-Noise

Object +12V27A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.0	30	25
4.0	30	30
8.0	40	35
12.0	40	40
16.0	45	40
20.0	45	40
24.0	55	45
27.0	60	50
29.7	65	60
--	-	-
--	-	-

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

<p>Model LFA300F-12-TY</p> <p>Item Ripple Voltage (by Ambient Temp.)</p> <p>Object +12V27A</p>	Testing Circuitry Figure C	
	2.Values	
Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100V	Input Volt. 230V
-30	50	45
-10	50	45
0	40	40
25	35	35
50	20	20
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	LFA300F-12-TY																																																					
Item	Ambient Temperature Drift																																																					
Object	+12V27A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>12.094</td><td>12.094</td><td>12.094</td></tr> <tr> <td>-10</td><td>12.094</td><td>12.093</td><td>12.093</td></tr> <tr> <td>0</td><td>12.092</td><td>12.093</td><td>12.092</td></tr> <tr> <td>10</td><td>12.092</td><td>12.092</td><td>12.093</td></tr> <tr> <td>20</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr> <td>25</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr> <td>30</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr> <td>40</td><td>12.090</td><td>12.090</td><td>12.090</td></tr> <tr> <td>50</td><td>12.085</td><td>12.085</td><td>12.086</td></tr> <tr> <td>60</td><td>12.078</td><td>12.079</td><td>12.079</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	12.094	12.094	12.094	-10	12.094	12.093	12.093	0	12.092	12.093	12.092	10	12.092	12.092	12.093	20	12.093	12.093	12.093	25	12.093	12.093	12.093	30	12.093	12.093	12.093	40	12.090	12.090	12.090	50	12.085	12.085	12.086	60	12.078	12.079	12.079	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
-20	12.094	12.094	12.094																																																			
-10	12.094	12.093	12.093																																																			
0	12.092	12.093	12.092																																																			
10	12.092	12.092	12.093																																																			
20	12.093	12.093	12.093																																																			
25	12.093	12.093	12.093																																																			
30	12.093	12.093	12.093																																																			
40	12.090	12.090	12.090																																																			
50	12.085	12.085	12.086																																																			
60	12.078	12.079	12.079																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated ambient temperature.																																																					



Model	LFA300F-12-TY	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V27A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 27A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	20	264	0	12.100	± 8	± 0.1
Minimum Voltage	50	200	27	12.085		

COSEL

Model	LFA300F-12-TY	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V27A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.102</td></tr> <tr><td>0.5</td><td>12.093</td></tr> <tr><td>1.0</td><td>12.093</td></tr> <tr><td>2.0</td><td>12.092</td></tr> <tr><td>3.0</td><td>12.092</td></tr> <tr><td>4.0</td><td>12.092</td></tr> <tr><td>5.0</td><td>12.092</td></tr> <tr><td>6.0</td><td>12.092</td></tr> <tr><td>7.0</td><td>12.092</td></tr> <tr><td>8.0</td><td>12.091</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.102	0.5	12.093	1.0	12.093	2.0	12.092	3.0	12.092	4.0	12.092	5.0	12.092	6.0	12.092	7.0	12.092	8.0	12.091
Time since start [H]	Output Voltage [V]																								
0.0	12.102																								
0.5	12.093																								
1.0	12.093																								
2.0	12.092																								
3.0	12.092																								
4.0	12.092																								
5.0	12.092																								
6.0	12.092																								
7.0	12.092																								
8.0	12.091																								
<p>* The characteristic of AC230V is equal.</p>																									

COSEL


Model LFA300F-12-TY

Item Rise and Fall Time

Temperature 25°C
Testing Circuitry Figure A

Object +12V27A


1. Graph



2. Values


[ms]

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		181.0	18.5	199.5	29.8	12.2
230 V		162.5	18.5	181.0	33.5	12.1



Model	LFA300F-12-TY
Item	Hold-Up Time
Object	+12V27A

1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values


Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	57	29
85	59	30
100	60	29
120	61	30
200	68	33
230	70	34
264	72	36
280	73	36
--	-	-

Model	LFA300F-12-TY																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+12V27A																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>4.0</td><td>123</td><td>139</td><td>218</td></tr> <tr> <td>8.0</td><td>62</td><td>74</td><td>114</td></tr> <tr> <td>12.0</td><td>39</td><td>49</td><td>78</td></tr> <tr> <td>16.0</td><td>31</td><td>38</td><td>40</td></tr> <tr> <td>20.0</td><td>23</td><td>30</td><td>32</td></tr> <tr> <td>24.0</td><td>21</td><td>24</td><td>26</td></tr> <tr> <td>27.0</td><td>19</td><td>22</td><td>24</td></tr> <tr> <td>29.7</td><td>14</td><td>20</td><td>22</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	4.0	123	139	218	8.0	62	74	114	12.0	39	49	78	16.0	31	38	40	20.0	23	30	32	24.0	21	24	26	27.0	19	22	24	29.7	14	20	22	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
4.0	123	139	218																																																			
8.0	62	74	114																																																			
12.0	39	49	78																																																			
16.0	31	38	40																																																			
20.0	23	30	32																																																			
24.0	21	24	26																																																			
27.0	19	22	24																																																			
29.7	14	20	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	LFA300F-12-TY
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V27A

Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	40	57
-10	39	57
0	39	58
10	39	58
20	39	58
25	40	58
30	41	58
40	40	58
50	40	59
60	40	60
--	-	-

COSEL

Model	LFA300F-12-TY																																										
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																									
Object	+12V27A																																										
1. Graph																																											
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 230V</p>																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 6V to 0V.</p>																																											
2. Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>31.81</td><td>31.80</td></tr> <tr><td>11.4</td><td>31.92</td><td>31.91</td></tr> <tr><td>10.8</td><td>31.79</td><td>29.68</td></tr> <tr><td>9.6</td><td>32.28</td><td>32.26</td></tr> <tr><td>8.4</td><td>32.51</td><td>32.49</td></tr> <tr><td>7.2</td><td>32.80</td><td>32.80</td></tr> <tr><td>6.0</td><td>33.07</td><td>33.09</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	12.0	31.81	31.80	11.4	31.92	31.91	10.8	31.79	29.68	9.6	32.28	32.26	8.4	32.51	32.49	7.2	32.80	32.80	6.0	33.07	33.09	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																										
	Input Volt. 100[V]	Input Volt. 230[V]																																									
12.0	31.81	31.80																																									
11.4	31.92	31.91																																									
10.8	31.79	29.68																																									
9.6	32.28	32.26																																									
8.4	32.51	32.49																																									
7.2	32.80	32.80																																									
6.0	33.07	33.09																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									

Model	LFA300F-12-TY
Item	Overvoltage Protection
Object	+12V27A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	14.80	14.80
-10	14.86	14.86
0	14.98	14.98
10	14.98	14.98
20	15.09	15.09
25	15.21	15.21
30	15.20	15.21
40	15.26	15.26
50	15.38	15.38
60	15.49	15.49
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C