



## TEST DATA OF LFA30F-24


Regulated DC Power Supply  
June 29, 2009

Approved by :

  
Yoshiaki Shimizu

Design Manager

Prepared by :

  
Kazuo Ishimura

Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ripple-Noise . . . . .	13
14. Ripple Voltage (by Ambient Temperature) . . . . .	14
15. Ambient Temperature Drift . . . . .	15
16. Output Voltage Accuracy . . . . .	16
17. Time Lapse Drift . . . . .	17
18. Rise and Fall Time . . . . .	18
19. Hold-Up Time . . . . .	19
20. Instantaneous Interruption Compensation . . . . .	20
21. Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22. Overcurrent Protection . . . . .	22
23. Overvoltage Protection . . . . .	23
24. Figure of Testing Circuitry . . . . .	24


(Final Page 25)

**COSEL**

Model	LFA30F-24																																																		
Item	Input Current (by Load Current)																																																		
Object	<u> </u>																																																		
1.Graph	—▲— Input Volt. 100V - - -□--- Input Volt. 200V - · -○--- Input Volt. 230V																																																		
	<p>The graph shows three curves representing different input voltages. The 100V curve (triangles) has the steepest slope, followed by 230V (circles), and 200V (squares) has the shallowest slope. All curves start at (0,0) and end at approximately (1.3A, 0.7A). A diagonal line from (0,0) to (1.3A, 0.7A) represents the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.028</td><td>0.028</td><td>0.028</td></tr> <tr><td>0.20</td><td>0.126</td><td>0.083</td><td>0.078</td></tr> <tr><td>0.40</td><td>0.216</td><td>0.134</td><td>0.125</td></tr> <tr><td>0.60</td><td>0.302</td><td>0.187</td><td>0.172</td></tr> <tr><td>0.80</td><td>0.390</td><td>0.236</td><td>0.216</td></tr> <tr><td>1.00</td><td>0.478</td><td>0.284</td><td>0.259</td></tr> <tr><td>1.20</td><td>0.566</td><td>0.333</td><td>0.302</td></tr> <tr><td>1.30</td><td>0.611</td><td>0.357</td><td>0.324</td></tr> <tr><td>1.43</td><td>0.669</td><td>0.389</td><td>0.352</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.028	0.028	0.028	0.20	0.126	0.083	0.078	0.40	0.216	0.134	0.125	0.60	0.302	0.187	0.172	0.80	0.390	0.236	0.216	1.00	0.478	0.284	0.259	1.20	0.566	0.333	0.302	1.30	0.611	0.357	0.324	1.43	0.669	0.389	0.352	--	-	-	-	--	-	-	-	Temperature 25°C Testing Circuitry Figure A	
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																
0.00	0.028	0.028	0.028																																																
0.20	0.126	0.083	0.078																																																
0.40	0.216	0.134	0.125																																																
0.60	0.302	0.187	0.172																																																
0.80	0.390	0.236	0.216																																																
1.00	0.478	0.284	0.259																																																
1.20	0.566	0.333	0.302																																																
1.30	0.611	0.357	0.324																																																
1.43	0.669	0.389	0.352																																																
--	-	-	-																																																
--	-	-	-																																																
2.Values																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	LFA30F-24				
Item	Input Power (by Load Current)	Temperature	25°C		
Object	Testing Circuitry	Figure A			
1. Graph					
—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V					
 <p>The graph plots Input Power [W] on the Y-axis (0 to 50) against Load Current [A] on the X-axis (0.0 to 1.6). Three curves are shown for different input voltages: 100V (outermost), 200V (middle), and 230V (innermost). All curves show a linear increase in power with load current. A vertical slanted line is drawn through the intersection of the 200V and 230V curves, indicating the rated load current range.</p>					
2. Values					
Load Current [A]	Input Power [W]				
Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]			
0.00	1.00	1.40	1.50		
0.20	6.60	6.80	7.00		
0.40	12.20	12.10	12.50		
0.60	17.70	18.00	18.30		
0.80	23.30	23.40	23.70		
1.00	28.90	28.80	29.00		
1.20	34.70	34.20	34.40		
1.30	37.60	36.90	37.00		
1.43	41.50	40.40	40.60		
--	-	-	-		
--	-	-	-		

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	LFA30F-24
Item	Efficiency (by Input Voltage)
Object	—

1. Graph

Efficiency [%]

Input Voltage [V]

Legend: ---□--- Load 50%  
—△— Load 100%

 Temperature 25°C  
 Testing Circuitry Figure A

## 2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	80.8	80.1
85	81.6	81.8
100	82.0	83.3
120	82.4	84.4
200	80.7	84.9
230	79.5	84.6
264	78.3	83.7
280	77.9	83.3
-	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	LFA30F-24																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1.Graph																																																						
<p>—△— Input Volt. 100V        -□- Input Volt. 200V        -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>0.3</td><td>70</td><td>70</td><td>70</td></tr> <tr><td>0.4</td><td>73</td><td>73</td><td>73</td></tr> <tr><td>0.6</td><td>78</td><td>78</td><td>78</td></tr> <tr><td>0.8</td><td>80</td><td>80</td><td>80</td></tr> <tr><td>1.0</td><td>82</td><td>82</td><td>82</td></tr> <tr><td>1.2</td><td>83</td><td>83</td><td>83</td></tr> <tr><td>1.4</td><td>83</td><td>83</td><td>83</td></tr> <tr><td>1.6</td><td>83</td><td>83</td><td>83</td></tr> </tbody> </table>				Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	0.3	70	70	70	0.4	73	73	73	0.6	78	78	78	0.8	80	80	80	1.0	82	82	82	1.2	83	83	83	1.4	83	83	83	1.6	83	83	83															
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																			
0.3	70	70	70																																																			
0.4	73	73	73																																																			
0.6	78	78	78																																																			
0.8	80	80	80																																																			
1.0	82	82	82																																																			
1.2	83	83	83																																																			
1.4	83	83	83																																																			
1.6	83	83	83																																																			
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.20</td><td>73.3</td><td>71.1</td><td>69.1</td></tr> <tr><td>0.40</td><td>79.0</td><td>79.7</td><td>77.1</td></tr> <tr><td>0.60</td><td>81.7</td><td>80.3</td><td>79.0</td></tr> <tr><td>0.80</td><td>82.7</td><td>82.4</td><td>81.3</td></tr> <tr><td>1.00</td><td>83.4</td><td>83.7</td><td>83.1</td></tr> <tr><td>1.20</td><td>83.3</td><td>84.5</td><td>84.0</td></tr> <tr><td>1.30</td><td>83.3</td><td>84.9</td><td>84.6</td></tr> <tr><td>1.43</td><td>83.0</td><td>85.3</td><td>84.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.20	73.3	71.1	69.1	0.40	79.0	79.7	77.1	0.60	81.7	80.3	79.0	0.80	82.7	82.4	81.3	1.00	83.4	83.7	83.1	1.20	83.3	84.5	84.0	1.30	83.3	84.9	84.6	1.43	83.0	85.3	84.8	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.20	73.3	71.1	69.1																																																			
0.40	79.0	79.7	77.1																																																			
0.60	81.7	80.3	79.0																																																			
0.80	82.7	82.4	81.3																																																			
1.00	83.4	83.7	83.1																																																			
1.20	83.3	84.5	84.0																																																			
1.30	83.3	84.9	84.6																																																			
1.43	83.0	85.3	84.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

**COSEL**




Model	LFA30F-24	Temperature	25°C																																
Item	Power Factor (by Input Voltage)	Testing Circuitry	Figure A																																
Object																																			
1.Graph																																			
	<p style="text-align: center;">---□--- Load 50% —△— Load 100%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Power Factor</th> <th>Load 100% Power Factor</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.634</td><td>0.660</td></tr> <tr><td>85</td><td>0.609</td><td>0.639</td></tr> <tr><td>100</td><td>0.589</td><td>0.614</td></tr> <tr><td>120</td><td>0.556</td><td>0.587</td></tr> <tr><td>200</td><td>0.482</td><td>0.512</td></tr> <tr><td>230</td><td>0.464</td><td>0.495</td></tr> <tr><td>264</td><td>0.445</td><td>0.477</td></tr> <tr><td>280</td><td>0.438</td><td>0.469</td></tr> <tr><td>---</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor	75	0.634	0.660	85	0.609	0.639	100	0.589	0.614	120	0.556	0.587	200	0.482	0.512	230	0.464	0.495	264	0.445	0.477	280	0.438	0.469	---	-	-		
Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor																																	
75	0.634	0.660																																	
85	0.609	0.639																																	
100	0.589	0.614																																	
120	0.556	0.587																																	
200	0.482	0.512																																	
230	0.464	0.495																																	
264	0.445	0.477																																	
280	0.438	0.469																																	
---	-	-																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.634</td><td>0.660</td></tr> <tr><td>85</td><td>0.609</td><td>0.639</td></tr> <tr><td>100</td><td>0.589</td><td>0.614</td></tr> <tr><td>120</td><td>0.556</td><td>0.587</td></tr> <tr><td>200</td><td>0.482</td><td>0.512</td></tr> <tr><td>230</td><td>0.464</td><td>0.495</td></tr> <tr><td>264</td><td>0.445</td><td>0.477</td></tr> <tr><td>280</td><td>0.438</td><td>0.469</td></tr> <tr><td>---</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.634	0.660	85	0.609	0.639	100	0.589	0.614	120	0.556	0.587	200	0.482	0.512	230	0.464	0.495	264	0.445	0.477	280	0.438	0.469	---	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
75	0.634	0.660																																	
85	0.609	0.639																																	
100	0.589	0.614																																	
120	0.556	0.587																																	
200	0.482	0.512																																	
230	0.464	0.495																																	
264	0.445	0.477																																	
280	0.438	0.469																																	
---	-	-																																	
Note:	Slanted line shows the range of the rated input voltage.																																		

**COSEL**

Model	LFA30F-24																																																					
Item	Power Factor (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.400</td><td>0.296</td><td>0.278</td></tr> <tr><td>0.20</td><td>0.523</td><td>0.416</td><td>0.397</td></tr> <tr><td>0.40</td><td>0.565</td><td>0.455</td><td>0.436</td></tr> <tr><td>0.60</td><td>0.584</td><td>0.483</td><td>0.462</td></tr> <tr><td>0.80</td><td>0.595</td><td>0.496</td><td>0.476</td></tr> <tr><td>1.00</td><td>0.605</td><td>0.506</td><td>0.486</td></tr> <tr><td>1.20</td><td>0.612</td><td>0.513</td><td>0.494</td></tr> <tr><td>1.30</td><td>0.615</td><td>0.515</td><td>0.497</td></tr> <tr><td>1.43</td><td>0.619</td><td>0.518</td><td>0.501</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.400	0.296	0.278	0.20	0.523	0.416	0.397	0.40	0.565	0.455	0.436	0.60	0.584	0.483	0.462	0.80	0.595	0.496	0.476	1.00	0.605	0.506	0.486	1.20	0.612	0.513	0.494	1.30	0.615	0.515	0.497	1.43	0.619	0.518	0.501	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.400	0.296	0.278																																																			
0.20	0.523	0.416	0.397																																																			
0.40	0.565	0.455	0.436																																																			
0.60	0.584	0.483	0.462																																																			
0.80	0.595	0.496	0.476																																																			
1.00	0.605	0.506	0.486																																																			
1.20	0.612	0.513	0.494																																																			
1.30	0.615	0.515	0.497																																																			
1.43	0.619	0.518	0.501																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	LFA30F-24	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	_____		





Model	LFA30F-24	Temperature Testing Circuitry Figure B
Item	Leakage Current	
Object	_____	

## 1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.13	0.27	0.32	Operation
	One of phases	0.21	0.45	0.55	Stand by
IEC60950	Both phases	0.15	0.30	0.37	Operation
	One of phases	0.22	0.46	0.55	Stand by

The value for "One of phases" is the reference value only.


## 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	LFA30F-24
Item	Line Regulation
Object	+24V1.3A

## 1. Graph




Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	24.044	24.041
85	24.044	24.041
100	24.044	24.041
120	24.044	24.041
200	24.044	24.041
230	24.044	24.041
264	24.044	24.041
280	24.044	24.041
--	-	-

**COSEL**

Model	LFA30F-24	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+24V1.3A																																																					
1.Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 100V  <span style="color: gray;">---□---</span> Input Volt. 200V  <span style="color: gray;">---○---</span> Input Volt. 230V         </p> 	2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>24.047</td><td>24.047</td><td>24.047</td></tr> <tr> <td>0.20</td><td>24.046</td><td>24.046</td><td>24.046</td></tr> <tr> <td>0.40</td><td>24.045</td><td>24.045</td><td>24.045</td></tr> <tr> <td>0.60</td><td>24.044</td><td>24.044</td><td>24.044</td></tr> <tr> <td>0.80</td><td>24.043</td><td>24.043</td><td>24.043</td></tr> <tr> <td>1.00</td><td>24.042</td><td>24.042</td><td>24.042</td></tr> <tr> <td>1.20</td><td>24.041</td><td>24.041</td><td>24.041</td></tr> <tr> <td>1.30</td><td>24.041</td><td>24.041</td><td>24.041</td></tr> <tr> <td>1.43</td><td>24.040</td><td>24.040</td><td>24.040</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	24.047	24.047	24.047	0.20	24.046	24.046	24.046	0.40	24.045	24.045	24.045	0.60	24.044	24.044	24.044	0.80	24.043	24.043	24.043	1.00	24.042	24.042	24.042	1.20	24.041	24.041	24.041	1.30	24.041	24.041	24.041	1.43	24.040	24.040	24.040	--	-	-	-	--	-	-	-	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	24.047	24.047	24.047																																																			
0.20	24.046	24.046	24.046																																																			
0.40	24.045	24.045	24.045																																																			
0.60	24.044	24.044	24.044																																																			
0.80	24.043	24.043	24.043																																																			
1.00	24.042	24.042	24.042																																																			
1.20	24.041	24.041	24.041																																																			
1.30	24.041	24.041	24.041																																																			
1.43	24.040	24.040	24.040																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model LFA30F-24

Item Dynamic Load Response



Object +24V1.3A

Temperature  
Testing Circuitry      25°C  
Figure A



Input Volt. 100 V                          Response.  $t_1=t_2=50\mu s$ , Typ  
 Cycle 1000 ms



Min. Load (0A) ↔  
 Load 100% (1.3A)



Min. Load (0A) ↔  
 Load 50% (0.65A)




**COSEL**

Model	LFA30F-24
Item	Ripple Voltage (by Load Current)
Object	+24V1.3A

 Temperature 25°C  
 Testing Circuitry Figure C

## 1.Graph



## 2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	10	10
0.20	10	10
0.40	10	10
0.60	10	10
0.80	15	10
1.00	15	10
1.20	20	15
1.30	25	15
1.43	35	15
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.



 T1: Due to AC Input Line  
 T2: Due to Switching


Fig. Complex Ripple Wave Form

**COSEL**

Model	LFA30F-24
Item	Ripple-Noise
Object	+24V1.3A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure C

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	20	40
0.20	30	40
0.40	35	35
0.60	35	45
0.80	35	50
1.00	40	45
1.20	45	50
1.30	45	50
1.43	55	55
--	-	-
--	-	-





Fig. Complex Ripple Wave Form

**COSEL**

Model	LFA30F-24
Item	Ripple Voltage (by Ambient Temp.)
Object	+24V1.3A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure C

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	60	45
-10	40	25
0	35	20
25	25	15
50	25	15
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

**COSEL**

Model	LFA30F-24																																																					
Item	Ambient Temperature Drift																																																					
Object	+24V1.3A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>24.102</td> <td>24.103</td> <td>24.103</td> </tr> <tr> <td>-10</td> <td>24.090</td> <td>24.090</td> <td>24.090</td> </tr> <tr> <td>0</td> <td>24.074</td> <td>24.074</td> <td>24.074</td> </tr> <tr> <td>10</td> <td>24.062</td> <td>24.063</td> <td>24.062</td> </tr> <tr> <td>20</td> <td>24.050</td> <td>24.051</td> <td>24.051</td> </tr> <tr> <td>25</td> <td>24.045</td> <td>24.046</td> <td>24.046</td> </tr> <tr> <td>30</td> <td>24.040</td> <td>24.041</td> <td>24.041</td> </tr> <tr> <td>40</td> <td>24.026</td> <td>24.026</td> <td>24.026</td> </tr> <tr> <td>50</td> <td>24.010</td> <td>24.011</td> <td>24.011</td> </tr> <tr> <td>60</td> <td>23.991</td> <td>23.991</td> <td>23.991</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	24.102	24.103	24.103	-10	24.090	24.090	24.090	0	24.074	24.074	24.074	10	24.062	24.063	24.062	20	24.050	24.051	24.051	25	24.045	24.046	24.046	30	24.040	24.041	24.041	40	24.026	24.026	24.026	50	24.010	24.011	24.011	60	23.991	23.991	23.991	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
-20	24.102	24.103	24.103																																																			
-10	24.090	24.090	24.090																																																			
0	24.074	24.074	24.074																																																			
10	24.062	24.063	24.062																																																			
20	24.050	24.051	24.051																																																			
25	24.045	24.046	24.046																																																			
30	24.040	24.041	24.041																																																			
40	24.026	24.026	24.026																																																			
50	24.010	24.011	24.011																																																			
60	23.991	23.991	23.991																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated ambient temperature.



Model	LFA30F-24	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V1.3A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 1.3A

\* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	264	0	24.096	±43	±0.2
Minimum Voltage	50	85	1.3	24.010		

**COSEL**

Model	LFA30F-24
Item	Time Lapse Drift
Object	+24V1.3A

## 1.Graph



\* The characteristic of AC200V is equal.

 Temperature 25°C  
 Testing Circuitry Figure A


## 2.Values

Time since start [H]	Output Voltage [V]
0.0	24.042
0.5	24.035
1.0	24.035
2.0	24.035
3.0	24.035
4.0	24.035
5.0	24.035
6.0	24.035
7.0	24.036
8.0	24.036

**COSEL**


Model	LFA30F-24	Temperature Testing Circuitry 25°C Figure A
Item	Rise and Fall Time	
Object	+24V1.3A	

## 1. Graph



## 2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		127.3	6.3	133.6	23.5	19.3	
200 V		58.3	6.5	64.8	114.8	19.8	



**COSEL**

Model	LFA30F-24	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time																																	
Object	+24V1.3A																																	
1. Graph		2. Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>25</td><td>7</td></tr> <tr><td>85</td><td>34</td><td>12</td></tr> <tr><td>100</td><td>50</td><td>20</td></tr> <tr><td>120</td><td>75</td><td>33</td></tr> <tr><td>200</td><td>227</td><td>113</td></tr> <tr><td>230</td><td>304</td><td>155</td></tr> <tr><td>264</td><td>406</td><td>206</td></tr> <tr><td>280</td><td>460</td><td>234</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	25	7	85	34	12	100	50	20	120	75	33	200	227	113	230	304	155	264	406	206	280	460	234	-	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
75	25	7																																
85	34	12																																
100	50	20																																
120	75	33																																
200	227	113																																
230	304	155																																
264	406	206																																
280	460	234																																
-	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**

Model	LFA30F-24																																																			
Item	Instantaneous Interruption Compensation	Temperature      25°C Testing Circuitry      Figure A																																																		
Object	+24V1.3A																																																			
1.Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 100V  <span style="color: gray;">---□---</span> Input Volt. 200V  <span style="color: gray;">---○---</span> Input Volt. 230V         </p>																																																			
<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.20</td><td>152</td><td>639</td><td>851</td></tr> <tr><td>0.40</td><td>82</td><td>363</td><td>486</td></tr> <tr><td>0.60</td><td>55</td><td>248</td><td>331</td></tr> <tr><td>0.80</td><td>41</td><td>189</td><td>254</td></tr> <tr><td>1.00</td><td>31</td><td>151</td><td>204</td></tr> <tr><td>1.20</td><td>22</td><td>124</td><td>169</td></tr> <tr><td>1.30</td><td>20</td><td>111</td><td>155</td></tr> <tr><td>1.43</td><td>14</td><td>100</td><td>138</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.20	152	639	851	0.40	82	363	486	0.60	55	248	331	0.80	41	189	254	1.00	31	151	204	1.20	22	124	169	1.30	20	111	155	1.43	14	100	138	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																			
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																	
0.00	-	-	-																																																	
0.20	152	639	851																																																	
0.40	82	363	486																																																	
0.60	55	248	331																																																	
0.80	41	189	254																																																	
1.00	31	151	204																																																	
1.20	22	124	169																																																	
1.30	20	111	155																																																	
1.43	14	100	138																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	LFA30F-24	Testing Circuitry Figure A																																					
Item	Minimum Input Voltage for Regulated Output Voltage																																						
Object	+24V1.3A																																						
1.Graph		2.Values																																					
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>---□--- Load 50%</p> <p>—△— Load 100%</p>																																							
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>35</td><td>61</td> </tr> <tr> <td>-10</td><td>34</td><td>60</td> </tr> <tr> <td>0</td><td>34</td><td>59</td> </tr> <tr> <td>10</td><td>35</td><td>58</td> </tr> <tr> <td>20</td><td>33</td><td>58</td> </tr> <tr> <td>25</td><td>33</td><td>57</td> </tr> <tr> <td>30</td><td>33</td><td>57</td> </tr> <tr> <td>40</td><td>33</td><td>57</td> </tr> <tr> <td>50</td><td>33</td><td>58</td> </tr> <tr> <td>60</td><td>33</td><td>58</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	35	61	-10	34	60	0	34	59	10	35	58	20	33	58	25	33	57	30	33	57	40	33	57	50	33	58	60	33	58	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-20	35	61																																					
-10	34	60																																					
0	34	59																																					
10	35	58																																					
20	33	58																																					
25	33	57																																					
30	33	57																																					
40	33	57																																					
50	33	58																																					
60	33	58																																					
--	-	-																																					

Note: Slanted line shows the range of the rated ambient temperature.


**COSEL**

Model	LFA30F-24																																													
Item	Overcurrent Protection	Temperature      25°C Testing Circuitry      Figure A																																												
Object	+24V1.3A																																													
1.Graph																																														
<p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																														
<p>Intermittent operation occurs when the output voltage is from 13V to 0V.</p>																																														
2.Values																																														
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>24.0</td><td>1.30</td><td>1.30</td></tr> <tr><td>22.8</td><td>1.78</td><td>2.01</td></tr> <tr><td>21.6</td><td>1.82</td><td>2.07</td></tr> <tr><td>19.2</td><td>1.95</td><td>2.18</td></tr> <tr><td>16.8</td><td>2.08</td><td>2.31</td></tr> <tr><td>14.4</td><td>2.23</td><td>2.45</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 200[V]	24.0	1.30	1.30	22.8	1.78	2.01	21.6	1.82	2.07	19.2	1.95	2.18	16.8	2.08	2.31	14.4	2.23	2.45	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																													
	Input Volt. 100[V]	Input Volt. 200[V]																																												
24.0	1.30	1.30																																												
22.8	1.78	2.01																																												
21.6	1.82	2.07																																												
19.2	1.95	2.18																																												
16.8	2.08	2.31																																												
14.4	2.23	2.45																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												

**COSEL**

Model	LFA30F-24
Item	Ovvoltage Protection
Object	+24V1.3A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	30.02	29.95
-10	30.30	30.23
0	30.51	30.51
10	30.80	30.80
20	31.08	31.08
25	31.22	31.22
30	31.29	31.29
40	31.57	31.58
50	31.79	31.79
60	32.07	32.07
--	-	-

COSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950-1 )


**COSEL**

Figure C