

TEST DATA OF LFP150F-24-Y

Regulated DC Power Supply
February 4, 2013

Approved by : Yoshiaki Shimizu
Yoshiaki Shimizu Design Manager

Prepared by : Soshi Nakamura
Soshi Nakamura Design Engineer


COSEL CO.,LTD.

CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	LFP150F-24-Y																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	—	—	—																																																			
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p>  <p>The graph plots Input Current [A] on the Y-axis (0.0 to 5.0) against Load Current [A] on the X-axis (0.0 to 6.0). Three data series are shown: 100V (solid triangles), 200V (dashed squares), and 230V (dotted circles). All curves show a linear increase in input current with load current. A slanted line is drawn through the origin, representing the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.083</td><td>0.081</td><td>0.084</td></tr> <tr> <td>1.00</td><td>0.354</td><td>0.223</td><td>0.208</td></tr> <tr> <td>2.00</td><td>0.639</td><td>0.359</td><td>0.330</td></tr> <tr> <td>3.00</td><td>0.915</td><td>0.487</td><td>0.441</td></tr> <tr> <td>4.00</td><td>1.180</td><td>0.616</td><td>0.557</td></tr> <tr> <td>5.00</td><td>1.459</td><td>0.750</td><td>0.671</td></tr> <tr> <td>6.00</td><td>1.724</td><td>0.882</td><td>0.786</td></tr> <tr> <td>6.30</td><td>1.811</td><td>0.922</td><td>0.820</td></tr> <tr> <td>6.93</td><td>1.989</td><td>1.005</td><td>0.895</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.083	0.081	0.084	1.00	0.354	0.223	0.208	2.00	0.639	0.359	0.330	3.00	0.915	0.487	0.441	4.00	1.180	0.616	0.557	5.00	1.459	0.750	0.671	6.00	1.724	0.882	0.786	6.30	1.811	0.922	0.820	6.93	1.989	1.005	0.895	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.083	0.081	0.084																																																			
1.00	0.354	0.223	0.208																																																			
2.00	0.639	0.359	0.330																																																			
3.00	0.915	0.487	0.441																																																			
4.00	1.180	0.616	0.557																																																			
5.00	1.459	0.750	0.671																																																			
6.00	1.724	0.882	0.786																																																			
6.30	1.811	0.922	0.820																																																			
6.93	1.989	1.005	0.895																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


COSEL

Model	LFP150F-24-Y																																																		
Item	Input Power (by Load Current)																																																		
Object	_____																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [W]</th> <th>Input Volt. 200V [W]</th> <th>Input Volt. 230V [W]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.8</td><td>5.3</td><td>5.1</td></tr> <tr><td>1.00</td><td>33.8</td><td>34.0</td><td>34.0</td></tr> <tr><td>2.00</td><td>62.4</td><td>62.0</td><td>61.8</td></tr> <tr><td>3.00</td><td>90.3</td><td>87.9</td><td>87.8</td></tr> <tr><td>4.00</td><td>117.0</td><td>114.2</td><td>114.2</td></tr> <tr><td>5.00</td><td>144.8</td><td>140.7</td><td>140.4</td></tr> <tr><td>6.00</td><td>171.4</td><td>167.4</td><td>166.8</td></tr> <tr><td>6.30</td><td>180.0</td><td>175.3</td><td>174.7</td></tr> <tr><td>6.93</td><td>198.2</td><td>192.2</td><td>191.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V [W]	Input Volt. 200V [W]	Input Volt. 230V [W]	0.00	5.8	5.3	5.1	1.00	33.8	34.0	34.0	2.00	62.4	62.0	61.8	3.00	90.3	87.9	87.8	4.00	117.0	114.2	114.2	5.00	144.8	140.7	140.4	6.00	171.4	167.4	166.8	6.30	180.0	175.3	174.7	6.93	198.2	192.2	191.6	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 100V [W]	Input Volt. 200V [W]	Input Volt. 230V [W]																																																
0.00	5.8	5.3	5.1																																																
1.00	33.8	34.0	34.0																																																
2.00	62.4	62.0	61.8																																																
3.00	90.3	87.9	87.8																																																
4.00	117.0	114.2	114.2																																																
5.00	144.8	140.7	140.4																																																
6.00	171.4	167.4	166.8																																																
6.30	180.0	175.3	174.7																																																
6.93	198.2	192.2	191.6																																																
--	-	-	-																																																
--	-	-	-																																																
2.Values																																																			
Note: Slanted line shows the range of the rated load current.																																																			

COSEL

Model	LFP150F-24-Y
Item	Efficiency (by Input Voltage)
Object	_____

1.Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	80.9	83.2
85	81.2	84.9
100	82.1	85.7
120	83.3	86.4
200	84.0	88.1
230	84.1	88.4
264	83.7	88.4
280	84.2	88.5
--	-	-

COSEL


Model LFP150F-24-Y

Item Efficiency (by Load Current)

Object _____

1.Graph

—△— Input Volt. 100V
 - - -□- - Input Volt. 200V
 - - ○- - Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure A


2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
1.00	72.4	71.9	72.0
2.00	78.7	79.3	79.5
3.00	81.4	83.6	83.8
4.00	83.8	85.8	85.8
5.00	84.6	87.0	87.2
6.00	85.7	87.7	88.1
6.30	85.7	88.0	88.3
6.93	85.6	88.3	88.5
--	-	-	-
--	-	-	-

COSEL




Model	LFP150F-24-Y																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Power Factor</p> <p>Input Voltage [V]</p> <p>Load 50%</p> <p>Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.995</td><td>0.996</td> </tr> <tr> <td>85</td><td>0.993</td><td>0.997</td> </tr> <tr> <td>100</td><td>0.987</td><td>0.994</td> </tr> <tr> <td>120</td><td>0.978</td><td>0.991</td> </tr> <tr> <td>200</td><td>0.907</td><td>0.950</td> </tr> <tr> <td>230</td><td>0.869</td><td>0.925</td> </tr> <tr> <td>264</td><td>0.825</td><td>0.882</td> </tr> <tr> <td>280</td><td>0.630</td><td>0.702</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.995	0.996	85	0.993	0.997	100	0.987	0.994	120	0.978	0.991	200	0.907	0.950	230	0.869	0.925	264	0.825	0.882	280	0.630	0.702	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.995	0.996																																
85	0.993	0.997																																
100	0.987	0.994																																
120	0.978	0.991																																
200	0.907	0.950																																
230	0.869	0.925																																
264	0.825	0.882																																
280	0.630	0.702																																
--	-	-																																

COSEL

Model	LFP150F-24-Y																																																					
Item	Power Factor (by Load Current)																																																					
Object	_____																																																					
1.Graph	—△— Input Volt. 100V -□--- Input Volt. 200V -○--- Input Volt. 230V																																																					
 <p>The graph plots Power Factor (Y-axis, 0.4 to 1.0) against Load Current [A] (X-axis, 0.0 to 6.0). Three curves are shown for input voltages of 100V, 200V, and 230V. All curves start at approximately 0.68 at 0.0A and rise towards 1.0 as load current increases. A slanted line on the graph indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.689</td><td>0.324</td><td>0.266</td></tr> <tr><td>1.00</td><td>0.953</td><td>0.761</td><td>0.710</td></tr> <tr><td>2.00</td><td>0.977</td><td>0.861</td><td>0.814</td></tr> <tr><td>3.00</td><td>0.988</td><td>0.902</td><td>0.864</td></tr> <tr><td>4.00</td><td>0.992</td><td>0.926</td><td>0.891</td></tr> <tr><td>5.00</td><td>0.992</td><td>0.937</td><td>0.909</td></tr> <tr><td>6.00</td><td>0.995</td><td>0.948</td><td>0.922</td></tr> <tr><td>6.30</td><td>0.994</td><td>0.951</td><td>0.925</td></tr> <tr><td>6.93</td><td>0.994</td><td>0.956</td><td>0.931</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.689	0.324	0.266	1.00	0.953	0.761	0.710	2.00	0.977	0.861	0.814	3.00	0.988	0.902	0.864	4.00	0.992	0.926	0.891	5.00	0.992	0.937	0.909	6.00	0.995	0.948	0.922	6.30	0.994	0.951	0.925	6.93	0.994	0.956	0.931	--	-	-	-	--	-	-	-	Temperature 25°C Testing Circuitry Figure A					
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.689	0.324	0.266																																																			
1.00	0.953	0.761	0.710																																																			
2.00	0.977	0.861	0.814																																																			
3.00	0.988	0.902	0.864																																																			
4.00	0.992	0.926	0.891																																																			
5.00	0.992	0.937	0.909																																																			
6.00	0.995	0.948	0.922																																																			
6.30	0.994	0.951	0.925																																																			
6.93	0.994	0.956	0.931																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.689</td><td>0.324</td><td>0.266</td></tr> <tr><td>1.00</td><td>0.953</td><td>0.761</td><td>0.710</td></tr> <tr><td>2.00</td><td>0.977</td><td>0.861</td><td>0.814</td></tr> <tr><td>3.00</td><td>0.988</td><td>0.902</td><td>0.864</td></tr> <tr><td>4.00</td><td>0.992</td><td>0.926</td><td>0.891</td></tr> <tr><td>5.00</td><td>0.992</td><td>0.937</td><td>0.909</td></tr> <tr><td>6.00</td><td>0.995</td><td>0.948</td><td>0.922</td></tr> <tr><td>6.30</td><td>0.994</td><td>0.951</td><td>0.925</td></tr> <tr><td>6.93</td><td>0.994</td><td>0.956</td><td>0.931</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.689	0.324	0.266	1.00	0.953	0.761	0.710	2.00	0.977	0.861	0.814	3.00	0.988	0.902	0.864	4.00	0.992	0.926	0.891	5.00	0.992	0.937	0.909	6.00	0.995	0.948	0.922	6.30	0.994	0.951	0.925	6.93	0.994	0.956	0.931	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.689	0.324	0.266																																																			
1.00	0.953	0.761	0.710																																																			
2.00	0.977	0.861	0.814																																																			
3.00	0.988	0.902	0.864																																																			
4.00	0.992	0.926	0.891																																																			
5.00	0.992	0.937	0.909																																																			
6.00	0.995	0.948	0.922																																																			
6.30	0.994	0.951	0.925																																																			
6.93	0.994	0.956	0.931																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	LFP150F-24-Y	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	<hr/>		





Model	LFP150F-24-Y	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object			

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.28	0.40	0.46	Operation
	One of phases	0.24	0.52	0.63	Stand by
IEC60950-1	Both phases	0.16	0.41	0.45	Operation
	One of phases	0.26	0.63	0.64	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	LFP150F-24-Y
Item	Line Regulation
Object	+24V6.3A

Temperature 25°C
 Testing Circuitry Figure A

1. Graph




2. Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	24.463	24.457
85	24.463	24.457
100	24.462	24.457
120	24.462	24.456
200	24.462	24.456
230	24.461	24.456
264	24.461	24.455
280	24.461	24.455
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	LFP150F-24-Y	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+24V6.3A																																																					
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> 																																																					
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>24.460</td> <td>24.459</td> <td>24.458</td> </tr> <tr> <td>1.00</td> <td>24.458</td> <td>24.457</td> <td>24.456</td> </tr> <tr> <td>2.00</td> <td>24.458</td> <td>24.457</td> <td>24.455</td> </tr> <tr> <td>3.00</td> <td>24.457</td> <td>24.456</td> <td>24.455</td> </tr> <tr> <td>4.00</td> <td>24.457</td> <td>24.455</td> <td>24.454</td> </tr> <tr> <td>5.00</td> <td>24.456</td> <td>24.455</td> <td>24.454</td> </tr> <tr> <td>6.00</td> <td>24.456</td> <td>24.455</td> <td>24.454</td> </tr> <tr> <td>6.30</td> <td>24.456</td> <td>24.454</td> <td>24.453</td> </tr> <tr> <td>6.93</td> <td>24.455</td> <td>24.454</td> <td>24.453</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	24.460	24.459	24.458	1.00	24.458	24.457	24.456	2.00	24.458	24.457	24.455	3.00	24.457	24.456	24.455	4.00	24.457	24.455	24.454	5.00	24.456	24.455	24.454	6.00	24.456	24.455	24.454	6.30	24.456	24.454	24.453	6.93	24.455	24.454	24.453	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	24.460	24.459	24.458																																																			
1.00	24.458	24.457	24.456																																																			
2.00	24.458	24.457	24.455																																																			
3.00	24.457	24.456	24.455																																																			
4.00	24.457	24.455	24.454																																																			
5.00	24.456	24.455	24.454																																																			
6.00	24.456	24.455	24.454																																																			
6.30	24.456	24.454	24.453																																																			
6.93	24.455	24.454	24.453																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

COSEL



COSEL


Model	LFP150F-24-Y																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																					
Object	+24V6.3A																																						
1.Graph																																							
		2.Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.00</td> <td>20</td> <td>20</td> </tr> <tr> <td>2.00</td> <td>20</td> <td>20</td> </tr> <tr> <td>3.00</td> <td>20</td> <td>20</td> </tr> <tr> <td>4.00</td> <td>25</td> <td>25</td> </tr> <tr> <td>5.00</td> <td>25</td> <td>25</td> </tr> <tr> <td>6.00</td> <td>30</td> <td>30</td> </tr> <tr> <td>6.30</td> <td>30</td> <td>30</td> </tr> <tr> <td>6.93</td> <td>30</td> <td>30</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 100V	Input Volt. 230V	0.00	5	5	1.00	20	20	2.00	20	20	3.00	20	20	4.00	25	25	5.00	25	25	6.00	30	30	6.30	30	30	6.93	30	30	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 100V	Input Volt. 230V																																					
0.00	5	5																																					
1.00	20	20																																					
2.00	20	20																																					
3.00	20	20																																					
4.00	25	25																																					
5.00	25	25																																					
6.00	30	30																																					
6.30	30	30																																					
6.93	30	30																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<p>Fig. Complex Ripple Wave Form</p>																																							

COSEL

Model	LFP150F-24-Y
Item	Ripple-Noise
Object	+24V6.3A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.00	20	20
1.00	30	35
2.00	35	35
3.00	35	35
4.00	40	40
5.00	45	45
6.00	50	50
6.30	50	50
6.93	50	50
--	-	-
--	-	-

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	LFP150F-24-Y
Item	Ripple Voltage (by Ambient Temp.)
Object	+24V6.3A

1.Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
-30	60	60
-10	50	50
0	45	50
25	30	30
50	35	30
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Model LFP150F-24-Y

Item Ambient Temperature Drift

Object +24V6.3A

1. Graph

—▲— Input Volt. 100V
 - - - □ - - Input Volt. 200V
 - - ○ - - Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	24.479	24.479	24.479
-10	24.474	24.473	24.473
0	24.467	24.467	24.467
10	24.462	24.462	24.462
20	24.459	24.458	24.458
25	24.453	24.453	24.452
30	24.449	24.448	24.448
40	24.441	24.440	24.440
50	24.428	24.427	24.427
60	24.410	24.410	24.410
--	-	-	-



Model	LFP150F-24-Y	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V6.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 6.3A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	85	0	24.478	± 26	± 0.1
Minimum Voltage	50	264	6.3	24.427		

COSEL

Model	LFP150F-24-Y	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+24V6.3A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.453</td></tr> <tr><td>0.5</td><td>24.457</td></tr> <tr><td>1.0</td><td>24.457</td></tr> <tr><td>2.0</td><td>24.457</td></tr> <tr><td>3.0</td><td>24.457</td></tr> <tr><td>4.0</td><td>24.457</td></tr> <tr><td>5.0</td><td>24.457</td></tr> <tr><td>6.0</td><td>24.457</td></tr> <tr><td>7.0</td><td>24.457</td></tr> <tr><td>8.0</td><td>24.457</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.453	0.5	24.457	1.0	24.457	2.0	24.457	3.0	24.457	4.0	24.457	5.0	24.457	6.0	24.457	7.0	24.457	8.0	24.457
Time since start [H]	Output Voltage [V]																								
0.0	24.453																								
0.5	24.457																								
1.0	24.457																								
2.0	24.457																								
3.0	24.457																								
4.0	24.457																								
5.0	24.457																								
6.0	24.457																								
7.0	24.457																								
8.0	24.457																								
<p>* The characteristic of AC230V is equal.</p>																									

COSEL


Model LFP150F-24-Y

Item Rise and Fall Time

Temperature 25°C
Testing Circuitry Figure A

Object +24V6.3A


1.Graph



2.Values

[ms]

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		187.8	9.0	196.8	29.2	33.6
230 V		166.8	9.0	175.8	32.9	34.0




COSEL

Model	LFP150F-24-Y
Item	Hold-Up Time
Object	+24V6.3A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	53	26
85	54	27
100	55	27
120	56	28
200	61	30
230	62	31
264	65	32
280	67	33
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	LFP150F-24-Y	Temperature	25°C																																																				
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																				
Object	+24V6.3A																																																						
1.Graph	<p>—△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>1.00</td><td>154</td><td>189</td><td>190</td></tr> <tr><td>2.00</td><td>77</td><td>97</td><td>106</td></tr> <tr><td>3.00</td><td>51</td><td>64</td><td>73</td></tr> <tr><td>4.00</td><td>38</td><td>47</td><td>56</td></tr> <tr><td>5.00</td><td>31</td><td>39</td><td>39</td></tr> <tr><td>6.00</td><td>28</td><td>35</td><td>35</td></tr> <tr><td>6.30</td><td>27</td><td>30</td><td>31</td></tr> <tr><td>6.93</td><td>26</td><td>30</td><td>30</td></tr> </tbody> </table>				Load Current [A]	100V [ms]	200V [ms]	230V [ms]	1.00	154	189	190	2.00	77	97	106	3.00	51	64	73	4.00	38	47	56	5.00	31	39	39	6.00	28	35	35	6.30	27	30	31	6.93	26	30	30															
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																				
1.00	154	189	190																																																				
2.00	77	97	106																																																				
3.00	51	64	73																																																				
4.00	38	47	56																																																				
5.00	31	39	39																																																				
6.00	28	35	35																																																				
6.30	27	30	31																																																				
6.93	26	30	30																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>154</td><td>189</td><td>190</td></tr> <tr><td>2.00</td><td>77</td><td>97</td><td>106</td></tr> <tr><td>3.00</td><td>51</td><td>64</td><td>73</td></tr> <tr><td>4.00</td><td>38</td><td>47</td><td>56</td></tr> <tr><td>5.00</td><td>31</td><td>39</td><td>39</td></tr> <tr><td>6.00</td><td>28</td><td>35</td><td>35</td></tr> <tr><td>6.30</td><td>27</td><td>30</td><td>31</td></tr> <tr><td>6.93</td><td>26</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	1.00	154	189	190	2.00	77	97	106	3.00	51	64	73	4.00	38	47	56	5.00	31	39	39	6.00	28	35	35	6.30	27	30	31	6.93	26	30	30	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	-	-	-																																																				
1.00	154	189	190																																																				
2.00	77	97	106																																																				
3.00	51	64	73																																																				
4.00	38	47	56																																																				
5.00	31	39	39																																																				
6.00	28	35	35																																																				
6.30	27	30	31																																																				
6.93	26	30	30																																																				
--	-	-	-																																																				
--	-	-	-																																																				
<p>Note: Slanted line shows the range of the rated load current.</p>																																																							

COSEL

Model	LFP150F-24-Y
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+24V6.3A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	33	44
-10	33	44
0	33	44
10	33	44
20	33	44
25	33	44
30	33	44
40	32	43
50	33	43
60	32	43
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	LFP150F-24-Y
Item	Overcurrent Protection
Object	+24V6.3A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 15V to 0V.

2.Values


Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
22.8	14.10	14.05
21.6	14.15	14.10
19.2	14.27	14.24
16.8	14.33	14.28
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	LFP150F-24-Y
Item	Overvoltage Protection
Object	+24V6.3A

1.Graph

—▲— Input Volt. 100V
 - - - □ - - Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	30.75	30.64
-10	30.93	30.87
0	31.16	31.04
10	31.34	31.34
20	31.57	31.45
25	31.63	31.63
30	31.75	31.75
40	31.98	31.86
50	32.16	32.16
60	32.33	32.33
--	-	-

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)


COSEL

Figure C