



TEST DATA OF LGA100A-15

Regulated DC Power Supply
May 20, 2011

Approved by : Kenji Shiho
Kenji Shiho Design Manager

Prepared by : Hironobu Shimizu
Hironobu Shimizu Design Engineer


COSEL CO.,LTD.




CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage	12
13. Ripple Noise	13
14. Ripple Voltage(by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL


COSEL

Model	LGA100A-15																																																					
Item	Input Power (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	—△— Input Volt. 85V - -□--- Input Volt. 100V - -○--- Input Volt. 132V																																																					
	 <p>The graph shows three linear plots of Input Power (W) versus Load Current (A) for three different input voltages: 85V (solid line with triangles), 100V (dashed line with squares), and 132V (dash-dot line with circles). The x-axis represents Load Current from 0 to 8 A, and the y-axis represents Input Power from 0 to 200 W. A slanted line on the right side of the graph indicates the rated load current range.</p>																																																					
	2.Values <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>2.9</td> <td>3.3</td> <td>4.3</td> </tr> <tr> <td>1.0</td> <td>20.6</td> <td>21.2</td> <td>22.7</td> </tr> <tr> <td>2.0</td> <td>37.4</td> <td>37.9</td> <td>39.5</td> </tr> <tr> <td>3.0</td> <td>54.4</td> <td>54.6</td> <td>56.0</td> </tr> <tr> <td>4.0</td> <td>72.0</td> <td>71.6</td> <td>72.6</td> </tr> <tr> <td>5.0</td> <td>89.4</td> <td>89.4</td> <td>90.0</td> </tr> <tr> <td>6.0</td> <td>107.4</td> <td>106.8</td> <td>107.1</td> </tr> <tr> <td>7.0</td> <td>125.7</td> <td>124.8</td> <td>124.5</td> </tr> <tr> <td>7.7</td> <td>138.6</td> <td>137.4</td> <td>136.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	2.9	3.3	4.3	1.0	20.6	21.2	22.7	2.0	37.4	37.9	39.5	3.0	54.4	54.6	56.0	4.0	72.0	71.6	72.6	5.0	89.4	89.4	90.0	6.0	107.4	106.8	107.1	7.0	125.7	124.8	124.5	7.7	138.6	137.4	136.8	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	2.9	3.3	4.3																																																			
1.0	20.6	21.2	22.7																																																			
2.0	37.4	37.9	39.5																																																			
3.0	54.4	54.6	56.0																																																			
4.0	72.0	71.6	72.6																																																			
5.0	89.4	89.4	90.0																																																			
6.0	107.4	106.8	107.1																																																			
7.0	125.7	124.8	124.5																																																			
7.7	138.6	137.4	136.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	Note: Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LGA100A-15																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>83.5</td> <td>83.3</td> </tr> <tr> <td>80</td> <td>84.2</td> <td>83.7</td> </tr> <tr> <td>85</td> <td>84.2</td> <td>83.9</td> </tr> <tr> <td>90</td> <td>84.1</td> <td>84.1</td> </tr> <tr> <td>100</td> <td>83.8</td> <td>84.5</td> </tr> <tr> <td>110</td> <td>83.4</td> <td>84.7</td> </tr> <tr> <td>120</td> <td>83.0</td> <td>84.7</td> </tr> <tr> <td>132</td> <td>82.2</td> <td>84.7</td> </tr> <tr> <td>140</td> <td>81.7</td> <td>84.5</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	83.5	83.3	80	84.2	83.7	85	84.2	83.9	90	84.1	84.1	100	83.8	84.5	110	83.4	84.7	120	83.0	84.7	132	82.2	84.7	140	81.7	84.5
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	83.5	83.3																																
80	84.2	83.7																																
85	84.2	83.9																																
90	84.1	84.1																																
100	83.8	84.5																																
110	83.4	84.7																																
120	83.0	84.7																																
132	82.2	84.7																																
140	81.7	84.5																																


COSEL

Model	LGA100A-15																																																					
Item	Efficiency (by Load Current)																																																					
Object																																																						
1.Graph																																																						
	Temperature 25°C Testing Circuitry Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>1.0</td><td>74.7</td><td>72.5</td><td>67.7</td></tr> <tr> <td>2.0</td><td>81.2</td><td>80.1</td><td>76.9</td></tr> <tr> <td>3.0</td><td>83.5</td><td>83.2</td><td>81.1</td></tr> <tr> <td>4.0</td><td>83.9</td><td>84.3</td><td>83.2</td></tr> <tr> <td>5.0</td><td>84.3</td><td>84.3</td><td>83.7</td></tr> <tr> <td>6.0</td><td>84.2</td><td>84.7</td><td>84.4</td></tr> <tr> <td>7.0</td><td>83.9</td><td>84.5</td><td>84.7</td></tr> <tr> <td>7.7</td><td>83.6</td><td>84.4</td><td>84.7</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-	-	-	1.0	74.7	72.5	67.7	2.0	81.2	80.1	76.9	3.0	83.5	83.2	81.1	4.0	83.9	84.3	83.2	5.0	84.3	84.3	83.7	6.0	84.2	84.7	84.4	7.0	83.9	84.5	84.7	7.7	83.6	84.4	84.7	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	-	-	-																																																			
1.0	74.7	72.5	67.7																																																			
2.0	81.2	80.1	76.9																																																			
3.0	83.5	83.2	81.1																																																			
4.0	83.9	84.3	83.2																																																			
5.0	84.3	84.3	83.7																																																			
6.0	84.2	84.7	84.4																																																			
7.0	83.9	84.5	84.7																																																			
7.7	83.6	84.4	84.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model	LGA100A-15																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	<hr/>																																	
1. Graph																																		
<p style="text-align: center;"> --- □ --- Load 50% — ▲ — Load 100% </p>		2.Values																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="text-align: center; padding: 5px;">Input Voltage [V]</th> <th colspan="2" style="text-align: center; padding: 5px;">Power Factor</th> </tr> <tr> <th style="text-align: center; padding: 5px;">Load 50%</th> <th style="text-align: center; padding: 5px;">Load 100%</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 5px;">75</td><td style="text-align: center; padding: 5px;">0.527</td><td style="text-align: center; padding: 5px;">0.586</td></tr> <tr> <td style="text-align: center; padding: 5px;">80</td><td style="text-align: center; padding: 5px;">0.511</td><td style="text-align: center; padding: 5px;">0.574</td></tr> <tr> <td style="text-align: center; padding: 5px;">85</td><td style="text-align: center; padding: 5px;">0.500</td><td style="text-align: center; padding: 5px;">0.563</td></tr> <tr> <td style="text-align: center; padding: 5px;">90</td><td style="text-align: center; padding: 5px;">0.491</td><td style="text-align: center; padding: 5px;">0.552</td></tr> <tr> <td style="text-align: center; padding: 5px;">100</td><td style="text-align: center; padding: 5px;">0.474</td><td style="text-align: center; padding: 5px;">0.532</td></tr> <tr> <td style="text-align: center; padding: 5px;">110</td><td style="text-align: center; padding: 5px;">0.459</td><td style="text-align: center; padding: 5px;">0.514</td></tr> <tr> <td style="text-align: center; padding: 5px;">120</td><td style="text-align: center; padding: 5px;">0.445</td><td style="text-align: center; padding: 5px;">0.499</td></tr> <tr> <td style="text-align: center; padding: 5px;">132</td><td style="text-align: center; padding: 5px;">0.433</td><td style="text-align: center; padding: 5px;">0.483</td></tr> <tr> <td style="text-align: center; padding: 5px;">140</td><td style="text-align: center; padding: 5px;">0.425</td><td style="text-align: center; padding: 5px;">0.473</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.527	0.586	80	0.511	0.574	85	0.500	0.563	90	0.491	0.552	100	0.474	0.532	110	0.459	0.514	120	0.445	0.499	132	0.433	0.483	140	0.425	0.473
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.527	0.586																																
80	0.511	0.574																																
85	0.500	0.563																																
90	0.491	0.552																																
100	0.474	0.532																																
110	0.459	0.514																																
120	0.445	0.499																																
132	0.433	0.483																																
140	0.425	0.473																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	LGA100A-15																																																					
Item	Power Factor (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	<p style="text-align: center;"> Input Volt. 85V Input Volt. 100V Input Volt. 132V </p> 																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.340</td><td>0.319</td><td>0.294</td></tr> <tr><td>1.0</td><td>0.424</td><td>0.405</td><td>0.375</td></tr> <tr><td>2.0</td><td>0.463</td><td>0.440</td><td>0.405</td></tr> <tr><td>3.0</td><td>0.491</td><td>0.463</td><td>0.425</td></tr> <tr><td>4.0</td><td>0.515</td><td>0.483</td><td>0.441</td></tr> <tr><td>5.0</td><td>0.532</td><td>0.504</td><td>0.458</td></tr> <tr><td>6.0</td><td>0.549</td><td>0.518</td><td>0.470</td></tr> <tr><td>7.0</td><td>0.564</td><td>0.532</td><td>0.482</td></tr> <tr><td>7.7</td><td>0.572</td><td>0.540</td><td>0.489</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.340	0.319	0.294	1.0	0.424	0.405	0.375	2.0	0.463	0.440	0.405	3.0	0.491	0.463	0.425	4.0	0.515	0.483	0.441	5.0	0.532	0.504	0.458	6.0	0.549	0.518	0.470	7.0	0.564	0.532	0.482	7.7	0.572	0.540	0.489	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	0.340	0.319	0.294																																																			
1.0	0.424	0.405	0.375																																																			
2.0	0.463	0.440	0.405																																																			
3.0	0.491	0.463	0.425																																																			
4.0	0.515	0.483	0.441																																																			
5.0	0.532	0.504	0.458																																																			
6.0	0.549	0.518	0.470																																																			
7.0	0.564	0.532	0.482																																																			
7.7	0.572	0.540	0.489																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LGA100A-15	Temperature 25°C Testing Circuitry Figure A
Item	Inrush Current	
Object	_____	




Input Voltage 100 V

Frequency 60 Hz

Load 100 %

Primary inrush current 13.3 A

Secondary inrush current 7.9 A





Model	LGA100A-15	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 100 [V]	Input Volt. 120 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.29	0.37	0.41
(B)IEC60950-1	0.29	0.35	0.40

frequency 60Hz

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	LGA100A-15																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+15V7A																																	
1. Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>15.029</td> <td>15.030</td> </tr> <tr> <td>80</td> <td>15.029</td> <td>15.030</td> </tr> <tr> <td>85</td> <td>15.029</td> <td>15.030</td> </tr> <tr> <td>90</td> <td>15.030</td> <td>15.030</td> </tr> <tr> <td>100</td> <td>15.030</td> <td>15.030</td> </tr> <tr> <td>110</td> <td>15.030</td> <td>15.030</td> </tr> <tr> <td>120</td> <td>15.030</td> <td>15.030</td> </tr> <tr> <td>132</td> <td>15.030</td> <td>15.031</td> </tr> <tr> <td>140</td> <td>15.030</td> <td>15.030</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	15.029	15.030	80	15.029	15.030	85	15.029	15.030	90	15.030	15.030	100	15.030	15.030	110	15.030	15.030	120	15.030	15.030	132	15.030	15.031	140	15.030	15.030
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	15.029	15.030																																
80	15.029	15.030																																
85	15.029	15.030																																
90	15.030	15.030																																
100	15.030	15.030																																
110	15.030	15.030																																
120	15.030	15.030																																
132	15.030	15.031																																
140	15.030	15.030																																

COSSEL


Model	LGA100A-15			
Item	Load Regulation			
Object	+15V7A			
1.Graph	Input Volt. 85V Input Volt. 100V Input Volt. 132V	2.Values		
<p>Note: Slanted line shows the range of the rated load current.</p>				
Load Current [A]	Output Voltage [V]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	15.030	15.030	15.030	
1.0	15.029	15.030	15.030	
2.0	15.029	15.030	15.030	
3.0	15.030	15.030	15.030	
4.0	15.030	15.030	15.030	
5.0	15.030	15.030	15.031	
6.0	15.030	15.030	15.031	
7.0	15.030	15.030	15.031	
7.7	15.030	15.031	15.031	
--	-	-	-	-
--	-	-	-	-

COSEL

Model	LGA100A-15	Temperature Testing Circuitry Figure C	25°C
Item	Dynamic Load Response		
Object	+15V7A		

Input Volt. 100 V
Cycle 1000 ms


Response. $t_1=t_2=50 \mu\text{s}$. Typ



Min. Load (0A) ↔
Load 100% (7A)

100 mV/div


10 ms/div





Min. Load (0A) ↔
Load 50% (3.5A)

100 mV/div

10 ms/div




COSEL

Model	LGA100A-15																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+15V7A																																							
1. Graph																																								
<p style="text-align: center;"> Input Volt. 85V Input Volt. 132V </p>  <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 85V)</th> <th>Ripple Voltage [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>1.0</td><td>20</td><td>20</td></tr> <tr><td>2.0</td><td>30</td><td>30</td></tr> <tr><td>3.0</td><td>30</td><td>35</td></tr> <tr><td>4.0</td><td>30</td><td>35</td></tr> <tr><td>5.0</td><td>30</td><td>35</td></tr> <tr><td>6.0</td><td>30</td><td>40</td></tr> <tr><td>7.0</td><td>30</td><td>40</td></tr> <tr><td>7.7</td><td>40</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)	0.0	10	10	1.0	20	20	2.0	30	30	3.0	30	35	4.0	30	35	5.0	30	35	6.0	30	40	7.0	30	40	7.7	40	40	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)																																						
0.0	10	10																																						
1.0	20	20																																						
2.0	30	30																																						
3.0	30	35																																						
4.0	30	35																																						
5.0	30	35																																						
6.0	30	40																																						
7.0	30	40																																						
7.7	40	40																																						
--	-	-																																						
--	-	-																																						
2. Values																																								
<table border="1" style="width: 100%;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>1.0</td><td>20</td><td>20</td></tr> <tr><td>2.0</td><td>30</td><td>30</td></tr> <tr><td>3.0</td><td>30</td><td>35</td></tr> <tr><td>4.0</td><td>30</td><td>35</td></tr> <tr><td>5.0</td><td>30</td><td>35</td></tr> <tr><td>6.0</td><td>30</td><td>40</td></tr> <tr><td>7.0</td><td>30</td><td>40</td></tr> <tr><td>7.7</td><td>40</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	1.0	20	20	2.0	30	30	3.0	30	35	4.0	30	35	5.0	30	35	6.0	30	40	7.0	30	40	7.7	40	40	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	10	10																																						
1.0	20	20																																						
2.0	30	30																																						
3.0	30	35																																						
4.0	30	35																																						
5.0	30	35																																						
6.0	30	40																																						
7.0	30	40																																						
7.7	40	40																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p style="text-align: center;">T1: Due to AC Input Line T2: Due to Switching</p> 																																								
<p style="text-align: center;">Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	LGA100A-15
Item	Ripple-Noise
Object	+15V7A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	30	40
1.0	40	50
2.0	50	55
3.0	60	65
4.0	60	65
5.0	60	70
6.0	60	70
7.0	60	70
7.7	70	70
--	-	-
--	-	-



 T1: Due to AC Input Line
 T2: Due to Switching


Fig. Complex Ripple Wave Form

COSSEL

Model	LGA100A-15	Testing Circuitry Figure C																										
Item	Ripple Voltage (by Ambient Temp.)																											
Object	+15V7A																											
1. Graph		2. Values																										
<p>Ambient Temperature [°C]</p> <p>Ripple Voltage [mV]</p> <p>Input Volt. 100V</p> <p>Input Load. 100%</p> <p>Measured by 20 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>80</td></tr> <tr><td>-10</td><td>50</td></tr> <tr><td>0</td><td>40</td></tr> <tr><td>25</td><td>30</td></tr> <tr><td>50</td><td>30</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]	-30	80	-10	50	0	40	25	30	50	30	--	-	--	-	--	-	--	-	--	-	--	-	--	-
Ambient Temperature [°C]	Ripple Voltage [mV]																											
-30	80																											
-10	50																											
0	40																											
25	30																											
50	30																											
--	-																											
--	-																											
--	-																											
--	-																											
--	-																											
--	-																											
--	-																											
<p>T1: Due to AC Input Line</p> <p>T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p>																												
<p>Fig. Complex Ripple Wave Form</p>																												

COSSEL

Model	LGA100A-15																																																					
Item	Ambient Temperature Drift																																																					
Object	+15V7A																																																					
1.Graph	 <p>—△— Input Volt. 85V ---□--- Input Volt. 100V -·○--- Input Volt. 132V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>15.032</td><td>15.032</td><td>15.033</td></tr> <tr> <td>-10</td><td>15.032</td><td>15.033</td><td>15.033</td></tr> <tr> <td>0</td><td>15.032</td><td>15.032</td><td>15.033</td></tr> <tr> <td>10</td><td>15.032</td><td>15.033</td><td>15.033</td></tr> <tr> <td>20</td><td>15.033</td><td>15.033</td><td>15.033</td></tr> <tr> <td>25</td><td>15.033</td><td>15.033</td><td>15.033</td></tr> <tr> <td>30</td><td>15.032</td><td>15.033</td><td>15.033</td></tr> <tr> <td>40</td><td>15.030</td><td>15.030</td><td>15.031</td></tr> <tr> <td>50</td><td>15.026</td><td>15.026</td><td>15.026</td></tr> <tr> <td>60</td><td>15.018</td><td>15.019</td><td>15.019</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	15.032	15.032	15.033	-10	15.032	15.033	15.033	0	15.032	15.032	15.033	10	15.032	15.033	15.033	20	15.033	15.033	15.033	25	15.033	15.033	15.033	30	15.032	15.033	15.033	40	15.030	15.030	15.031	50	15.026	15.026	15.026	60	15.018	15.019	15.019	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	15.032	15.032	15.033																																																			
-10	15.032	15.033	15.033																																																			
0	15.032	15.032	15.033																																																			
10	15.032	15.033	15.033																																																			
20	15.033	15.033	15.033																																																			
25	15.033	15.033	15.033																																																			
30	15.032	15.033	15.033																																																			
40	15.030	15.030	15.031																																																			
50	15.026	15.026	15.026																																																			
60	15.018	15.019	15.019																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						



Model	LGA100A-15	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 132V

Load Current : 0 - 7A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2


$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	20	132	7	15.033	±4	±0.1
Minimum Voltage	50	85	7	15.026		

COSEL

Model	LGA100A-15	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+15V7A																							
1.Graph		2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.033</td></tr> <tr><td>0.5</td><td>15.030</td></tr> <tr><td>1.0</td><td>15.030</td></tr> <tr><td>2.0</td><td>15.029</td></tr> <tr><td>3.0</td><td>15.029</td></tr> <tr><td>4.0</td><td>15.029</td></tr> <tr><td>5.0</td><td>15.028</td></tr> <tr><td>6.0</td><td>15.028</td></tr> <tr><td>7.0</td><td>15.028</td></tr> <tr><td>8.0</td><td>15.028</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.033	0.5	15.030	1.0	15.030	2.0	15.029	3.0	15.029	4.0	15.029	5.0	15.028	6.0	15.028	7.0	15.028	8.0	15.028
Time since start [H]	Output Voltage [V]																							
0.0	15.033																							
0.5	15.030																							
1.0	15.030																							
2.0	15.029																							
3.0	15.029																							
4.0	15.029																							
5.0	15.028																							
6.0	15.028																							
7.0	15.028																							
8.0	15.028																							

COSEL

COSEL

Model	LGA100A-15	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+15V7A																																		
1.Graph																																			
<p>Legend: ---□--- Load 50% —△— Load 100%</p> <p>Y-axis: Hold-Up Time [ms] X-axis: Input Voltage [V]</p>																																			
2.Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>19</td><td>7</td></tr> <tr><td>80</td><td>24</td><td>10</td></tr> <tr><td>85</td><td>30</td><td>13</td></tr> <tr><td>90</td><td>36</td><td>16</td></tr> <tr><td>100</td><td>50</td><td>23</td></tr> <tr><td>110</td><td>65</td><td>31</td></tr> <tr><td>120</td><td>81</td><td>39</td></tr> <tr><td>132</td><td>103</td><td>50</td></tr> <tr><td>140</td><td>119</td><td>58</td></tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	19	7	80	24	10	85	30	13	90	36	16	100	50	23	110	65	31	120	81	39	132	103	50	140	119	58
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	19	7																																	
80	24	10																																	
85	30	13																																	
90	36	16																																	
100	50	23																																	
110	65	31																																	
120	81	39																																	
132	103	50																																	
140	119	58																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			


COSEL

Model	LGA100A-15		Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation		Testing Circuitry	Figure A																																																			
Object	+15V7A																																																						
1.Graph	<p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p> <p>Input Volt. 85V Input Volt. 100V Input Volt. 132V</p>																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>1.0</td><td>106</td><td>165</td><td>325</td></tr> <tr> <td>2.0</td><td>55</td><td>88</td><td>178</td></tr> <tr> <td>3.0</td><td>36</td><td>56</td><td>121</td></tr> <tr> <td>4.0</td><td>23</td><td>43</td><td>90</td></tr> <tr> <td>5.0</td><td>20</td><td>31</td><td>72</td></tr> <tr> <td>6.0</td><td>14</td><td>27</td><td>59</td></tr> <tr> <td>7.0</td><td>12</td><td>22</td><td>48</td></tr> <tr> <td>7.7</td><td>11</td><td>20</td><td>45</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-	-	-	1.0	106	165	325	2.0	55	88	178	3.0	36	56	121	4.0	23	43	90	5.0	20	31	72	6.0	14	27	59	7.0	12	22	48	7.7	11	20	45	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.0	-	-	-																																																				
1.0	106	165	325																																																				
2.0	55	88	178																																																				
3.0	36	56	121																																																				
4.0	23	43	90																																																				
5.0	20	31	72																																																				
6.0	14	27	59																																																				
7.0	12	22	48																																																				
7.7	11	20	45																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

COSEL

Model	LGA100A-15
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V7A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	61	68
-10	60	68
0	60	68
10	60	67
20	59	67
25	59	67
30	59	67
40	59	67
50	59	66
60	59	66
--	-	-

COSEL

Model	LGA100A-15	Temperature 25°C Testing Circuitry Figure A																																																									
Item	Overcurrent Protection																																																										
Object	+15V7A																																																										
1.Graph	<p>— Input Volt. 85V — Input Volt. 100V — Input Volt. 132V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																									
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>7.45</td><td>7.47</td><td>7.52</td></tr> <tr><td>14.3</td><td>8.43</td><td>8.43</td><td>8.48</td></tr> <tr><td>13.5</td><td>8.43</td><td>8.43</td><td>8.48</td></tr> <tr><td>12.0</td><td>8.46</td><td>8.46</td><td>8.49</td></tr> <tr><td>10.5</td><td>8.52</td><td>8.53</td><td>8.63</td></tr> <tr><td>9.0</td><td>8.58</td><td>8.57</td><td>8.61</td></tr> <tr><td>7.5</td><td>8.61</td><td>8.64</td><td>8.72</td></tr> <tr><td>6.0</td><td>8.73</td><td>8.74</td><td>8.78</td></tr> <tr><td>4.5</td><td>8.78</td><td>8.77</td><td>8.76</td></tr> <tr><td>3.0</td><td>8.76</td><td>8.74</td><td>8.77</td></tr> <tr><td>1.5</td><td>8.70</td><td>8.69</td><td>8.66</td></tr> <tr><td>0.0</td><td>8.89</td><td>8.85</td><td>8.92</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	15.0	7.45	7.47	7.52	14.3	8.43	8.43	8.48	13.5	8.43	8.43	8.48	12.0	8.46	8.46	8.49	10.5	8.52	8.53	8.63	9.0	8.58	8.57	8.61	7.5	8.61	8.64	8.72	6.0	8.73	8.74	8.78	4.5	8.78	8.77	8.76	3.0	8.76	8.74	8.77	1.5	8.70	8.69	8.66	0.0	8.89	8.85	8.92
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
15.0	7.45	7.47	7.52																																																								
14.3	8.43	8.43	8.48																																																								
13.5	8.43	8.43	8.48																																																								
12.0	8.46	8.46	8.49																																																								
10.5	8.52	8.53	8.63																																																								
9.0	8.58	8.57	8.61																																																								
7.5	8.61	8.64	8.72																																																								
6.0	8.73	8.74	8.78																																																								
4.5	8.78	8.77	8.76																																																								
3.0	8.76	8.74	8.77																																																								
1.5	8.70	8.69	8.66																																																								
0.0	8.89	8.85	8.92																																																								
		<p>Note: Slanted line shows the range of the rated load current.</p>																																																									



Model	LGA100A-15																																				
Item	Overvoltage Protection																																				
Object	+15V7A																																				
1.Graph																																					
<p style="text-align: center;"> Input Volt. 85V Input Volt. 132V </p> <table border="1" style="margin-top: 10px; border-collapse: collapse; text-align: center;"> <tr> <th>Ambient Temperature [°C]</th> <th>Operating Point [V] (Input Volt. 85[V])</th> <th>Operating Point [V] (Input Volt. 132[V])</th> </tr> <tr> <td>-20</td> <td>18.56</td> <td>18.56</td> </tr> <tr> <td>-10</td> <td>18.73</td> <td>18.73</td> </tr> <tr> <td>0</td> <td>18.85</td> <td>18.85</td> </tr> <tr> <td>10</td> <td>19.02</td> <td>19.02</td> </tr> <tr> <td>20</td> <td>19.14</td> <td>19.14</td> </tr> <tr> <td>25</td> <td>19.20</td> <td>19.20</td> </tr> <tr> <td>30</td> <td>19.26</td> <td>19.26</td> </tr> <tr> <td>40</td> <td>19.43</td> <td>19.43</td> </tr> <tr> <td>50</td> <td>19.55</td> <td>19.55</td> </tr> <tr> <td>60</td> <td>19.72</td> <td>19.72</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </table>		Ambient Temperature [°C]	Operating Point [V] (Input Volt. 85[V])	Operating Point [V] (Input Volt. 132[V])	-20	18.56	18.56	-10	18.73	18.73	0	18.85	18.85	10	19.02	19.02	20	19.14	19.14	25	19.20	19.20	30	19.26	19.26	40	19.43	19.43	50	19.55	19.55	60	19.72	19.72	--	-	-
Ambient Temperature [°C]	Operating Point [V] (Input Volt. 85[V])	Operating Point [V] (Input Volt. 132[V])																																			
-20	18.56	18.56																																			
-10	18.73	18.73																																			
0	18.85	18.85																																			
10	19.02	19.02																																			
20	19.14	19.14																																			
25	19.20	19.20																																			
30	19.26	19.26																																			
40	19.43	19.43																																			
50	19.55	19.55																																			
60	19.72	19.72																																			
--	-	-																																			
2.Values																																					

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)


COSEL

Figure C