



# TEST DATA OF LGA100A-24

Regulated DC Power Supply  
April 15 , 2008

Approved by :   
Yoshiaki Shimizu Design Manager

Prepared by :   
Kazuo Ishimura Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ripple-Noise . . . . .	13
14. Ripple Voltage (by Ambient Temperature) . . . . .	14
15. Ambient Temperature Drift . . . . .	15
16. Output Voltage Accuracy . . . . .	16
17. Time Lapse Drift . . . . .	17
18. Rise and Fall Time . . . . .	18
19. Hold-Up Time . . . . .	19
20. Instantaneous Interruption Compensation . . . . .	20
21. Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22. Overcurrent Protection . . . . .	22
23. Overvoltage Protection . . . . .	23
24. Figure of Testing Circuitry . . . . .	24

(Final Page 25)



Model	LGA100A-24																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	—△— Input Volt. 85V - - □ - - Input Volt. 100V - - ○ - - Input Volt. 132V																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.106</td><td>0.102</td><td>0.108</td></tr> <tr> <td>0.80</td><td>0.629</td><td>0.596</td><td>0.502</td></tr> <tr> <td>1.60</td><td>1.087</td><td>0.981</td><td>0.823</td></tr> <tr> <td>2.40</td><td>1.528</td><td>1.369</td><td>1.150</td></tr> <tr> <td>3.20</td><td>1.937</td><td>1.739</td><td>1.452</td></tr> <tr> <td>4.00</td><td>2.370</td><td>2.107</td><td>1.737</td></tr> <tr> <td>4.30</td><td>2.520</td><td>2.239</td><td>1.852</td></tr> <tr> <td>4.73</td><td>2.739</td><td>2.433</td><td>2.004</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.106	0.102	0.108	0.80	0.629	0.596	0.502	1.60	1.087	0.981	0.823	2.40	1.528	1.369	1.150	3.20	1.937	1.739	1.452	4.00	2.370	2.107	1.737	4.30	2.520	2.239	1.852	4.73	2.739	2.433	2.004	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	0.106	0.102	0.108																																																			
0.80	0.629	0.596	0.502																																																			
1.60	1.087	0.981	0.823																																																			
2.40	1.528	1.369	1.150																																																			
3.20	1.937	1.739	1.452																																																			
4.00	2.370	2.107	1.737																																																			
4.30	2.520	2.239	1.852																																																			
4.73	2.739	2.433	2.004																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					



Model	LGA100A-24																																																					
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	—△— Input Volt. 85V - - -□--- Input Volt. 100V - · -○--- Input Volt. 132V																																																					
Note:	Slanted line shows the range of the rated load current.																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values																																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>2.8</td> <td>3.2</td> <td>3.8</td> </tr> <tr> <td>0.80</td> <td>24.5</td> <td>25.1</td> <td>26.5</td> </tr> <tr> <td>1.60</td> <td>45.9</td> <td>46.3</td> <td>47.5</td> </tr> <tr> <td>2.40</td> <td>67.8</td> <td>67.7</td> <td>68.7</td> </tr> <tr> <td>3.20</td> <td>90.0</td> <td>90.0</td> <td>90.6</td> </tr> <tr> <td>4.00</td> <td>112.8</td> <td>112.2</td> <td>112.2</td> </tr> <tr> <td>4.30</td> <td>121.5</td> <td>120.6</td> <td>120.6</td> </tr> <tr> <td>4.73</td> <td>134.1</td> <td>132.9</td> <td>132.6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	2.8	3.2	3.8	0.80	24.5	25.1	26.5	1.60	45.9	46.3	47.5	2.40	67.8	67.7	68.7	3.20	90.0	90.0	90.6	4.00	112.8	112.2	112.2	4.30	121.5	120.6	120.6	4.73	134.1	132.9	132.6	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	2.8	3.2	3.8																																																			
0.80	24.5	25.1	26.5																																																			
1.60	45.9	46.3	47.5																																																			
2.40	67.8	67.7	68.7																																																			
3.20	90.0	90.0	90.6																																																			
4.00	112.8	112.2	112.2																																																			
4.30	121.5	120.6	120.6																																																			
4.73	134.1	132.9	132.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



Model	LGA100A-24	Temperature Testing Circuitry	25°C Figure A																														
Item	Efficiency (by Input Voltage)																																
Object	_____																																
1. Graph			2. Values																														
<p>The graph plots Efficiency [%] on the y-axis (34 to 90) against Input Voltage [V] on the x-axis (70 to 150). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency remaining high (around 84%) across the tested input voltage range. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>84.9</td><td>84.2</td></tr> <tr><td>80</td><td>85.0</td><td>84.6</td></tr> <tr><td>85</td><td>85.0</td><td>85.0</td></tr> <tr><td>90</td><td>84.9</td><td>85.2</td></tr> <tr><td>100</td><td>84.7</td><td>85.6</td></tr> <tr><td>110</td><td>84.3</td><td>85.8</td></tr> <tr><td>120</td><td>83.9</td><td>85.8</td></tr> <tr><td>132</td><td>83.2</td><td>85.7</td></tr> <tr><td>140</td><td>82.7</td><td>85.6</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	75	84.9	84.2	80	85.0	84.6	85	85.0	85.0	90	84.9	85.2	100	84.7	85.6	110	84.3	85.8	120	83.9	85.8	132	83.2	85.7	140	82.7	85.6
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																															
75	84.9	84.2																															
80	85.0	84.6																															
85	85.0	85.0																															
90	84.9	85.2																															
100	84.7	85.6																															
110	84.3	85.8																															
120	83.9	85.8																															
132	83.2	85.7																															
140	82.7	85.6																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	



Model	LGA100A-24																																																		
Item	Efficiency (by Load Current)																																																		
Object	_____																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.80</td><td>78.7</td><td>76.9</td><td>72.8</td></tr> <tr><td>1.60</td><td>84.0</td><td>83.3</td><td>81.1</td></tr> <tr><td>2.40</td><td>85.2</td><td>85.2</td><td>84.0</td></tr> <tr><td>3.20</td><td>85.6</td><td>85.8</td><td>85.2</td></tr> <tr><td>4.00</td><td>85.3</td><td>85.8</td><td>85.7</td></tr> <tr><td>4.30</td><td>85.0</td><td>85.6</td><td>85.8</td></tr> <tr><td>4.73</td><td>84.7</td><td>85.4</td><td>85.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	-	-	-	0.80	78.7	76.9	72.8	1.60	84.0	83.3	81.1	2.40	85.2	85.2	84.0	3.20	85.6	85.8	85.2	4.00	85.3	85.8	85.7	4.30	85.0	85.6	85.8	4.73	84.7	85.4	85.8	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
0.00	-	-	-																																																
0.80	78.7	76.9	72.8																																																
1.60	84.0	83.3	81.1																																																
2.40	85.2	85.2	84.0																																																
3.20	85.6	85.8	85.2																																																
4.00	85.3	85.8	85.7																																																
4.30	85.0	85.6	85.8																																																
4.73	84.7	85.4	85.8																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
2.Values																																																			
Note: Slanted line shows the range of the rated load current.																																																			

**COSEL**

Model	LGA100A-24																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____	_____																																
1.Graph																																		
<p>Power Factor</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.517</td><td>0.578</td></tr> <tr><td>80</td><td>0.506</td><td>0.565</td></tr> <tr><td>85</td><td>0.491</td><td>0.553</td></tr> <tr><td>90</td><td>0.484</td><td>0.543</td></tr> <tr><td>100</td><td>0.467</td><td>0.522</td></tr> <tr><td>110</td><td>0.452</td><td>0.505</td></tr> <tr><td>120</td><td>0.440</td><td>0.489</td></tr> <tr><td>132</td><td>0.428</td><td>0.475</td></tr> <tr><td>140</td><td>0.420</td><td>0.465</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.517	0.578	80	0.506	0.565	85	0.491	0.553	90	0.484	0.543	100	0.467	0.522	110	0.452	0.505	120	0.440	0.489	132	0.428	0.475	140	0.420	0.465
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.517	0.578																																
80	0.506	0.565																																
85	0.491	0.553																																
90	0.484	0.543																																
100	0.467	0.522																																
110	0.452	0.505																																
120	0.440	0.489																																
132	0.428	0.475																																
140	0.420	0.465																																

**COSEL**


Model	LGA100A-24	Temperature Testing Circuitry	25°C																																																			
Item	Power Factor (by Load Current)	Figure A																																																				
Object																																																						
1.Graph	<p>—△— Input Volt. 85V        - - -□- - Input Volt. 100V        - - ○- - Input Volt. 132V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.342</td><td>0.330</td><td>0.306</td></tr> <tr><td>0.80</td><td>0.431</td><td>0.412</td><td>0.381</td></tr> <tr><td>1.60</td><td>0.472</td><td>0.449</td><td>0.412</td></tr> <tr><td>2.40</td><td>0.503</td><td>0.474</td><td>0.434</td></tr> <tr><td>3.20</td><td>0.526</td><td>0.498</td><td>0.454</td></tr> <tr><td>4.00</td><td>0.546</td><td>0.516</td><td>0.468</td></tr> <tr><td>4.30</td><td>0.553</td><td>0.522</td><td>0.474</td></tr> <tr><td>4.73</td><td>0.562</td><td>0.530</td><td>0.481</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	0.342	0.330	0.306	0.80	0.431	0.412	0.381	1.60	0.472	0.449	0.412	2.40	0.503	0.474	0.434	3.20	0.526	0.498	0.454	4.00	0.546	0.516	0.468	4.30	0.553	0.522	0.474	4.73	0.562	0.530	0.481	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	0.342	0.330	0.306																																																			
0.80	0.431	0.412	0.381																																																			
1.60	0.472	0.449	0.412																																																			
2.40	0.503	0.474	0.434																																																			
3.20	0.526	0.498	0.454																																																			
4.00	0.546	0.516	0.468																																																			
4.30	0.553	0.522	0.474																																																			
4.73	0.562	0.530	0.481																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model LGA100A-24


Item Inrush Current

Object

Temperature 25°C  
Testing Circuitry Figure AInput  
Current  
[20A/div]

Input Voltage	100 V
Frequency	60 Hz
Load	100 %

Primary inrush current	12.7 A
Secondary inrush current	7.9 A





Model	LGA100A-24	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 100 [V]	Input Volt. 120 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.29	0.37	0.41
(B)IEC60950	0.29	0.35	0.40

frequency 60Hz

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


**COSEL**

Model	LGA100A-24																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+24V4.3A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: - - - □ - - - Load 50% — △ — Load 100%</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>24.075</td><td>24.069</td></tr> <tr><td>80</td><td>24.075</td><td>24.069</td></tr> <tr><td>85</td><td>24.075</td><td>24.069</td></tr> <tr><td>90</td><td>24.075</td><td>24.069</td></tr> <tr><td>100</td><td>24.075</td><td>24.069</td></tr> <tr><td>110</td><td>24.075</td><td>24.069</td></tr> <tr><td>120</td><td>24.075</td><td>24.069</td></tr> <tr><td>132</td><td>24.075</td><td>24.069</td></tr> <tr><td>140</td><td>24.075</td><td>24.069</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	24.075	24.069	80	24.075	24.069	85	24.075	24.069	90	24.075	24.069	100	24.075	24.069	110	24.075	24.069	120	24.075	24.069	132	24.075	24.069	140	24.075	24.069
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	24.075	24.069																																
80	24.075	24.069																																
85	24.075	24.069																																
90	24.075	24.069																																
100	24.075	24.069																																
110	24.075	24.069																																
120	24.075	24.069																																
132	24.075	24.069																																
140	24.075	24.069																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



Model	LGA100A-24																																																					
Item	Load Regulation																																																					
Object	+24V4.3A																																																					
1. Graph <div style="text-align: center; margin-top: 10px;"> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul> </div>																																																						
2. Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>24.070</td><td>24.070</td><td>24.070</td></tr> <tr><td>0.80</td><td>24.067</td><td>24.067</td><td>24.067</td></tr> <tr><td>1.60</td><td>24.066</td><td>24.066</td><td>24.066</td></tr> <tr><td>2.40</td><td>24.065</td><td>24.065</td><td>24.065</td></tr> <tr><td>3.20</td><td>24.064</td><td>24.064</td><td>24.064</td></tr> <tr><td>4.00</td><td>24.063</td><td>24.063</td><td>24.063</td></tr> <tr><td>4.30</td><td>24.063</td><td>24.063</td><td>24.063</td></tr> <tr><td>4.73</td><td>24.063</td><td>24.063</td><td>24.063</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	24.070	24.070	24.070	0.80	24.067	24.067	24.067	1.60	24.066	24.066	24.066	2.40	24.065	24.065	24.065	3.20	24.064	24.064	24.064	4.00	24.063	24.063	24.063	4.30	24.063	24.063	24.063	4.73	24.063	24.063	24.063	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.00	24.070	24.070	24.070																																																			
0.80	24.067	24.067	24.067																																																			
1.60	24.066	24.066	24.066																																																			
2.40	24.065	24.065	24.065																																																			
3.20	24.064	24.064	24.064																																																			
4.00	24.063	24.063	24.063																																																			
4.30	24.063	24.063	24.063																																																			
4.73	24.063	24.063	24.063																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

**COSEL**

Model	LGA100A-24																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+24V4.3A																																							
1. Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two sets of data points: Input Volt. 85V (solid line with triangle markers) and Input Volt. 132V (dashed line with circle markers). The x-axis represents Load Current [A] from 0 to 5. The y-axis represents Ripple Voltage [mV] from 0 to 200. A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 85V)</th> <th>Ripple Voltage [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>15</td></tr> <tr><td>0.80</td><td>15</td><td>15</td></tr> <tr><td>1.60</td><td>15</td><td>15</td></tr> <tr><td>2.40</td><td>20</td><td>20</td></tr> <tr><td>3.20</td><td>20</td><td>20</td></tr> <tr><td>4.00</td><td>25</td><td>25</td></tr> <tr><td>4.30</td><td>25</td><td>25</td></tr> <tr><td>4.73</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)	0.00	10	15	0.80	15	15	1.60	15	15	2.40	20	20	3.20	20	20	4.00	25	25	4.30	25	25	4.73	30	30	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)																																						
0.00	10	15																																						
0.80	15	15																																						
1.60	15	15																																						
2.40	20	20																																						
3.20	20	20																																						
4.00	25	25																																						
4.30	25	25																																						
4.73	30	30																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>15</td></tr> <tr><td>0.80</td><td>15</td><td>15</td></tr> <tr><td>1.60</td><td>15</td><td>15</td></tr> <tr><td>2.40</td><td>20</td><td>20</td></tr> <tr><td>3.20</td><td>20</td><td>20</td></tr> <tr><td>4.00</td><td>25</td><td>25</td></tr> <tr><td>4.30</td><td>25</td><td>25</td></tr> <tr><td>4.73</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	10	15	0.80	15	15	1.60	15	15	2.40	20	20	3.20	20	20	4.00	25	25	4.30	25	25	4.73	30	30	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.00	10	15																																						
0.80	15	15																																						
1.60	15	15																																						
2.40	20	20																																						
3.20	20	20																																						
4.00	25	25																																						
4.30	25	25																																						
4.73	30	30																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope.      Ripple Voltage is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line      T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								

**COSEL**


Model LGA100A-24

Item Ripple-Noise

Object +24V4.3A

## 1. Graph

—△— Input Volt. 85V  
 -·○--- Input Volt. 132V



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure C

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.00	15	15
0.80	30	30
1.60	35	35
2.40	45	45
3.20	55	55
4.00	65	65
4.30	70	70
4.73	80	80
--	-	-
--	-	-
--	-	-



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

Model	LGA100A-24	Testing Circuitry FigureC																										
Item	Ripple Voltage (by Ambient Temp.)																											
Object	+24V4.3A																											
1. Graph		2. Values																										
<p>Ambient Temperature [°C]</p> <p>Ripple Voltage [mV]</p> <p>Input Volt. 100V</p> <p>Input Load. 100%</p>		<table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>125</td></tr> <tr><td>-10</td><td>65</td></tr> <tr><td>0</td><td>40</td></tr> <tr><td>25</td><td>25</td></tr> <tr><td>50</td><td>25</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]	-30	125	-10	65	0	40	25	25	50	25	--	-	--	-	--	-	--	-	--	-	--	-	--	-
Ambient Temperature [°C]	Ripple Voltage [mV]																											
-30	125																											
-10	65																											
0	40																											
25	25																											
50	25																											
--	-																											
--	-																											
--	-																											
--	-																											
--	-																											
--	-																											
--	-																											
<p>Measured by 20 MHz Oscilloscope.</p> <p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																												
<p>T1: Due to AC Input Line</p> <p>T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p>																												
<p>Fig. Complex Ripple Wave Form</p>																												



Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	24.148	24.149	24.150
-10	24.132	24.133	24.133
0	24.117	24.118	24.118
10	24.103	24.103	24.104
20	24.088	24.088	24.089
25	24.079	24.079	24.080
30	24.070	24.071	24.071
40	24.052	24.053	24.053
50	24.033	24.033	24.034
60	24.005	24.006	24.006
--	-	-	-



Model	LGA100A-24	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V4.3A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 132V

Load Current : 0 - 4.3A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	85	0	24.140	±54	±0.2
Minimum Voltage	50	85	4.3	24.033		




Model	LGA100A-24	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+24V4.3A																								
1.Graph			2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.082</td></tr> <tr><td>0.5</td><td>24.059</td></tr> <tr><td>1.0</td><td>24.059</td></tr> <tr><td>2.0</td><td>24.060</td></tr> <tr><td>3.0</td><td>24.060</td></tr> <tr><td>4.0</td><td>24.060</td></tr> <tr><td>5.0</td><td>24.062</td></tr> <tr><td>6.0</td><td>24.060</td></tr> <tr><td>7.0</td><td>24.061</td></tr> <tr><td>8.0</td><td>24.061</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.082	0.5	24.059	1.0	24.059	2.0	24.060	3.0	24.060	4.0	24.060	5.0	24.062	6.0	24.060	7.0	24.061	8.0	24.061
Time since start [H]	Output Voltage [V]																								
0.0	24.082																								
0.5	24.059																								
1.0	24.059																								
2.0	24.060																								
3.0	24.060																								
4.0	24.060																								
5.0	24.062																								
6.0	24.060																								
7.0	24.061																								
8.0	24.061																								

COSEL

Model	LGA100A-24
Item	Rise and Fall Time
Object	+24V4.3A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		75.0	52.0	127.0	55.7	24.2	
100 %		75.0	52.0	127.0	25.9	12.1	






Model	LGA100A-24
Item	Hold-Up Time
Object	+24V4.3A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	19	7
80	25	10
85	32	13
90	38	17
100	53	24
110	69	32
120	87	41
132	110	53
140	127	62

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
Note: Slanted line shows the range of the rated input voltage.




<p>Model      LGA100A-24</p> <p>Item      Instantaneous Interruption Compensation</p> <p>Object    +24V4.3A</p>	<p>Temperature      25°C Testing Circuitry      Figure A</p>																																																				
	<p>2. Values</p>																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr> <tr> <th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.80</td><td>89</td><td>143</td><td>281</td></tr> <tr> <td>1.60</td><td>46</td><td>73</td><td>148</td></tr> <tr> <td>2.40</td><td>30</td><td>48</td><td>101</td></tr> <tr> <td>3.20</td><td>20</td><td>36</td><td>73</td></tr> <tr> <td>4.00</td><td>14</td><td>25</td><td>59</td></tr> <tr> <td>4.30</td><td>14</td><td>23</td><td>55</td></tr> <tr> <td>4.73</td><td>12</td><td>22</td><td>48</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	-	-	-	0.80	89	143	281	1.60	46	73	148	2.40	30	48	101	3.20	20	36	73	4.00	14	25	59	4.30	14	23	55	4.73	12	22	48	--	-	-	-	--	-	-	-	--	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																		
0.00	-	-	-																																																		
0.80	89	143	281																																																		
1.60	46	73	148																																																		
2.40	30	48	101																																																		
3.20	20	36	73																																																		
4.00	14	25	59																																																		
4.30	14	23	55																																																		
4.73	12	22	48																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1. Graph</p> <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p> <p>—△— Input Volt. 85V</p> <p>- - □ - - Input Volt. 100V</p> <p>- · ○ - - Input Volt. 132V</p>																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

**COSEL**

Model	LGA100A-24
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+24V4.3A

Testing Circuitry Figure A

## 1.Graph




## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	60	67
-10	59	67
0	59	66
10	59	66
20	58	66
25	58	66
30	58	66
40	58	65
50	58	65
60	57	65
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	LGA100A-24																																																									
Item	Overcurrent Protection	Temperature Testing Circuitry	25°C Figure A																																																							
Object	+24V4.3A																																																									
1.Graph	 <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 85V</p> <p>Input Volt. 100V</p> <p>Input Volt. 132V</p>																																																									
Note:	Slanted line shows the range of the rated load current.																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr> <tr> <th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr> </thead> <tbody> <tr><td>24.0</td><td>5.12</td><td>5.14</td><td>5.20</td></tr> <tr><td>22.8</td><td>5.13</td><td>5.16</td><td>5.22</td></tr> <tr><td>21.6</td><td>5.14</td><td>5.18</td><td>5.24</td></tr> <tr><td>19.2</td><td>5.17</td><td>5.20</td><td>5.26</td></tr> <tr><td>16.8</td><td>5.21</td><td>5.26</td><td>5.29</td></tr> <tr><td>14.4</td><td>5.28</td><td>5.32</td><td>5.37</td></tr> <tr><td>12.0</td><td>5.27</td><td>5.30</td><td>5.39</td></tr> <tr><td>9.6</td><td>5.31</td><td>5.35</td><td>5.40</td></tr> <tr><td>7.2</td><td>5.36</td><td>5.39</td><td>5.46</td></tr> <tr><td>4.8</td><td>5.36</td><td>5.39</td><td>5.45</td></tr> <tr><td>2.4</td><td>5.33</td><td>5.35</td><td>5.39</td></tr> <tr><td>0.0</td><td>5.46</td><td>5.67</td><td>5.72</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	24.0	5.12	5.14	5.20	22.8	5.13	5.16	5.22	21.6	5.14	5.18	5.24	19.2	5.17	5.20	5.26	16.8	5.21	5.26	5.29	14.4	5.28	5.32	5.37	12.0	5.27	5.30	5.39	9.6	5.31	5.35	5.40	7.2	5.36	5.39	5.46	4.8	5.36	5.39	5.45	2.4	5.33	5.35	5.39	0.0	5.46	5.67	5.72
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
24.0	5.12	5.14	5.20																																																							
22.8	5.13	5.16	5.22																																																							
21.6	5.14	5.18	5.24																																																							
19.2	5.17	5.20	5.26																																																							
16.8	5.21	5.26	5.29																																																							
14.4	5.28	5.32	5.37																																																							
12.0	5.27	5.30	5.39																																																							
9.6	5.31	5.35	5.40																																																							
7.2	5.36	5.39	5.46																																																							
4.8	5.36	5.39	5.45																																																							
2.4	5.33	5.35	5.39																																																							
0.0	5.46	5.67	5.72																																																							



Model	LGA100A-24
Item	Ovv Protection
Object	+24V4.3A



## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	29.94	29.94	29.94
-10	30.25	30.25	30.25
0	30.60	30.60	30.60
10	30.95	30.89	30.89
20	31.19	31.19	31.19
25	31.36	31.36	31.36
30	31.48	31.48	31.48
40	31.77	31.77	31.77
50	32.06	32.06	32.06
60	32.47	32.36	32.36
--	-	-	-

coSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950-1 )




Figure C