


DATA SHEET		Date	17-Jul-10
Model	LGA150A-3R3-Y	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Y.Oyama

LINE CONDUCTION

Model Name : LGA150A-3R3-Y
Model No. :
Serial No. :
Points : 2
Detector : PEAK/QP/Ave.
Line Mode : VA/VB
Power Supply : AC100V 60Hz
Limit1: [EN 55022] Class B(QP)
Limit2: [EN 55022] Class B(Ave.)

Temp. : 25 degreeC
Humi. : 40%
Date : 2010/7/17 15:18
Test Equip. : R3132.ESPC
Load Line : 100mm
Comment :




Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]
0.2672	32.5	44.0	9.8	42.3	53.8	VB	51.2	61.2	8.9	7.4
0.8027	29.3	40.1	9.9	39.2	50.0	VB	46.0	56.0	6.8	6.0

RADIATED EMISSION

Model Name : LGA150A-3R3-Y
Model No. :
Serial No. :
Points : 2
Detector : PEAK/QP
Line Mode : Hori. & Vert.
Power Supply : AC100V 60Hz
Limit1: [EN 55022] Class B<3m>


Temp. : 25 degreeC
Humi. : 40%
Date : 2010/7/17 16:39
Test Equip. : R3132.ESPC
Load Line : 100mm
Comment :



Frequency [MHz]	Meter Reading (QP) [dBuV]	Ant. Type	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]
53.0140	48.5	BL	-21.1	27.4	26	159	Hori.	40	12.6
52.8240	55.0	BL	-21.0	34.0	114	122	Vert.	40	6.0

DATA SHEET		Date	17-Jul-10
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Y.Oyama

1. Line conduction



2. Radiated emission

