



TEST DATA OF LGA50A-3R3-Y

Regulated DC Power Supply
May 20, 2011

Approved by : Kenji Shiho
Kenji Shiho Design Manager

Prepared by : Yosuke Saitou
Yosuke Saitou Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage	12
13. Ripple Noise	13
14. Ripple Voltage(by Ambient Temperture)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	LGA50A-3R3-Y																																																					
Item	Input Current (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —▲— Input Volt. 85V -□--- Input Volt. 100V -○--- Input Volt. 132V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.045</td><td>0.047</td><td>0.050</td></tr> <tr> <td>2</td><td>0.231</td><td>0.213</td><td>0.190</td></tr> <tr> <td>4</td><td>0.390</td><td>0.353</td><td>0.302</td></tr> <tr> <td>6</td><td>0.553</td><td>0.495</td><td>0.415</td></tr> <tr> <td>8</td><td>0.725</td><td>0.644</td><td>0.533</td></tr> <tr> <td>10</td><td>0.900</td><td>0.797</td><td>0.657</td></tr> <tr> <td>11</td><td>0.992</td><td>0.878</td><td>0.723</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.045	0.047	0.050	2	0.231	0.213	0.190	4	0.390	0.353	0.302	6	0.553	0.495	0.415	8	0.725	0.644	0.533	10	0.900	0.797	0.657	11	0.992	0.878	0.723	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	0.045	0.047	0.050																																																			
2	0.231	0.213	0.190																																																			
4	0.390	0.353	0.302																																																			
6	0.553	0.495	0.415																																																			
8	0.725	0.644	0.533																																																			
10	0.900	0.797	0.657																																																			
11	0.992	0.878	0.723																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LGA50A-3R3-Y																																																					
Item	Input Power (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 85V ---□--- Input Volt. 100V ---○--- Input Volt. 132V </p>																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>1.36</td><td>1.59</td><td>2.19</td></tr> <tr><td>2</td><td>9.45</td><td>9.79</td><td>10.71</td></tr> <tr><td>4</td><td>17.70</td><td>17.87</td><td>18.69</td></tr> <tr><td>6</td><td>26.20</td><td>26.30</td><td>27.10</td></tr> <tr><td>8</td><td>35.10</td><td>35.10</td><td>35.70</td></tr> <tr><td>10</td><td>44.40</td><td>44.30</td><td>44.60</td></tr> <tr><td>11</td><td>49.10</td><td>49.00</td><td>49.20</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	1.36	1.59	2.19	2	9.45	9.79	10.71	4	17.70	17.87	18.69	6	26.20	26.30	27.10	8	35.10	35.10	35.70	10	44.40	44.30	44.60	11	49.10	49.00	49.20	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	1.36	1.59	2.19																																																			
2	9.45	9.79	10.71																																																			
4	17.70	17.87	18.69																																																			
6	26.20	26.30	27.10																																																			
8	35.10	35.10	35.70																																																			
10	44.40	44.30	44.60																																																			
11	49.10	49.00	49.20																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LGA50A-3R3-Y																																
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object	—																																
1.Graph																																	
		2.Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>76.3</td><td>74.2</td></tr> <tr><td>80</td><td>76.0</td><td>74.6</td></tr> <tr><td>85</td><td>76.0</td><td>74.7</td></tr> <tr><td>90</td><td>75.6</td><td>74.9</td></tr> <tr><td>100</td><td>75.0</td><td>74.9</td></tr> <tr><td>110</td><td>74.3</td><td>74.7</td></tr> <tr><td>120</td><td>73.7</td><td>74.7</td></tr> <tr><td>132</td><td>72.6</td><td>74.4</td></tr> <tr><td>140</td><td>71.8</td><td>74.1</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	76.3	74.2	80	76.0	74.6	85	76.0	74.7	90	75.6	74.9	100	75.0	74.9	110	74.3	74.7	120	73.7	74.7	132	72.6	74.4	140	71.8	74.1
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
75	76.3	74.2																															
80	76.0	74.6																															
85	76.0	74.7																															
90	75.6	74.9																															
100	75.0	74.9																															
110	74.3	74.7																															
120	73.7	74.7																															
132	72.6	74.4																															
140	71.8	74.1																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	


COSEL

Model	LGA50A-3R3-Y																																																					
Item	Efficiency (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V Input Volt. 100V Input Volt. 132V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>2</td><td>70.1</td><td>67.7</td><td>61.9</td></tr> <tr> <td>4</td><td>74.9</td><td>74.2</td><td>70.9</td></tr> <tr> <td>6</td><td>75.9</td><td>75.6</td><td>73.3</td></tr> <tr> <td>8</td><td>75.5</td><td>75.5</td><td>74.2</td></tr> <tr> <td>10</td><td>74.6</td><td>74.7</td><td>74.2</td></tr> <tr> <td>11</td><td>74.2</td><td>74.3</td><td>74.0</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	-	-	-	2	70.1	67.7	61.9	4	74.9	74.2	70.9	6	75.9	75.6	73.3	8	75.5	75.5	74.2	10	74.6	74.7	74.2	11	74.2	74.3	74.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	-	-	-																																																			
2	70.1	67.7	61.9																																																			
4	74.9	74.2	70.9																																																			
6	75.9	75.6	73.3																																																			
8	75.5	75.5	74.2																																																			
10	74.6	74.7	74.2																																																			
11	74.2	74.3	74.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	LGA50A-3R3-Y
Item	Power Factor (by Input Voltage)
Object	_____

1. Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.556	0.602
80	0.549	0.584
85	0.540	0.572
90	0.532	0.562
100	0.518	0.545
110	0.505	0.531
120	0.492	0.517
132	0.480	0.503
140	0.474	0.497

COSEL


Model	LGA50A-3R3-Y																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
Object	Testing Circuitry	Figure A																																																				
1.Graph	—▲— Input Volt. 85V - - □ - - Input Volt. 100V - - ○ - - Input Volt. 132V																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.354</td><td>0.338</td><td>0.329</td></tr> <tr> <td>2</td><td>0.481</td><td>0.460</td><td>0.428</td></tr> <tr> <td>4</td><td>0.533</td><td>0.507</td><td>0.469</td></tr> <tr> <td>6</td><td>0.557</td><td>0.532</td><td>0.495</td></tr> <tr> <td>8</td><td>0.570</td><td>0.545</td><td>0.507</td></tr> <tr> <td>10</td><td>0.580</td><td>0.556</td><td>0.514</td></tr> <tr> <td>11</td><td>0.582</td><td>0.558</td><td>0.516</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.354	0.338	0.329	2	0.481	0.460	0.428	4	0.533	0.507	0.469	6	0.557	0.532	0.495	8	0.570	0.545	0.507	10	0.580	0.556	0.514	11	0.582	0.558	0.516	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	0.354	0.338	0.329																																																			
2	0.481	0.460	0.428																																																			
4	0.533	0.507	0.469																																																			
6	0.557	0.532	0.495																																																			
8	0.570	0.545	0.507																																																			
10	0.580	0.556	0.514																																																			
11	0.582	0.558	0.516																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model LGA50A-3R3-Y


Item Inrush Current

Object

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]

Input Voltage	100 V
Frequency	60 Hz
Load	100 %

Primary inrush current 24.8 A





Model	LGA50A-3R3-Y	Temperature Testing Circuitry	25°C Figure B	
Item	Leakage Current			
Object	_____			

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 100 [V]	Input Volt. 120 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.18	0.20	0.24
(B)IEC60950-1	0.18	0.25	0.27

frequency 60Hz

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL


Model	LGA50A-3R3-Y																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+3.3V10A																																	
1.Graph																																		
		2.Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>3.327</td><td>3.325</td></tr> <tr> <td>80</td><td>3.327</td><td>3.325</td></tr> <tr> <td>85</td><td>3.327</td><td>3.325</td></tr> <tr> <td>90</td><td>3.327</td><td>3.325</td></tr> <tr> <td>100</td><td>3.327</td><td>3.325</td></tr> <tr> <td>110</td><td>3.327</td><td>3.325</td></tr> <tr> <td>120</td><td>3.327</td><td>3.325</td></tr> <tr> <td>132</td><td>3.327</td><td>3.325</td></tr> <tr> <td>140</td><td>3.327</td><td>3.325</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	3.327	3.325	80	3.327	3.325	85	3.327	3.325	90	3.327	3.325	100	3.327	3.325	110	3.327	3.325	120	3.327	3.325	132	3.327	3.325	140	3.327	3.325
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	3.327	3.325																																
80	3.327	3.325																																
85	3.327	3.325																																
90	3.327	3.325																																
100	3.327	3.325																																
110	3.327	3.325																																
120	3.327	3.325																																
132	3.327	3.325																																
140	3.327	3.325																																

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	LGA50A-3R3-Y																																																					
Item	Load Regulation																																																					
Object	+3.3V10A																																																					
1.Graph	—△— Input Volt. 85V - - □ - - Input Volt. 100V - - ○ - - Input Volt. 132V																																																					
Note:	Slanted line shows the range of the rated load current.																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values																																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.328</td><td>3.328</td><td>3.328</td></tr> <tr><td>2</td><td>3.327</td><td>3.327</td><td>3.327</td></tr> <tr><td>4</td><td>3.326</td><td>3.327</td><td>3.327</td></tr> <tr><td>6</td><td>3.326</td><td>3.326</td><td>3.326</td></tr> <tr><td>8</td><td>3.325</td><td>3.325</td><td>3.326</td></tr> <tr><td>10</td><td>3.324</td><td>3.324</td><td>3.324</td></tr> <tr><td>11</td><td>3.324</td><td>3.324</td><td>3.324</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	3.328	3.328	3.328	2	3.327	3.327	3.327	4	3.326	3.327	3.327	6	3.326	3.326	3.326	8	3.325	3.325	3.326	10	3.324	3.324	3.324	11	3.324	3.324	3.324	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	3.328	3.328	3.328																																																			
2	3.327	3.327	3.327																																																			
4	3.326	3.327	3.327																																																			
6	3.326	3.326	3.326																																																			
8	3.325	3.325	3.326																																																			
10	3.324	3.324	3.324																																																			
11	3.324	3.324	3.324																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



COSEL



COSEL

Model	LGA50A-3R3-Y																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+3.3V10A																																							
1. Graph																																								
		2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85V [mV]</th> <th>Input Volt. 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>2</td><td>15</td><td>15</td></tr> <tr><td>4</td><td>20</td><td>20</td></tr> <tr><td>6</td><td>20</td><td>20</td></tr> <tr><td>8</td><td>25</td><td>25</td></tr> <tr><td>10</td><td>25</td><td>25</td></tr> <tr><td>11</td><td>25</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85V [mV]	Input Volt. 132V [mV]	0	5	5	2	15	15	4	20	20	6	20	20	8	25	25	10	25	25	11	25	25	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85V [mV]	Input Volt. 132V [mV]																																						
0	5	5																																						
2	15	15																																						
4	20	20																																						
6	20	20																																						
8	25	25																																						
10	25	25																																						
11	25	25																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>T1: Due to AC Input Line T2: Due to Switching</p>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								


COSEL

Model	LGA50A-3R3-Y																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure C																																						
Object	+3.3V10A																																							
1. Graph																																								
<p style="text-align: center;"> —▲— Input Volt. 85V ---○--- Input Volt. 132V </p>  <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 85V)</th> <th>Ripple-Noise [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>10</td><td>15</td></tr> <tr><td>2</td><td>20</td><td>25</td></tr> <tr><td>4</td><td>25</td><td>30</td></tr> <tr><td>6</td><td>30</td><td>30</td></tr> <tr><td>8</td><td>35</td><td>35</td></tr> <tr><td>10</td><td>40</td><td>40</td></tr> <tr><td>11</td><td>45</td><td>45</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV] (Input Volt. 85V)	Ripple-Noise [mV] (Input Volt. 132V)	0	10	15	2	20	25	4	25	30	6	30	30	8	35	35	10	40	40	11	45	45															
Load Current [A]	Ripple-Noise [mV] (Input Volt. 85V)	Ripple-Noise [mV] (Input Volt. 132V)																																						
0	10	15																																						
2	20	25																																						
4	25	30																																						
6	30	30																																						
8	35	35																																						
10	40	40																																						
11	45	45																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>10</td><td>15</td></tr> <tr><td>2</td><td>20</td><td>25</td></tr> <tr><td>4</td><td>25</td><td>30</td></tr> <tr><td>6</td><td>30</td><td>30</td></tr> <tr><td>8</td><td>35</td><td>35</td></tr> <tr><td>10</td><td>40</td><td>40</td></tr> <tr><td>11</td><td>45</td><td>45</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0	10	15	2	20	25	4	25	30	6	30	30	8	35	35	10	40	40	11	45	45	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0	10	15																																						
2	20	25																																						
4	25	30																																						
6	30	30																																						
8	35	35																																						
10	40	40																																						
11	45	45																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>T1: Due to AC Input Line T2: Due to Switching</p> 																																								
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

<p>Model LGA50A-3R3-Y</p> <p>Item Ripple Voltage (by Ambient Temp.)</p> <p>Object +3.3V10A</p>	Testing Circuitry Figure C																							
	1.Graph	2.Values																						
	<p>Ambient Temperature [°C]</p> <p>Ripple Voltage [mV]</p> <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>120</td></tr> <tr><td>-10</td><td>60</td></tr> <tr><td>0</td><td>45</td></tr> <tr><td>25</td><td>30</td></tr> <tr><td>45</td><td>30</td></tr> <tr><td>50</td><td>30</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> <tr><td>--</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]	-30	120	-10	60	0	45	25	30	45	30	50	30	--	-	--	-	--	-	--	-	--
Ambient Temperature [°C]	Ripple Voltage [mV]																							
-30	120																							
-10	60																							
0	45																							
25	30																							
45	30																							
50	30																							
--	-																							
--	-																							
--	-																							
--	-																							
--	-																							
<p>Input Volt. 100V</p> <p>Input Load. 100%</p> <p>Measured by 20 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	<p>T1: Due to AC Input Line</p> <p>T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p> <p>Fig. Complex Ripple Wave Form</p>																							

COSEL

		Testing Circuitry Figure A																																																					
Model	LGA50A-3R3-Y																																																						
Item	Ambient Temperature Drift																																																						
Object	+3.3V10A																																																						
1.Graph	<p>—▲— Input Volt. 85V - - - □ - - Input Volt. 100V - - - ○ - - Input Volt. 132V</p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>3.324</td> <td>3.324</td> <td>3.325</td> </tr> <tr> <td>-10</td> <td>3.324</td> <td>3.325</td> <td>3.325</td> </tr> <tr> <td>0</td> <td>3.325</td> <td>3.325</td> <td>3.325</td> </tr> <tr> <td>10</td> <td>3.326</td> <td>3.326</td> <td>3.326</td> </tr> <tr> <td>20</td> <td>3.326</td> <td>3.326</td> <td>3.326</td> </tr> <tr> <td>25</td> <td>3.327</td> <td>3.327</td> <td>3.327</td> </tr> <tr> <td>30</td> <td>3.326</td> <td>3.327</td> <td>3.327</td> </tr> <tr> <td>40</td> <td>3.326</td> <td>3.326</td> <td>3.326</td> </tr> <tr> <td>50</td> <td>3.325</td> <td>3.326</td> <td>3.326</td> </tr> <tr> <td>60</td> <td>3.325</td> <td>3.325</td> <td>3.325</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	3.324	3.324	3.325	-10	3.324	3.325	3.325	0	3.325	3.325	3.325	10	3.326	3.326	3.326	20	3.326	3.326	3.326	25	3.327	3.327	3.327	30	3.326	3.327	3.327	40	3.326	3.326	3.326	50	3.325	3.326	3.326	60	3.325	3.325	3.325	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	3.324	3.324	3.325																																																				
-10	3.324	3.325	3.325																																																				
0	3.325	3.325	3.325																																																				
10	3.326	3.326	3.326																																																				
20	3.326	3.326	3.326																																																				
25	3.327	3.327	3.327																																																				
30	3.326	3.327	3.327																																																				
40	3.326	3.326	3.326																																																				
50	3.325	3.326	3.326																																																				
60	3.325	3.325	3.325																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated ambient temperature.



Model	LGA50A-3R3-Y	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V10A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 132V

Load Current : 0 - 10A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	40	85	0	3.330	± 3	± 0.1
Minimum Voltage	-10	85	10	3.324		

COSEL

Model	LGA50A-3R3-Y	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+3.3V10A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.325</td></tr> <tr><td>0.5</td><td>3.326</td></tr> <tr><td>1.0</td><td>3.326</td></tr> <tr><td>2.0</td><td>3.326</td></tr> <tr><td>3.0</td><td>3.326</td></tr> <tr><td>4.0</td><td>3.326</td></tr> <tr><td>5.0</td><td>3.326</td></tr> <tr><td>6.0</td><td>3.326</td></tr> <tr><td>7.0</td><td>3.326</td></tr> <tr><td>8.0</td><td>3.326</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	3.325	0.5	3.326	1.0	3.326	2.0	3.326	3.0	3.326	4.0	3.326	5.0	3.326	6.0	3.326	7.0	3.326	8.0	3.326
Time since start [H]	Output Voltage [V]																								
0.0	3.325																								
0.5	3.326																								
1.0	3.326																								
2.0	3.326																								
3.0	3.326																								
4.0	3.326																								
5.0	3.326																								
6.0	3.326																								
7.0	3.326																								
8.0	3.326																								

COSEL


Model LGA50A-3R3-Y

Item Rise and Fall Time

Temperature 25°C
Testing Circuitry Figure A

Object +3.3V10A


1. Graph



2. Values

[ms]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		67.0	9.8	76.8	76.0	5.3
100 %		66.8	9.8	76.6	35.2	2.7



COSEL

Model	LGA50A-3R3-Y																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+3.3V10A																																	
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>29</td><td>12</td></tr> <tr> <td>80</td><td>38</td><td>16</td></tr> <tr> <td>85</td><td>46</td><td>21</td></tr> <tr> <td>90</td><td>56</td><td>25</td></tr> <tr> <td>100</td><td>76</td><td>35</td></tr> <tr> <td>110</td><td>98</td><td>47</td></tr> <tr> <td>120</td><td>123</td><td>59</td></tr> <tr> <td>132</td><td>155</td><td>76</td></tr> <tr> <td>140</td><td>179</td><td>88</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	29	12	80	38	16	85	46	21	90	56	25	100	76	35	110	98	47	120	123	59	132	155	76	140	179	88	
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
75	29	12																																
80	38	16																																
85	46	21																																
90	56	25																																
100	76	35																																
110	98	47																																
120	123	59																																
132	155	76																																
140	179	88																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	LGA50A-3R3-Y																																																					
Item	Instantaneous Interruption Compensation																																																					
Object	+3.3V10A																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V Input Volt. 100V Input Volt. 132V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2</td><td>117</td><td>187</td><td>365</td></tr> <tr><td>4</td><td>57</td><td>97</td><td>196</td></tr> <tr><td>6</td><td>37</td><td>63</td><td>131</td></tr> <tr><td>8</td><td>27</td><td>46</td><td>97</td></tr> <tr><td>10</td><td>17</td><td>35</td><td>76</td></tr> <tr><td>11</td><td>17</td><td>28</td><td>68</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	-	-	-	2	117	187	365	4	57	97	196	6	37	63	131	8	27	46	97	10	17	35	76	11	17	28	68	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	-	-	-																																																			
2	117	187	365																																																			
4	57	97	196																																																			
6	37	63	131																																																			
8	27	46	97																																																			
10	17	35	76																																																			
11	17	28	68																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


COSEL

<p>Model LGA50A-3R3-Y</p> <p>Item Minimum Input Voltage for Regulated Output Voltage</p> <p>Object +3.3V10A</p>	Testing Circuitry Figure A																																						
	1.Graph	2.Values																																					
	<p style="text-align: center;">---□--- Load 50% —△— Load 100%</p> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>61</td><td>67</td></tr> <tr><td>-10</td><td>60</td><td>66</td></tr> <tr><td>0</td><td>59</td><td>66</td></tr> <tr><td>10</td><td>59</td><td>65</td></tr> <tr><td>20</td><td>59</td><td>65</td></tr> <tr><td>25</td><td>58</td><td>65</td></tr> <tr><td>30</td><td>58</td><td>64</td></tr> <tr><td>40</td><td>58</td><td>64</td></tr> <tr><td>50</td><td>58</td><td>64</td></tr> <tr><td>60</td><td>57</td><td>64</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	61	67	-10	60	66	0	59	66	10	59	65	20	59	65	25	58	65	30	58	64	40	58	64	50	58	64	60	57	64	--	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-20	61	67																																					
-10	60	66																																					
0	59	66																																					
10	59	65																																					
20	59	65																																					
25	58	65																																					
30	58	64																																					
40	58	64																																					
50	58	64																																					
60	57	64																																					
--	-	-																																					

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	LGA50A-3R3-Y
Item	Overcurrent Protection
Object	+3.3V10A



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 1.65V to 0V.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Output Voltage [V]	Load Current [A]		
	85[V]	100[V]	132[V]
3.30	10.52	10.68	10.69
3.14	14.14	14.18	14.45
2.97	14.20	14.25	14.52
2.64	14.28	14.37	14.67
2.31	14.42	14.51	14.93
1.98	14.52	14.59	15.30
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	LGA50A-3R3-Y
Item	Overvoltage Protection
Object	+3.3V10A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 85[V]	Input Volt. 132[V]
-20	4.84	4.84
-10	4.84	4.84
0	4.84	4.84
10	4.84	4.84
20	4.84	4.84
25	4.84	4.84
30	4.84	4.84
40	4.84	4.84
50	4.73	4.73
60	4.73	4.73
--	-	-

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)


COSEL

Figure C