



# TEST DATA OF LGA75A-5

Regulated DC Power Supply  
April 4, 2008

Approved by : Yoshiaki Shimizu Design Manager  
Yoshiaki Shimizu

Prepared by : Yousuke Murata Design Engineer  
Yousuke Murata

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ripple-Noise . . . . .	13
14. Ripple Voltage (by Ambient Temperature) . . . . .	14
15. Ambient Temperature Drift . . . . .	15
16. Output Voltage Accuracy . . . . .	16
17. Time Lapse Drift . . . . .	17
18. Rise and Fall Time . . . . .	18
19. Hold-Up Time . . . . .	19
20. Instantaneous Interruption Compensation . . . . .	20
21. Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22. Overcurrent Protection . . . . .	22
23. Overvoltage Protection . . . . .	23
24. Figure of Testing Circuitry . . . . .	24


(Final Page 25)

**COSEL**

Model LGA75A-5

Item Input Current (by Load Current)

Object \_\_\_\_\_



Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	0.063	0.062	0.065
3.0	0.467	0.413	0.351
6.0	0.822	0.727	0.604
9.0	1.193	1.057	0.869
12.0	1.566	1.387	1.137
15.0	1.951	1.723	1.403
16.5	2.144	1.891	1.541
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model LGA75A-5

Item Input Power (by Load Current)

Object \_\_\_\_\_

1.Graph

—△— Input Volt. 85V  
 - - -□--- Input Volt. 100V  
 - - -○--- Input Volt. 132V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	1.8	2.1	2.8
3.0	20.1	20.3	21.3
6.0	38.3	38.4	39.3
9.0	57.4	57.4	58.0
12.0	77.4	77.2	77.3
15.0	97.9	97.3	97.0
16.5	108.4	107.7	107.3
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

# COSEL

Model	LGA75A-5																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1.Graph																																		
		2.Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>81.1</td><td>78.4</td></tr> <tr><td>80</td><td>81.4</td><td>78.9</td></tr> <tr><td>85</td><td>81.5</td><td>79.2</td></tr> <tr><td>90</td><td>81.5</td><td>79.4</td></tr> <tr><td>100</td><td>81.3</td><td>79.7</td></tr> <tr><td>110</td><td>81.0</td><td>79.8</td></tr> <tr><td>120</td><td>80.6</td><td>79.9</td></tr> <tr><td>132</td><td>80.0</td><td>79.8</td></tr> <tr><td>140</td><td>79.6</td><td>79.7</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	81.1	78.4	80	81.4	78.9	85	81.5	79.2	90	81.5	79.4	100	81.3	79.7	110	81.0	79.8	120	80.6	79.9	132	80.0	79.8	140	79.6	79.7
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	81.1	78.4																																
80	81.4	78.9																																
85	81.5	79.2																																
90	81.5	79.4																																
100	81.3	79.7																																
110	81.0	79.8																																
120	80.6	79.9																																
132	80.0	79.8																																
140	79.6	79.7																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**

Model	LGA75A-5																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 85V ---□--- Input Volt. 100V ---○--- Input Volt. 132V</p>																																																					
<p>Efficiency [%] Load Current [A]</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>77.3</td><td>76.5</td><td>72.9</td></tr> <tr><td>6.0</td><td>81.0</td><td>80.8</td><td>79.1</td></tr> <tr><td>9.0</td><td>81.2</td><td>81.1</td><td>80.3</td></tr> <tr><td>12.0</td><td>80.2</td><td>80.4</td><td>80.3</td></tr> <tr><td>15.0</td><td>79.2</td><td>79.6</td><td>79.9</td></tr> <tr><td>16.5</td><td>78.5</td><td>79.1</td><td>79.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-	-	-	3.0	77.3	76.5	72.9	6.0	81.0	80.8	79.1	9.0	81.2	81.1	80.3	12.0	80.2	80.4	80.3	15.0	79.2	79.6	79.9	16.5	78.5	79.1	79.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	-	-	-																																																			
3.0	77.3	76.5	72.9																																																			
6.0	81.0	80.8	79.1																																																			
9.0	81.2	81.1	80.3																																																			
12.0	80.2	80.4	80.3																																																			
15.0	79.2	79.6	79.9																																																			
16.5	78.5	79.1	79.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	LGA75A-5																																
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object																																	
1.Graph																																	
		2.Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.568</td><td>0.612</td></tr> <tr><td>80</td><td>0.560</td><td>0.598</td></tr> <tr><td>85</td><td>0.552</td><td>0.589</td></tr> <tr><td>90</td><td>0.545</td><td>0.579</td></tr> <tr><td>100</td><td>0.530</td><td>0.562</td></tr> <tr><td>110</td><td>0.518</td><td>0.548</td></tr> <tr><td>120</td><td>0.508</td><td>0.535</td></tr> <tr><td>132</td><td>0.496</td><td>0.521</td></tr> <tr><td>140</td><td>0.488</td><td>0.513</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.568	0.612	80	0.560	0.598	85	0.552	0.589	90	0.545	0.579	100	0.530	0.562	110	0.518	0.548	120	0.508	0.535	132	0.496	0.521	140	0.488	0.513
Input Voltage [V]	Power Factor																																
	Load 50%	Load 100%																															
75	0.568	0.612																															
80	0.560	0.598																															
85	0.552	0.589																															
90	0.545	0.579																															
100	0.530	0.562																															
110	0.518	0.548																															
120	0.508	0.535																															
132	0.496	0.521																															
140	0.488	0.513																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	

COSEL

Model	LGA75A-5																																																					
Item	Power Factor (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul>																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.333</td><td>0.334</td><td>0.322</td></tr> <tr><td>3.0</td><td>0.505</td><td>0.492</td><td>0.459</td></tr> <tr><td>6.0</td><td>0.547</td><td>0.527</td><td>0.491</td></tr> <tr><td>9.0</td><td>0.564</td><td>0.542</td><td>0.504</td></tr> <tr><td>12.0</td><td>0.580</td><td>0.555</td><td>0.514</td></tr> <tr><td>15.0</td><td>0.589</td><td>0.564</td><td>0.522</td></tr> <tr><td>16.5</td><td>0.594</td><td>0.568</td><td>0.527</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.333	0.334	0.322	3.0	0.505	0.492	0.459	6.0	0.547	0.527	0.491	9.0	0.564	0.542	0.504	12.0	0.580	0.555	0.514	15.0	0.589	0.564	0.522	16.5	0.594	0.568	0.527	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	0.333	0.334	0.322																																																			
3.0	0.505	0.492	0.459																																																			
6.0	0.547	0.527	0.491																																																			
9.0	0.564	0.542	0.504																																																			
12.0	0.580	0.555	0.514																																																			
15.0	0.589	0.564	0.522																																																			
16.5	0.594	0.568	0.527																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model LGA75A-5

Temperature 25°C  
Testing Circuitry Figure A

Item Inrush Current

Object

Input  
Current  
[20A/div]Input  
Voltage  
[100V/div]

Time [50ms/div]


Input Voltage 100 V

Frequency 60 Hz

Load 100 %

Primary inrush current 25.3 A

Secondary inrush current 3.9 A





Model	LGA75A-5	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 100 [V]	Input Volt. 120 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.08	0.10	0.12
(B)IEC60950	0.09	0.11	0.12

frequency 60Hz

Standards	Leakage Current [mA]		
	Input Volt. [V]	Input Volt. [V]	Input Volt. [V]
(B)IEC60950	-	-	-

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	LGA75A-5																																	
Item	Line Regulation	Temperature      25°C Testing Circuitry      Figure A																																
Object	+5V15A																																	
1. Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>5.172</td> <td>5.165</td> </tr> <tr> <td>80</td> <td>5.172</td> <td>5.166</td> </tr> <tr> <td>85</td> <td>5.172</td> <td>5.166</td> </tr> <tr> <td>90</td> <td>5.172</td> <td>5.166</td> </tr> <tr> <td>100</td> <td>5.171</td> <td>5.166</td> </tr> <tr> <td>110</td> <td>5.171</td> <td>5.166</td> </tr> <tr> <td>120</td> <td>5.171</td> <td>5.165</td> </tr> <tr> <td>132</td> <td>5.171</td> <td>5.165</td> </tr> <tr> <td>140</td> <td>5.171</td> <td>5.165</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	5.172	5.165	80	5.172	5.166	85	5.172	5.166	90	5.172	5.166	100	5.171	5.166	110	5.171	5.166	120	5.171	5.165	132	5.171	5.165	140	5.171	5.165
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	5.172	5.165																																
80	5.172	5.166																																
85	5.172	5.166																																
90	5.172	5.166																																
100	5.171	5.166																																
110	5.171	5.166																																
120	5.171	5.165																																
132	5.171	5.165																																
140	5.171	5.165																																

**COSEL**


Model LGA75A-5

Item Load Regulation

Object +5V15A

1.Graph

—△— Input Volt. 85V  
 - - -□--- Input Volt. 100V  
 - - ○--- Input Volt. 132V




Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
 Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	5.179	5.178	5.177
3.0	5.175	5.175	5.174
6.0	5.173	5.172	5.172
9.0	5.171	5.170	5.170
12.0	5.168	5.168	5.168
15.0	5.166	5.166	5.166
16.5	5.165	5.165	5.165
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

**COSEL**

Model	LGA75A-5																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+5V15A																																							
1.Graph																																								
<p>—△— Input Volt. 85V ---○--- Input Volt. 132V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (85V)</th> <th>Ripple Voltage [mV] (132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>3.0</td><td>20</td><td>20</td></tr> <tr><td>6.0</td><td>25</td><td>20</td></tr> <tr><td>9.0</td><td>30</td><td>20</td></tr> <tr><td>12.0</td><td>35</td><td>20</td></tr> <tr><td>15.0</td><td>40</td><td>20</td></tr> <tr><td>16.5</td><td>45</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (85V)	Ripple Voltage [mV] (132V)	0.0	10	10	3.0	20	20	6.0	25	20	9.0	30	20	12.0	35	20	15.0	40	20	16.5	45	25	--	-	-	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (85V)	Ripple Voltage [mV] (132V)																																						
0.0	10	10																																						
3.0	20	20																																						
6.0	25	20																																						
9.0	30	20																																						
12.0	35	20																																						
15.0	40	20																																						
16.5	45	25																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>3.0</td><td>20</td><td>20</td></tr> <tr><td>6.0</td><td>25</td><td>20</td></tr> <tr><td>9.0</td><td>30</td><td>20</td></tr> <tr><td>12.0</td><td>35</td><td>20</td></tr> <tr><td>15.0</td><td>40</td><td>20</td></tr> <tr><td>16.5</td><td>45</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	3.0	20	20	6.0	25	20	9.0	30	20	12.0	35	20	15.0	40	20	16.5	45	25	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	10	10																																						
3.0	20	20																																						
6.0	25	20																																						
9.0	30	20																																						
12.0	35	20																																						
15.0	40	20																																						
16.5	45	25																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																																								


**COSEL**

Model	LGA75A-5																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure C																																						
Object	+5V15A																																							
1.Graph																																								
<p>—▲— Input Volt. 85V -○--- Input Volt. 132V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (85V)</th> <th>Ripple-Noise [mV] (132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>3.0</td><td>40</td><td>50</td></tr> <tr><td>6.0</td><td>50</td><td>70</td></tr> <tr><td>9.0</td><td>60</td><td>70</td></tr> <tr><td>12.0</td><td>65</td><td>75</td></tr> <tr><td>15.0</td><td>75</td><td>80</td></tr> <tr><td>16.5</td><td>80</td><td>95</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV] (85V)	Ripple-Noise [mV] (132V)	0.0	10	10	3.0	40	50	6.0	50	70	9.0	60	70	12.0	65	75	15.0	75	80	16.5	80	95	--	-	-	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple-Noise [mV] (85V)	Ripple-Noise [mV] (132V)																																						
0.0	10	10																																						
3.0	40	50																																						
6.0	50	70																																						
9.0	60	70																																						
12.0	65	75																																						
15.0	75	80																																						
16.5	80	95																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>3.0</td><td>40</td><td>50</td></tr> <tr><td>6.0</td><td>50</td><td>70</td></tr> <tr><td>9.0</td><td>60</td><td>70</td></tr> <tr><td>12.0</td><td>65</td><td>75</td></tr> <tr><td>15.0</td><td>75</td><td>80</td></tr> <tr><td>16.5</td><td>80</td><td>95</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	3.0	40	50	6.0	50	70	9.0	60	70	12.0	65	75	15.0	75	80	16.5	80	95	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	10	10																																						
3.0	40	50																																						
6.0	50	70																																						
9.0	60	70																																						
12.0	65	75																																						
15.0	75	80																																						
16.5	80	95																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple-Noise [mVp-p]</p> <p>T1</p> <p>T2</p>																																								
Fig. Complex Ripple Wave Form																																								

**COSEL**

Model	LGA75A-5
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V15A

## 1. Graph



Input Volt. 100V  
Input Load. 100%

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

T1: Due to AC Input Line  
T2: Due to Switching





Fig. Complex Ripple Wave Form

Testing Circuitry FigureC

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]
-30	105
-10	45
0	40
25	30
50	30
-	-
-	-
-	-
-	-
-	-
-	-
-	-

**COSEL**

Model	LGA75A-5																																																					
Item	Ambient Temperature Drift																																																					
Object	+5V15A																																																					
1.Graph	—△— Input Volt. 85V - - □ - - Input Volt. 100V - · ○ - - Input Volt. 132V																																																					
	 <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					
	Testing Circuitry Figure A																																																					
	2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>5.158</td> <td>5.158</td> <td>5.159</td> </tr> <tr> <td>-10</td> <td>5.159</td> <td>5.160</td> <td>5.160</td> </tr> <tr> <td>0</td> <td>5.160</td> <td>5.161</td> <td>5.161</td> </tr> <tr> <td>10</td> <td>5.162</td> <td>5.162</td> <td>5.162</td> </tr> <tr> <td>20</td> <td>5.163</td> <td>5.163</td> <td>5.163</td> </tr> <tr> <td>25</td> <td>5.163</td> <td>5.164</td> <td>5.164</td> </tr> <tr> <td>30</td> <td>5.164</td> <td>5.164</td> <td>5.164</td> </tr> <tr> <td>40</td> <td>5.164</td> <td>5.165</td> <td>5.165</td> </tr> <tr> <td>50</td> <td>5.164</td> <td>5.165</td> <td>5.165</td> </tr> <tr> <td>60</td> <td>5.164</td> <td>5.164</td> <td>5.164</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	5.158	5.158	5.159	-10	5.159	5.160	5.160	0	5.160	5.161	5.161	10	5.162	5.162	5.162	20	5.163	5.163	5.163	25	5.163	5.164	5.164	30	5.164	5.164	5.164	40	5.164	5.165	5.165	50	5.164	5.165	5.165	60	5.164	5.164	5.164	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	5.158	5.158	5.159																																																			
-10	5.159	5.160	5.160																																																			
0	5.160	5.161	5.161																																																			
10	5.162	5.162	5.162																																																			
20	5.163	5.163	5.163																																																			
25	5.163	5.164	5.164																																																			
30	5.164	5.164	5.164																																																			
40	5.164	5.165	5.165																																																			
50	5.164	5.165	5.165																																																			
60	5.164	5.164	5.164																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated ambient temperature.



Model	LGA75A-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V15A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 132V

Load Current : 0 - 15A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	40	85	0	5.177	$\pm 9$	$\pm 0.2$
Minimum Voltage	-10	85	15	5.159		


**COSEL**

Model	LGA75A-5	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift																								
Object	+5V15A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.167</td></tr> <tr><td>0.5</td><td>5.165</td></tr> <tr><td>1.0</td><td>5.165</td></tr> <tr><td>2.0</td><td>5.166</td></tr> <tr><td>3.0</td><td>5.166</td></tr> <tr><td>4.0</td><td>5.166</td></tr> <tr><td>5.0</td><td>5.166</td></tr> <tr><td>6.0</td><td>5.166</td></tr> <tr><td>7.0</td><td>5.166</td></tr> <tr><td>8.0</td><td>5.166</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.167	0.5	5.165	1.0	5.165	2.0	5.166	3.0	5.166	4.0	5.166	5.0	5.166	6.0	5.166	7.0	5.166	8.0	5.166
Time since start [H]	Output Voltage [V]																								
0.0	5.167																								
0.5	5.165																								
1.0	5.165																								
2.0	5.166																								
3.0	5.166																								
4.0	5.166																								
5.0	5.166																								
6.0	5.166																								
7.0	5.166																								
8.0	5.166																								

**COSEL**


Model	LGA75A-5	Temperature Testing Circuitry	25°C Figure A
Item	Rise and Fall Time		
Object	+5V15A		

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		68.8	3.3	72.1	51.6	5.8	
100 %		67.8	4.5	72.3	24.0	3.0	




**COSEL**

Model	LGA75A-5
Item	Hold-Up Time
Object	+5V15A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	19	7
80	25	10
85	31	13
90	37	16
100	52	23
110	68	31
120	85	40
132	109	51
140	126	60

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.


# COSEL

Model LGA75A-5

Item Instantaneous Interruption Compensation

Object +5V15A

1. Graph



Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A


2. Values

Load Current [A]	Time [ms]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	-	-	-
3.0	80	123	239
6.0	39	64	138
9.0	26	44	89
12.0	18	31	64
15.0	13	22	53
16.5	12	21	47
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	LGA75A-5
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V15A

## 1.Graph



Note: Slanted line shows the range of the rated ambient temperature.


## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	60	66
-10	59	66
0	59	66
10	59	65
20	58	65
25	58	65
30	58	65
40	58	65
50	58	65
60	57	64
—	-	-

**COSEL**

Model	LGA75A-5
Item	Overcurrent Protection
Object	+5V15A



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 3V to 0V.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
5.00	17.86	17.72	17.75
4.75	17.90	17.81	17.88
4.50	17.96	17.88	17.97
4.00	18.09	18.04	18.18
3.50	18.23	18.21	18.40
3.00	18.36	18.37	18.63
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	LGA75A-5
Item	Ovvoltage Protection
Object	+5V15A
1.Graph	
<p>The graph plots the operating point voltage (Y-axis, 5.0 to 7.0 V) against ambient temperature (X-axis, -40 to 80 °C). Three curves are shown for input voltages of 85V, 100V, and 132V. The 85V curve starts at ~6.46V at -20°C and remains flat until ~40°C, then drops to ~6.44V at 60°C. The 100V curve follows a similar path but stays slightly higher (~6.47V). The 132V curve is the highest (~6.5V). A slanted line from approximately (-20, 6.46) to (60, 6.44) represents the rated ambient temperature range.</p>	
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>	
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>	

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	6.46	6.46	6.46
-10	6.47	6.47	6.47
0	6.47	6.47	6.47
10	6.47	6.47	6.47
20	6.47	6.47	6.47
25	6.47	6.47	6.47
30	6.47	6.47	6.47
40	6.47	6.47	6.46
50	6.46	6.46	6.46
60	6.46	6.46	6.40
--	-	-	-

COSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 -1)


**COSEL**

Figure C