



# TEST DATA OF LHA100F-12

Regulated DC Power Supply  
September 4, 2019

Approved by : Junya Kaneda  
Junya Kaneda Design Manager

Prepared by : Shuto Takai  
Shuto Takai Design Engineer

**COSEL CO.,LTD.**




## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Efficiency (by Load Current) . . . . .	2
3.Power Factor (by Load Current) . . . . .	3
4.Inrush Current . . . . .	4
5.Leakage Current . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple-Noise (by Load Current) . . . . .	9
10.Ambient Temperature Drift . . . . .	10
11.Rise and Fall Time . . . . .	11
12.Hold-Up Time . . . . .	12
13.Instantaneous Interruption Compensation . . . . .	13
14.Minimum Input Voltage for Regulated Output Voltage . . . . .	14
15.Overcurrent Protection . . . . .	15
16.Overvoltage Protection . . . . .	16
17.Figure of Testing Circuitry . . . . .	17

(Final Page 18)

**COSEL**

Model	LHA100F-12
Item	Input Current (by Load Current)
Object	_____


 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.052	0.088	0.102
1.60	0.257	0.194	0.193
3.20	0.474	0.291	0.280
4.80	0.690	0.391	0.367
6.40	0.908	0.495	0.455
8.50	1.207	0.633	0.576
9.35	1.331	0.691	0.626
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**




Model	LHA100F-12																																																					
Item	Efficiency (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Load Current [A] on the x-axis (0 to 10). Three data series are shown for different input voltages: 100V (solid line with open triangle markers), 200V (dashed line with open square markers), and 230V (dash-dot line with open circle markers). All three curves show efficiency increasing slightly with load current. A slanted line is drawn across the graph, starting from approximately (1.6, 84) and ending at (9.35, 87), indicating the range of the rated load current.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>1.60</td><td>84.0</td><td>82.6</td><td>81.0</td></tr> <tr> <td>3.20</td><td>86.3</td><td>87.2</td><td>86.7</td></tr> <tr> <td>4.80</td><td>87.2</td><td>88.7</td><td>88.6</td></tr> <tr> <td>6.40</td><td>87.6</td><td>89.2</td><td>89.4</td></tr> <tr> <td>8.50</td><td>87.3</td><td>89.3</td><td>89.4</td></tr> <tr> <td>9.35</td><td>87.0</td><td>89.2</td><td>89.3</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	1.60	84.0	82.6	81.0	3.20	86.3	87.2	86.7	4.80	87.2	88.7	88.6	6.40	87.6	89.2	89.4	8.50	87.3	89.3	89.4	9.35	87.0	89.2	89.3	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
1.60	84.0	82.6	81.0																																																			
3.20	86.3	87.2	86.7																																																			
4.80	87.2	88.7	88.6																																																			
6.40	87.6	89.2	89.4																																																			
8.50	87.3	89.3	89.4																																																			
9.35	87.0	89.2	89.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	LHA100F-12																																																					
Item	Power Factor (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____																																																					
1.Graph																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th><th colspan="3">Power Factor</th></tr> <tr> <th>Input Volt. 100[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 230[V]</th></tr> </thead> <tbody> <tr><td>0.00</td><td>0.245</td><td>0.073</td><td>0.063</td></tr> <tr><td>1.60</td><td>0.907</td><td>0.619</td><td>0.552</td></tr> <tr><td>3.20</td><td>0.952</td><td>0.774</td><td>0.705</td></tr> <tr><td>4.80</td><td>0.968</td><td>0.846</td><td>0.788</td></tr> <tr><td>6.40</td><td>0.975</td><td>0.882</td><td>0.836</td></tr> <tr><td>8.50</td><td>0.978</td><td>0.913</td><td>0.874</td></tr> <tr><td>9.35</td><td>0.980</td><td>0.920</td><td>0.885</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.245	0.073	0.063	1.60	0.907	0.619	0.552	3.20	0.952	0.774	0.705	4.80	0.968	0.846	0.788	6.40	0.975	0.882	0.836	8.50	0.978	0.913	0.874	9.35	0.980	0.920	0.885	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.245	0.073	0.063																																																			
1.60	0.907	0.619	0.552																																																			
3.20	0.952	0.774	0.705																																																			
4.80	0.968	0.846	0.788																																																			
6.40	0.975	0.882	0.836																																																			
8.50	0.978	0.913	0.874																																																			
9.35	0.980	0.920	0.885																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	LHA100F-12	Temperature Testing Circuitry Figure A
Item	Inrush Current	
Object	_____	





Model	LHA100F-12	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	<hr/>		

### 1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure B-1	Both phases	0.16	0.33	0.34	Operation
		One of phases	0.25	0.65	0.67	Stand by
IEC62368-1	Figure B-2	Both phases	0.11	0.26	0.27	Operation
		One of phases	0.20	0.52	0.54	Stand by
	Figure B-3	Both phases	0.10	0.26	0.27	Operation
		One of phases	0.20	0.52	0.55	Stand by

The value for "One of phases" is the reference value only.

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	LHA100F-12
Item	Line Regulation
Object	+12V8.5A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	12.097	-
90	12.097	12.096
100	12.097	12.097
120	12.097	12.097
200	12.097	12.097
230	12.097	12.097
264	12.097	12.097
280	12.097	12.097
--	-	-

Note: Slanted line shows the range of the rated input voltage.


**COSEL**

Model	LHA100F-12																																																					
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+12V8.5A																																																					
1.Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 100V  <span style="color: black;">---□---</span> Input Volt. 200V  <span style="color: black;">---○---</span> Input Volt. 230V         </p> 	2.Values																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.103</td><td>12.093</td><td>12.115</td></tr> <tr><td>1.60</td><td>12.101</td><td>12.101</td><td>12.101</td></tr> <tr><td>3.20</td><td>12.100</td><td>12.100</td><td>12.100</td></tr> <tr><td>4.80</td><td>12.099</td><td>12.099</td><td>12.099</td></tr> <tr><td>6.40</td><td>12.098</td><td>12.098</td><td>12.098</td></tr> <tr><td>8.50</td><td>12.097</td><td>12.097</td><td>12.096</td></tr> <tr><td>9.35</td><td>12.096</td><td>12.096</td><td>12.095</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	12.103	12.093	12.115	1.60	12.101	12.101	12.101	3.20	12.100	12.100	12.100	4.80	12.099	12.099	12.099	6.40	12.098	12.098	12.098	8.50	12.097	12.097	12.096	9.35	12.096	12.096	12.095	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	12.103	12.093	12.115																																																			
1.60	12.101	12.101	12.101																																																			
3.20	12.100	12.100	12.100																																																			
4.80	12.099	12.099	12.099																																																			
6.40	12.098	12.098	12.098																																																			
8.50	12.097	12.097	12.096																																																			
9.35	12.096	12.096	12.095																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						


**COSEL**

Model	LHA100F-12	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V8.5A		


Input Volt. 12 V  
 Cycle 1000 ms



Min.Load (0A)↔  
 Load 50% (4.25A)



Load 50% (4.25A)↔  
 Load 100% (8.5A)




# COSEL

Model	LHA100F-12
Item	Ripple-Noise (by Load Current)
Object	+12V8.5A

Temperature 25°C  
Testing Circuitry Figure C

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.00	185	185
1.60	30	30
3.20	35	35
4.80	40	40
6.40	45	45
8.50	50	50
9.35	55	55
--	-	-
--	-	-
--	-	-
--	-	-

T1: Due to AC Input Line  
T2: Due to Switching





Fig. Complex Ripple Wave Form

**COSEL**

Model	LHA100F-12
Item	Ambient Temperature Drift
Object	+12V8.5A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	12.055	12.055	12.056
-15	12.062	12.062	12.062
-10	12.067	12.068	12.068
0	12.078	12.078	12.079
25	12.098	12.098	12.098
40	12.106	12.106	12.106
50	12.109	12.109	12.109
60	12.110	12.110	12.110
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	LHA100F-12
Item	Rise and Fall Time
Object	+12V8.5A

Temperature  
Testing Circuitry      25°C  
Figure A


## 1. Graph



## 2. Values

[ms]

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		93.5	7.0	100.5	21.8	2.8
230 V		81.5	7.0	88.5	21.8	2.8




**COSEL**

Model	LHA100F-12
Item	Hold-Up Time
Object	+12V8.5A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	44	-
90	44	22
100	44	22
120	44	22
200	44	22
230	44	22
264	44	22
280	44	22
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	LHA100F-12																																																					
Item	Instantaneous Interruption Compensation																																																					
Object	+12V8.5A																																																					
1.Graph																																																						
<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>																																																						
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						
Temperature 25°C		Testing Circuitry Figure A																																																				
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>1.60</td><td>106</td><td>113</td><td>114</td></tr> <tr> <td>3.20</td><td>31</td><td>55</td><td>56</td></tr> <tr> <td>4.80</td><td>31</td><td>38</td><td>38</td></tr> <tr> <td>6.40</td><td>28</td><td>28</td><td>29</td></tr> <tr> <td>8.50</td><td>21</td><td>21</td><td>21</td></tr> <tr> <td>9.35</td><td>14</td><td>14</td><td>15</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	1.60	106	113	114	3.20	31	55	56	4.80	31	38	38	6.40	28	28	29	8.50	21	21	21	9.35	14	14	15	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
1.60	106	113	114																																																			
3.20	31	55	56																																																			
4.80	31	38	38																																																			
6.40	28	28	29																																																			
8.50	21	21	21																																																			
9.35	14	14	15																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

**COSEL**

Model	LHA100F-12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V8.5A

Testing Circuitry Figure A

## 1. Graph



## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	64	65
-15	64	65
-10	64	65
0	64	65
25	64	65
40	64	65
50	64	65
60	64	65
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	LHA100F-12
Item	Overcurrent Protection
Object	+12V8.5A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



Note: Slanted line shows the range of the rated load current.

Overcurrent protection is Hiccup mode.

## 2.Values


Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
12.0	10.29	10.29
11.4	-	-
10.8	-	-
9.6	-	-
8.4	-	-
7.2	-	-
6.0	-	-
4.8	-	-
3.6	-	-
2.4	-	-
1.2	-	-
0.0	-	-

**COSEL**

Model	LHA100F-12
Item	Overvoltage Protection
Object	+12V8.5A

## Testing Circuitry Figure A

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	14.98	14.91
-15	14.98	14.98
-10	15.05	15.05
0	15.12	15.12
25	15.33	15.33
40	15.47	15.47
50	15.54	15.54
60	15.68	15.68
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B-1 (DEN-AN)




Figure B-2 (IEC62368-1 refer to IEC60990 Fig.4)





Figure B-3 ( IEC62368-1 refer to IEC60990 Fig.5 )



$$C1 = 0.1 \mu\text{F}$$

( Film capacitor)

$$C2 = 22 \mu\text{F}$$

(Electrolytic capacitor)

Figure C