

TEST DATA OF LHA100F-5

Regulated DC Power Supply
September 9, 2019

Approved by : Junya Kaneda
Junya Kaneda Design Manager

Prepared by : Shuto Takai
Shuto Takai Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Load Current)	1
2. Efficiency (by Load Current)	2
3. Power Factor (by Load Current)	3
4. Inrush Current	4
5. Leakage Current	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple-Noise (by Load Current)	9
10. Ambient Temperature Drift	10
11. Rise and Fall Time	11
12. Hold-Up Time	12
13. Instantaneous Interruption Compensation	13
14. Minimum Input Voltage for Regulated Output Voltage	14
15. Overcurrent Protection	15
16. Overvoltage Protection	16
17. Figure of Testing Circuitry	17

(Final Page 18)



Model		LHA100F-5		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 100V</p> <p>- - - □ - - Input Volt. 200V</p> <p>- · - ○ - · - Input Volt. 230V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.052</td><td>0.090</td><td>0.102</td></tr> <tr><td>3.0</td><td>0.219</td><td>0.176</td><td>0.177</td></tr> <tr><td>6.0</td><td>0.396</td><td>0.255</td><td>0.248</td></tr> <tr><td>9.0</td><td>0.570</td><td>0.335</td><td>0.319</td></tr> <tr><td>12.0</td><td>0.751</td><td>0.420</td><td>0.391</td></tr> <tr><td>15.0</td><td>0.943</td><td>0.511</td><td>0.469</td></tr> <tr><td>16.5</td><td>1.044</td><td>0.557</td><td>0.510</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.052	0.090	0.102	3.0	0.219	0.176	0.177	6.0	0.396	0.255	0.248	9.0	0.570	0.335	0.319	12.0	0.751	0.420	0.391	15.0	0.943	0.511	0.469	16.5	1.044	0.557	0.510	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Input Current [A]																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	0.052	0.090	0.102																																																					
3.0	0.219	0.176	0.177																																																					
6.0	0.396	0.255	0.248																																																					
9.0	0.570	0.335	0.319																																																					
12.0	0.751	0.420	0.391																																																					
15.0	0.943	0.511	0.469																																																					
16.5	1.044	0.557	0.510																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								






<p>Model LHA100F-5</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item</p>	<p>Efficiency (by Load Current)</p>																																																				
<p>Object</p>	<p>_____</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>79.0</td><td>77.2</td><td>75.3</td></tr> <tr><td>6.0</td><td>81.9</td><td>82.5</td><td>81.6</td></tr> <tr><td>9.0</td><td>83.1</td><td>84.3</td><td>84.0</td></tr> <tr><td>12.0</td><td>83.1</td><td>84.6</td><td>84.6</td></tr> <tr><td>15.0</td><td>82.2</td><td>83.9</td><td>84.1</td></tr> <tr><td>16.5</td><td>81.8</td><td>83.4</td><td>83.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	3.0	79.0	77.2	75.3	6.0	81.9	82.5	81.6	9.0	83.1	84.3	84.0	12.0	83.1	84.6	84.6	15.0	82.2	83.9	84.1	16.5	81.8	83.4	83.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
3.0	79.0	77.2	75.3																																																		
6.0	81.9	82.5	81.6																																																		
9.0	83.1	84.3	84.0																																																		
12.0	83.1	84.6	84.6																																																		
15.0	82.2	83.9	84.1																																																		
16.5	81.8	83.4	83.6																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V - · - ○ - · - - Input Volt. 230V </p> <p> Note: Slanted line shows the range of the rated load current. </p>																																																					



<p>Model LHA100F-5</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Power Factor (by Load Current)																																																				
Object	<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V ···○··· Input Volt. 230V </p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.250</td><td>0.075</td><td>0.063</td></tr> <tr><td>3.0</td><td>0.875</td><td>0.559</td><td>0.495</td></tr> <tr><td>6.0</td><td>0.933</td><td>0.720</td><td>0.650</td></tr> <tr><td>9.0</td><td>0.959</td><td>0.804</td><td>0.738</td></tr> <tr><td>12.0</td><td>0.969</td><td>0.853</td><td>0.795</td></tr> <tr><td>15.0</td><td>0.975</td><td>0.882</td><td>0.835</td></tr> <tr><td>16.5</td><td>0.975</td><td>0.894</td><td>0.848</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.250	0.075	0.063	3.0	0.875	0.559	0.495	6.0	0.933	0.720	0.650	9.0	0.959	0.804	0.738	12.0	0.969	0.853	0.795	15.0	0.975	0.882	0.835	16.5	0.975	0.894	0.848	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	0.250	0.075	0.063																																																		
3.0	0.875	0.559	0.495																																																		
6.0	0.933	0.720	0.650																																																		
9.0	0.959	0.804	0.738																																																		
12.0	0.969	0.853	0.795																																																		
15.0	0.975	0.882	0.835																																																		
16.5	0.975	0.894	0.848																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model		LHA100F-5	Temperature 25°C Testing Circuitry Figure A
Item		Inrush Current	
Object		_____	





COSEL		Temperature 25°C Testing Circuitry Figure B
Model	LHA100F-5	
Item	Leakage Current	
Object	_____	

1.Results

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure B-1	Both phases	0.16	0.33	0.34	Operation
		One of phases	0.25	0.65	0.67	Stand by
IEC62368-1	Figure B-2	Both phases	0.11	0.26	0.27	Operation
		One of phases	0.20	0.52	0.54	Stand by
	Figure B-3	Both phases	0.10	0.26	0.27	Operation
		One of phases	0.20	0.52	0.55	Stand by

The value for "One of phases" is the reference value only.

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



COSEL																																			
Model	LHA100F-5	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+5V15A																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>5.043</td><td>-</td></tr> <tr><td>90</td><td>5.043</td><td>5.041</td></tr> <tr><td>100</td><td>5.043</td><td>5.041</td></tr> <tr><td>120</td><td>5.043</td><td>5.041</td></tr> <tr><td>200</td><td>5.043</td><td>5.041</td></tr> <tr><td>230</td><td>5.043</td><td>5.041</td></tr> <tr><td>264</td><td>5.043</td><td>5.041</td></tr> <tr><td>280</td><td>5.043</td><td>5.041</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	5.043	-	90	5.043	5.041	100	5.043	5.041	120	5.043	5.041	200	5.043	5.041	230	5.043	5.041	264	5.043	5.041	280	5.043	5.041	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	5.043	-																																	
90	5.043	5.041																																	
100	5.043	5.041																																	
120	5.043	5.041																																	
200	5.043	5.041																																	
230	5.043	5.041																																	
264	5.043	5.041																																	
280	5.043	5.041																																	
--	-	-																																	




<p>Model LHA100F-5</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Load Regulation</p>																																																					
<p>Object +5V15A</p>																																																					
<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V ···○··· Input Volt. 230V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.047</td><td>5.047</td><td>5.046</td></tr> <tr><td>3.0</td><td>5.046</td><td>5.046</td><td>5.046</td></tr> <tr><td>6.0</td><td>5.045</td><td>5.045</td><td>5.045</td></tr> <tr><td>9.0</td><td>5.044</td><td>5.044</td><td>5.044</td></tr> <tr><td>12.0</td><td>5.043</td><td>5.043</td><td>5.042</td></tr> <tr><td>15.0</td><td>5.041</td><td>5.041</td><td>5.041</td></tr> <tr><td>16.5</td><td>5.038</td><td>5.038</td><td>5.038</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	5.047	5.047	5.046	3.0	5.046	5.046	5.046	6.0	5.045	5.045	5.045	9.0	5.044	5.044	5.044	12.0	5.043	5.043	5.042	15.0	5.041	5.041	5.041	16.5	5.038	5.038	5.038	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	5.047	5.047	5.046																																																		
3.0	5.046	5.046	5.046																																																		
6.0	5.045	5.045	5.045																																																		
9.0	5.044	5.044	5.044																																																		
12.0	5.043	5.043	5.042																																																		
15.0	5.041	5.041	5.041																																																		
16.5	5.038	5.038	5.038																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					




Model	LHA100F-5	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+5V15A		

Input Volt. 230 V
Cycle 1000 ms




Min. Load (0A) ←→
Load 100% (15A)

200 mV/div




1 ms/div




10 ms/div

Min. Load (0A) ←→
Load 50% (7.5A)

200 mV/div




1 ms/div




10 ms/div

Load 50% (7.5A) ←→
Load 100% (15A)

200 mV/div



1 ms/div




10 ms/div



Model	LHA100F-5	Temperature	25°C
Item	Ripple-Noise (by Load Current)	Testing Circuitry	Figure C
Object	+5V15A		

1.Graph



Measured by 20 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.0	90	90
3.0	40	40
6.0	55	55
9.0	50	50
12.0	40	40
15.0	60	60
16.5	70	70
--	-	-
--	-	-
--	-	-
--	-	-





Fig. Complex Ripple Wave Form



Model	LHA100F-5
Item	Ambient Temperature Drift
Object	+5V15A

Testing Circuitry Figure A

- 1.Graph
- △— Input Volt. 100V
 - - - □ - - - Input Volt. 200V
 - · - ○ - · - - Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.


2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	5.021	5.022	5.023
-15	5.024	5.025	5.026
-10	5.027	5.027	5.028
0	5.032	5.032	5.033
25	5.042	5.042	5.042
40	5.045	5.045	5.045
50	5.047	5.047	5.047
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-




Model		LHA100F-5	Temperature 25°C Testing Circuitry Figure A
Item		Rise and Fall Time	
Object		+5V15A	

1. Graph



2. Values

		[ms]				
Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		98.0	3.0	101.0	27.8	1.2
230 V		85.5	2.5	88.0	27.9	1.2





COSEL																																		
Model	LHA100F-5																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+5V15A																																	
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>57</td><td>-</td></tr> <tr><td>90</td><td>57</td><td>28</td></tr> <tr><td>100</td><td>57</td><td>28</td></tr> <tr><td>120</td><td>57</td><td>28</td></tr> <tr><td>200</td><td>57</td><td>28</td></tr> <tr><td>230</td><td>57</td><td>28</td></tr> <tr><td>264</td><td>58</td><td>28</td></tr> <tr><td>280</td><td>60</td><td>29</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	57	-	90	57	28	100	57	28	120	57	28	200	57	28	230	57	28	264	58	28	280	60	29	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
85	57	-																																
90	57	28																																
100	57	28																																
120	57	28																																
200	57	28																																
230	57	28																																
264	58	28																																
280	60	29																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		



<p>Model LHA100F-5</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Instantaneous Interruption Compensation</p>																																																					
<p>Object +5V15A</p>																																																					
<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V ···○··· Input Volt. 230V </p> <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>131</td><td>139</td><td>139</td></tr> <tr><td>6.0</td><td>31</td><td>70</td><td>70</td></tr> <tr><td>9.0</td><td>31</td><td>47</td><td>47</td></tr> <tr><td>12.0</td><td>31</td><td>35</td><td>35</td></tr> <tr><td>15.0</td><td>27</td><td>27</td><td>28</td></tr> <tr><td>16.5</td><td>23</td><td>24</td><td>24</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	3.0	131	139	139	6.0	31	70	70	9.0	31	47	47	12.0	31	35	35	15.0	27	27	28	16.5	23	24	24	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
3.0	131	139	139																																																		
6.0	31	70	70																																																		
9.0	31	47	47																																																		
12.0	31	35	35																																																		
15.0	27	27	28																																																		
16.5	23	24	24																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



COSEL																																								
Model	LHA100F-5																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+5V15A																																							
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>64</td><td>64</td></tr> <tr><td>-15</td><td>64</td><td>64</td></tr> <tr><td>-10</td><td>64</td><td>64</td></tr> <tr><td>0</td><td>64</td><td>64</td></tr> <tr><td>25</td><td>64</td><td>65</td></tr> <tr><td>40</td><td>64</td><td>65</td></tr> <tr><td>50</td><td>64</td><td>65</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	64	64	-15	64	64	-10	64	64	0	64	64	25	64	65	40	64	65	50	64	65	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-20	64	64																																						
-15	64	64																																						
-10	64	64																																						
0	64	64																																						
25	64	65																																						
40	64	65																																						
50	64	65																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



COSEL																																												
Model	LHA100F-5	Temperature	25°C																																									
Item	Overcurrent Protection	Testing Circuitry	Figure A																																									
Object	+5V15A																																											
<p>1.Graph</p> <div style="text-align: right;"> <p>————— Input Volt. 100V</p> <p>————— Input Volt. 230V</p> </div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Overcurrent protection is Hiccup mode.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>18.85</td><td>18.85</td></tr> <tr><td>4.75</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	5.00	18.85	18.85	4.75	-	-	4.50	-	-	4.00	-	-	3.50	-	-	3.00	-	-	2.50	-	-	2.00	-	-	1.50	-	-	1.00	-	-	0.50	-	-	0.00	-	-
Output Voltage [V]	Load Current [A]																																											
	Input Volt. 100[V]	Input Volt. 230[V]																																										
5.00	18.85	18.85																																										
4.75	-	-																																										
4.50	-	-																																										
4.00	-	-																																										
3.50	-	-																																										
3.00	-	-																																										
2.50	-	-																																										
2.00	-	-																																										
1.50	-	-																																										
1.00	-	-																																										
0.50	-	-																																										
0.00	-	-																																										



COSEL																																								
Model	LHA100F-5																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+5V15A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 100V</p> <p>- - - □ - - - Input Volt. 230V</p> </div> <p style="text-align: center;">Ambient Temperature [°C] Load 0%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>6.33</td><td>6.33</td></tr> <tr><td>-15</td><td>6.33</td><td>6.33</td></tr> <tr><td>-10</td><td>6.33</td><td>6.33</td></tr> <tr><td>0</td><td>6.33</td><td>6.33</td></tr> <tr><td>25</td><td>6.33</td><td>6.33</td></tr> <tr><td>40</td><td>6.33</td><td>6.33</td></tr> <tr><td>50</td><td>6.33</td><td>6.33</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 230[V]	-20	6.33	6.33	-15	6.33	6.33	-10	6.33	6.33	0	6.33	6.33	25	6.33	6.33	40	6.33	6.33	50	6.33	6.33	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 100[V]	Input Volt. 230[V]																																						
-20	6.33	6.33																																						
-15	6.33	6.33																																						
-10	6.33	6.33																																						
0	6.33	6.33																																						
25	6.33	6.33																																						
40	6.33	6.33																																						
50	6.33	6.33																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								




Figure A




Figure B-1 (DEN-AN)




Figure B-2 (IEC62368-1 refer to IEC60990 Fig.4)





Figure B-3 (IEC62368-1 refer to IEC60990 Fig.5)



C1= 0.1 μF
 (Film capacitor)
 C2= 22 μF
 (Electrolytic capacitor)

Figure C