



EXTRA TEST DATA OF LHA10F-3R3-Y

*Regulated DC Power Supply
Aug, 20, 2022*

COSEL CO.,LTD.



CONTENTS

1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Overtoltage Protection (waveform)	3
4.Hiccup cycle (by Overcurrent Protection)	4
5.Figure of Testing Circuitry	5

(Final Page 5)

COSEL

Model	LHA10F-3R3-Y		
Item	Inrush Current (enlargement)	Temperature	25°C
Object	_____	Testing Circuitry	A




COSEL

Model	LHA10F-3R3-Y	Temperature 25°C Testing Circuitry A	
Item	Dynamic Line Regulation		
Object	_____		

Input Voltage
[200V/div]

Output Voltage
[50mV/div]




Input Voltage :
100V \leftrightarrow 230V

Frequency : 50Hz
Load : 100%

Time
[400ms/div]

Input Voltage
[200V/div]



Output Voltage
[50mV/div]




Input Voltage :
230V \leftrightarrow 100V

Frequency : 50Hz
Load : 100%


Time
[400ms/div]



COSEL

Model	LHA10F-3R3-Y	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object		Load	: Short

Output
Current
[1A/div]



Input Voltage : 100V


Short-circuit
current : 5.5A

ON Time : 210ms

Hiccup mode
time : 1636ms

Time
[400ms/div]

Output
Current
[1A/div]



Input Voltage : 230V

Short-circuit
current : 5.7A

ON Time : 210ms

Hiccup mode
time : 1635ms

Time
[400ms/div]

