



DATA SHEET

DATA SHEET		Date	08-Feb-22
Model	LHA15F-3R3-Y	Temp.	25 degreeC
Test	EMI	Humid.	40 %RH
	Line conduction & Radiated emission	Tested by	K.Yamamoto



Frequency MHz	Line	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/Fail	Remark
		QP	AV	QP	AV	QP	AV		
0.198	N	54.5	39.1	63.7	53.7	9.2	14.6	Pass	
3.848	N	43.2	38	56	46	12.8	8	Pass	




Frequency MHz	Polarization	Stability	Level dB(μV/m)		Limit dB(μV/m)		Margin dB	Pass/Fail	Height cm	Angle deg	Remark
			QP	AV	QP	AV					
183.992	H	Stable	27.3		40		12.7	Pass	199.7	176	
110.314	V	Stable	23.6		40		16.4	Pass	100.2	264.8	


DATA SHEET

		Date	08-Feb-22
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	K.Yamamoto

1. Line conduction



2. Radiated emission






Conditions

Test : EMI
Model Name : LHA15F

Photographs of test set-up

1.LINE CONDUCTION



2.RADIATED EMISSION

