



EXTRA TEST DATA OF LHA300F-48-Y

*Regulated DC Power Supply
Mar 20, 2021*

COSEL CO.,LTD.






CONTENTS

1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Ovvervoltage Protection (waveform)	3
4.Hiccup cycle (by Overcurrent Protection)	4
5.Power Consumption (by Input Voltage)	5
6.Figure of Testing Circuitry	6

(Final Page 6)




COSEL

Model	LHA300F-48-Y	Temperature	25°C
Item	Inrush Current (enlargement)	Testing Circuitry	A
Object	<hr/>		





COSEL

Model	LHA300F-48-Y	Temperature	25°C
Item	Dynamic Line Regulation	Testing Circuitry	A
Object	_____		






COSEL

Model	LHA300F-48-Y	Temperature 25°C
Item	Over Voltage Protection	Testing Circuitry A
Object	_____	Input Voltage : 100V

Output
Voltage
[10V/div]Load : 0%
Overvoltage protection
value : 66.4VOutput
Voltage
[10V/div]Load : 100%
Overvoltage protection
value : 65.6V

COSEL

Model	LHA300F-48-Y	Temperature	25°C
Item	Short Circuit Current	Testing Circuitry	A
Object	_____	Load	: Short

Output
Current
[5A/div]Output
Current
[5A/div]

COSEL

Model	LHA300F-48-R2Y	Temperature	25°C																												
Item	Input voltage - Power consumption	Testing Circuitry	-																												
Object	_____	Load	: 0%																												
1. Graph			2. Values																												
<p>The graph plots Power consumption [W] on the y-axis (0.00 to 5.00) against Input Voltage [V] on the x-axis (50 to 300). The data points show a non-linear increase in power consumption as input voltage increases.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Power consumption [W]</th> </tr> </thead> <tbody> <tr><td>85</td><td>0.09</td></tr> <tr><td>100</td><td>0.12</td></tr> <tr><td>115</td><td>0.14</td></tr> <tr><td>200</td><td>0.35</td></tr> <tr><td>230</td><td>0.69</td></tr> <tr><td>264</td><td>0.91</td></tr> </tbody> </table>			Input Voltage [V]	Power consumption [W]	85	0.09	100	0.12	115	0.14	200	0.35	230	0.69	264	0.91	<table border="1"> <thead> <tr> <th>Input voltage [V]</th> <th>Power consumption [W]</th> </tr> </thead> <tbody> <tr><td>85</td><td>0.09</td></tr> <tr><td>100</td><td>0.12</td></tr> <tr><td>115</td><td>0.14</td></tr> <tr><td>200</td><td>0.35</td></tr> <tr><td>230</td><td>0.69</td></tr> <tr><td>264</td><td>0.91</td></tr> </tbody> </table>	Input voltage [V]	Power consumption [W]	85	0.09	100	0.12	115	0.14	200	0.35	230	0.69	264	0.91
Input Voltage [V]	Power consumption [W]																														
85	0.09																														
100	0.12																														
115	0.14																														
200	0.35																														
230	0.69																														
264	0.91																														
Input voltage [V]	Power consumption [W]																														
85	0.09																														
100	0.12																														
115	0.14																														
200	0.35																														
230	0.69																														
264	0.91																														
<p>Reducing standby power is possible by OFF signal of the remote control.</p>																															


COSEL

Figure A