



DATA SHEET

Date		15-Nov-19	
Model	LHA30F-3R3-Y	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Y.Haginaka



Frequency	Line	Level		Limit		Margin		Pass/Fail	Remark
MHz		dB(μV)		dB(μV)		dB			
		QP	AV	QP	AV	QP	AV		
0.824	N	36.4	35.4	56	46	19.6	10.6	Pass	
0.275	L1	45.8	42.3	61	51	15.2	8.7	Pass	




Frequency	Polarization	Stability	Level	Limit	Margin	Pass/Fail	Height	Angle	Remark
MHz			dB(μV/m)	dB(μV/m)	dB				
			QP	QP	QP				
35.087	V	Stable	32.6	40	7.4	Pass	100.2	332.1	
57.535	V	Stable	30.3	40	9.7	Pass	100.2	113.7	


DATA SHEET

		Date	15-Nov-19
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Y.Haginaka

1. Line conduction



2. Radiated emission



Conditions

Test : EMI
Model Name : LHA30F

Photographs of test set-up

1.LINE CONDUCTION



2.RADIATED EMISSION

