

# TEST DATA OF MGFS102412

Regulated DC Power Supply  
December 13, 2016

Approved by : Takayuki Fukuda  
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi  
Takaaki Sekiguchi Design Engineer

**COSEL CO.,LTD.**




## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Switching frequency (by Load Current) . . . . .	18
19.Figure of Testing Circuitry . . . . .	19

(Final Page 19)

**COSEL**

Model	MGFS102412
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
6.0	0.004	0.004	0.003
8.0	0.003	0.003	0.003
8.2	0.003	0.003	0.003
8.4	0.037	0.745	1.498
8.6	0.036	0.725	1.479
8.8	0.035	0.709	1.442
9.0	0.035	0.694	1.407
12.0	0.029	0.514	1.029
18.0	0.022	0.341	0.677
24.0	0.018	0.257	0.506
30.0	0.007	0.209	0.405
36.0	0.005	0.175	0.339
40.0	0.004	0.159	0.306
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	MGFS102412
Item	Input Current (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Load Current [A]	Input Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
0.00	0.035	0.029	0.022	0.018	0.005
0.18	0.291	0.219	0.150	0.113	0.080
0.36	0.558	0.416	0.279	0.210	0.143
0.54	0.837	0.620	0.410	0.307	0.208
0.72	1.124	0.827	0.546	0.408	0.272
0.81	1.271	0.932	0.613	0.458	0.306
0.90	- *	1.029	0.677	0.506	0.339
0.99	- *	1.148	0.750	0.559	0.373
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

\* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFS102412																																																																								
Item	Input Power (by Load Current)																																																																								
Object	_____																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 9V</li> <li>Input Volt. 12V</li> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> </ul> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.31</td><td>0.34</td><td>0.39</td><td>0.44</td><td>0.18</td></tr> <tr><td>0.18</td><td>2.59</td><td>2.61</td><td>2.68</td><td>2.72</td><td>2.90</td></tr> <tr><td>0.36</td><td>4.96</td><td>4.95</td><td>4.98</td><td>5.02</td><td>5.15</td></tr> <tr><td>0.54</td><td>7.41</td><td>7.36</td><td>7.33</td><td>7.34</td><td>7.47</td></tr> <tr><td>0.72</td><td>9.93</td><td>9.79</td><td>9.75</td><td>9.75</td><td>9.80</td></tr> <tr><td>0.81</td><td>11.27</td><td>11.03</td><td>10.94</td><td>10.94</td><td>11.00</td></tr> <tr><td>0.90</td><td>-</td><td>12.27</td><td>12.14</td><td>12.13</td><td>12.19</td></tr> <tr><td>0.99</td><td>-</td><td>13.57</td><td>13.37</td><td>13.35</td><td>13.41</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.31	0.34	0.39	0.44	0.18	0.18	2.59	2.61	2.68	2.72	2.90	0.36	4.96	4.95	4.98	5.02	5.15	0.54	7.41	7.36	7.33	7.34	7.47	0.72	9.93	9.79	9.75	9.75	9.80	0.81	11.27	11.03	10.94	10.94	11.00	0.90	-	12.27	12.14	12.13	12.19	0.99	-	13.57	13.37	13.35	13.41	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																				
0.00	0.31	0.34	0.39	0.44	0.18																																																																				
0.18	2.59	2.61	2.68	2.72	2.90																																																																				
0.36	4.96	4.95	4.98	5.02	5.15																																																																				
0.54	7.41	7.36	7.33	7.34	7.47																																																																				
0.72	9.93	9.79	9.75	9.75	9.80																																																																				
0.81	11.27	11.03	10.94	10.94	11.00																																																																				
0.90	-	12.27	12.14	12.13	12.19																																																																				
0.99	-	13.57	13.37	13.35	13.41																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									
Note:	Slanted line shows the range of the rated load current.																																																																								
	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																								

**COSEL**

Model	MGFS102412																																
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object																																	
1.Graph																																	
		2.Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.6</td><td>88.0</td><td>87.3 ※1</td></tr> <tr><td>9.0</td><td>87.8</td><td>87.7 ※1</td></tr> <tr><td>12.0</td><td>88.5</td><td>88.7</td></tr> <tr><td>15.0</td><td>88.5</td><td>89.0</td></tr> <tr><td>18.0</td><td>88.5</td><td>89.6</td></tr> <tr><td>24.0</td><td>87.8</td><td>89.6</td></tr> <tr><td>30.0</td><td>86.9</td><td>89.3</td></tr> <tr><td>36.0</td><td>85.9</td><td>89.2</td></tr> <tr><td>40.0</td><td>84.6</td><td>88.8</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.6	88.0	87.3 ※1	9.0	87.8	87.7 ※1	12.0	88.5	88.7	15.0	88.5	89.0	18.0	88.5	89.6	24.0	87.8	89.6	30.0	86.9	89.3	36.0	85.9	89.2	40.0	84.6	88.8
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
8.6	88.0	87.3 ※1																															
9.0	87.8	87.7 ※1																															
12.0	88.5	88.7																															
15.0	88.5	89.0																															
18.0	88.5	89.6																															
24.0	87.8	89.6																															
30.0	86.9	89.3																															
36.0	85.9	89.2																															
40.0	84.6	88.8																															
※1: Load 80%																																	
Note: Slanted line shows the range of the rated input voltage.																																	


COSEL

Model	MGFS102412																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 9V</li> <li>- - □ - - Input Volt. 12V</li> <li>- - * - - Input Volt. 18V</li> <li>- - ○ - - Input Volt. 24V</li> <li>- - ◇ - - Input Volt. 36V</li> </ul>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.18</td> <td>84.1</td> <td>83.2</td> <td>81.0</td> <td>80.0</td> <td>74.8</td> </tr> <tr> <td>0.36</td> <td>87.7</td> <td>87.8</td> <td>87.5</td> <td>86.6</td> <td>84.4</td> </tr> <tr> <td>0.54</td> <td>88.0</td> <td>88.6</td> <td>89.0</td> <td>89.0</td> <td>87.4</td> </tr> <tr> <td>0.72</td> <td>87.7</td> <td>88.9</td> <td>89.2</td> <td>89.3</td> <td>88.7</td> </tr> <tr> <td>0.81</td> <td>86.9</td> <td>88.8</td> <td>89.4</td> <td>89.5</td> <td>89.0</td> </tr> <tr> <td>0.90</td> <td>- *</td> <td>88.7</td> <td>89.6</td> <td>89.6</td> <td>89.2</td> </tr> <tr> <td>0.99</td> <td>- *</td> <td>88.2</td> <td>89.5</td> <td>89.6</td> <td>89.2</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	-	-	0.18	84.1	83.2	81.0	80.0	74.8	0.36	87.7	87.8	87.5	86.6	84.4	0.54	88.0	88.6	89.0	89.0	87.4	0.72	87.7	88.9	89.2	89.3	88.7	0.81	86.9	88.8	89.4	89.5	89.0	0.90	- *	88.7	89.6	89.6	89.2	0.99	- *	88.2	89.5	89.6	89.2	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.18	84.1	83.2	81.0	80.0	74.8																																																																													
0.36	87.7	87.8	87.5	86.6	84.4																																																																													
0.54	88.0	88.6	89.0	89.0	87.4																																																																													
0.72	87.7	88.9	89.2	89.3	88.7																																																																													
0.81	86.9	88.8	89.4	89.5	89.0																																																																													
0.90	- *	88.7	89.6	89.6	89.2																																																																													
0.99	- *	88.2	89.5	89.6	89.2																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

**COSEL**

Model	MGFS102412	Temperature	25°C
Item	Line Regulation	Testing Circuitry	Figure A
Object	+12V0.9A		

## 1.Graph



Note: Slanted line shows the range of the rated input voltage.

## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	12.051	- *
9.0	12.051	- *
12.0	12.052	12.050
15.0	12.052	12.053
18.0	12.052	12.050
24.0	12.052	12.050
30.0	12.052	12.053
36.0	12.052	12.050
40.0	12.052	12.053


\* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFS102412																																																																																	
Item	Load Regulation																																																																																	
Object	+12V0.9A																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 9V</li> <li>Input Volt. 12V</li> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> </ul>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.061</td><td>12.061</td><td>12.060</td><td>12.060</td><td>12.060</td></tr> <tr><td>0.150</td><td>12.060</td><td>12.059</td><td>12.059</td><td>12.058</td><td>12.058</td></tr> <tr><td>0.300</td><td>12.058</td><td>12.057</td><td>12.057</td><td>12.057</td><td>12.056</td></tr> <tr><td>0.450</td><td>12.056</td><td>12.056</td><td>12.056</td><td>12.056</td><td>12.055</td></tr> <tr><td>0.600</td><td>12.055</td><td>12.055</td><td>12.055</td><td>12.054</td><td>12.054</td></tr> <tr><td>0.750</td><td>12.053</td><td>12.053</td><td>12.054</td><td>12.053</td><td>12.053</td></tr> <tr><td>0.825</td><td>12.052</td><td>12.052</td><td>12.052</td><td>12.052</td><td>12.051</td></tr> <tr><td>0.900</td><td>-</td><td>12.050</td><td>12.050</td><td>12.050</td><td>12.050</td></tr> <tr><td>0.990</td><td>-</td><td>12.052</td><td>12.052</td><td>12.051</td><td>12.051</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.000	12.061	12.061	12.060	12.060	12.060	0.150	12.060	12.059	12.059	12.058	12.058	0.300	12.058	12.057	12.057	12.057	12.056	0.450	12.056	12.056	12.056	12.056	12.055	0.600	12.055	12.055	12.055	12.054	12.054	0.750	12.053	12.053	12.054	12.053	12.053	0.825	12.052	12.052	12.052	12.052	12.051	0.900	-	12.050	12.050	12.050	12.050	0.990	-	12.052	12.052	12.051	12.051	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.000	12.061	12.061	12.060	12.060	12.060																																																																													
0.150	12.060	12.059	12.059	12.058	12.058																																																																													
0.300	12.058	12.057	12.057	12.057	12.056																																																																													
0.450	12.056	12.056	12.056	12.056	12.055																																																																													
0.600	12.055	12.055	12.055	12.054	12.054																																																																													
0.750	12.053	12.053	12.054	12.053	12.053																																																																													
0.825	12.052	12.052	12.052	12.052	12.051																																																																													
0.900	-	12.050	12.050	12.050	12.050																																																																													
0.990	-	12.052	12.052	12.051	12.051																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																		


**COSEL**

Model	MGFS102412
Item	Dynamic Load Response
Object	+12V0.9A

Temperature 25°C  
Testing Circuitry Figure AInput Volt. 24 V  
Cycle 100 msMin.Load (0A)↔  
Load 100% (0.9A)

500 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔  
Load 50% (0.45A)

500 mV/div

2 ms/div




2 ms/div

Load 50% (0.45A)↔  
Load 100% (0.9A)

500 mV/div

2 ms/div




2 ms/div

**COSEL**

Model	MGFS102412
Item	Ripple Voltage (by Load Current)
Object	+12V0.9A

 Temperature 25°C  
 Testing Circuitry Figure B

## 1.Graph



## 2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 12 [V]	Input Volt. 36 [V]
0.00	5	10
0.18	5	10
0.36	5	10
0.54	10	10
0.72	10	5
0.81	15	5
0.90	20	5
0.99	30	10
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.  
 load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

**COSEL**

Model	MGFS102412
Item	Ripple-Noise
Object	+12V0.9A

 Temperature 25°C  
 Testing Circuitry Figure B

## 1.Graph



## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 12 [V]	Input Volt. 36 [V]
0.00	5	15
0.18	10	10
0.36	10	10
0.54	10	15
0.72	15	15
0.81	20	15
0.90	25	15
0.99	30	15
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	MGFS102412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.9A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


## Testing Circuitry Figure B

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	10	10
0	5	10
25	10	10
55	5	10
65	5	10
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

Model	MGFS102412
Item	Ambient Temperature Drift
Object	+12V0.9A



Note: Slanted line shows the range of the rated ambient temperature.

### Testing Circuitry Figure A

#### 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	11.955	11.954	11.955	11.956	11.956
-40	11.987	11.986	11.988	11.989	11.989
-20	12.015	12.014	12.016	12.016	12.017
0	12.035	12.034	12.035	12.036	12.036
25	12.050	12.050	12.050	12.050	12.050
55	12.058	12.057	12.059	12.058	12.058
65	12.058	12.058	12.058	12.058	12.058
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 9V, Load 80%.  
Other case Load 100%.



Model	MGFS102412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.9A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 12 - 36V

Load Current : 0 - 0.9A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	55	24	0	12.066	±40	±0.3
Minimum Voltage	-40	12	0.9	11.986		

**COSEL**

Model	MGFS102412
Item	Time Lapse Drift
Object	+12V0.9A

Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



Input Volt. 24V  
 Load 100%

## 2.Values


Time since start [H]	Output Voltage [V]
0.0	12.045
0.5	12.054
1.0	12.053
2.0	12.054
3.0	12.054
4.0	12.053
5.0	12.053
6.0	12.053
7.0	12.053
8.0	12.053

**COSEL**

Model	MGFS102412
Item	Rise and Fall Time
Object	+12V0.9A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.5	0.8	2.3	0.2	2.1	
100 %		1.5	1.0	2.5	0.1	1.0	




**COSEL**

Model	MGFS102412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.9A

Testing Circuitry Figure A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.6	7.6
-40	7.6	7.6
-20	7.6	7.6
0	7.6	7.6
25	7.6	7.6
55	7.5	7.5
65	7.5	7.5
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

Model	MGFS102412																																																																																						
Item	Overcurrent Protection																																																																																						
Object	+12V0.9A																																																																																						
1.Graph																																																																																							
<p>The graph plots Output Voltage [V] on the Y-axis (0 to 16) against Load Current [A] on the X-axis (0.0 to 3.0). Five curves represent different input voltages: 9V (black), 12V (blue), 18V (green), 24V (red), and 36V (magenta). All curves show a linear decrease in output voltage as load current increases. A slanted line is drawn from approximately (0.8, 12) to (1.8, 0), indicating the range of the rated load current.</p>																																																																																							
2.Values																																																																																							
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>11.4</td> <td>0.955</td> <td>1.098</td> <td>1.187</td> <td>1.149</td> <td>1.127</td> </tr> <tr> <td>10.8</td> <td>0.993</td> <td>1.134</td> <td>1.223</td> <td>1.179</td> <td>1.150</td> </tr> <tr> <td>9.6</td> <td>1.079</td> <td>1.213</td> <td>1.302</td> <td>1.242</td> <td>1.195</td> </tr> <tr> <td>8.4</td> <td>1.176</td> <td>1.307</td> <td>1.385</td> <td>1.307</td> <td>1.243</td> </tr> <tr> <td>7.2</td> <td>1.288</td> <td>1.417</td> <td>1.466</td> <td>1.375</td> <td>1.298</td> </tr> <tr> <td>6.0</td> <td>1.412</td> <td>1.527</td> <td>1.550</td> <td>1.445</td> <td>1.355</td> </tr> <tr> <td>4.8</td> <td>1.487</td> <td>1.639</td> <td>1.637</td> <td>1.514</td> <td>1.414</td> </tr> <tr> <td>3.6</td> <td>1.570</td> <td>1.756</td> <td>1.737</td> <td>1.597</td> <td>1.484</td> </tr> <tr> <td>2.4</td> <td>1.771</td> <td>1.887</td> <td>1.892</td> <td>1.706</td> <td>1.562</td> </tr> <tr> <td>1.2</td> <td>1.991</td> <td>2.075</td> <td>2.007</td> <td>1.806</td> <td>1.635</td> </tr> <tr> <td>0.0</td> <td>2.271</td> <td>2.225</td> <td>2.045</td> <td>1.794</td> <td>1.557</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Output Voltage [V]	Load Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	11.4	0.955	1.098	1.187	1.149	1.127	10.8	0.993	1.134	1.223	1.179	1.150	9.6	1.079	1.213	1.302	1.242	1.195	8.4	1.176	1.307	1.385	1.307	1.243	7.2	1.288	1.417	1.466	1.375	1.298	6.0	1.412	1.527	1.550	1.445	1.355	4.8	1.487	1.639	1.637	1.514	1.414	3.6	1.570	1.756	1.737	1.597	1.484	2.4	1.771	1.887	1.892	1.706	1.562	1.2	1.991	2.075	2.007	1.806	1.635	0.0	2.271	2.225	2.045	1.794	1.557	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																						
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																																		
11.4	0.955	1.098	1.187	1.149	1.127																																																																																		
10.8	0.993	1.134	1.223	1.179	1.150																																																																																		
9.6	1.079	1.213	1.302	1.242	1.195																																																																																		
8.4	1.176	1.307	1.385	1.307	1.243																																																																																		
7.2	1.288	1.417	1.466	1.375	1.298																																																																																		
6.0	1.412	1.527	1.550	1.445	1.355																																																																																		
4.8	1.487	1.639	1.637	1.514	1.414																																																																																		
3.6	1.570	1.756	1.737	1.597	1.484																																																																																		
2.4	1.771	1.887	1.892	1.706	1.562																																																																																		
1.2	1.991	2.075	2.007	1.806	1.635																																																																																		
0.0	2.271	2.225	2.045	1.794	1.557																																																																																		
--	-	-	-	-	-																																																																																		

Note: Slanted line shows the range of the rated load current.

Maximum output current at minimum input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFS102412																																																																																		
Item	Switching frequency (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																																																	
Object	+12V0.9A																																																																																		
1.Graph																																																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>740</td> <td>833</td> <td>950</td> <td>1013</td> <td>1020</td> </tr> <tr> <td>0.18</td> <td>396</td> <td>488</td> <td>625</td> <td>707</td> <td>792</td> </tr> <tr> <td>0.36</td> <td>270</td> <td>348</td> <td>464</td> <td>539</td> <td>623</td> </tr> <tr> <td>0.54</td> <td>202</td> <td>268</td> <td>368</td> <td>436</td> <td>514</td> </tr> <tr> <td>0.72</td> <td>161</td> <td>218</td> <td>305</td> <td>365</td> <td>438</td> </tr> <tr> <td>0.81</td> <td>147</td> <td>200</td> <td>282</td> <td>340</td> <td>410</td> </tr> <tr> <td>0.90</td> <td>- *</td> <td>183</td> <td>260</td> <td>314</td> <td>382</td> </tr> <tr> <td>0.99</td> <td>- *</td> <td>169</td> <td>242</td> <td>293</td> <td>358</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>						Load Current [A]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	740	833	950	1013	1020	0.18	396	488	625	707	792	0.36	270	348	464	539	623	0.54	202	268	368	436	514	0.72	161	218	305	365	438	0.81	147	200	282	340	410	0.90	- *	183	260	314	382	0.99	- *	169	242	293	358	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
0.00	740	833	950	1013	1020																																																																														
0.18	396	488	625	707	792																																																																														
0.36	270	348	464	539	623																																																																														
0.54	202	268	368	436	514																																																																														
0.72	161	218	305	365	438																																																																														
0.81	147	200	282	340	410																																																																														
0.90	- *	183	260	314	382																																																																														
0.99	- *	169	242	293	358																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Note:	Slanted line shows the range of the rated load current.																																																																																		
	When load current is low, MG operates intermittently, so switching frequency would not become constant.																																																																																		
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																		

COSEL




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)